Permit Number 20006

This table lists the maximum allowable emission rates and all sources of air contaminants on the applicant's property covered by this permit. The emission rates shown are those derived from information submitted as part of the application for permit and are the maximum rates allowed for these facilities. Any proposed increase in emission rates may require an application for a modification of the facilities covered by this permit.

AIR CONTAMINANTS DATA

Emission	Source	Air Contaminant	Emission Rates *	
Point No. (1)	Name (2)	Name (3)	lb/hr	TPY**
A2	Dryer Line 5 POC Stack	NO _x CO PM SO ₂ VOC	0.112 0.05 0.011 0.0005 0.003	0.50 0.22 0.048 0.003 0.014
A3-1	Dryer Line 6 POC Vent 1	NO _x CO PM SO ₂ VOC	0.112 0.05 0.011 0.0005 0.003	0.50 0.22 0.048 0.003 0.014
A3-2	Dryer Line 6 POC Vent 2	NO _x CO PM SO ₂ VOC	0.112 0.05 0.011 0.0005 0.003	0.50 0.22 0.048 0.003 0.014
A5	Steam Generator 7.6 MMBtu/hr POC Stack	NO_x CO PM/PM_{10} SO_2 VOC	0.20 0.08 0.02 0.01 0.01	0.876 0.351 0.088 0.044 0.044
A6	Steam Generator 7.6 MMBtu/hr POC Stack	NO_x CO PM/PM_{10} SO_2 VOC	0.20 0.08 0.02 0.01 0.01	0.876 0.351 0.088 0.044 0.044

AB1	Tunnel Kiln No. 4 POC Stack	NO _x CO PM SO ₂ VOC HF Pb HCI NH ₃	3.69 30.30 4.25 13.80 1.68 0.06 0.0002 0.42 2.7	16.2 96.4 18.6 24.9 7.4 0.27 0.0007 1.82 9.4
AC1	Tunnel Kiln No. 5 POC Stack	NO_x CO PM PM_{10} SO_2 VOC HF	4.10 30.30 0.45 0.23 1.21 1.68 0.636 0.22	18.0 96.4 2.0 1.1 5.3 7.4 1.6 1.0
В	Rotary KIIn POC Stack	NO _x CO PM SO ₂ VOC	0.20 0.08 0.02 0.01 0.01	0.876 0.351 0.088 0.044 0.044
E	Dryer Unconventional Line Scrubber Stack	NO _x CO PM SO ₂ VOC HF Formic Acid NH ₃	0.056 0.0244 0.0055 0.0012 0.0012 0.001 0.44 0.90	0.245 0.11 0.024 0.002 0.002 0.004 1.93 3.94
F	Dryer Unconventional Line	РМ	0.7	3.07

G	Cooling Stack Steam Generator	NO _x CO PM SO ₂ VOC	0.2 0.08 0.02 0.01 0.01	0.876 0.351 0.088 0.044 0.044
Н	Tunnel Kiln No. 1 POC Stack	NO_x CO PM_{10} SO_2 VOC HF Pb HCI	4.1 30.30 2.5 1.21 1.68 0.36 0.0002 0.22	18.0 96.4 11.0 5.3 7.4 0.66 0.0007 0.04
N	Tunnel Kiln No. 2 POC Stack	NOx CO PM SO₂ VOC HF Pb HCI	4.1 30.30 4.25 1.21 1.68 0.36 0.0002 0.22	18.0 96.4 18.6 5.3 7.4 1.6 0.0007 0.04
N1	Dryer NexGen POC Stack	NO _x CO PM SO ₂ VOC	0.112 0.05 0.011 0.0005 0.003	0.50 0.22 0.048 0.003 0.014
N2	Dryer NexGen	NO_x	0.112	0.50

	POC Stack	CO PM SO ₂ VOC	0.05 0.011 0.0005 0.003	0.22 0.048 0.003 0.014
X	Dryer Line 4 Scrubber and POC Stack	NO _x CO PM SO ₂	0.308 0.134 0.03 0.002	1.35 0.59 0.132 0.01
		VOC Formic Acid NH ₃	0.006 0.12 0.18	0.03 0.50 0.80

- (1) Emission point identification either specific equipment designation or emission point number from a plot plan.
- (2) Specific point source names. For fugitive sources, use an area name or fugitive source name.
- (3) Air Contaminant Name.

VOC - volatile organic compounds as defined in Title 30 Texas Administrative Code § 101.1

NO_x - total oxides of nitrogen

SO₂ - sulfur dioxide

PM - particulate matter, suspended in the atmosphere, including PM₁₀ and PM_{2.5}

PM₁₀ - particulate matter equal to or less than 10 microns in diameter PM_{2.5} - particulate matter equal to or less than 2.5 microns in diameter

CO - carbon monoxide HCl - hydrogen chloride HF - hydrogen fluoride

Permit Number 20006 Page 5

EMISSION SOURCES - MAXIMUM ALLOWABLE EMISSION RATES

Pb - lead

NH₄F -

NH₃ - ammonia

HAP - hazardous air pollutant as listed in § 112(b) of the Federal Clean Air Act or Title 40

Code of Federal Regulations Part 63, Subpart C

- (4) Fugitive emissions are an estimate only and should not be considered as a maximum allowable emission rate.
- * Emission rates are based on and the facilities are limited by the following maximum operating schedule:

_Hrs/day _Days/week __Weeks/year or 8,760 Hrs/year

** Compliance with annual emission limits is based on a rolling 12-month period.

Dated