

## EMISSION SOURCES - MAXIMUM ALLOWABLE EMISSION RATES

Permit Numbers 18384 and NA-TX-002

This table lists the maximum allowable emission rates and all sources of air contaminants on the applicant's property covered by this permit. The emission rates shown are those derived from information submitted as part of the application for permit and are the maximum rates allowed for these facilities. Any proposed increase in emission rates may require an application for a modification of the facilities covered by this permit.

### AIR CONTAMINANTS DATA

Emission Point No. (1)	Source Name (2)	Air Contaminant Name (3)	Emission Rates *	
			lb/hr	TPY**
70A/B	Dryer/Centrifuge No. 1	VOC (5)	25.20	
		PM	1.48	
		VCM	7.35	
71A/B	Dryer/Centrifuge No. 2	VOC (5)	19.08	
		PM	1.48	
		VCM	7.00	
72A/B	Dryer/Centrifuge No. 3	VOC (5)	21.00	
		PM	1.48	
		VCM	7.00	
83A/B	Dryer/Centrifuge No. 4	VOC (5)	20.00	
		PM	1.37	
		VCM	8.80	
89A/B	Dryer/Centrifuge No. 5	VOC (5)	20.00	
		PM	1.48	
		VCM	8.80	
90A/B	Dryer/Centrifuge No. 6	VOC (5)	20.00	
		PM	1.48	
		VCM	8.80	
92A/B/C	Dryer/Centrifuges No. 7	VOC (5)	26.50	
		PM	2.26	
		VCM	11.66	

70A/B, 71A/B, 72A/B, 83A/B, 89A/B, 90A/B and 92A/B/C	PVC Dryer Emission Production Lines 1-7	Caps: VOC (5, 6, 7, and 8) PM VCM		308.00 48.30 62.15
77A-H, 77J-N, and 77P-Y	PVC Storage Silos	PM VOC	1.31 0.74	5.74 3.25
77A-L-77H-L, 77J-L- 77N-L and 77P-L- 77Y-L	PVC Loading	VOC	0.02	0.03
78A	Off-Loading Silos	PM VOC	0.09 0.05	0.07 0.04
78B	Off-Loading Silos	PM VOC	0.09 0.05	0.07 0.04
78A-L	Railcar Reloading Spot	VOC	0.01	0.01
78B-L	Railcar Reloading Spot	VOC	0.01	0.01
F-74	Process Fugitives (4)	VOC (5 and 6) VCM	6.81 6.48	29.76 28.32
88/140	Incinerator/Scrubber	VCM HCl SO <sub>2</sub> NO <sub>x</sub> PM CO VOC (5 and 6)	0.13 0.05 0.06 2.00 0.15 1.68 0.54	0.57 0.22 0.26 8.76 0.66 7.36 1.06
120	Cooling Tower 120 (6)	VOC	1.41	6.18
130	Solution Preparation	VOC	4.75	0.44
131	Solution Preparation Blower Vent	VOC	0.99	0.04
140	Gas Holder (6)	VCM	0.56	0.11
75	Flare	NO <sub>x</sub> CO SO <sub>2</sub>	0.09 0.17 0.01	0.39 0.74 0.01

- (1) Emission point identification - either specific equipment designation or emission point number from plot plan.
- (2) Specific point source name. For fugitive sources use area name or fugitive source name.
- (3) VOC - volatile organic compounds as defined in Title 30 Texas Administrative Code ' 101.1.  
PM - particulate matter, suspended in the atmosphere, including PM<sub>10</sub>.  
PM<sub>10</sub> - particulate matter equal to or less than 10 microns in diameter. Where PM is not listed, it shall be assumed that no particulate matter greater than 10 microns is emitted  
VCM - vinyl chloride monomer  
HCl - hydrogen chloride  
SO<sub>2</sub> - sulfur dioxide  
NO<sub>x</sub> - nitrogen oxides  
CO - carbon monoxide
- (4) Emission rate is an estimate and is enforceable through compliance with the applicable special condition(s) and permit application representations.
- (5) The maximum allowable VOC emission rates include the allowable VCM emissions.
- (6) The VOC (including VCM) emissions subject to non-attainment new source review under NA-TX-002.
- (7) The annual VOC (including VCM) emissions for Dryer/Centrifuge No. 2 (EPN 71A/B) shall not equal or exceed 40 tons/yr.
- (8) The annual VOC (including VCM) emissions for Dryer/Centrifuge No. 3 (EPN 72A/B) shall not equal or exceed 40 tons/yr.

\* Emission rates are based on and the facilities are limited by the following maximum operating schedule:

\*\* Annual emissions are based on a rolling 12-month average.

\_\_\_\_\_ Hrs/day \_\_\_\_\_ Days/week \_\_\_\_\_ Weeks/year or 8,784 Hrs/year

Dated March 17, 2008