#### Permit Number 7103

This table lists the maximum allowable emission rates and all sources of air contaminants on the applicant's property covered by this permit. The emission rates shown are those derived from information submitted as part of the application for permit and are the maximum rates allowed for these facilities. Any proposed increase in emission rates may require an application for a modification of the facilities covered by this permit.

Emission	Source	Air Contaminant <u>Emission Rates</u>		<u>Rates</u>
Point No. (1)	Name (2)	Name (3)	lb/hr	<u>TPY</u>
Α	15,000 cfm Dust Collector Sta (cutoff and power pac)	ck PM/PM <sub>10</sub>	1.30	5.70
В	8,000 cfm Sintamatic Dust Collector Stack (cutoff)	PM/PM <sub>10</sub>	0.86	3.77
С	5,000 cfm Torit Dust Collector Stack (metal control)	PM/PM <sub>10</sub>	0.43	1.88
AJ	8,000 cfm Sintamatic Dust Collector Stack (cutoff)	PM/PM <sub>10</sub>	0.86	3.77
AAE	3,200 cfm Torit Dust Collector Stack (knockout and case bla		0.01	0.04
AAD	1,000 cfm Torit Dust Collector Stack (grit reclaim)	PM/PM <sub>10</sub>	<0.01	0.01
K	Flash Fire Dewax Furnace and Afterburner	$NO_x$ $CO$ $VOC$ $SO_2$ $PM/PM_{10}$	0.96 0.47 0.03 <0.01 0.12	4.18 2.08 0.14 0.01 0.53
L1	Dewax Furnace and Afterburner	$NO_x$ $CO$ $VOC$ $SO_2$ $PM/PM_{10}$	1.43 0.71 0.05 <0.01 0.18	6.27 3.12 0.21 0.02 0.80

# ${\tt EMISSION} \ {\tt SOURCES} \ {\tt -MAXIMUM} \ {\tt ALLOWABLE} \ {\tt EMISSION} \ {\tt RATES}$

Emission	Source	Air Contaminant	Emission Rates	
Point No. (1)	Name (2)	Name (3)	lb/hr	TPY
L2	Cooling Tunnel	$NO_x$ $CO$ $VOC$ $SO_2$ $PM/PM_{10}$	<0.01 <0.01 <0.01 <0.01 <0.01	<0.01 <0.01 <0.01 <0.01 <0.01
U	Casters No. 1	PM/PM <sub>10</sub>	<0.01	<0.01
V	Casters No. 2	PM/PM <sub>10</sub>	<0.01	<0.01
W	Casters No. 3	PM/PM <sub>10</sub>	<0.01	<0.01
AT	Casters No. 4	PM/PM <sub>10</sub>	<0.01	<0.01
AV	Casters No. 5	PM/PM <sub>10</sub>	<0.01	<0.01
AM1	BC3 Dewax Furnace and Afterburner	$NO_x$ $CO$ $VOC$ $SO_2$ $PM/PM_{10}$	1.23 0.54 0.04 <0.01 0.17	5.40 2.38 0.16 0.01 0.73
AM2	BC3 Cooling Tunnel	$NO_x$ $CO$ $VOC$ $SO_2$ $PM/PM_{10}$	<0.01 <0.01 <0.01 <0.01 <0.01	<0.01 <0.01 <0.01 <0.01 <0.01
AU	Can Slammer No. 1	PM/PM <sub>10</sub>	5.62	2.76
AW	BC3 Can Slammer No. 2	PM/PM <sub>10</sub>	5.62	2.76
FUG1	Can Slammer Fugitives (4)	PM/PM <sub>10</sub>	1.25	0.61

Emission	Source	Air Contaminant		Emission Rates	
Point No. (1)	Name (2)		Name (3)	lb/hr	TPY
FUG2	Shell and Penetrant Inspection (4)		Inorganic VOC	0.13 0.38	0.56 0.84
Н	Shell Core Removal No. 1	-	Inorganics	0.95	2.08
1	Shell Core Removal No. 2	2	Inorganics	0.95	2.08
J	Shell Core Removal No. 3	3	Inorganics	0.95	2.08
AG	Shell Softening No. 4		Inorganics	0.95	2.08
M	Dehumidification No. 1	PM/P SO <sub>2</sub> NO <sub>x</sub> CO	VOC M <sub>10</sub> <0.01 0.03 0.02	<0.01 <0.01 <0.01 0.11 0.09	<0.01 <0.01
Ο	Dehumidification No. 3	PM/P SO <sub>2</sub> NO <sub>x</sub> CO	VOC M <sub>10</sub> <0.01 0.03 0.02	<0.01 <0.01 <0.01 0.11 0.09	<0.01 <0.01
P	Preheat Molds No. 2	PM/P SO <sub>2</sub> NO <sub>x</sub> CO		<0.01 0.01 <0.01 0.61 0.52	0.03 0.05
Q	Preheat Molds No. 3	PM/P SO <sub>2</sub> NO <sub>x</sub> CO	VOC M <sub>10</sub> <0.01 0.14 0.12	<0.01 0.01 <0.01 0.61 0.52	0.03 0.05
R	Preheat Molds No. 4	PM/P	VOC M <sub>10</sub>	<0.01 0.01	0.03 0.05

Emission	Source	Air Contaminant		Emission Rates	
Point No. (1)	Name (2)		Name (3)	lb/hr	<u>TPY</u>
		SO <sub>2</sub> NO <sub>x</sub> CO	<0.01 0.14 0.12	<0.01 0.61 0.52	
S	Preheat Molds No. 5	PM/P SO <sub>2</sub> NO <sub>x</sub> CO	VOC PM <sub>10</sub> <0.01 0.14 0.12	<0.01 0.01 <0.01 0.61 0.52	0.03 0.05
Т	Preheat Molds No. 7	PM/P SO <sub>2</sub> NO <sub>x</sub> CO	VOC 9M <sub>10</sub> <0.01 0.14 0.12	<0.01 0.01 <0.01 0.61 0.52	0.03 0.05
Y	Dehumidification No. 4 an Dehumidification No. 6	SO <sub>2</sub> NO <sub>x</sub> CO	VOC PM/PM <sub>10</sub> <0.01 0.19 0.16	0.01 0.01 <0.01 0.83 0.70	0.06 0.05
Z	Dehumidification No. 5	PM/P SO <sub>2</sub> NO <sub>x</sub> CO	VOC PM <sub>10</sub> <0.01 0.14 0.12	<0.01 0.01 <0.01 0.61 0.51	0.03 0.05
AC	Autoclave Boiler	PM/P SO <sub>2</sub> NO <sub>x</sub> CO	VOC PM <sub>10</sub> <0.01 0.21 0.18	0.01 0.02 <0.01 0.92 0.77	0.05 0.07
AO	BC3 Dehumidification No.	PM/P	VOC PM <sub>10</sub> <0.01	<0.01 <0.01 <0.01	<0.01 <0.01

Emission	Source	Air Contaminant	Emission Rates	
Point No. (1)	Name (2)	Name (3)	lb/hr	TPY
		NO <sub>x</sub> 0.03 CO 0.02	0.11 0.09	
AP	BC3 Dehumidification No.	8 VOC PM/PM <sub>10</sub> SO <sub>2</sub> <0.01 NO <sub>x</sub> 0.04 CO 0.03	<0.01 <0.01 <0.01 0.18 0.15	<0.01 0.01
AR	Preheat Molds No. 6	$\begin{array}{c} \text{VOC} \\ \text{PM/PM}_{10} \\ \text{SO}_2 & < 0.01 \\ \text{NO}_x & 0.04 \\ \text{CO} & 0.03 \\ \end{array}$	<0.01 <0.01 <0.01 0.18 0.15	<0.01 0.01
AS	Dehumidification No. 11	$\begin{array}{c} VOC \\ PM/PM_{10} \\ SO_2 < 0.01 \\ NO_x  0.03 \\ CO  0.02 \\ \end{array}$	<0.01 <0.01 <0.01 0.11 0.09	<0.01 <0.01
AB	Backup Generator No. 1	$VOC$ $PM/PM_{10}$ $SO_2$ 0.77 $NO_x$ 11.63 $CO$ 2.51	0.93 0.83 0.34 5.09 1.10	0.41 0.36
AAB	Backup Generator No. 2	VOC PM/PM <sub>10</sub> SO <sub>2</sub> 6.11	0.53 0.53 2.68	0.23 0.23

#### AIR CONTAMINANTS DATA

Emission	Source	Air Contaminant	Emission Rates	
Point No. (1)	Name (2)	Name (3)	lb/hr	<u>TPY</u>
		NO <sub>x</sub> 18.12	7.94	
		CO 4.15	1.82	

- (1) Emission point identification either specific equipment designation or emission point number from a plot plan.
- (2) Specific point source names. For fugitive sources use area name or fugitive source name.
- (3) PM particulate matter, suspended in the atmosphere, including PM<sub>10</sub>
  - $PM_{10}$  particulate matter equal to or less than 10 microns in diameter. Where PM is not listed, it shall be assumed that no particulate matter greater than 10 microns is emitted.
  - $NO_x$  total oxides of nitrogen
  - CO carbon monoxide
    - VOC volatile organic compounds as defined in Title 30 Texas Administrative Code § 101.1
  - SO<sub>2</sub> sulfur dioxide
  - Inorganics combination of citric acid, nitric acid, and hydrogen chloride.
- (4) Fugitive emissions are an estimate only.

Dated August 29, 2007