

Emission Sources - Maximum Allowable Emission Rates

Permit Number 2718

This table lists the maximum allowable emission rates and all sources of air contaminants on the applicant's property covered by this permit. The emission rates shown are those derived from information submitted as part of the application for permit and are the maximum rates allowed for these facilities, sources, and related activities. Any proposed increase in emission rates may require an application for a modification of the facilities covered by this permit.

Air Contaminants Data

Emission Point No. (1)	Source Name (2)	Air Contaminant Name (3)	Emission Rates (9)	
			lbs/hour	TPY (4)
CHF	Cullet Handling Fugitives (Rail and Truck Unloading, Stockpile, and Transfer to Crusher Feed Hopper)	PM	0.12	0.53
		PM ₁₀	0.05	0.24
TRACKBLDG	Track Shed Building Fugitives (Bulk Bag Unloader Dust Collector, Premix Material Batch Scale Dust Sock, and Premix Blending Dust Collector) (10)	PM	<0.01	<0.01
		PM ₁₀	<0.01	<0.01
		PM _{2.5}	<0.01	<0.01
BATCHHOUSE	Batch House Fugitives for Minor Raw Material Ingredients (Premix Transport Dust Collector) (10)	PM	<0.01	<0.01
		PM ₁₀	<0.01	<0.01
		PM _{2.5}	<0.01	<0.01
1 (7)	Furnace A Stack	PM	16.00	70.10
		PM ₁₀	16.00	70.10
		VOC	0.40	1.80
		CO	5.50	24.10
		NO _x	75.30	329.80
		SO ₂	38.50	168.60
		H ₂ SO ₄	7.00	30.70
		HCl	0.50	2.20
		Pb	0.03	0.11
1 (8)	Furnace A Stack	PM	8.38	36.72

Emission Sources - Maximum Allowable Emission Rates

		PM ₁₀	8.32	36.45
		PM _{2.5}	8.32	36.45
		VOC	0.40	1.80
		CO	5.50	24.10
		NO _x	24.64	92.56
		SO ₂	30.27	61.71
		H ₂ SO ₄	2.64	11.56
		HCl	0.50	2.20
		Pb	0.03	0.11
		NH ₃	0.68	2.97
55A	Furnace A Refiner Fugitives	PM	0.03	0.13
		PM ₁₀	0.03	0.13
		PM _{2.5}	0.03	0.13
		VOC	0.02	0.09
		CO	0.32	1.41
		NO _x	0.38	1.67
		SO ₂	0.01	0.01
56A (7)	Furnace A Alcoves and Forehearths Fugitives	PM	0.05	0.22
		PM ₁₀	0.05	0.22
		PM _{2.5}	0.05	0.22
		VOC	0.04	0.16
		CO	0.56	2.45
		NO _x	0.67	2.92
		SO ₂	0.01	0.02

Emission Sources - Maximum Allowable Emission Rates

56A (8)	Furnace A Alcoves and Forehearths Fugitives	PM	0.07	0.30
		PM ₁₀	0.07	0.30
		PM _{2.5}	0.07	0.30
		VOC	0.05	0.22
		CO	0.76	3.34
		NO _x	0.91	3.98
		SO ₂	0.01	0.02
58A (7)	Furnace A Forming Machines Fugitives	PM	0.77	3.35
		PM ₁₀	0.77	3.35
		PM _{2.5}	0.77	3.35
58A (8)	Furnace A Forming Machines Fugitives	PM	0.88	3.87
		PM ₁₀	0.88	3.87
		PM _{2.5}	0.88	3.87
		VOC	0.88	3.87
2 (11)	Furnace B Stack	PM	13.10	57.50
		PM ₁₀	13.10	57.50
		VOC	2.63	11.50
		CO	2.63	11.50
		NO _x	81.40	356.00
		SO ₂	44.60	195.00
		H ₂ SO ₄	10.32	45.20
		HCl	0.36	1.58
		Pb	0.02	0.10
2 (12)	Furnace B Stack	PM	7.81	34.15

Emission Sources - Maximum Allowable Emission Rates

		PM ₁₀	7.75	33.90
		PM _{2.5}	7.75	33.90
		VOC	2.63	11.50
		CO	2.76	12.09
		NO _x	22.96	86.08
		SO ₂	28.21	57.39
		H ₂ SO ₄	2.99	13.07
		HCl	0.36	1.58
		Pb	0.02	0.10
		NH ₃	0.64	2.81
55B (11)	Furnace B Refiner Fugitives	PM	0.02	0.10
		PM ₁₀	0.02	0.10
		PM _{2.5}	0.02	0.10
		VOC	0.02	0.08
		CO	0.26	1.15
		NO _x	0.31	1.37
		SO ₂	0.01	0.01
55B (12)	Furnace B Refiner Fugitives	PM	0.03	0.11
		PM ₁₀	0.03	0.11
		PM _{2.5}	0.03	0.11
		VOC	0.02	0.08
		CO	0.29	1.26
		NO _x	0.34	1.50
		SO ₂	0.01	0.01

Emission Sources - Maximum Allowable Emission Rates

56B (11)	Furnace B Alcoves and Forehearths Fugitives	PM	0.05	0.23
		PM ₁₀	0.05	0.23
		PM _{2.5}	0.05	0.23
		VOC	0.04	0.16
		CO	0.57	2.49
		NO _x	0.68	2.96
		SO ₂	0.01	0.02
56B (12)	Furnace B Alcoves and Forehearths Fugitives	PM	0.06	0.28
		PM ₁₀	0.06	0.28
		PM _{2.5}	0.06	0.28
		VOC	0.05	0.21
		CO	0.72	3.14
		NO _x	0.85	3.74
		SO ₂	0.01	0.02
58B (11)	Furnace B Forming Machines Fugitives	PM	0.66	2.89
		PM ₁₀	0.66	2.89
		PM _{2.5}	0.66	2.89
58B (12)	Furnace B Forming Machines Fugitives	PM	0.85	3.73
		PM ₁₀	0.85	3.73
		PM _{2.5}	0.85	3.73
		VOC	0.85	3.73
4 (5)	Furnace D Stack	PM	30.38	134.90
		PM ₁₀	30.38	134.90
		VOC	0.20	0.90

Emission Sources - Maximum Allowable Emission Rates

		CO	8.90	39.00
		NO _x	121.70	533.00
		SO ₂	61.20	268.00
		H ₂ SO ₄	10.90	47.70
		HCl	0.40	1.80
		Pb	0.03	0.12
4 (6)	Furnace D Stack	PM	9.28	40.60
		PM ₁₀	9.21	40.30
		PM _{2.5}	9.21	40.30
		VOC	0.20	0.90
		CO	3.90	17.10
		NO _x	27.30	102.30
		SO ₂	33.54	68.20
		H ₂ SO ₄	3.40	14.90
		HCl	0.53	2.30
		Pb	0.02	0.09
		NH ₃	0.75	3.30
55D	Furnace D Refiner Fugitives	PM	0.03	0.13
		PM ₁₀	0.03	0.13
		PM _{2.5}	0.03	0.13
		VOC	0.02	0.10
		CO	0.34	1.48
		NO _x	0.40	1.76
		SO ₂	0.01	0.01

Emission Sources - Maximum Allowable Emission Rates

56D (5)	Furnace D Alcoves and Forehearths Fugitives	PM	0.04	0.18
		PM ₁₀	0.04	0.18
		PM _{2.5}	0.04	0.18
		VOC	0.03	0.13
		CO	0.46	2.02
		NO _x	0.55	2.40
		SO ₂	0.01	0.01
56D (6)	Furnace D Alcoves and Forehearths Fugitives	PM	0.06	0.27
		PM ₁₀	0.06	0.27
		PM _{2.5}	0.06	0.27
		VOC	0.05	0.20
		CO	0.69	3.03
		NO _x	0.82	3.61
		SO ₂	0.01	0.02
58D (5)	Furnace D Forming Machines Fugitives	PM	0.84	3.67
		PM ₁₀	0.84	3.67
		PM _{2.5}	0.84	3.67
58D (6)	Furnace D Forming Machines Fugitives	PM	0.98	4.28
		PM ₁₀	0.98	4.28
		PM _{2.5}	0.98	4.28
		VOC	0.98	4.28
7	Grit Blast Fugitives	PM	0.02	0.10
		PM ₁₀	0.02	0.10
8	Grit Blast Fugitives	PM	0.02	0.10

Emission Sources - Maximum Allowable Emission Rates

		PM ₁₀	0.02	0.10
18A - 18D	Raw Material Receiving Batch and Mixing Baghouse Stacks	PM	2.48	12.00
		PM ₁₀	2.48	12.00
18E	Minor Raw Material Surge Hopper Baghouse Stack	PM	0.02	<0.01
		PM ₁₀	0.02	<0.01
57	Shear Spray Fugitives	VOC	2.00	8.75
59A	Lehr Fugitives	PM	0.30	1.31
		PM ₁₀	0.30	1.31
		PM _{2.5}	0.30	1.31
		VOC	0.22	0.94
		CO	3.29	14.43
		NO _x	3.92	17.18
		SO ₂	0.02	0.10
59B	Belt Heater Fugitives	PM	0.01	0.07
		PM ₁₀	0.01	0.07
		PM _{2.5}	0.01	0.07
		VOC	0.01	0.05
		CO	0.16	0.72
		NO _x	0.20	0.86
		SO ₂	0.01	0.01
19	Hot End Surface Treatment Baghouse Stack	PM	0.46	2.07
		PM ₁₀	0.46	2.07
		NH ₃	2.86	12.50
		HCl	0.04	0.17

Emission Sources - Maximum Allowable Emission Rates

		VOC	0.72	3.15
71	Bottle Coder Fugitives	VOC	0.21	0.93
72	Glue Pot Fugitives	VOC	0.45	1.97
73	Carton Coder Fugitives	VOC	0.15	0.66
30	Reagent Silo Dust Collector Stack	PM	0.12	0.01
		PM ₁₀	0.12	0.01
		PM _{2.5}	0.12	0.01
31	ESP Dust Silo Dust Collector Stack	PM	0.02	0.09
		PM ₁₀	0.02	0.09
		PM _{2.5}	0.02	0.09
35	Emergency Generator Stack	PM	0.85	0.04
		PM ₁₀	0.71	0.04
		PM _{2.5}	0.69	0.04
		VOC	0.58	0.03
		CO	13.50	0.68
		NO _x	24.11	1.21
		SO ₂	0.03	<0.01
70	Oil/Water Separator Fugitives	VOC	1.2	5.26
74	Cooling Tower Vents	PM	0.40	1.75
		PM ₁₀	0.30	1.31
		PM _{2.5}	0.30	1.31
75	Parts Washer Fugitives	VOC	0.22	0.97
MSS-A	Furnace A MSS	PM	12.41	2.00
		PM ₁₀	11.80	2.00

Emission Sources - Maximum Allowable Emission Rates

		PM _{2.5}	11.31	2.00
		NO _x	73.75	36.00
		SO ₂	78.67	38.00
		H ₂ SO ₄	8.60	5.00
MSS-B	Furnace B MSS	PM	7.00	1.00
		PM ₁₀	6.60	1.00
		PM _{2.5}	6.30	1.00
		NO _x	68.60	33.00
		SO ₂	36.60	21.00
		H ₂ SO ₄	4.80	2.30
MSS-D	Furnace D MSS	PM	31.07	4.00
		PM ₁₀	29.51	4.00
		PM _{2.5}	28.25	4.00
		NO _x	116.43	56.00
		SO ₂	124.27	60.00
		H ₂ SO ₄	13.59	7.00

- (1) Emission point identification - either specific equipment designation or emission point number from plot plan.
- (2) Specific point source name. For fugitive sources, use area name or fugitive source name.
- (3)

VOC	-	volatile organic compounds as defined in Title 30 Texas Administrative Code § 101.1
NO _x	-	total oxides of nitrogen
SO ₂	-	sulfur dioxide
PM	-	total particulate matter, suspended in the atmosphere, including PM ₁₀ and PM _{2.5} , as represented
PM ₁₀	-	total particulate matter equal to or less than 10 microns in diameter, including PM _{2.5} , as represented
PM _{2.5}	-	particulate matter equal to or less than 2.5 microns in diameter
CO	-	carbon monoxide
H ₂ SO ₄	-	sulfuric acid
HCl	-	hydrogen chloride
Pb	-	lead as particulate matter
NH ₃	-	ammonia

Emission Sources - Maximum Allowable Emission Rates

- (4) Compliance with annual emission limits (tons per year) is based on a 12-month rolling period.
- (5) Effective prior to installation and commencing operation of all control devices and rebuilding of alcoves, forehearths, and forming machines represented in the 2012 Amendment Application.
- (6) Effective after installation and commencing operation of all control devices and rebuilding of alcoves, forehearths, and forming machines represented in the 2012 Amendment Application.
- (7) Effective prior to installation and commencing operation of all control devices and rebuilding of alcoves, forehearths, and forming machines represented in the 2013 Amendment Application.
- (8) Effective after installation and commencing operation of all control devices and rebuilding of alcoves, forehearths, and forming machines represented in the 2013 Amendment Application.
- (9) Planned startup and shutdown emissions are included. Maintenance activities, except as specified in Special Condition Nos. 26 through 30, are not authorized by this permit and will need separate authorization, unless the activity can meet the conditions of 30 TAC § 116.119.
- (10) Emission rate is an estimate and is enforceable through compliance with the applicable special condition(s) and permit application representations.
- (11) Effective prior to installation and commencing operation of all control devices and rebuilding of alcoves, forehearths, and forming machines represented in the 2014 Amendment Application (issued July 2014).
- (12) Effective after installation and commencing operation of all control devices and rebuilding of alcoves, forehearths, and forming machines represented in the 2014 Amendment Application (issued July 2014).

Date: July 23, 2014