

# EMISSION SOURCES - MAXIMUM ALLOWABLE EMISSION RATES

Permit Number 49076

This table lists the maximum allowable emission rates and all sources of air contaminants on the applicant's property covered by this permit. The emission rates shown are those derived from information submitted as part of the application for permit and are the maximum rates allowed for these facilities. Any proposed increase in emission rates may require an application for a modification of the facilities covered by this permit.

## AIR CONTAMINANTS DATA

Emission Point No. (1)	Source Name (2)	Air Contaminant Name (3)	Emission Rates *	
			lb/hr	TPY **
165-ATM-1	Base Resin Feed Hopper 1A	VOC	0.43	0.59
		PM	0.13	0.25
165-ATM-2	Base Resin Feed Hopper 1B	VOC	0.43	0.59
		PM	0.34	0.25
165-ATM-3	Base Resin Feed Hopper 1S	VOC	0.22	0.06
		PM	0.34	0.20
165-ATM-4	Base Resin Feed Hopper 2B	VOC	0.12	0.33
		PM	0.34	0.45
165-ATM-5	Base Resin Feed Hopper 2S	VOC	0.01	0.01
		PM	0.16	0.20
165-ATM-6	Base Resin Feed Hopper 2RW	VOC	0.12	0.14
		PM	0.06	0.10
165-ATM-7	Base Resin Feed Hopper 3N	VOC	0.22	0.24
		PM	0.04	0.10
165-ATM-8	Base Resin Feed Hopper 3B	VOC	0.43	0.67
		PM	0.34	0.25
165-ATM-9	Base Resin Feed Hopper 3RW	VOC	0.22	0.34
		PM	0.15	0.10
165-SOC-1	Natural Resin Unloading	PM	0.01	0.03
165-SEP-1	No. 3 Direct Packaging Separator	PM	0.02	0.11

## AIR CONTAMINANTS DATA

## EMISSION SOURCES - MAXIMUM ALLOWABLE EMISSION RATES

Emission Point No. (1)	Source Name (2)	Air Contaminant Name (3)	Emission Rates *	
			lb/hr	TPY **
165-SEP-2	No. 2X Waste Separator	VOC	0.01	0.01
		PM	0.02	0.01
165-ATM-10	No. 1X Centrifugal Dryer	VOC	0.18	0.55
		PM	0.92	0.60
165-ATM-11	No. 2X Centrifugal Dryer	VOC	0.01	0.03
		PM	0.92	0.60
165-ATM-12	No. 3X Centrifugal Dryer	VOC	0.18	0.55
		PM	0.92	0.60
165-TK-1	No. 2 and 3 Xtrdr Acid Return Tank	VOC	0.01	0.01
165-SOC-2	No. 1 H/C Unloading Blower Filter	PM	0.01	0.01
165-SOC-3	No. 1 H/C Unloading Blower Filter	PM	0.01	0.01
165-SOC-4	No. 4 H/C Unloading Blower Filter	PM	0.01	0.01
165-SOC-5	Zinc H/C Unloading Blower Filter	PM	0.01	0.01
165-SOC-6	North Pkg. Blower Filter	PM	0.01	0.01
165-SOC-7	South Pkg. Blower Filter	PM	0.01	0.01
165-SOC-8	165 Building Vacuum System	VOC	0.11	0.42
		PM	0.01	0.01
165-SOC-9	R-125 System	PM	0.01	0.01

## AIR CONTAMINANTS DATA

## EMISSION SOURCES - MAXIMUM ALLOWABLE EMISSION RATES

Emission Point No. (1)	Source Name (2)	Air Contaminant Name (3)	Emission Rates *	
			lb/hr	TPY **
165-SEP-3	No. 3 South Concentrate Sep.	VOC	0.13	0.42
		PM	0.01	0.02
166-BAG-1	North Area Fines Collection Filter	VOC	21.69	32.75
		PM	0.08	0.06
166-ATM-1	XM-Hoppers	VOC	0.18	0.55
		PM	0.56	0.40
166-BAG-2	XM Hopper Fines Dust Collector	PM	0.03	0.02
166-SEP-1	Direct Packaging Separator	VOC	0.13	0.42
		PM	0.02	0.06
166-SEP-2	AA@ Separator	PM	0.26	0.02
166-SEP-4	North Area Silo Waste Separator	PM	0.08	0.01
166-SEP-3	AB@ Separator	PM	0.06	0.02
166-SOC-1	166 Building Vacuum System	PM	0.01	0.01
167-BAG-1	North/South/Surlyn H/C Filter	PM	0.03	0.03
167-SEP-1	South H/C Loading Separator	PM	0.78	1.07
167-SEP-2	North H/C Loading Separator	PM	0.84	1.07
167-SEP-3	Surlyn H/C Loading Kice Separator	PM	0.13	0.16
167-SEP-4	H/C Loading Waste Separator	PM	0.08	0.41
189-VNT	Building 189 Combined Emissions	VOC	19.43	9.23
		PM	0.70	9.55
AIR CONTAMINANTS DATA				

Emission	Source	Air Contaminant	Emission Rates *	
----------	--------	-----------------	------------------	--

## EMISSION SOURCES - MAXIMUM ALLOWABLE EMISSION RATES

Point No. (1)	Name (2)	Name (3)	lb/hr	TPY **
192.-BAG-1	Unloading/Packaging/Transfer	PM	0.01	0.01
192-PTK-1	Propane Tank Loading	VOC	0.07	0.03
FUG	CSD Fugitives (4)	VOC	0.34	1.48
192-ATM-1	Weigh Bins	PM	0.12	0.10
192-SEP-1	Waste Separator	PM	0.13	0.01
192-BAG-2	H/C Unloading Filter	PM	0.01	0.01
534-Comb	SEP -(1-12) and BAG-1	VOC	0.71	0.04
		PM	1.21	4.39
534-SEP-13	No. 3 Box Line	PM	0.08	0.06
534-SOC-1	No. 1 Bag Rework Blower Filter		PM 0.01	0.01
534-SOC-2	No. 2 Bag Rework Blower Filter		PM 0.02	0.01
534-BAG-2	534 Building Vacuum System	PM	0.01	0.01
534-SOC-3	4X Jumbo Transfer Blower Filter	PM	0.01	0.01
534-ATM-1	Portable Hopper Car Unloading		PM 0.01	0.06
700-SOC-1	Base Resin Feed Primary Filter		VOC 6.00	1.63
		PM	0.01	0.03
700-SOC-2	Hopper Car Suction Blower Bag		PM 0.01	0.01
192-TRLR	192 Pad Waste Pellets	VOC	20.41	35.00
700-SOC-3	700 Building Vacuum System	VOC	1.30	4.80

## EMISSION SOURCES - MAXIMUM ALLOWABLE EMISSION RATES

AIR CONTAMINANTS DATA				
		PM	0.01	0.01
Emission Point No. (1)	Source Name (2)	Air Contaminant Name (3)	<u>Emission Rates *</u>	
			lb/hr	TPY **
700-ATM-1	Centrifugal Dryer	VOC	0.10	0.36
		PM	0.04	0.09
700-SOC-4	Pellet Cooler Product Separator		PM	0.01
	Filter		0.03	
700-SOC-5	Weight Hopper	PM	0.01	0.01
700-SEP-1	Ballast Separator	VOC	0.01	0.01
		PM	0.06	0.10
700-SEP-2	Direct Boxing Separator	VOC	0.06	0.24
		PM	0.06	0.60
700-TK-1	Waste Acid Tank	VOC	0.01	0.01
CSD-CT-1	Cooling Tower	PM	0.04	0.17
EXTDR-MSS	MSS Emissions to Atmosphere		VOC	0.34
	0.22			

- (1) Emission point identification - either specific equipment designation or emission point number from a plot plan.
- (2) Specific point source names. For fugitive sources, use an area name or fugitive source name.
- (3) VOC - volatile organic compounds as defined in Title 30 Texas Administrative Code § 101.1  
 PM - particulate matter, suspended in the atmosphere, including PM<sub>10</sub>.  
 PM<sub>10</sub> - particulate matter equal to or less than 10 microns in diameter.
- (4) Fugitive emissions are an estimate only and should not be considered as a maximum allowable emission rate.

\* Emission rates are based on and the facilities are limited by the following maximum operating schedule:

\_\_\_ Hrs/day \_\_\_ Days/week \_\_\_ Weeks/year or 8,760 Hrs/year

\*\* Compliance with annual emission limits is based on a rolling 12-month period.

EMISSION SOURCES - MAXIMUM ALLOWABLE EMISSION RATES

Dated December 29, 2009