Permit Number 75702

This table lists the maximum allowable emission rates and all sources of air contaminants on the applicant's property covered by this permit. The emission rates shown are those derived from information submitted as part of the application for permit and are the maximum rates allowed for these facilities. Any proposed increase in emission rates may require an application for a modification of the facilities covered by this permit. **(5/09)**

AIR CONTAMINANTS DATA

Emission *	Source	Air Contaminant	<u>Emiss</u>	ion Rates
Point No. (1) TPY**	Name (2)	Name (3)	lb/hr	
S-20	Unloading Baghouse	PM/PM ₁₀	2.06	9.01
S-30	Hammermilling Baghouse	PM/PM ₁₀	1.20	5.26
S-70	Drying/Cooling Baghouse	PM/PM ₁₀ VOC	1.29 1.77	5.63 7.75
S-90	DDGS Loadout Baghouse	PM/PM ₁₀	0.39	1.71
S-40	Fermentation Scrubber	PM PM ₁₀ VOC	0.31 0.10 15.58	1.37 0.68 68.25
S-110A	Boiler Stack 1	PM/PM_{10} NO_x SO_2 CO VOC	0.91 1.20 0.07 4.20 0.66	4.00 5.26 0.32 18.40 2.89
S-110B	Boiler Stack 2	PM/PM ₁₀ NO _x SO ₂ CO VOC	0.91 1.20 0.07 4.20 0.66	4.00 5.26 0.32 18.40 2.89
S-10	Dryers A and B and RTO	PM/PM ₁₀ NO _x CO VOC	0.50 5.00 18.30 4.70	22.14 21.90 80.16 20.59

AIR CONTAMINANTS DATA

Emission *	Source	Air Contaminant <u>Em</u>		nission Rates
Point No. (1) TPY**	Name (2)	Name (3)	lb/hr	
F-80	Cooling Tower	SO ₂ PM/PM ₁₀ VOC	11.40 3.13 0.01	49.95 13.70 0.04
S-50	Truck/Rail Loadout Flare	NO _x CO VOC SO ₂	0.36 1.89 4.36 0.01	1.56 8.30 2.00 0.01
S-60	Methanator Flare	NO _x CO VOC SO ₂	0.45 2.38 0.33 0.01	1.95 10.41 1.46 0.01
T-1	190 Proof Ethanol Tank	VOC	0.13	0.59
T-2	200 Proof Ethanol Tank	VOC	0.13	0.59
T-3	Denaturant Gasoline Tank	VOC	0.37	1.63
T-4	Denatured Ethanol and 1 Tank	VOC	0.08	0.35
T-5	Denatured Ethanol and 2 Tank	VOC	0.08	0.35
T-6	Corrosion Inhibitor Tank	VOC	0.01	0.01
S-100	Emergency Water Pump Engine	PM/PM ₁₀ NO _x CO VOC SO ₂	0.01 0.20 0.01 0.01 0.02	0.02 0.86 0.05 0.02 0.10
GH-FUG, RL-FUG, SS-FUG	Grain and DDGS Fugitives (4)	PM PM ₁₀	1.41 0.78	2.51 1.37

AIR CONTAMINANTS DATA

Emission *	Source	Air Contaminant	<u>Emissio</u>	n Rates
Point No. (1) TPY**	Name (2)	Name (3)	lb/hr	_
LD-FUG	Loading Fugitives (4) (Rail & Truck)	VOC	10.77	2.20
EQ-FUG	Fugitive Components (4) (Equipment Leaks)	VOC	2.01	8.84
PV-FUG	Insig. Process Vents (4)	VOC	0.15	0.65
WD-FUG	Wetcake Emissions (4)	VOC PM PM ₁₀	1.08 0.01 0.01	4.71 0.03 0.01

- (1) Emission point identification either specific equipment designation or emission point number from a plot plan.
- (2) Specific point source names. For fugitive sources, use an area name or fugitive source name.
- (3) PM particulate matter, suspended in the atmosphere, including PM₁₀.
 - PM₁₀ particulate matter equal to or less than 10 microns in diameter. Where PM is not listed, it shall be assumed that no PM greater than 10 microns is emitted.
 - VOC volatile organic compounds as defined in Title 30 Texas Administrative Code § 101.1
 - NO_x total oxides of nitrogen
 - CO carbon monoxide
 - SO₂ sulfur dioxide
 - NH₃ ammonia
- (4) Fugitive emissions are an estimate only and should not be considered as a maximum allowable emission rate.
- * Emission rates are based on and the facilities are limited by the following maximum operating schedule:
 - 24 Hrs/day 7 Days/week 52 Weeks/year
- ** Compliance with annual emission limits is based on a rolling 12-month period.

AIR CONTAMINANTS DATA

Emission	Source	Air Contami	Air Contaminant	
*				
Point No. (1)	Name (2)	Name (3)	lb/hr	
TPY**				

Dated__