

EMISSION SOURCES - MAXIMUM ALLOWABLE EMISSION RATES

Permit Numbers 9654A, PSDTX833M3, and N60M2

This table lists the maximum allowable emission rates and all sources of air contaminants on the applicant's property covered by this permit. The emission rates shown are those derived from information submitted as part of the application for permit and are the maximum rates allowed for these facilities, sources, and related activities. Any proposed increase in emission rates may require an application for a modification of the facilities covered by this permit.

AIR CONTAMINANTS DATA

| Emission Point No. (1) | Source Name (2) | Air Contaminant Name (3) | Emission Rates (14) | |
|---------------------------|----------------------------------|--------------------------------|---------------------|---------|
| | | | lbs/hour | TPY (4) |
| 1A* | No. 1 Recovery Furnace ESP Stack | VOC(6) | 19.60 | 85.84 |
| | | NO _x | 88.71 | 337.53 |
| | | SO ₂ | 408.58 | 1566.62 |
| | | PM(7) | 59.62 | 261.15 |
| | | PM ₁₀ (8) | 43.03 | 188.46 |
| | | PM _{2.5} (8) | 39.42 | 172.68 |
| | | CO | 266.61 | 1167.76 |
| | | TRS(6) | 16.78 | 73.49 |
| | | HAPS | 19.23 | 82.88 |
| | | H ₂ SO ₄ | 0.67 | 2.93 |
| 1B* | No. 2 Recovery Furnace ESP Stack | VOC(6) | 19.60 | 85.84 |
| | | NO _x | 88.71 | 337.53 |
| | | SO ₂ | 408.58 | 1566.62 |
| | | PM(7) | 59.62 | 261.15 |
| | | PM ₁₀ (8) | 43.03 | 188.46 |
| | | PM _{2.5} (8) | 39.42 | 172.68 |
| | | CO | 266.61 | 1167.76 |
| | | TRS(6) | 16.78 | 73.49 |
| | | HAPS | 19.23 | 82.88 |
| | | H ₂ SO ₄ | 0.67 | 2.93 |

EMISSION SOURCES - MAXIMUM ALLOWABLE EMISSION RATES

| | | | | |
|-----|--------------------------------------|--------------------------------|--------|--------|
| 2** | Bark Boiler Scrubber Stack | VOC(6) | 11.15 | 41.70 |
| | | NO _x | 108.62 | 406.12 |
| | | SO ₂ | 7.44 | 32.22 |
| | | PM(7) | 55.76 | 208.49 |
| | | PM ₁₀ (9) | 55.76 | 208.49 |
| | | PM _{2.5} (9) | 55.76 | 208.49 |
| | | CO | 262.40 | 981.12 |
| | | TRS(6) | 0.06 | 0.23 |
| | | H ₂ SO ₄ | 0.53 | 1.93 |
| | | NH ₃ | 16.19 | 70.93 |
| 2A | No. 1 PFI Boiler Stack | VOC(6) | 1.63 | 7.13 |
| | | NO _x | 45.30 | 198.41 |
| | | SO ₂ | 0.79 | 0.93 |
| | | PM | 2.25 | 10.06 |
| | | PM ₁₀ | 2.25 | 10.06 |
| | | PM _{2.5} | 2.25 | 10.06 |
| | | CO | 70.00 | 306.60 |
| 3# | No. 1 Dissolving Tank Scrubber Stack | VOC(6) | 0.83 | 3.64 |
| | | NO _x | 1.15 | 5.06 |
| | | SO ₂ | 0.29 | 1.26 |
| | | PM(7) | 11.54 | 50.55 |
| | | PM ₁₀ (9) | 10.36 | 45.40 |
| | | PM _{2.5} (9) | 10.36 | 45.40 |
| | | CO | 0.46 | 2.02 |
| | | TRS(6) | 0.35 | 1.52 |

EMISSION SOURCES - MAXIMUM ALLOWABLE EMISSION RATES

| | | | | |
|-------|--|-----------------------|-------|--------|
| | | NH ₃ | 0.82 | 3.59 |
| 4# | No. 2 Dissolving Tank Scrubber Stack | VOC(6) | 0.83 | 3.64 |
| | | NO _x | 1.15 | 5.06 |
| | | SO ₂ | 0.29 | 1.26 |
| | | PM(7) | 11.54 | 50.55 |
| | | PM ₁₀ (9) | 10.36 | 45.40 |
| | | PM _{2.5} (9) | 10.36 | 45.40 |
| | | CO | 0.46 | 2.02 |
| | | TRS(6) | 0.35 | 1.52 |
| | | NH ₃ | 0.82 | 3.59 |
| 9 | Lime Silo Scrubber Stack | PM | 0.53 | 0.68 |
| | | PM ₁₀ | 0.53 | 0.68 |
| | | PM _{2.5} | 0.53 | 0.68 |
| 10 | No. 1 Slaker Scrubber Stack ^{A1} | VOC(6) | 0.01 | 0.01 |
| | | PM(7) | 0.34 | 1.49 |
| | | PM ₁₀ (9) | 0.34 | 1.49 |
| | | PM _{2.5} (9) | 0.34 | 1.49 |
| | | TRS(6) | 0.01 | 0.01 |
| | | NH ₃ | 7.53 | 12.19 |
| 11*** | Lime Kiln Scrubber Stack | VOC(6) | 1.01 | 3.36 |
| | | NO _x | 43.09 | 147.77 |
| | | SO ₂ | 7.00 | 24.24 |
| | | PM(7) | 31.58 | 104.78 |
| | | PM ₁₀ (9) | 27.28 | 90.53 |
| | | PM _{2.5} (9) | 27.28 | 90.53 |

EMISSION SOURCES - MAXIMUM ALLOWABLE EMISSION RATES

| | | | | |
|-------|---|--------------------------------|-------|-------|
| | | CO | 2.99 | 9.92 |
| | | TRS(6) | 6.11 | 20.28 |
| | | H ₂ SO ₄ | 0.46 | 1.53 |
| 13 | No. 2 Slaker Scrubber Stack ^{A1} | VOC(6) | 0.01 | 0.01 |
| | | PM(7) | 0.34 | 1.49 |
| | | PM ₁₀ (9) | 0.34 | 1.49 |
| | | PM _{2.5} (9) | 0.34 | 1.49 |
| | | TRS(6) | 0.01 | 0.01 |
| | | NH ₃ | 7.35 | 12.19 |
| 16/17 | Brown Stock Washers A and B ^{B1} | VOC(6) | 19.66 | 7.86 |
| | | TRS(6) | 0.39 | 0.16 |
| 27 | Brine Storage Tank | VOC(6) | <0.01 | <0.01 |
| | | TRS(6) | <0.01 | <0.01 |
| 30 | No. 1 Tall Oil Storage Tank ^{A2} | VOC(6) | 0.21 | 0.05 |
| | | TRS(6) | 0.02 | 0.01 |
| 31 | No. 2 Tall Oil Storage Tank ^{A2} | VOC(6) | 0.21 | 0.05 |
| | | TRS(6) | 0.02 | 0.01 |
| 32 | Turpentine Storage Tank ^{B2} | VOC(6) | 0.03 | 0.12 |

| | | | | |
|------|--|--------|-------|------|
| 36 | No. 5 White Liquor Tank Vent ^{A3} | VOC(6) | 0.25 | 1.10 |
| | | TRS(6) | 0.59 | 2.60 |
| 39## | South Mud Tank | --- | --- | --- |
| 40## | North Mud Tank | --- | --- | --- |
| 41 | No. 3 Green Liquor Clarifier | VOC(6) | <0.01 | 0.01 |
| | | TRS(6) | 0.02 | 0.06 |

EMISSION SOURCES - MAXIMUM ALLOWABLE EMISSION RATES

| | | | | |
|------|---|--------|-------|-------|
| 43## | Weak Wash Storage Tank | --- | --- | --- |
| 44## | Scrubber Water Clarifier | --- | --- | --- |
| 45 | No. 1 White Liquor Storage Tank ^{A3} | VOC(6) | 0.25 | 1.10 |
| | | TRS(6) | 0.59 | 2.60 |
| 46 | No. 2 White Liquor Storage Tank ^{A3} | VOC(6) | 0.25 | 1.10 |
| | | TRS(6) | 0.59 | 2.60 |
| 47 | No. 1 Green Liquor Storage Tank ^{A5} | VOC(6) | 0.02 | 0.08 |
| | | TRS(6) | 0.09 | 0.40 |
| 49 | No. 2 Green Liquor Clarifier | VOC(6) | <0.01 | 0.01 |
| | | TRS(6) | 0.02 | 0.06 |
| 50 | Green Liquor Equalization Tank | VOC(6) | <0.01 | <0.01 |
| | | TRS(6) | <0.01 | <0.01 |
| 51 | No. 3 Green Liquor Storage Tank ^{A5} | VOC(6) | 0.02 | 0.08 |
| | | TRS(6) | 0.09 | 0.40 |
| 56 | "A" Blend Tank ^{A4,B3} | VOC(6) | 0.08 | 0.28 |
| | | TRS(6) | 0.01 | 0.03 |
| 57 | "B" Blend Tank ^{A4,B3} | VOC(6) | 0.03 | 0.12 |
| | | TRS(6) | <0.01 | 0.01 |
| 58 | Reject Tank ^{B3} | VOC(6) | 0.10 | 0.11 |
| | | TRS(6) | <0.01 | <0.01 |
| 61 | "A" High Density Storage Tank ^{A6} | VOC(6) | 0.33 | 1.43 |
| | | TRS(6) | 0.21 | 0.93 |
| 62 | "B" High Density Storage Tank ^{A6} | VOC(6) | 0.33 | 1.43 |
| | | TRS(6) | 0.21 | 0.93 |
| 63 | No. 1 Weak Black Liquor Storage Tank | VOC(6) | 0.35 | 1.55 |

EMISSION SOURCES - MAXIMUM ALLOWABLE EMISSION RATES

| | | | | |
|----|---------------------------------------|-------------------|-------|--------|
| | | TRS(6) | 0.10 | 0.44 |
| 64 | No. 2 Weak Black Liquor Storage Tank | VOC(6) | 0.35 | 1.55 |
| | | TRS(6) | 0.10 | 0.44 |
| 65 | Black Liquor Swing Tank | VOC(6) | 0.35 | 1.55 |
| | | TRS(6) | 0.24 | 1.04 |
| 66 | No. 1 Heavy Black Liquor Storage Tank | VOC(6) | 0.04 | 0.16 |
| | | TRS(6) | 0.17 | 0.74 |
| 67 | No. 2 Heavy Black Liquor Storage Tank | VOC(6) | 0.04 | 0.16 |
| | | TRS(6) | 0.17 | 0.74 |
| 68 | Boilout Tank | VOC(6) | 0.35 | 1.55 |
| | | TRS(6) | 0.24 | 1.03 |
| 72 | Gasoline Tank | VOC | --- | 0.30 |
| 80 | Wood Yard (5) | PM | 7.17 | 16.33 |
| | | PM ₁₀ | 2.89 | 6.69 |
| | | PM _{2.5} | <0.01 | 0.02 |
| 81 | Truck Traffic Fugitives (5) | PM | --- | 123.69 |
| | | PM ₁₀ | --- | 34.37 |
| | | PM _{2.5} | --- | 3.44 |
| 88 | No. 1 Causticizer | TRS(6) | 1.30 | 4.31 |
| | | NH ₃ | 4.47 | 14.82 |
| 89 | No. 2 Causticizer | TRS(6) | 1.30 | 4.31 |
| | | NH ₃ | 4.47 | 14.82 |
| 90 | No. 3 Causticizer | TRS(6) | 1.30 | 4.31 |
| | | NH ₃ | 4.47 | 14.82 |
| 91 | No. 4 Causticizer | TRS(6) | 1.30 | 4.31 |

EMISSION SOURCES - MAXIMUM ALLOWABLE EMISSION RATES

| | | | | |
|--|--|-------------------|-------|--------|
| | | NH ₃ | 4.47 | 14.82 |
| 92 | No. 5 Causticizer | TRS(6) | 1.30 | 4.31 |
| | | NH ₃ | 4.47 | 14.82 |
| 93 - 98 | Wastewater Collection and Treatment (5) | VOC(6) | 26.45 | 96.54 |
| | | TRS(6) | 3.64 | 13.30 |
| 99** | Power Boiler No. 3 Stack | VOC(10) | 2.54 | 9.95 |
| | | NO _x | 21.00 | 91.98 |
| | | SO ₂ | 1.59 | 1.44 |
| | | PM | 3.13 | 13.71 |
| | | PM ₁₀ | 3.13 | 13.71 |
| | | PM _{2.5} | 3.13 | 13.71 |
| | | CO | 37.80 | 165.56 |
| 100 | Chemi-Washer (5) ^{B5} | VOC(6) | 0.01 | 0.04 |
| | | TRS(6) | <0.01 | 0.02 |
| 101 – 130, 132 - 158 167 - 172, 174 – 175 (11) | Nos. 1 & 2 Linerboard Machines ^{B5} | VOC(6) | 27.66 | 88.84 |
| | | TRS(6) | 0.42 | 1.55 |
| 159 – 166, 173 (12) | Secondary Fiber System | VOC(6) | 0.34 | 1.24 |
| 192## | Lime Kiln Precoat Filter | --- | --- | --- |
| 193## | Precoat Mud Filter Vacuum Pump West | --- | --- | --- |
| 194## | Precoat Mud Filter Vacuum Pump East | --- | --- | --- |
| 205 | No. 4 White Liquor Storage Tank ^{A3} | VOC(6) | 0.25 | 1.10 |
| | | TRS(6) | 0.59 | 2.60 |
| 210 | West Black Liquor Storage Tank | VOC(6) | 0.35 | 1.55 |
| | | TRS(6) | 0.24 | 1.03 |

EMISSION SOURCES - MAXIMUM ALLOWABLE EMISSION RATES

| | | | | |
|-------|-----------------------------------|--------|------|------|
| 211 | Center Black Liquor Storage Tank | VOC(6) | 0.35 | 1.55 |
| | | TRS(6) | 0.24 | 1.03 |
| 212 | East Black Liquor Storage Tank | VOC(6) | 0.35 | 1.55 |
| | | TRS(6) | 0.24 | 1.03 |
| 213## | Eco-Filter White Liquor Feed tank | --- | --- | --- |
| 214## | White Liquor Eco-Filter | --- | --- | --- |
| 215## | Eco-Filter White Liquor Standpipe | --- | --- | --- |
| 216## | Eco-Filter Lime Mud Dilution Tank | --- | --- | --- |
| 217## | Eco-Filter Mud Washer | --- | --- | --- |

| | | | | |
|-------|---|-------------------|-------|-------|
| 218## | Eco-Filter Weak Wash Standpipe | --- | --- | --- |
| 221 | No. 2 Dry Bottom Mix Tank | VOC(6) | 0.46 | 2.00 |
| | | SO ₂ | 0.07 | 0.32 |
| | | TRS(6) | 0.61 | 2.68 |
| 222 | No. 1 Dry Bottom Mix Tank | VOC(6) | 0.46 | 2.00 |
| | | SO ₂ | 0.07 | 0.32 |
| | | TRS(6) | 0.61 | 2.68 |
| 224 | Lime Mud Reclaim System (5) | PM | 0.02 | 0.05 |
| | | PM ₁₀ | 0.01 | 0.03 |
| | | PM _{2.5} | <0.01 | <0.01 |
| 225 | No. 2 Fuel Oil Tank | VOC | ---- | 0.01 |
| 232## | Green Liquor Dregs Filter and Vacuum Pump | --- | --- | --- |
| 235 | Liquor Loading (5) | VOC(6) | 1.04 | 3.64 |

EMISSION SOURCES - MAXIMUM ALLOWABLE EMISSION RATES

| | | | | |
|-----------|---|---------------------------|--------|-------|
| 275 | Clean Condensate Collection Tank | VOC(6) | 0.01 | <0.01 |
| 278 | Turpentine Loading (5) | VOC(6) | 0.27 | 0.10 |
| 279 | Fuel Oil Day Tank | VOC | 0.07 | 0.01 |
| 280 | Fuel Oil Storage Tank | VOC | 0.07 | 0.04 |
| 281 | Pet Coke Silo Stack | PM | 0.26 | 1.13 |
| | | PM ₁₀ | 0.26 | 1.13 |
| | | PM _{2.5} | 0.26 | 1.13 |
| 282 | Bark Boiler Ash Bin | PM | 0.26 | 1.13 |
| | | PM ₁₀ | 0.26 | 1.13 |
| | | PM _{2.5} | 0.26 | 1.13 |
| 283 | Cooling Tower No. 1 | VOC(6) | 0.98 | 4.30 |
| 284 | Cooling Tower No. 2 | VOC(6) | 0.09 | 0.38 |
| 286 | Caustic Solution Tank | | | |
| | | NaSH/Na ₂ S### | 0.04 | 0.04 |
| NCG-FUG1 | Switching LVHC and HVLC NCG Venting For Bypass and Preventative Maintenance (5)(13) | VOC | 145.00 | 0.25 |
| | | TRS | 0.06 | <0.01 |
| | | Acetone | 2.40 | 0.02 |
| P-VBURNER | Propane Vaporizer Burner | VOC(6) | 0.16 | 0.04 |
| | | NO _x | 2.56 | 0.67 |
| | | SO ₂ | 0.10 | 0.03 |
| | | PM | 0.14 | 0.04 |
| | | PM ₁₀ | 0.14 | 0.04 |
| | | PM _{2.5} | 0.14 | 0.04 |
| | | CO | 1.47 | 0.38 |

EMISSION SOURCES - MAXIMUM ALLOWABLE EMISSION RATES

- (1) Emission point identification - either specific equipment designation or emission point number from plot plan.
 - (2) Specific point source name. For fugitive sources, use area name or fugitive source name.
 - (3) VOC - volatile organic compounds as defined in Title 30 Texas Administrative Code § 101.1
 - NO_x - total oxides of nitrogen
 - SO₂ - sulfur dioxide
 - PM - total particulate matter, suspended in the atmosphere, including PM₁₀ and PM_{2.5}, as represented
 - PM₁₀ - total particulate matter equal to or less than 10 microns in diameter, including PM_{2.5}, as represented
 - PM_{2.5} - particulate matter equal to or less than 2.5 microns in diameter
 - CO - carbon monoxide
 - H₂SO₄ - sulfuric acid
 - TRS - total reduced sulfide
 - HAP of - hazardous air pollutants as listed in § 112(b) of the Federal Clean Air Act or Title 40 Code of Federal regulations Part 63, Subpart C
 - NH₃ - ammonia
 - NaSH - sodium hydrosulfide
 - Na₂S - sodium sulfide
 - (4) Compliance with annual emission limits (tons per year) is based on a 12 month rolling period.
 - (5) Emission rate is an estimate and is enforceable through compliance with the applicable special condition(s) and permit application representations.
 - (6) VOC and TRS are represented as carbon and H₂S, respectively, unless otherwise indicated.
 - (7) PM includes filterable and condensable PM, and compliance will be determined based on the sum of Method 5 and Method 202 (revised 12/1/2010).
 - (8) PM₁₀ and PM_{2.5} include filterable and condensable PM₁₀ and PM_{2.5}, respectively, and compliance will be determined based on the sum of Method 201A (revised 12/1/2010) and Method 202 (revised 12/1/2010).
 - (9) PM₁₀ and PM_{2.5} include filterable and condensable PM₁₀ and PM_{2.5}, respectively, and compliance will be determined based on the sum of Method 5 and Method 202 (Revised 12/1/2010) until such time that the EPA methods are revised to account for particle size distribution data for wet sources.
 - (10) VOC is represented as carbon
 - (11) Includes PM1 False Ceiling Exhaust Fan (EPN 167), PM1 Roof Exhaust (EPN 168), PM1 Cleaner Exhaust Southeast (EPN 174), PM1 Cleaner Exhaust Southwest (EPN 175), PM2 Roof Exhausts (EPNs 169, 171, and 175), PM2 5th Section Hood Exhaust Fan (EPN 172), PM Base Sheet Low Density Tank, No. 1 and No. 2 Paper Machine Base Sheet Secondary, PM TS Low Density Chest, Strained White Water Chest Strainers, White Top High Density Storage Chest, Excess White Water Storage Chest, and No. 2 Paper Machine Fourdrinier Low Vacuum Seal Tank.
 - (12) Includes SFS Exhaust Fan North (EPN 173), Secondary Fiber Surge Chest, Secondary Fiber Screen Stock Tank, Secondary Fiber Rejects Tank, Secondary Fiber Rejects Tank East, Secondary Fiber White Water Chest North, MD Storage Chest Secondary Fiber, Secondary Fiber Wax Tank, and Feed Tank for Combisorter.
 - (13) Emissions resulting from re-routing non-condensable gases between combustion sources [Lime Kiln (EPN 11) and Bark Boiler (EPN 2)].
 - (14) Planned startup and shutdown emissions are included, as well as planned maintenance activities identified as part of the permit alteration issued on April 25, 2013.
- A1 = For determination of compliance, the annual emissions should be summed for the No. 1 Slaker (EPN 10) and No. 2 Slaker (EPN 13).

B1-B6 = Hourly emission rates based on 24-hour averaging time.

EMISSION SOURCES - MAXIMUM ALLOWABLE EMISSION RATES

- A2 = For determination of compliance, the annual emissions should be summed for the No. 1 Tall Oil Storage Tank (EPN 30) and the No. 2 Tall Oil Storage Tank (EPN 31).
- A3 = For determination of compliance, the annual emissions should be summed for the Nos. 1, 2, 4, and 5 White Liquor Storage Tanks (EPNs 36, 45, 46, and 205).
- A4 = For determination of compliance, the annual emissions should be summed for the "A" Blend Tank (EPN 56) and the "B" Blend Tank (EPN 57).
- A5 = For determination of compliance, the annual emissions should be summed for the No. 1 Green Liquor Storage Tank (EPN 47) and the No. 2 Green Liquor Storage Tank (EPN 51).
- A6 = For determination of compliance, the annual emissions should be summed for the "A" High Density Storage Tank (EPN 61) and the "B" High Density Storage Tank (EPN 62).
- * Compliance with TRS and SO₂ short-term emission rates is based on a 12-hour block average. Short-term emission rates for all other pollutants are based on a 24-hour rolling average.
- ** Compliance with CO and NO_x short-term emission rates is based on a 30-day rolling average. Compliance with NH₃ short-term emission rate is based on a 3-hour average. Short-term emission rates for all other pollutants are based on a 24-hour rolling average.
- *** Compliance with CO and NO_x short-term emission rate is based on a 30-day rolling average. Compliance with TRS short-term emission rate is based on a 12-hour block average. Short-term emission rates for all other pollutants are based on a 24-hour rolling average.
- # Compliance with PM, PM₁₀, and PM_{2.5} short-term emission rate is based on a 3-hour average.
- ## This piece of equipment is authorized by the permit and is no longer considered a source of emissions.
- ### Emissions conservatively assumed to be 100 percent NaSH or 100 percent Na₂S.

Date: May 6, 2013