EMISSION SOURCES - MAXIMUM ALLOWABLE EMISSION RATES

Permit Number 35732

This table lists the maximum allowable emission rates and all sources of air contaminants on the applicant's property covered by this permit. The emission rates shown are those derived from information submitted as part of the application for permit and are the maximum rates allowed for these facilities. Any proposed increase in emission rates may require an application for a modification of the facilities covered by this permit.

AIR CONTAMINANTS DATA

Emission	Source	Air Contaminant	Emission Rates *	
Point No. (1)	Name (2)	Name (3)	lb/hr	TPY**
1	Dryer Baghouse Stack	PM	13.20	5.78
1	Diyer Bayriouse Stack	PM ₁₀	9.20	4.03
		VOC	12.80	5.60
		NO _x	22.00	9.63
		CO	52.00	22.75
		SO ₂	4.40	1.93
2	Material Handling (4)	PM	1.44	0.63
_	waterial Hariding (4)	PM ₁₀	0.41	0.18
		1 14110	0.41	0.10
3	Aggregate Stockpiles (4)	PM		2.51
		PM_{10}		1.26
4	Oil Heater	PM_{10}	0.15	0.65
		VOC	0.11	0.47
		NO_x	1.94	8.51
		CO	0.17	0.76
		SO ₂	0.01	0.05
		_		
5	Asphalt Storage Tanks	VOC	0.36	0.09
6	Diesel Storage Tank	VOC	0.35	0.01
	<u> </u>			
7	Antistrip Additive Tank	VOC	0.14	<0.01
	•			

⁽¹⁾ Emission point identification - either specific equipment designation or emission point number from a plot plan.

⁽²⁾ Specific point source names. For fugitive sources, use an area name or fugitive source name.

EMISSION SOURCES - MAXIMUM ALLOWABLE EMISSION RATES

(3) PM - particulate matter, suspended in the atmosphere, including PM₁₀ and PM_{2.5}

 PM_{10} - particulate matter equal to or less than 10 microns in diameter $PM_{2.5}$ - particulate matter equal to or less than 2.5 microns in diameter

VOC - volatile organic compounds as defined in Title 30 Texas Administrative Code § 101.1

NO_x - total oxides of nitrogen

CO - carbon monoxide

SO₂ - sulfur dioxide

(4) Fugitive emissions are an estimate only.

* Emission rates are based on and the facilities are limited by the following maximum operating schedule and production rates:

<u>14</u> Hrs/day <u>6</u> Days/week <u>50</u> Weeks/year or <u>4,200</u> Hrs/year

Standard hot mix asphalt: 400 tons/hour; 350,000 tons/year

RAP modified hot mix asphalt: 400 tons/hour; 100,000 tons/year

** Compliance with annual emission limits is based on a rolling 12-month period.

Dated November 9, 2009