

Emission Sources - Maximum Allowable Emission Rates

Permit Number 18356

This table lists the maximum allowable emission rates and all sources of air contaminants on the applicant's property covered by this permit. The emission rates shown are those derived from information submitted as part of the application for permit and are the maximum rates allowed for these facilities, sources, and related activities. Any proposed increase in emission rates may require an application for a modification of the facilities covered by this permit.

Air Contaminants Data

Emission Point No. (1)	Source Name (2)	Air Contaminant Name (3)	Emission Rates (6)	
			lbs/hour	TPY (4)
10	Planer Shavings Cyclone Stack	PM	2.00	8.76
		PM ₁₀	1.06	4.63
		PM _{2.5}	0.59	2.59
BLR1	Boiler No. 1 Cyclone Stack	PM	5.90	25.84
		PM ₁₀	5.90	25.84
		PM _{2.5}	3.54	15.51
		VOC	0.50	2.20
		NO _x	10.47	45.87
		CO	11.36	49.75
		SO ₂	0.74	3.23
BLR1a	Boiler Bypass Vent No. 1 Stack	PM	5.90	2.21
		PM ₁₀	5.90	2.21
		PM _{2.5}	3.54	1.33
		VOC	2.13	0.80
		NO _x	10.47	3.93
		CO	11.36	4.26
		SO ₂	0.74	0.28
BLR2	Boiler No. 2 Cyclone Stack	PM	5.90	25.84
		PM ₁₀	5.90	25.84
		PM _{2.5}	3.54	15.51
		VOC	0.50	2.20
		NO _x	10.47	45.87
		CO	11.36	49.75
		SO ₂	0.74	3.23

Emission Sources - Maximum Allowable Emission Rates

BLR2a	Boiler Bypass Vent No. 2 Stack	PM	5.90	2.21
		PM ₁₀	5.90	2.21
		PM _{2.5}	3.54	1.33
		VOC	2.13	0.80
		NO _x	10.47	3.93
		CO	11.36	4.26
		SO ₂	0.74	0.28
BLR3G	Boiler No. 3 Cyclone Stack	PM	5.90	25.84
		PM ₁₀	5.90	25.84
		PM _{2.5}	3.54	15.51
		VOC	0.50	2.20
		NO _x	10.47	45.87
		CO	11.36	49.75
		SO ₂	0.74	3.23
BLR3Ga	Boiler Bypass Vent No. 3 Stack	PM	5.90	2.21
		PM ₁₀	5.90	2.21
		PM _{2.5}	3.54	1.33
		VOC	2.13	0.80
		NO _x	10.47	3.93
		CO	11.36	4.26
		SO ₂	0.74	0.28
DK1	Steam Dry Kiln No. 1	VOC	4.40	227.20
DK2	Steam Dry Kiln No. 2	VOC	4.40	227.20
DK3	Steam Dry Kiln No. 3	VOC	2.95	227.20
TODK1	Thermal Oil Dry Kiln No. 1	VOC	20.96	227.20
TODK2	Thermal Oil Dry Kiln No. 2	VOC	20.96	227.20
KILNS	Total Combined Kilns (DK1, DK2, DK3, TODK1 and TODK1)	VOC	--	227.20
TOHSTK	Thermal Oil Heater Stack	PM	0.43	1.86
		PM ₁₀	0.43	1.86

Emission Sources - Maximum Allowable Emission Rates

		PM _{2.5}	0.43	1.86
		VOC	0.31	1.35
		NO _x	3.53	15.45
		CO	3.23	14.16
		SO ₂	0.03	0.15
SAWFUG	Log Sawing Fugitives (5)	PM	2.20	2.56
		PM ₁₀	0.14	0.17
		PM _{2.5}	0.14	0.17
DBRKFUG	Debarking Fugitives (5)	PM	0.03	0.03
		PM ₁₀	0.01	0.01
		PM _{2.5}	0.01	0.01
CHIPFUG	Chipper Fugitives (5)	PM	0.01	0.01
		PM ₁₀	<0.01	0.01
		PM _{2.5}	<0.01	0.01
SCRNFUG	Screening Fugitives (5)	PM	0.01	0.01
		PM ₁₀	<0.01	<0.01
		PM _{2.5}	<0.01	<0.01
TUBFUG	Tub Grinder Fugitives (5)	PM	0.02	0.02
		PM ₁₀	0.01	0.01
		PM _{2.5}	0.01	0.01
BRKLOAD	Bark Loading Fugitives (5)	PM	0.27	0.35
		PM ₁₀	0.02	0.02
		PM _{2.5}	0.02	0.02
CTRKLOAD	Chip Truck Loading (5)	PM	1.18	1.23
		PM ₁₀	0.08	0.08
		PM _{2.5}	0.08	0.08
SILOLOAD	Sawdust Silo Loading (5)	PM	0.93	1.11
		PM ₁₀	0.06	0.07
		PM _{2.5}	0.06	0.07
DTRKLOAD	Sawdust Truck Loading (5)	PM	0.24	0.25
		PM ₁₀	0.02	0.02

Emission Sources - Maximum Allowable Emission Rates

		PM _{2.5}	0.02	0.02
STRKLOAD	Shavings Truck Loading (5)	PM	0.40	0.35
		PM ₁₀	0.03	0.02
		PM _{2.5}	0.03	0.02
BSAWFUG	Buck Saw Fugitives (5)	PM	0.18	0.21
		PM ₁₀	0.01	0.01
		PM _{2.5}	0.01	0.01
ASHLOAD	Ash Handling (5)	PM	0.05	0.01
		PM ₁₀	0.01	<0.01
		PM _{2.5}	0.01	<0.01
PAINT	Paint Marking (5)	VOC	1.00	0.60
		PM	0.04	0.02
		PM ₁₀	0.04	0.02
		PM _{2.5}	0.04	0.02
PARTWASH	Remote Reservoir Parts Washer (4)	VOC	0.67	0.74

- (1) Emission point identification - either specific equipment designation or emission point number from plot plan.
- (2) Specific point source name. For fugitive sources, use area name or fugitive source name.
- (3) VOC - volatile organic compounds as defined in Title 30 Texas Administrative Code § 101.1
 NO_x - total oxides of nitrogen
 SO₂ - sulfur dioxide
 PM - total particulate matter, suspended in the atmosphere, including PM₁₀ and PM_{2.5}, as represented
 PM₁₀ - total particulate matter equal to or less than 10 microns in diameter, including PM_{2.5}, as represented
 PM_{2.5} - particulate matter equal to or less than 2.5 microns in diameter
 CO - carbon monoxide
- (4) Compliance with annual emission limits (tons per year) is based on a 12 month rolling period.
- (5) Emission rate is an estimate and is enforceable through compliance with the applicable special condition(s) and permit application representations.
- (6) Planned startup and shutdown emissions are included. Maintenance activities are not authorized by this permit.

Date: September 30, 2014