

EMISSION SOURCES - MAXIMUM ALLOWABLE EMISSION RATES

Permit Number 26712

This table lists the maximum allowable emission rates and all sources of air contaminants on the applicant's property covered by this permit. The emission rates shown are those derived from information submitted as part of the application for permit and are the maximum rates allowed for these facilities. Any proposed increase in emission rates may require an application for a modification of the facilities covered by this permit.

AIR CONTAMINANTS DATA

Emission Point No. (1)	Source Name (2)	Air Contaminant Name (3)	Emission Rates *	
			lb/hr	TPY
10	Dryer Baghouse Stack (5)	PM	16.50	14.85
		PM ₁₀	11.50	10.35
		VOC (a)	16.00	12.80
		VOC (b)	90.40	5.65
		VOC(c)	787.50	43.75
		NO _x	27.50	24.75
		SO ₂	29.00	26.10
		CO	65.00	58.50
		TOC	22.00	19.80
		HCl	0.11	0.09
11	Lime Silo Baghouse	PM ₁₀	0.05	<0.01
RMSPF	Raw Material Stockpile (4) Fugitives	PM	-	2.17
		PM ₁₀	-	1.03
CMSPF	Cold Mix Stockpile	VOC(c)	21.00	5.47
1-6	Material Handling (4)	PM	<0.03	0.02
		PM ₁₀	0.01	0.01
9	Aggregate Screen (4)	PM	0.84	0.75
		PM ₁₀	0.40	0.36
18	RAP Feed Bin (4)	PM	<0.01	0.01
		PM ₁₀	<0.01	<0.01
19 and 20	RAP Conveyors (4)	PM	<0.01	0.04
		PM ₁₀	<0.01	<0.02

EMISSION SOURCES - MAXIMUM ALLOWABLE EMISSION RATES

AIR CONTAMINANTS DATA

Emission * Point No. (1)	Source Name (2)	Air Contaminant Name (3)	Emission Rates	
			lb/hr	TPY
21	RAP Screen (4)	PM	<0.01	0.32
		PM ₁₀	<0.01	0.15
22	RAP Crusher (4)	PM ₁₀	<0.30	0.11
14	Hot Oil Heater Stack (5)	PM ₁₀	0.02	0.05
		NO _x	0.29	0.64
		SO ₂	0.04	0.10
		CO	0.25	0.54
		TOC	0.03	0.07
12A	AC Tank No. 1 (5)	TOC	<0.01	0.02
		PM	<0.0001	<0.002
		CO	<0.0001	<0.01
12B	AC Tank No. 2 (5)	TOC	<0.01	0.02
		PM	<0.0001	<0.002
		CO	<0.0001	<0.01
12C	AC Tank No. 3 (5)	TOC	<0.01	0.02
15	Silo Filling (5)	PM	0.29	0.26
		Organic PM	0.17	0.15
		VOC	6.10	5.48
		CO	0.59	0.53
16	Truck Loadout (4 and 5)	PM	0.29	0.26
	Fugitives	Organic PM	0.17	0.15
		VOC	6.10	5.48
		CO	0.59	0.53
18	Yard Emissions (4 and 5)	Organic PM	0.05	0.04
		TOC	0.55	0.50
		CO	0.18	0.16

EMISSION SOURCES - MAXIMUM ALLOWABLE EMISSION RATES

- (1) Emission point identification - either specific equipment designation or emission point number from plot plan.
- (2) Specific point source name. For fugitive sources use area name or fugitive source name.
- (3) PM - particulate matter, suspended in the atmosphere, including PM₁₀.
PM₁₀ - particulate matter equal to or less than 10 microns in diameter. Where PM is not listed, it shall be assumed that no particulate matter greater than 10 microns is emitted.
VOC - volatile organic compounds as defined in Title 30 Texas Administrative Code § 101.1.
VOC (a) - mainly asphalt vapors
VOC (b) - additional VOC due to the use of crumb rubber
VOC (c) - primarily diesel or kerosene vapors
TOC - total organic compounds
NO_x - total oxides of nitrogen
SO₂ - sulfur dioxide
CO - carbon monoxide
HCl - hydrogen chloride
- (4) Fugitive emissions are an estimate only.
- (5) Speciated compounds to include hazardous air pollutants and their respective emission rates are represented in the permit application. The speciated compounds are included in the PM and /or VOC values shown on the maximum allowable emission rates table.

* Emission rates are based on and the facilities are limited by the following maximum production rates:

Standard Hot Mix: Tons/hour 500 Tons/year 800,000

Hot Mix with Crumb Rubber option: Tons/hour 400 Tons/year 50,000

Emulsified Cold Mix: Tons/hour 450 Tons/week 10,000 Tons/year 50,000

Dated October 27, 2003