

The REST API is now versioned. For more information, see "[About API versioning](#)."

Secret scanning

Use the REST API to retrieve and update secret alerts from a repository.

About secret scanning

You can use the API to:

- Enable or disable secret scanning and push protection for a repository. For more information, see "[Repositories](#)" and expand the "Properties of the `security_and_analysis` object" section in the REST API documentation.
- Retrieve and update secret scanning alerts from a repository. For further details, see the sections below.

For more information about secret scanning, see "[About secret scanning](#)."

List secret scanning alerts for an enterprise

Lists secret scanning alerts for eligible repositories in an enterprise, from newest to oldest. To use this endpoint, you must be a member of the enterprise, and you must use an access token with the `repo` scope or `security_events` scope. Alerts are only returned for organizations in the enterprise for which you are an organization owner or a [security manager](#).

Parameters for "List secret scanning alerts for an enterprise"

Headers

accept string

Setting to `application/vnd.github+json` is recommended.

Path parameters

enterprise string **Required**

The slug version of the enterprise name. You can also substitute this value with the enterprise id.

Query parameters

state string

Set to `open` or `resolved` to only list secret scanning alerts in a specific state.

Can be one of: `open` , `resolved`

secret_type string

A comma-separated list of secret types to return. By default all secret types are returned. See "[Secret scanning patterns](#)" for a

A comma-separated list of secret types to return. By default all secret types are returned. See [secret scanning patterns](#) for a complete list of secret types.

resolution string

A comma-separated list of resolutions. Only secret scanning alerts with one of these resolutions are listed. Valid resolutions are `false_positive`, `wont_fix`, `revoked`, `pattern_edited`, `pattern_deleted` or `used_in_tests`.

sort string

The property to sort the results by. `created` means when the alert was created. `updated` means when the alert was updated or resolved.

Default: `created`

Can be one of: `created`, `updated`

direction string

The direction to sort the results by.

Default: `desc`

Can be one of: `asc`, `desc`

per_page integer

The number of results per page (max 100).

Default: `30`

before string

A cursor, as given in the [Link header](#). If specified, the query only searches for results before this cursor.

after string

A cursor, as given in the [Link header](#). If specified, the query only searches for results after this cursor.

HTTP response status codes for "List secret scanning alerts for an enterprise"

Status code	Description
200	OK
404	Resource not found
503	Service unavailable

Code samples for "List secret scanning alerts for an enterprise"

GET /enterprises/{enterprise}/secret-scanning/alerts

cURL

JavaScript

GitHub CLI

```
curl -L \ -H "Accept: application/vnd.github+json" \ -H "Authorization: Bearer <YOUR-TOKEN>" \ -H "X-GitHub-API-Version: 2022-11-28" \ https://api.github.com/enterprises/ENTERPRISE/secret-scanning/alerts
```

Response

Example response

Response schema

Status: 200

```
[ { "number": 2, "created_at": "2020-11-06T18:48:51Z", "url": "https://api.github.com/repos/owner/private-repo/secret-scanning/alerts/2", "html_url": "https://github.com/owner/private-repo/security/secret-scanning/2", "locations_url": "https://api.github.com/repos/owner/private-repo/secret-scanning/alerts/2/locations", "state": "resolved", "resolution": "false_positive", "resolved_at": "2020-11-07T02:47:13Z", "resolved_by": { "login": "monalisa", "id": 2, "node_id": "MDQ6VXNlcjI=", "avatar_url": "https://alambic.github.com/avatars/u/2?", "gravatar_id": "", "url": "https://api.github.com/users/monalisa", "html_url": "https://github.com/monalisa", "followers_url": "https://api.github.com/users/monalisa/followers", "following_url":
```

List secret scanning alerts for an organization

✔ Works with [GitHub Apps](#)

Lists secret scanning alerts for eligible repositories in an organization, from newest to oldest. To use this endpoint, you must be an administrator or security manager for the organization, and you must use an access token with the `repo` scope or `security_events` scope. For public repositories, you may instead use the `public_repo` scope.

GitHub Apps must have the `secret_scanning_alerts` read permission to use this endpoint.

Parameters for "List secret scanning alerts for an organization"

Headers

accept string
Setting to `application/vnd.github+json` is recommended.

Path parameters

org string **Required**
The organization name. The name is not case sensitive.

Query parameters

state string
Set to `open` or `resolved` to only list secret scanning alerts in a specific state.
Can be one of: `open` , `resolved`

secret_type string
A comma-separated list of secret types to return. By default all secret types are returned. See "[Secret scanning patterns](#)" for a complete list of secret types.

resolution string
A comma-separated list of resolutions. Only secret scanning alerts with one of these resolutions are listed. Valid resolutions are `false_positive` , `wont_fix` , `revoked` , `pattern_edited` , `pattern_deleted` or `used_in_tests` .

sort string
The property to sort the results by. `created` means when the alert was created. `updated` means when the alert was updated or resolved.
Default: `created`
Can be one of: `created` , `updated`

direction string
The direction to sort the results by.

Default: desc
Can be one of: asc , desc

page integer

Page number of the results to fetch.

Default: 1

per_page integer

The number of results per page (max 100).

Default: 30

before string

A cursor, as given in the [Link header](#). If specified, the query only searches for events before this cursor. To receive an initial cursor on your first request, include an empty "before" query string.

after string

A cursor, as given in the [Link header](#). If specified, the query only searches for events after this cursor. To receive an initial cursor on your first request, include an empty "after" query string.

HTTP response status codes for "List secret scanning alerts for an organization"

Status code	Description
200	OK
404	Resource not found
503	Service unavailable

Code samples for "List secret scanning alerts for an organization"

GET /orgs/{org}/secret-scanning/alerts

cURLJavaScriptGitHub CLI

```
curl -L \ -H "Accept: application/vnd.github+json" \ -H "Authorization: Bearer <YOUR-TOKEN>" \ -H "X-GitHub-API-Version: 2022-11-28" \ https://api.github.com/orgs/ORG/secret-scanning/alerts
```

Response

Example responseResponse schema

Status: 200

```
[ { "number": 2, "created_at": "2020-11-06T18:48:51Z", "url": "https://api.github.com/repos/owner/private-repo/secret-scanning/alerts/2", "html_url": "https://github.com/owner/private-repo/security/secret-scanning/2", "locations_url": "https://api.github.com/repos/owner/private-repo/secret-scanning/alerts/2/locations", "state": "resolved", "resolution": "false_positive", "resolved_at": "2020-11-07T02:47:13Z", "resolved_by": { "login": "monalisa", "id": 2, "node_id": "MDQ6VXNlcjI=", "avatar_url": "https://alambic.github.com/avatars/u/2?", "gravatar_id": "", "url": "https://api.github.com/users/monalisa", "html_url": "https://github.com/monalisa", "followers_url": "https://api.github.com/users/monalisa/followers", "following_url":
```

List secret scanning alerts for a repository

✔ Works with [GitHub Apps](#)

Lists secret scanning alerts for an eligible repository, from newest to oldest. To use this endpoint, you must be an administrator for the repository or for the organization that owns the repository, and you must use a personal access token with the `repo` scope or `security_events` scope. For public repositories, you may instead use the `public_repo` scope.

GitHub Apps must have the `secret_scanning_alerts` read permission to use this endpoint.

Parameters for "List secret scanning alerts for a repository"

Headers

accept string
Setting to `application/vnd.github+json` is recommended.

Path parameters

owner string **Required**
The account owner of the repository. The name is not case sensitive.

repo string **Required**
The name of the repository without the `.git` extension. The name is not case sensitive.

Query parameters

state string
Set to `open` or `resolved` to only list secret scanning alerts in a specific state.
Can be one of: `open` , `resolved`

secret_type string
A comma-separated list of secret types to return. By default all secret types are returned. See "[Secret scanning patterns](#)" for a complete list of secret types.

resolution string
A comma-separated list of resolutions. Only secret scanning alerts with one of these resolutions are listed. Valid resolutions are `false_positive` , `wont_fix` , `revoked` , `pattern_edited` , `pattern_deleted` or `used_in_tests` .

sort string
The property to sort the results by. `created` means when the alert was created. `updated` means when the alert was updated or resolved.
Default: `created`
Can be one of: `created` , `updated`

direction string
The direction to sort the results by.
Default: `desc`
Can be one of: `asc` , `desc`

page integer

Page number of the results to fetch.

Default: 1

per_page integer

The number of results per page (max 100).

Default: 30

before string

A cursor, as given in the [Link header](#). If specified, the query only searches for events before this cursor. To receive an initial cursor on your first request, include an empty "before" query string.

after string

A cursor, as given in the [Link header](#). If specified, the query only searches for events after this cursor. To receive an initial cursor on your first request, include an empty "after" query string.

HTTP response status codes for "List secret scanning alerts for a repository"

Status code	Description
200	OK
404	Repository is public or secret scanning is disabled for the repository
503	Service unavailable

Code samples for "List secret scanning alerts for a repository"

GET

/repos/{owner}/{repo}/secret-scanning/alerts

cURL

JavaScript

GitHub CLI

```
curl -L \ -H "Accept: application/vnd.github+json" \ -H "Authorization: Bearer <YOUR-TOKEN>" \ -H "X-GitHub-API-Version: 2022-11-28" \ https://api.github.com/repos/OWNER/REPO/secret-scanning/alerts
```

Response

Example response

Response schema

Status: 200

[{ "number": 2, "created_at": "2020-11-06T18:48:51Z", "url": "https://api.github.com/repos/owner/private-repo/secret-scanning/alerts/2", "html_url": "https://github.com/owner/private-repo/security/secret-scanning/2", "locations_url": "https://api.github.com/repos/owner/private-repo/secret-scanning/alerts/2/locations", "state": "resolved", "resolution": "false_positive", "resolved_at": "2020-11-07T02:47:13Z", "resolved_by": { "login": "monalisa", "id": 2, "node_id": "MDQ6VXNlcjI=", "avatar_url": "https://alambic.github.com/avatars/u/2?", "gravatar_id": "", "url": "https://api.github.com/users/monalisa", "html_url": "https://github.com/monalisa", "followers_url": "https://api.github.com/users/monalisa/followers", "following_url":

Get a secret scanning alert

✔ Works with [GitHub Apps](#)

Gets a single secret scanning alert detected in an eligible repository. To use this endpoint, you must be an administrator for the repository or for the organization that owns the repository, and you must use a personal access token with the `repo` scope or `security_events` scope. For public repositories, you may instead use the `public_repo` scope.

GitHub Apps must have the `secret_scanning_alerts` read permission to use this endpoint.

Parameters for "Get a secret scanning alert"

Headers

accept string
Setting to `application/vnd.github+json` is recommended.

Path parameters

- owner** string **Required**
The account owner of the repository. The name is not case sensitive.
- repo** string **Required**
The name of the repository without the `.git` extension. The name is not case sensitive.
- alert_number** integer **Required**
The number that identifies an alert. You can find this at the end of the URL for a code scanning alert within GitHub, and in the `number` field in the response from the `GET /repos/{owner}/{repo}/code-scanning/alerts` operation.

HTTP response status codes for "Get a secret scanning alert"

Status code	Description
200	OK
304	Not modified
404	Repository is public, or secret scanning is disabled for the repository, or the resource is not found
503	Service unavailable

Code samples for "Get a secret scanning alert"

GET `/repos/{owner}/{repo}/secret-scanning/alerts/{alert_number}`

cURLJavaScriptGitHub CLI

```
curl -L \ -H "Accept: application/vnd.github+json" \ -H "Authorization: Bearer <YOUR-TOKEN>" \ -H "X-GitHub-API-Version: 2022-11-28" \ https://api.github.com/repos/OWNER/REPO/secret-scanning/alerts/ALERT_NUMBER
```



Response

Example response

Response schema

Status: 200

```
{ "number": 42, "created_at": "2020-11-06T18:18:30Z", "url": "https://api.github.com/repos/owner/private-repo/secret-scanning/alerts/42", "html_url": "https://github.com/owner/private-repo/security/secret-scanning/42", "locations_url": "https://api.github.com/repos/owner/private-repo/secret-scanning/alerts/42/locations", "state": "open", "resolution": null, "resolved_at": null, "resolved_by": null, "secret_type": "mailchimp_api_key", "secret_type_display_name": "Mailchimp API Key", "secret": "XXXXXXXXXXXXXXXXXXXXXXXXXXXX-us2", "push_protection_bypassed_by": null, "push_protection_bypassed": false, "push_protection_bypassed_at": null, "resolution_comment": null }
```

Update a secret scanning alert [↗](#)

✔ Works with [GitHub Apps](#)

Updates the status of a secret scanning alert in an eligible repository. To use this endpoint, you must be an administrator for the repository or for the organization that owns the repository, and you must use a personal access token with the `repo` scope or `security_events` scope. For public repositories, you may instead use the `public_repo` scope.

GitHub Apps must have the `secret_scanning_alerts` write permission to use this endpoint.

Parameters for "Update a secret scanning alert"

Headers

accept string

Setting to `application/vnd.github+json` is recommended.

Path parameters

owner string **Required**

The account owner of the repository. The name is not case sensitive.

repo string **Required**

The name of the repository without the `.git` extension. The name is not case sensitive.

alert_number integer **Required**

The number that identifies an alert. You can find this at the end of the URL for a code scanning alert within GitHub, and in the `number` field in the response from the `GET /repos/{owner}/{repo}/code-scanning/alerts` operation.

Body parameters

state string **Required**

Sets the state of the secret scanning alert. You must provide `resolution` when you set the state to `resolved`.

Can be one of: `open`, `resolved`

Can be one of: `open`, `resolved`

resolution string or null

Required when the `state` is `resolved`. The reason for resolving the alert.

Can be one of: `false_positive`, `wont_fix`, `revoked`, `used_in_tests`, `null`

resolution_comment string or null

An optional comment when closing an alert. Cannot be updated or deleted. Must be `null` when changing `state` to `open`.

HTTP response status codes for "Update a secret scanning alert"

Status code	Description
200	OK
400	Bad request, resolution comment is invalid or the resolution was not changed.
404	Repository is public, or secret scanning is disabled for the repository, or the resource is not found
422	State does not match the resolution or resolution comment
503	Service unavailable

Code samples for "Update a secret scanning alert"

PATCH /repos/{owner}/{repo}/secret-scanning/alerts/{alert_number}

cURL JavaScript GitHub CLI



```
curl -L \ -X PATCH \ -H "Accept: application/vnd.github+json" \ -H "Authorization: Bearer <YOUR-TOKEN>" \ -H "X-GitHub-API-Version: 2022-11-28" \ https://api.github.com/repos/OWNER/REPO/secret-scanning/alerts/ALERT_NUMBER \ -d '{"state":"resolved","resolution":"false_positive"}'
```

Response

Example response

Response schema

Status: 200

```
{ "number": 42, "created_at": "2020-11-06T18:18:30Z", "url": "https://api.github.com/repos/owner/private-repo/secret-scanning/alerts/42", "html_url": "https://github.com/owner/private-repo/security/secret-scanning/42", "locations_url": "https://api.github.com/repos/owner/private-repo/secret-scanning/alerts/42/locations", "state": "resolved", "resolution": "used_in_tests", "resolved_at": "2020-11-16T22:42:07Z", "resolved_by": { "login": "monalisa", "id": 2, "node_id": "MDQ6VXNlcjI=", "avatar_url": "https://alambic.github.com/avatars/u/2?", "gravatar_id": "", "url": "https://api.github.com/users/monalisa", "html_url": "https://github.com/monalisa", "followers_url": "https://api.github.com/users/monalisa/followers", "following_url":
```

List locations for a secret scanning alert

✔ Works with [GitHub Apps](#)

Lists all locations for a given secret scanning alert for an eligible repository. To use this endpoint, you must be an

administrator for the repository or for the organization that owns the repository, and you must use a personal access token with the `repo` scope or `security_events` scope. For public repositories, you may instead use the `public_repo` scope.

GitHub Apps must have the `secret_scanning_alerts` read permission to use this endpoint.

Parameters for "List locations for a secret scanning alert"

Headers

accept string
Setting to `application/vnd.github+json` is recommended.

Path parameters

owner string **Required**
The account owner of the repository. The name is not case sensitive.

repo string **Required**
The name of the repository without the `.git` extension. The name is not case sensitive.

alert_number integer **Required**
The number that identifies an alert. You can find this at the end of the URL for a code scanning alert within GitHub, and in the `number` field in the response from the `GET /repos/{owner}/{repo}/code-scanning/alerts` operation.

Query parameters

page integer
Page number of the results to fetch.
Default: `1`

per_page integer
The number of results per page (max 100).
Default: `30`

HTTP response status codes for "List locations for a secret scanning alert"

Status code	Description
200	OK
404	Repository is public, or secret scanning is disabled for the repository, or the resource is not found
503	Service unavailable

Code samples for "List locations for a secret scanning alert"

GET

`/repos/{owner}/{repo}/secret-scanning/alerts/{alert_number}/locations`

cURL

JavaScript

GitHub CLI

```
curl -L \
  -H "Accept: application/vnd.github+json" \
  -H "Authorization: Bearer <YOUR-TOKEN>" \
  -H "X-GitHub-API-Version: 2022-11-28" \
  https://api.github.com/repos/OWNER/REPO/secret-scanning/alerts/ALERT_NUMBER/locations
```

Response

Example response

Response schema

Status: 200

```
[ { "type": "commit", "details": { "path": "/example/secrets.txt", "start_line": 1, "end_line": 1, "start_column": 1, "end_column": 64, "blob_sha": "af5626b4a114abcb82d63db7c8082c3c4756e51b", "blob_url": "https://api.github.com/repos/octocat/hello-world/git/blobs/af5626b4a114abcb82d63db7c8082c3c4756e51b", "commit_sha": "f14d7debf9775f957cf4f1e8176da0786431f72b", "commit_url": "https://api.github.com/repos/octocat/hello-world/git/commits/f14d7debf9775f957cf4f1e8176da0786431f72b" } }, { "type": "issue_title", "details": { "issue_title_url": "https://api.github.com/repos/octocat/Hello-World/issues/1347" } }, { "type": "issue_body", "details": { "issue_body_url": "https://api.github.com/repos/octocat/Hello-World/issues/1347" } }, { "type":
```

Legal