

REST API / Activity / Watching

The REST API is now versioned. For more information, see "About API versioning."

Watching

Use the REST API to subscribe to notifications for activity in a repository.

About watching @

You can use the REST API to subscribe to notifications for activity in a repository. To bookmark a repository instead, see "<u>Starring</u>."

Watching versus starring @

In August 2012, we <u>changed the way watching works</u> on GitHub. Some API client applications may still be using the original "watcher" endpoints for accessing this data. You should now use the "star" endpoints instead. For more information, see the REST API "<u>Starring</u>" documentation and the <u>Watcher API Change post</u>.

In responses from the REST API, subscribers_count corresponds to the number of watchers, whereas watchers, watchers count, and stargazers count correspond to the number of users that have starred a repository.

List watchers @

Works with <u>GitHub Apps</u>

Lists the people watching the specified repository.

Parameters for "List watchers"

Headers

accept string

Setting to application/vnd.github+json is recommended.

Path parameters

owner string Required

The account owner of the repository. The name is not case sensitive.

repo string Required

The name of the repository without the .git extension. The name is not case sensitive.

Query parameters

pei_page integer

The number of results per page (max 100).

Default: 30

page integer

Page number of the results to fetch.

Default: 1

HTTP response status codes for "List watchers"

Status code	Description
200	OK

Code samples for "List watchers"



Response

```
Example response Response schema

Status: 200

[ { "login": "octocat", "id": 1, "node_id": "MDQ6VXNlcjE=", "avatar_url": "https://github.com/images/error/octocat_happy.gif", "gravatar_id": "", "url": "https://api.github.com/users/octocat", "html_url": "https://github.com/octocat", "followers_url": "https://api.github.com/users/octocat/followers", "following_url": "https://api.github.com/users/octocat/following{/other_user}", "gists_url": "https://api.github.com/users/octocat/starred{/owner}{/repo}", "subscriptions_url": "https://api.github.com/users/octocat/orgs", "wittps://api.github.com/users/octocat/orgs", "organizations_url": "https://api.github.com/users/octocat/orgs", "wittps://api.github.com/users/octocat/orgs", "wittps://api.github.com/user
```

Get a repository subscription *∂*

Gets information about whether the authenticated user is subscribed to the repository.

Parameters for "Get a repository subscription"

Headers

accept string

Setting to application/vnd.github+json is recommended.

Path parameters

owner string Required

The account owner of the repository. The name is not case sensitive.

repo string Required

The name of the repository without the .git extension. The name is not case sensitive.

HTTP response status codes for "Get a repository subscription"

Status code	Description
200	if you subscribe to the repository
403	Forbidden
404	Not Found if you don't subscribe to the repository

Code samples for "Get a repository subscription"



if you subscribe to the repository

```
Example response Response schema

Status: 200

{ "subscribed": true, "ignored": false, "reason": null, "created_at": "2012-10-06T21:34:12Z", "url": "https://api.github.com/repos/octocat/example/subscription", "repository_url": "https://api.github.com/repos/octocat/example" }
```

Set a repository subscription ∂

If you would like to watch a repository, set subscribed to true. If you would like to ignore notifications made within a repository, set ignored to true. If you would like to stop watching a repository, delete the repository's subscription completely.

Parameters for "Set a repository subscription"

Headers

accept string

Setting to application/vnd.github+json is recommended.

Path parameters

owner string Required

The account owner of the repository. The name is not case sensitive.

repo string Required

The name of the repository without the <code>.git</code> extension. The name is not case sensitive.

Body parameters

subscribed boolean

Determines if notifications should be received from this repository.

ignored boolean

Determines if all notifications should be blocked from this repository.

HTTP response status codes for "Set a repository subscription"

Status code Description

200 OK

Code samples for "Set a repository subscription"



Response

Example response Response schema

Status: 200

{ "subscribed": true, "ignored": false, "reason": null, "created_at": "2012-10-06T21:34:12Z", "url": "https://api.github.com/repos/octocat/example/subscription", "repository_url": "https://api.github.com/repos/octocat/example" }

Delete a repository subscription *∂*

This endpoint should only be used to stop watching a repository. To control whether or not you wish to receive

notifications from a repository, set the repository's subscription manually.

Parameters for "Delete a repository subscription"

Headers

accept string

Setting to application/vnd.github+json is recommended.

Path parameters

owner string Required

The account owner of the repository. The name is not case sensitive.

repo string Required

The name of the repository without the <code>.git</code> extension. The name is not case sensitive.

HTTP response status codes for "Delete a repository subscription"

Status code Description

No Content

Code samples for "Delete a repository subscription"



Response

Status: 204

List repositories watched by the authenticated user &

Lists repositories the authenticated user is watching.

Parameters for "List repositories watched by the authenticated user"

Headers

accept string

Query parameters

per_page integer

The number of results per page (max 100).

Default: 30

page integer

Page number of the results to fetch.

Default: 1

HTTP response status codes for "List repositories watched by the authenticated user"

Status code	Description
200	ОК
304	Not modified
401	Requires authentication
403	Forbidden

Code samples for "List repositories watched by the authenticated user"



Response

```
Example response Response schema

Status: 200

[ { "id": 1296269, "node_id": "MDEwOlJlcG9zaXRvcnkxMjk2MjY5", "name": "Hello-World", "full_name": "octocat/Hello-World", "owner": { "login": "octocat", "id": 1, "node_id": "MDQ6VXNlcjE=", "avatar_url": "https://github.com/images/error/octocat_happy.gif", "gravatar_id": "", "url": "https://api.github.com/users/octocat", "html_url": "https://github.com/octocat", "followers_url": "https://api.github.com/users/octocat/followers", "following_url": "https://api.github.com/users/octocat/following{/other_user}", "gists_url": "https://api.github.com/users/octocat/gists{/gist_id}", "starred_url": "https://api.github.com/users/octocat/starred{/owner}{/repo}", "subscriptions_url": "#ttps://api.github.com/users/octocat/starred{/owner}{/repo}", "#ttps://api.github.com/users/octocat/starred{/owner}{/repo}", "#ttps://api.github.com/users/octocat/starred{/owner}{/repo}", "#ttps://api.github.com/users/octocat/starred{/owner}{/repo}", "#ttps://api.github.com/users/octocat/starred{/owner}{/repo}", "#ttps://api.github.com/users/octocat/starred{/owner}{/repo}", "#ttps://api.github.com/users/octocat/starred{/owner}{/repo}", "#ttps://api.github.com/users/octocat/starred{/owner}{/repo}", "#ttps://api.github.com/users/octocat/starred{/owner}{/repo}"
```

List repositories watched by a user &

✓ Works with <u>GitHub Apps</u>

Lists repositories a user is watching.

Parameters for "List repositories watched by a user"

Headers

accept string

Setting to application/vnd.github+json is recommended.

Path parameters

username string Required

The handle for the GitHub user account.

Query parameters

per_page integer

The number of results per page (max 100).

Default: 30

page integer

Page number of the results to fetch.

Default: 1

HTTP response status codes for "List repositories watched by a user"

Status code Description

200

Code samples for "List repositories watched by a user"

GET /users/{username}/subscriptions

cURL JavaScript GitHub CLI

curl -L \ -H "Accept: application/vnd.github+json" \ -H "Authorization: Bearer <YOUR-TOKEN>" \ -H "X-GitHub-Api-Version: 2022-11-28"

ſŪ

OK

\ https://api.github.com/users/USERNAME/subscriptions

Response

Example response Response schema

Status: 200

[{ "id": 1296269, "node_id": "MDEwOlJlcG9zaXRvcnkxMjk2MjY5", "name": "Hello-World", "full_name": "octocat/Hello-World", "owner": { "login": "octocat", "id": 1, "node_id": "MDQ6VXNlcjE=", "avatar_url": "https://github.com/images/error/octocat_happy.gif",

"gravatar_id": "", "url": "https://api.github.com/users/octocat", "html_url": "https://github.com/octocat", "followers_url": "https://api.github.com/users/octocat/following{/other_user}",

"gists_url": "https://api.github.com/users/octocat/gists{/gist_id}", "starred_url":

"https://api.github.com/users/octocat/starred{/owner}{/repo}", "subscriptions_url":

Legal

© 2023 GitHub, Inc. <u>Terms</u> <u>Privacy</u> <u>Status</u> <u>Pricing</u> <u>Expert services</u> <u>Blog</u>