



Permissions required for GitHub Apps

In this article

About GitHub App permissions

Business permissions for "Enterprise administration"

Organization permissions for "Administration"

Organization permissions for "Blocking users"

Organization permissions for "Custom repository roles"

Organization permissions for "Events"

Organization permissions for "GitHub Copilot for Business"

Organization permissions for "Members"

Organization permissions for "Organization announcement banners"

Organization permissions for "Organization codespaces secrets"

Organization permissions for "Organization codespaces settings"

Organization permissions for "Organization codespaces"

Organization permissions for "Organization dependabot secrets"

Organization permissions for "Personal access token requests"

Organization permissions for "Personal access tokens"

Organization permissions for "Projects"

Organization permissions for "Secrets"

Organization permissions for "Self-hosted runners"

Organization permissions for "Team discussions"

Organization permissions for "Variables"

Organization permissions for "Webhooks"

Repository permissions for "Actions"

Repository permissions for "Administration"

Repository permissions for "Checks"

Repository permissions for "Code scanning alerts"

Repository permissions for "Codespaces lifecycle admin"

Repository permissions for "Codespaces metadata"

Repository permissions for "Codespaces secrets"

Repository permissions for "Codespaces"

Repository permissions for "Commit statuses"

Repository permissions for "Contents"

Repository permissions for "Dependabot alerts"

Repository permissions for "Dependabot secrets"

Repository permissions for "Deployments"

Repository permissions for "Environments"

Repository permissions for "Issues"

Repository permissions for "Metadata"

Repository permissions for "Pages"

Repository permissions for "Projects"

Repository permissions for "Pull requests"

Repository permissions for "Repository security advisories"

Repository permissions for "Secret scanning alerts"

Repository permissions for "Secrets"

Repository permissions for "Variables" Repository permissions for "Webhooks" Repository permissions for "Workflows" User permissions for "Block another user" User permissions for "Codespaces user secrets" User permissions for "Email addresses" User permissions for "Followers" User permissions for "GPG keys" User permissions for "Gists" User permissions for "Git SSH keys" User permissions for "Interaction limits" User permissions for "Notifications" User permissions for "Plan" User permissions for "Profile" User permissions for "SSH signing keys" User permissions for "Starring"

User permissions for "Watching"

ô

These are the permissions required for a GitHub App to use each REST API endpoint that works with GitHub Apps.

About GitHub App permissions 2

GitHub Apps are created with a set of permissions. Permissions define what resources the GitHub App can access via the API. For more information, see "Choosing permissions for a GitHub App."

To help you choose the correct permissions, you will receive the X-Accepted-GitHub-Permissions header in the REST API response. The header will tell you what permissions are required in order to access the endpoint. For more information, see "Troubleshooting."

Some endpoints require additional permissions. When this is the case, the "Additional permissions" column will indicate the other permissions that are required to use the endpoint.

Business permissions for "Enterprise administration"

Endpoint	Access	Token types	Additional permissions
GET /enterprises/{enterprise}/actions/cache/usage	write	<u>UAT</u> <u>IAT</u>	×
PUT /enterprises/{enterprise}/actions/oidc/customization/iss uer	write	<u>UAT</u> <u>IAT</u>	×
GET /enterprises/{enterprise}/settings/billing/actions	write	<u>UAT</u>	×

ΙΔΤ

GET /enterprises/{enterprise}/settings/billing/advanced- security	write	<u>UAT</u> <u>IAT</u>	×
GET /enterprises/{enterprise}/settings/billing/packages	write	<u>UAT</u> <u>IAT</u>	×
GET /enterprises/{enterprise}/settings/billing/shared-storage	write	<u>UAT</u> <u>IAT</u>	×
GET /scim/v2/Groups	write	<u>UAT</u> <u>IAT</u>	×
POST /scim/v2/Groups	write	<u>UAT</u> <u>IAT</u>	×
GET /scim/v2/Groups/{scim_group_id}	write	<u>UAT</u> <u>IAT</u>	×
PUT /scim/v2/Groups/{scim_group_id}	write	<u>UAT</u> <u>IAT</u>	×
PATCH /scim/v2/Groups/{scim_group_id}	write	<u>UAT</u> <u>IAT</u>	×
DELETE /scim/v2/Groups/{scim_group_id}	write	<u>UAT</u> <u>IAT</u>	×
GET /scim/v2/Users	write	<u>UAT</u> <u>IAT</u>	×
POST /scim/v2/Users	write	<u>UAT</u> <u>IAT</u>	×
GET /scim/v2/Users/{scim_user_id}	write	<u>UAT</u> <u>IAT</u>	×
PUT /scim/v2/Users/{scim_user_id}	write	<u>UAT</u> <u>IAT</u>	×
DELETE /scim/v2/Users/{scim_user_id}	write	<u>UAT</u> <u>IAT</u>	×
GET /enterprise-installation/{enterprise_or_org}/server-statistics	read	<u>UAT</u> <u>IAT</u>	Organization permissions for "Administration"
GET /enterprises/{enterprise}/audit-log	read	<u>UAT</u> <u>IAT</u>	×

Organization permissions for "Administration" &

Endpoint	Access	Token types	Additional permissions
		types	permissions

PATCH /orgs/{org}	write	(<u>UAT</u>) (<u>IAT</u>)	×
DELETE /orgs/{org}	write	(UAT) (IAT)	×
PUT /orgs/{org}/actions/oidc/customization/sub	write	(UAT) (IAT)	*
PUT /orgs/{org}/actions/permissions	write	<u>UAT</u> <u>IAT</u>	*
PUT /orgs/{org}/actions/permissions/repositories	write	<u>UAT</u> <u>IAT</u>	×
PUT /orgs/{org}/actions/permissions/repositories/{repositor y_id}	write	<u>UAT</u> <u>IAT</u>	Repository permissions for "Metadata"
<pre>DELETE /orgs/{org}/actions/permissions/repositories/{repositor y_id}</pre>	write	<u>UAT</u> <u>IAT</u>	Repository permissions for "Metadata"
PUT /orgs/{org}/actions/permissions/selected-actions	write	<u>UAT</u> <u>IAT</u>	×
PUT /orgs/{org}/actions/permissions/workflow	write	<u>UAT</u> <u>IAT</u>	×
<pre>DELETE /orgs/{org}/credential- authorizations/{credential_id}</pre>	write	<u>UAT</u> <u>IAT</u>	×
PUT /orgs/{org}/interaction-limits	write	<u>UAT</u> <u>IAT</u>	×
DELETE /orgs/{org}/interaction-limits	write	(UAT) (IAT)	×
PATCH /orgs/{org}/properties/schema	write	<u>UAT</u> <u>IAT</u>	*
PUT		<u>UAT</u>	×
<pre>/orgs/{org}/properties/schema/{custom_property_nam e}</pre>	write	(IAT)	
DELETE /orgs/{org}/properties/schema/{custom_property_name}	write	<u>UAT</u> <u>IAT</u>	×
PATCH /orgs/{org}/properties/values	write	<u>UAT</u> <u>IAT</u>	×
GET /orgs/{org}/rulesets	write	(UAT) (IAT)	×
POST /orgs/{org}/rulesets	write	(UAT) (IAT)	×
GET /orgs/{org}/rulesets/rule-suites		<u>UAT</u>	×

	write	(IAT)	
<pre>GET /orgs/{org}/rulesets/rule-suites/{rule_suite_id}</pre>	write	(UAT) (IAT)	×
<pre>GET /orgs/{org}/rulesets/{ruleset_id}</pre>	write	(UAT) (IAT)	×
PUT /orgs/{org}/rulesets/{ruleset_id}	write	<u>UAT</u> <u>IAT</u>	×
<pre>DELETE /orgs/{org}/rulesets/{ruleset_id}</pre>	write	(UAT) (IAT)	×
PUT /orgs/{org}/security-managers/teams/{team_slug}	write	<u>UAT</u> <u>IAT</u>	×
DELETE /orgs/{org}/security- managers/teams/{team_slug}	write	<u>UAT</u> <u>IAT</u>	×
POST /orgs/{org}/{security_product}/{enablement}	write	(UAT) (IAT)	×
<pre>GET /enterprise-installation/{enterprise_or_org}/server- statistics</pre>	read	UAT IAT	Business permissions for "Enterprise administration"
GET /organizations/{organization_id}/custom_roles	read	UAT IAT	Organization permissions for "Custom repository roles"
GET /orgs/{org}/actions/cache/usage	read	(UAT) (IAT)	×
GET /orgs/{org}/actions/cache/usage-by-repository	read	(UAT) (IAT)	×
GET /orgs/{org}/actions/oidc/customization/sub	read	<u>UAT</u> <u>IAT</u>	×
GET /orgs/{org}/actions/permissions	read	<u>UAT</u> <u>LAT</u>	×
GET /orgs/{org}/actions/permissions/repositories	read	(UAT) (IAT)	×
GET /orgs/{org}/actions/permissions/selected-actions	read	(UAT) (IAT)	×
GET /orgs/{org}/actions/permissions/workflow	read	(UAT) (IAT)	×
GET /orgs/{org}/audit-log	read	<u>UAT</u> <u>IAT</u>	×
GET /orgs/{org}/credential-authorizations	read	<u>UAT</u>	×

		IAI	
GET /orgs/{org}/custom-repository-roles	read	(UAT) (IAT)	Organization permissions for "Custom repository roles"
<pre>GET /orgs/{org}/custom-repository-roles/{role_id}</pre>	read	<u>UAT</u> <u>IAT</u>	Organization permissions for "Custom repository roles"
<pre>GET /orgs/{org}/custom_roles/{role_id}</pre>	read	<u>UAT</u> <u>IAT</u>	Organization permissions for "Custom repository roles"
GET /orgs/{org}/fine_grained_permissions	read	<u>UAT</u> <u>IAT</u>	Organization permissions for "Custom repository roles"
GET /orgs/{org}/installations	read	UAT IAT	×
GET /orgs/{org}/interaction-limits	read	<u>UAT</u> <u>IAT</u>	×
GET /orgs/{org}/security-managers	read	<u>UAT</u> <u>IAT</u>	×
GET /orgs/{org}/settings/billing/actions	read	(UAT) (IAT)	×
GET /orgs/{org}/settings/billing/advanced-security	read	(UAT) (IAT)	×
GET /orgs/{org}/settings/billing/packages	read	(UAT) (IAT)	×
GET /orgs/{org}/settings/billing/shared-storage	read	<u>UAT</u> <u>IAT</u>	×

(IAT)

Organization permissions for "Blocking users" ${\mathscr O}$

Endpoint	Access	Token types	Additional permissions
PUT /orgs/{org}/blocks/{username}	write	(UAT) (IAT)	×
<pre>DELETE /orgs/{org}/blocks/{username}</pre>	write	<u>UAT</u> <u>IAT</u>	×
GET /orgs/{org}/blocks	read	<u>UAT</u> <u>IAT</u>	×
<pre>GET /orgs/{org}/blocks/{username}</pre>	read	<u>UAT</u>	×

Organization permissions for "Custom repository roles" $\mathscr Q$

Endpoint	Access	Token types	Additional permissions
POST /orgs/{org}/custom-repository-roles	write	<u>UAT</u> <u>IAT</u>	×
PATCH /orgs/{org}/custom-repository-roles/{role_id}	write	<u>UAT</u> <u>IAT</u>	×
<pre>DELETE /orgs/{org}/custom-repository-roles/{role_id}</pre>	write	<u>UAT</u> <u>IAT</u>	×
POST /orgs/{org}/custom_roles	write	(UAT) (IAT)	×
PATCH /orgs/{org}/custom_roles/{role_id}	write	(UAT) (IAT)	×
DELETE /orgs/{org}/custom_roles/{role_id}	write	(UAT) (IAT)	×
GET /organizations/{organization_id}/custom_roles	read	(UAT) (IAT)	Organization permissions for "Administration"
GET /orgs/{org}/custom-repository-roles	read	(UAT) (IAT)	Organization permissions for "Administration"
GET /orgs/{org}/custom-repository-roles/{role_id}	read	(UAT) (IAT)	Organization permissions for "Administration"
GET /orgs/{org}/custom_roles/{role_id}	read	(UAT) (IAT)	Organization permissions for "Administration"
GET /orgs/{org}/fine_grained_permissions	read	(UAT) (IAT)	Organization permissions for "Administration"

Organization permissions for "Events" &

Endpoint	Access	Token types	Additional permissions
GET /users/{username}/events/orgs/{org}	read	<u>UAT</u>	×

Organization permissions for "GitHub Copilot for Business" $\mathscr P$

Endpoint	Access	Token types	Additional permissions
GET /orgs/{org}/copilot/billing	write	<u>UAT</u> <u>IAT</u>	×
<pre>GET /orgs/{org}/copilot/billing/seats</pre>	write	(UAT) (IAT)	×
POST /orgs/{org}/copilot/billing/selected_teams	write	<u>UAT</u> (<u>IAT</u>)	×

Organization permissions for "Members" $\mathscr P$

Endpoint	Access	Token types	Additional permissions
GET /orgs/{org}/external-group/{group_id}	write	<u>UAT</u> <u>IAT</u>	×
GET /orgs/{org}/external-groups	write	<u>UAT</u> <u>LAT</u>	×
POST /orgs/{org}/invitations	write	<u>UAT</u> <u>IAT</u>	×
DELETE /orgs/{org}/invitations/{invitation_id}	write	<u>UAT</u> <u>IAT</u>	×
DELETE /orgs/{org}/members/{username}	write	UAT LAT	×
PUT /orgs/{org}/memberships/{username}	write	UAT LAT	×
DELETE /orgs/{org}/memberships/{username}	write	(UAT) (IAT)	×
PUT /orgs/{org}/outside_collaborators/{username}	write	<u>UAT</u>)	×
		<u>IAT</u>	
DELETE /orgs/{org}/outside_collaborators/{username}	write	(UAT) (IAT)	×
PUT /orgs/{org}/public_members/{username}	write	<u>UAT</u>	×
DELETE /orgs/{org}/public_members/{username}	write	<u>UAT</u>	×
GET /orgs/{org}/team-sync/groups	write	<u>UAT</u> <u>IAT</u>	×
POST /orgs/{org}/teams	write	<u>UAT</u> <u>IAT</u>	×
GET /orgs/{org}/teams/{team_slug}/external-groups	write	<u>UAT</u>	×

		(<u>IAT</u>)	
PATCH /orgs/{org}/teams/{team_slug}/external-groups	write	(UAT) (IAT)	×
DELETE /orgs/{org}/teams/{team_slug}/external- groups	write	(UAT) (IAT)	×
POST /scim/v2/organizations/{org}/Users	write	(UAT) (IAT)	×
PUT /scim/v2/organizations/{org}/Users/{scim_user_id}	write	(UAT) (IAT)	×
PATCH /scim/v2/organizations/{org}/Users/{scim_user_id}	write	(UAT) (IAT)	×
<u>DELETE</u> /scim/v2/organizations/{org}/Users/{scim_user_id}	write	<u>UAT</u> <u>IAT</u>	×
PUT /teams/{team_id}/members/{username}	write	<u>UAT</u> <u>IAT</u>	×
<pre>DELETE /teams/{team_id}/members/{username}</pre>	write	(UAT) (IAT)	×
PATCH /user/memberships/orgs/{org}	write	(UAT)	×
GET /orgs/{org}/failed_invitations	read	(UAT) (IAT)	×
GET /orgs/{org}/invitations	read	(UAT) (IAT)	×
GET /orgs/{org}/invitations/{invitation_id}/teams	read	(UAT) (IAT)	×
GET /orgs/{org}/members	read	(UAT) (IAT)	×
GET /orgs/{org}/members/{username}	read	<u>UAT</u>	×
GET /orgs/{org}/memberships/{username}	read	<u>UAT</u> <u>IAT</u>	×
GET /orgs/{org}/outside_collaborators	read	(UAT) (IAT)	×
GET /orgs/{org}/properties/schema	read	<u>UAT</u> <u>IAT</u>	×
GET /orgs/{org}/properties/schema/{custom_property_nam e}	read	<u>UAT</u> <u>IAT</u>	×
GET /orgs/{org}/properties/values	read	<u>UAT</u>	×

		(<u>IAI</u>)	
<pre>GET /orgs/{org}/public_members</pre>	read	<u>UAT</u> (IAT)	×
<pre>GET /orgs/{org}/public_members/{username}</pre>	read	<u>UAT</u> (IAT)	×
GET /orgs/{org}/teams	read	<u>UAT</u> (IAT)	×
GET /scim/v2/organizations/{org}/Users	read	<u>UAT</u> <u>IAT</u>	×
GET /scim/v2/organizations/{org}/Users/{scim_user_id}	read	<u>UAT</u> <u>IAT</u>	×
<pre>GET /teams/{team_id}/members/{username}</pre>	read	<u>UAT</u> <u>(IAT</u>)	×
GET /user/memberships/orgs/{org}	read	<u>UAT</u>	×

Organization permissions for "Organization announcement banners" \mathscr{P}

Endpoint	Access	Token types	Additional permissions
PATCH /orgs/{org}/announcement	write	(UAT) (IAT)	×
DELETE /orgs/{org}/announcement	write	(UAT) (IAT)	×
GET /orgs/{org}/announcement	read	(UAT) (IAT)	×

Organization permissions for "Organization codespaces secrets" &

Endpoint	Access	Token types	Additional permissions
<pre>PUT /orgs/{org}/codespaces/secrets/{secret_name}</pre>	write	<u>UAT</u> <u>IAT</u>	×
<pre>DELETE /orgs/{org}/codespaces/secrets/{secret_name}</pre>	write	<u>UAT</u> <u>IAT</u>	×
PUT /orgs/{org}/codespaces/secrets/{secret_name}/reposit ories	write	<u>UAT</u> <u>IAT</u>	*
PUT /orgs/{org}/codespaces/secrets/{secret_name}/reposit	write	<u>UAT</u>	Repository permissions for

ories/{repository_id}		(<u>IAT</u>)	<u>"Metadata"</u>
<pre>DELETE /orgs/{org}/codespaces/secrets/{secret_name}/reposit ories/{repository_id}</pre>	write	UAT IAT	Repository permissions for "Metadata"
GET /orgs/{org}/codespaces/secrets	read	(UAT) (IAT)	×
GET /orgs/{org}/codespaces/secrets/public-key	read	<u>UAT</u> <u>IAT</u>	×
<pre>GET /orgs/{org}/codespaces/secrets/{secret_name}</pre>	read	(UAT) (IAT)	×
<pre>GET /orgs/{org}/codespaces/secrets/{secret_name}/reposit ories</pre>	read	<u>UAT</u> <u>IAT</u>	×

Organization permissions for "Organization codespaces settings" &

Endpoint	Access	Token types	Additional permissions
PUT /orgs/{org}/codespaces/access	write	UAT IAT	×
POST /orgs/{org}/codespaces/access/selected_users	write	(UAT) (IAT)	×
DELETE /orgs/{org}/codespaces/access/selected_users	write	(UAT) (IAT)	×

Organization permissions for "Organization codespaces" $\mathscr O$

Endpoint	Access	Token types	Additional permissions
<pre>DELETE /orgs/{org}/members/{username}/codespaces/{codes pace_name}</pre>	write	UAT IAT	Repository permissions for "Codespaces"
POST /orgs/{org}/members/{username}/codespaces/{codespace_name}/stop	write	(UAT) (IAT)	Repository permissions for "Codespaces lifecycle admin"
GET /orgs/{org}/codespaces	read	(UAT) (IAT)	Repository permissions for "Codespaces"
<pre>GET /orgs/{org}/members/{username}/codespaces</pre>	read	<u>UAT</u> IAT	Repository permissions for

Organization permissions for "Organization dependabot secrets" ${\mathscr O}$

Endpoint	Access	Token types	Additional permissions
PUT /orgs/{org}/dependabot/secrets/{secret_name}	write	UAT IAT	×
<pre>DELETE /orgs/{org}/dependabot/secrets/{secret_name}</pre>	write	<u>UAT</u> <u>IAT</u>	×
PUT /orgs/{org}/dependabot/secrets/{secret_name}/reposit ories	write	(UAT) (IAT)	*
PUT /orgs/{org}/dependabot/secrets/{secret_name}/reposit ories/{repository_id}	write	(UAT) (IAT)	Repository permissions for "Metadata"
DELETE /orgs/{org}/dependabot/secrets/{secret_name}/reposit ories/{repository_id}	write	(UAT) (IAT)	Repository permissions for "Metadata"
GET /orgs/{org}/dependabot/secrets	read	<u>UAT</u> <u>IAT</u>	×
GET /orgs/{org}/dependabot/secrets/public-key	read	UAT IAT	×
<pre>GET /orgs/{org}/dependabot/secrets/{secret_name}</pre>	read	<u>UAT</u> <u>IAT</u>	×
GET /orgs/{org}/dependabot/secrets/{secret_name}/reposit ories	read	UAT IAT	×

Organization permissions for "Personal access token requests" @

Endpoint	Access	Token types	Additional permissions
POST /orgs/{org}/personal-access-token-requests	write	UAT IAT	×
POST /orgs/{org}/personal-access-token-requests/{pat_request_id}	write	<u>UAT</u> <u>IAT</u>	×
GET /orgs/{org}/personal-access-token-requests	read	(UAT) (IAT)	×
GET /orgs/{org}/personal-access-token-requests/{pat_request_id}/repositories	read	(UAT) (IAT)	×

Organization permissions for "Personal access tokens" ${\mathscr O}$

Endpoint	Access	Token types	Additional permissions
POST /orgs/{org}/personal-access-tokens	write	(UAT) (IAT)	×
POST /orgs/{org}/personal-access-tokens/{pat_id}	write	(UAT) (IAT)	×
GET /orgs/{org}/personal-access-tokens	read	(UAT) (IAT)	×
GET /orgs/{org}/personal-access- tokens/{pat_id}/repositories	read	<u>UAT</u> <u>IAT</u>	×

Organization permissions for "Projects" &

Endpoint	Access	Token types	Additional permissions
<pre>GET /projects/{project_id}/collaborators</pre>	admin	(UAT) (IAT)	Repository permissions for "Projects"
<pre>PUT /projects/{project_id}/collaborators/{username}</pre>	admin	(UAT) (IAT)	Repository permissions for "Projects"
<pre>DELETE /projects/{project_id}/collaborators/{username}</pre>	admin	(UAT) (IAT)	Repository permissions for "Projects"
GET /projects/{project_id}/collaborators/{username}/permis sion	admin	<u>UAT</u> <u>IAT</u>	Repository permissions for "Projects"
POST /orgs/{org}/projects	write	<u>UAT</u>	×
PATCH /projects/columns/cards/{card_id}	write	(UAT) (IAT)	Repository permissions for "Projects"
DELETE /projects/columns/cards/{card_id}	write	(UAT) (IAT)	Repository permissions for "Projects"
POST /projects/columns/cards/{card_id}/moves	write	(UAT) (IAT)	Repository permissions for "Projects"
PATCH /projects/columns/{column_id}	write	UAT IAT	Repository permissions for "Projects"

DELETE /projects/columns/{column_id}	write	UAT LAT	Repository permissions for "Projects"
POST /projects/columns/{column_id}/cards	write	UAT IAT	Repository permissions for "Projects"
POST /projects/columns/{column_id}/moves	write	UAT LAT	Repository permissions for "Projects"
PATCH /projects/{project_id}	write	<u>UAT</u> <u>IAT</u>	Repository permissions for "Projects"
DELETE /projects/{project_id}	write	UAT LAT	Repository permissions for "Projects"
POST /projects/{project_id}/columns	write	UAT IAT	Repository permissions for "Projects"
GET /orgs/{org}/projects	read	<u>UAT</u> <u>IAT</u>	×
GET /projects/columns/cards/{card_id}	read	<u>UAT</u> <u>IAT</u>	Repository permissions for "Projects"
GET /projects/columns/{column_id}	read	<u>UAT</u> <u>IAT</u>	Repository permissions for "Projects"
GET /projects/columns/{column_id}/cards	read	UAT IAT	Repository permissions for "Projects"
<pre>GET /projects/{project_id}</pre>	read	<u>UAT</u> <u>IAT</u>	Repository permissions for "Projects"
GET /projects/{project_id}/columns	read	<u>UAT</u>	Repository permissions for "Projects"

Organization permissions for "Secrets" $\mathscr P$

Endpoint	Access	Token types	Additional permissions
<pre>PUT /orgs/{org}/actions/secrets/{secret_name}</pre>	write	(UAT) (IAT)	×
<pre>DELETE /orgs/{org}/actions/secrets/{secret_name}</pre>	write	(UAT) (IAT)	×
PUT /oras/Soral/actions/socrats//socrat_namel/repositories	write	<u>UAT</u>	×

(0195/1019]/actions/secrets/15ecret_iname//repositories		(\underline{IAT})	
PUT /orgs/{org}/actions/secrets/{secret_name}/repositories /{repository_id}	write	<u>UAT</u> <u>IAT</u>	Repository permissions for "Metadata"
<pre>DELETE /orgs/{org}/actions/secrets/{secret_name}/repositories /{repository_id}</pre>	write	<u>UAT</u> <u>IAT</u>	Repository permissions for "Metadata"
GET /orgs/{org}/actions/secrets	read	<u>UAT</u> <u>IAT</u>	×
GET /orgs/{org}/actions/secrets/public-key	read	<u>UAT</u> <u>IAT</u>	×
<pre>GET /orgs/{org}/actions/secrets/{secret_name}</pre>	read	<u>UAT</u> <u>IAT</u>	×
GET /orgs/{org}/actions/secrets/{secret_name}/repositories	read	<u>UAT</u> <u>IAT</u>	×

Organization permissions for "Self-hosted runners" &

Endpoint	Access	Token types	Additional permissions
POST /orgs/{org}/actions/runner-groups	write	<u>UAT</u> <u>IAT</u>	×
PATCH /orgs/{org}/actions/runner-groups/{runner_group_id}	write	<u>UAT</u> <u>IAT</u>	×
<pre>DELETE /orgs/{org}/actions/runner- groups/{runner_group_id}</pre>	write	<u>UAT</u> <u>IAT</u>	×
PUT /orgs/{org}/actions/runner-groups/{runner_group_id}/repositories	write	<u>UAT</u> <u>IAT</u>	×
PUT /orgs/{org}/actions/runner- groups/{runner_group_id}/repositories/{repository_id}	write	(UAT)	Repository permissions for "Metadata"
<pre>DELETE /orgs/{org}/actions/runner- groups/{runner_group_id}/repositories/{repository_id}</pre>	write	<u>UAT</u> <u>IAT</u>	Repository permissions for "Metadata"
PUT /orgs/{org}/actions/runner- groups/{runner_group_id}/runners	write	<u>UAT</u> <u>IAT</u>	×
<pre>PUT /orgs/{org}/actions/runner- groups/{runner_group_id}/runners/{runner_id}</pre>	write	<u>UAT</u> <u>IAT</u>	×
<pre>DELETE /orgs/{org}/actions/runner- groups/{runner_group_id}/runners/{runner_id}</pre>	write	<u>UAT</u> <u>IAT</u>	×
POST /orgs/{org}/actions/runners/generate-jitconfig	writa	<u>UAT</u>	×

	WIILE	(IAT)
POST /orgs/{org}/actions/runners/registration-token	write	UAT *
POST /orgs/{org}/actions/runners/remove-token	write	UAT *
<pre>DELETE /orgs/{org}/actions/runners/{runner_id}</pre>	write	UAT X
POST /orgs/{org}/actions/runners/{runner_id}/labels	write	UAT *
PUT /orgs/{org}/actions/runners/{runner_id}/labels	write	<u>UAT</u> *
DELETE /orgs/{org}/actions/runners/{runner_id}/labels	write	UAT *
<pre>DELETE /orgs/{org}/actions/runners/{runner_id}/labels/{name}</pre>	write	UAT *
GET /orgs/{org}/actions/runner-groups	read	UAT X
<pre>GET /orgs/{org}/actions/runner- groups/{runner_group_id}</pre>	read	<u>UAT</u> *
<pre>GET /orgs/{org}/actions/runner- groups/{runner_group_id}/repositories</pre>	read	UAT *
<pre>GET /orgs/{org}/actions/runner- groups/{runner_group_id}/runners</pre>	read	UAT *
GET /orgs/{org}/actions/runners	read	UAT *
GET /orgs/{org}/actions/runners/downloads	read	(UAT) *
<pre>GET /orgs/{org}/actions/runners/{runner_id}</pre>	read	UAT *
GET /orgs/{org}/actions/runners/{runner_id}/labels	read	UAT X

Organization permissions for "Team discussions" ${\mathscr O}$

Endpoint	Access	Token types	Additional permissions
<pre>DELETE /orgs/{org}/teams/{team_slug}/discussions/{discussio n_number}/comments/{comment_number}/reactions/{ reaction_id}</pre>	write	UAT LAT	*

n_number}/reactions/{reaction_id}

write

<u>UAT</u>

(IAT)

Organization permissions for "Variables" &

Endpoint	Access	Token types	Additional permissions
POST /orgs/{org}/actions/variables	write	<u>UAT</u> <u>IAT</u>	×
PATCH /orgs/{org}/actions/variables/{name}	write	<u>UAT</u> <u>IAT</u>	×
DELETE /orgs/{org}/actions/variables/{name}	write	<u>UAT</u> <u>IAT</u>	×
PUT /orgs/{org}/actions/variables/{name}/repositories	write	<u>UAT</u> <u>IAT</u>	×
PUT /orgs/{org}/actions/variables/{name}/repositories/{repository_id}	write	<u>UAT</u> <u>IAT</u>	Repository permissions for "Metadata"
GET /orgs/{org}/actions/variables	read	<u>UAT</u> <u>IAT</u>	×
<pre>GET /orgs/{org}/actions/variables/{name}</pre>	read	<u>UAT</u> <u>IAT</u>	×
GET /orgs/{org}/actions/variables/{name}/repositories	read	<u>UAT</u> <u>IAT</u>	×

Organization permissions for "Webhooks" 🔗

Endpoint	Access	Token types	Additional permissions
POST /orgs/{org}/hooks	write	<u>UAT</u> <u>IAT</u>	×
PATCH /orgs/{org}/hooks/{hook_id}	write	<u>UAT</u> <u>IAT</u>	×
<pre>DELETE /orgs/{org}/hooks/{hook_id}</pre>	write	<u>UAT</u> <u>IAT</u>	×
PATCH /orgs/{org}/hooks/{hook_id}/config	write	<u>UAT</u> <u>IAT</u>	×
POST /orgs/{org}/hooks/{hook_id}/deliveries/{delivery_id}/at tempts	write	<u>UAT</u> <u>IAT</u>	×

POST /orgs/{org}/hooks/{hook_id}/pings	write	<u>UAT</u> *
GET /orgs/{org}/hooks	read	<u>UAT</u> *
<pre>GET /orgs/{org}/hooks/{hook_id}</pre>	read	<u>UAT</u> *
<pre>GET /orgs/{org}/hooks/{hook_id}/config</pre>	read	UAT *
<pre>GET /orgs/{org}/hooks/{hook_id}/deliveries</pre>	read	UAT *
<pre>GET /orgs/{org}/hooks/{hook_id}/deliveries/{delivery_id}</pre>	read	UAT X

Repository permissions for "Actions" @

Endpoint	Access	Token types	Additional permissions
<pre>DELETE /repos/{owner}/{repo}/actions/artifacts/{artifact_id}</pre>	write	(UAT) (IAT)	×
DELETE /repos/{owner}/{repo}/actions/caches	write	(UAT) (IAT)	×
<pre>DELETE /repos/{owner}/{repo}/actions/caches/{cache_id}</pre>	write	(UAT) (IAT)	×
POST /repos/{owner}/{repo}/actions/jobs/{job_id}/rerun	write	(UAT) (IAT)	×
PUT /repos/{owner}/{repo}/actions/oidc/customization/sub	write	(UAT) (IAT)	×
DELETE /repos/{owner}/{repo}/actions/runs/{run_id}	write	(UAT)	×
POST /repos/{owner}/{repo}/actions/runs/{run_id}/approve	write	(UAT) (IAT)	×
POST /repos/{owner}/{repo}/actions/runs/{run_id}/cancel	write	(UAT) (IAT)	×
POST /repos/{owner}/{repo}/actions/runs/{run_id}/force- cancel	write	<u>UAT</u> <u>IAT</u>	×
DELETE /repos/{owner}/{repo}/actions/runs/{run_id}/logs	write	(UAT) (IAT)	×
POST /repos/{owner}/{repo}/actions/runs/{run id}/rerun	write	<u>UAT</u>	×

		(<u>IAI</u>)	
POST /repos/{owner}/{repo}/actions/runs/{run_id}/rerun- failed-jobs	write	<u>UAT</u> <u>IAT</u>	×
PUT /repos/{owner}/{repo}/actions/workflows/{workflow_id }/disable	write	UAT IAT	×
POST /repos/{owner}/{repo}/actions/workflows/{workflow_id }/dispatches	write	<u>UAT</u> <u>IAT</u>	×
PUT /repos/{owner}/{repo}/actions/workflows/{workflow_id }/enable	write	<u>UAT</u> <u>IAT</u>	×
GET /repos/{owner}/{repo}/actions/artifacts	read	(UAT) (IAT)	×
GET /repos/{owner}/{repo}/actions/artifacts/{artifact_id}	read	(UAT) (IAT)	×
<pre>GET /repos/{owner}/{repo}/actions/artifacts/{artifact_id}/{ archive_format}</pre>	read	<u>UAT</u> <u>IAT</u>	×
GET /repos/{owner}/{repo}/actions/cache/usage	read	UAT IAT	×
GET /repos/{owner}/{repo}/actions/caches	read	<u>UAT</u> <u>IAT</u>	×
<pre>GET /repos/{owner}/{repo}/actions/jobs/{job_id}</pre>	read	<u>UAT</u> <u>IAT</u>	×
GET /repos/{owner}/{repo}/actions/jobs/{job_id}/logs	read	(UAT) (IAT)	×
GET /repos/{owner}/{repo}/actions/oidc/customization/sub	read	(UAT) (IAT)	×
GET /repos/{owner}/{repo}/actions/runs	read	<u>UAT</u> <u>IAT</u>	×
<pre>GET /repos/{owner}/{repo}/actions/runs/{run_id}</pre>	read	(UAT) (IAT)	×
GET /repos/{owner}/{repo}/actions/runs/{run_id}/approvals	read	<u>UAT</u> <u>IAT</u>	×
GET /repos/{owner}/{repo}/actions/runs/{run_id}/artifacts	read	(UAT) (IAT)	×
GET /repos/{owner}/{repo}/actions/runs/{run_id}/attempts/ {attempt_number}	read	<u>UAT</u> <u>IAT</u>	×
GET		<u>UAT</u>	×

/repos/{owner}/{repo}/actions/runs/{run_ia}/attempts/ {attempt_number}/jobs	read	(IAT)	
GET /repos/{owner}/{repo}/actions/runs/{run_id}/attempts/ {attempt_number}/logs	read	(UAT) (IAT)	×
GET /repos/{owner}/{repo}/actions/runs/{run_id}/jobs	read	<u>UAT</u> <u>IAT</u>	×
GET /repos/{owner}/{repo}/actions/runs/{run_id}/logs	read	(UAT) (IAT)	×
GET /repos/{owner}/{repo}/actions/runs/{run_id}/pending_ deployments	read	<u>UAT</u> <u>IAT</u>	×
POST /repos/{owner}/{repo}/actions/runs/{run_id}/pending_ deployments	read	UAT IAT	Repository permissions for "Checks", Repository permissions for "Deployments"
<pre>GET /repos/{owner}/{repo}/actions/runs/{run_id}/timing</pre>	read	<u>UAT</u> <u>IAT</u>	×
GET /repos/{owner}/{repo}/actions/workflows	read	<u>UAT</u> <u>IAT</u>	*
GET /repos/{owner}/{repo}/actions/workflows/{workflow_id} }	read	(UAT) (IAT)	×
GET /repos/{owner}/{repo}/actions/workflows/{workflow_id }/runs	read	(UAT) (IAT)	*
<pre>GET /repos/{owner}/{repo}/actions/workflows/{workflow_id }/timing</pre>	read	<u>UAT</u> <u>IAT</u>	×
GET /repos/{owner}/{repo}/environments	read	<u>UAT</u> <u>IAT</u>	×
GET /repos/{owner}/{repo}/environments/{environment_na_me}	read	(UAT) (IAT)	×
GET /repos/{owner}/{repo}/environments/{environment_na} me}/deployment-branch-policies	read	(UAT) (IAT)	×
GET /repos/{owner}/{repo}/environments/{environment_name}/deployment-branch-policies/{branch_policy_id}	read	UAT IAT	×
GET /repos/{owner}/{repo}/environments/{environment_name}/deployment_protection_rules	read	(UAT) (IAT)	×
GET /repos/{owner}/{repo}/environments/{environment_na	read	<u>UAT</u>	×

Repository permissions for "Administration" &

Endpoint	Access	Token types	Additional permissions
POST /orgs/{org}/repos	write	<u>UAT</u> <u>IAT</u>	×
PATCH /repos/{owner}/{repo}	write	<u>UAT</u> <u>IAT</u>	×
DELETE /repos/{owner}/{repo}	write	<u>UAT</u> <u>LAT</u>	×
PUT /repos/{owner}/{repo}/actions/permissions	write	<u>UAT</u> <u>LAT</u>	×
PUT /repos/{owner}/{repo}/actions/permissions/access	write	<u>UAT</u> <u>LAT</u>	×
PUT /repos/{owner}/{repo}/actions/permissions/selected- actions	write	<u>UAT</u> <u>IAT</u>	×
PUT /repos/{owner}/{repo}/actions/permissions/workflow	write	<u>UAT</u> <u>LAT</u>	×
POST /repos/{owner}/{repo}/actions/runners/generate- jitconfig	write	<u>UAT</u> <u>IAT</u>	×
POST /repos/{owner}/{repo}/actions/runners/registration- token	write	<u>UAT</u> <u>IAT</u>	×
POST /repos/{owner}/{repo}/actions/runners/remove-token	write	<u>UAT</u> <u>LAT</u>	×
<pre>DELETE /repos/{owner}/{repo}/actions/runners/{runner_id}</pre>	write	<u>UAT</u> <u>IAT</u>	×
POST /repos/{owner}/{repo}/actions/runners/{runner_id}/lab els	write	<u>UAT</u> <u>IAT</u>	×
PUT /repos/{owner}/{repo}/actions/runners/{runner_id}/lab els	write	UAT IAT	×
DELETE /repos/{owner}/{repo}/actions/runners/{runner_id}/lab els	write	<u>UAT</u> <u>IAT</u>	×
DELETE /repos/{owner}/{repo}/actions/runners/{runner_id}/lab els/{name}	write	<u>UAT</u> <u>IAT</u>	×
POST /repos/{owner}/{repo}/autolinks	write	<u>UAT</u>	×

		<u>IAT</u>	
DELETE /repos/{owner}/{repo}/autolinks/{autolink_id}	write	(UAT) (IAT)	*
PUT /repos/{owner}/{repo}/automated-security-fixes	write	(UAT) (IAT)	×
DELETE /repos/{owner}/{repo}/automated-security- fixes	write	<u>UAT</u> <u>IAT</u>	×
PUT /repos/{owner}/{repo}/branches/{branch}/protection	write	<u>UAT</u> <u>IAT</u>	×
<pre>DELETE /repos/{owner}/{repo}/branches/{branch}/protection</pre>	write	<u>UAT</u> <u>IAT</u>	×
POST /repos/{owner}/{repo}/branches/{branch}/protection/ enforce_admins	write	<u>UAT</u> <u>IAT</u>	×
<u>DELETE</u> /repos/{owner}/{repo}/branches/{branch}/protection/ enforce_admins	write	(UAT) (IAT)	×
PATCH /repos/{owner}/{repo}/branches/{branch}/protection/r equired_pull_request_reviews	write	(UAT) (IAT)	×
DELETE /repos/{owner}/{repo}/branches/{branch}/protection/required_pull_request_reviews	write	(UAT) (IAT)	×
POST /repos/{owner}/{repo}/branches/{branch}/protection/required_signatures	write	(UAT) (IAT)	×
DELETE /repos/{owner}/{repo}/branches/{branch}/protection/required_signatures	write	(UAT) (IAT)	×
PATCH /repos/{owner}/{repo}/branches/{branch}/protection/required_status_checks	write	(JAT)	×
DELETE /repos/{owner}/{repo}/branches/{branch}/protection/required_status_checks	write	(UAT) (IAT)	×
POST /repos/{owner}/{repo}/branches/{branch}/protection/required_status_checks/contexts	write	(UAT) (IAT)	×
PUT /repos/{owner}/{repo}/branches/{branch}/protection/r equired_status_checks/contexts	write	(UAT) (IAT)	×
DELETE /repos/{owner}/{repo}/branches/{branch}/protection/required_status_checks/contexts	write	<u>UAT</u> <u>IAT</u>	×
<pre>DELETE /repos/{owner}/{repo}/branches/{branch}/protection/r</pre>	write	<u>UAT</u> IAT	×

20	tri	ict	nc

POST /repos/{owner}/{repo}/branches/{branch}/protection/r estrictions/apps	write	<u>UAT</u> <u>IAT</u>	×
PUT /repos/{owner}/{repo}/branches/{branch}/protection/r estrictions/apps	write	(UAT) (IAT)	×
DELETE /repos/{owner}/{repo}/branches/{branch}/protection/restrictions/apps	write	(UAT) (IAT)	×
POST /repos/{owner}/{repo}/branches/{branch}/protection/restrictions/teams	write	(UAT) (IAT)	×
PUT /repos/{owner}/{repo}/branches/{branch}/protection/restrictions/teams	write	(UAT) (IAT)	×
DELETE /repos/{owner}/{repo}/branches/{branch}/protection/restrictions/teams	write	(UAT) (IAT)	×
POST /repos/{owner}/{repo}/branches/{branch}/protection/restrictions/users	write	<u>UAT</u> <u>IAT</u>	×
PUT /repos/{owner}/{repo}/branches/{branch}/protection/r estrictions/users	write	(UAT) (IAT)	×
DELETE /repos/{owner}/{repo}/branches/{branch}/protection/restrictions/users	write	(UAT) (IAT)	×
PATCH /repos/{owner}/{repo}/code-scanning/default-setup	write	<u>UAT</u> <u>IAT</u>	×
PUT /repos/{owner}/{repo}/codespaces/secrets/{secret_na_me}	write	<u>UAT</u> <u>IAT</u>	Repository permissions for "Codespaces secrets"
DELETE /repos/{owner}/{repo}/codespaces/secrets/{secret_name}	write	<u>UAT</u> <u>IAT</u>	Repository permissions for "Codespaces secrets"
PUT /repos/{owner}/{repo}/collaborators/{username}	write	<u>UAT</u> <u>IAT</u>	×
<pre>DELETE /repos/{owner}/{repo}/collaborators/{username}</pre>	write	(UAT) (IAT)	×
PUT /repos/{owner}/{repo}/environments/{environment_name}	write	(UAT) (IAT)	×
DELETE /repos/{owner}/{repo}/environments/{environment_na	write	(UAT) (IAT)	×

<u>me</u> }		<u></u>	
POST /repos/{owner}/{repo}/environments/{environment_name}/deployment-branch-policies	write	(UAT) (IAT)	*
PUT /repos/{owner}/{repo}/environments/{environment_na} me}/deployment-branch-policies/{branch_policy_id}	write	<u>UAT</u> <u>IAT</u>	×
DELETE /repos/{owner}/{repo}/environments/{environment_na me}/deployment-branch-policies/{branch_policy_id}	write	UAT LAT	×
POST /repos/{owner}/{repo}/environments/{environment_na me}/deployment_protection_rules	write	UAT LAT	×
DELETE /repos/{owner}/{repo}/environments/{environment_na me}/deployment_protection_rules/{protection_rule_id}	write	UAT LAT	×
POST /repos/{owner}/{repo}/forks	write	<u>UAT</u> <u>IAT</u>	Repository permissions for "Contents"
PUT /repos/{owner}/{repo}/interaction-limits	write	(UAT) (IAT)	*
DELETE /repos/{owner}/{repo}/interaction-limits	write	(UAT) (IAT)	×
PATCH /repos/{owner}/{repo}/invitations/{invitation_id}	write	<u>UAT</u> <u>IAT</u>	×
DELETE /repos/{owner}/{repo}/invitations/{invitation_id}	write	(UAT) (IAT)	×
POST /repos/{owner}/{repo}/keys	write	(UAT) (IAT)	×
DELETE /repos/{owner}/{repo}/keys/{key_id}	write	(UAT) (IAT)	×
POST /repos/{owner}/{repo}/pages	write	UAT IAT	Repository permissions for "Pages"
PUT /repos/{owner}/{repo}/pages	write	UAT LAT	Repository permissions for "Pages"
DELETE /repos/{owner}/{repo}/pages	write	(UAT) (IAT)	Repository permissions for "Pages"
GET /repos/{owner}/{repo}/pages/health	write	UAT IAT	Repository permissions for "Pages"
PUT /repos/{owner}/{repo}/private-vulnerability-reporting	write	<u>UAT</u>	×

		<u> </u>	
DELETE /repos/{owner}/{repo}/private-vulnerability-reporting	write	(UAT) (IAT)	×
POST /repos/{owner}/{repo}/rulesets	write	UAT IAT	×
GET /repos/{owner}/{repo}/rulesets/rule-suites	write	<u>UAT</u> <u>IAT</u>	×
GET /repos/{owner}/{repo}/rulesets/rule- suites/{rule_suite_id}	write	<u>UAT</u> <u>IAT</u>	×
PUT /repos/{owner}/{repo}/rulesets/{ruleset_id}	write	<u>UAT</u> <u>IAT</u>	×
DELETE /repos/{owner}/{repo}/rulesets/{ruleset_id}	write	UAT IAT	×
POST /repos/{owner}/{repo}/tags/protection	write	<u>UAT</u> <u>IAT</u>	×
<pre>DELETE /repos/{owner}/{repo}/tags/protection/{tag_protection _id}</pre>	write	(UAT) (IAT)	×
PUT /repos/{owner}/{repo}/topics	write	<u>UAT</u> <u>IAT</u>	×
POST /repos/{owner}/{repo}/transfer	write	<u>UAT</u>	×
PUT /repos/{owner}/{repo}/vulnerability-alerts	write	<u>UAT</u> <u>IAT</u>	×
DELETE /repos/{owner}/{repo}/vulnerability-alerts	write	UAT IAT	×
POST /user/repos	write	<u>UAT</u>	×
PATCH /user/repository_invitations/{invitation_id}	write	<u>UAT</u>	×
DELETE /user/repository_invitations/{invitation_id}	write	<u>UAT</u>	×
GET /repos/{owner}/{repo}/actions/permissions	read	<u>UAT</u> <u>IAT</u>	×
GET /repos/{owner}/{repo}/actions/permissions/access	read	<u>UAT</u> <u>IAT</u>	×
GET /repos/{owner}/{repo}/actions/permissions/selected- actions	read	(UAT) (IAT)	×
GET /repos/{owner}/{repo}/actions/permissions/workflow	read	UAT IAT	×
GET /repos/{owner}/{repo}/actions/runners	read	(UAT) (IAT)	×

GET /repos/{owner}/{repo}/actions/runners/downloads	read	UAT IAT	×
<pre>GET /repos/{owner}/{repo}/actions/runners/{runner_id}</pre>	read	<u>UAT</u> <u>IAT</u>	×
GET /repos/{owner}/{repo}/actions/runners/{runner_id}/lab els	read	<u>UAT</u> <u>IAT</u>	×
GET /repos/{owner}/{repo}/autolinks	read	<u>UAT</u> <u>(IAT</u>)	×
<pre>GET /repos/{owner}/{repo}/autolinks/{autolink_id}</pre>	read	(UAT) (IAT)	×
GET /repos/{owner}/{repo}/automated-security-fixes	read	UAT LAT	×
GET /repos/{owner}/{repo}/branches/{branch}/protection	read	<u>UAT</u> <u>IAT</u>	×
GET /repos/{owner}/{repo}/branches/{branch}/protection/ enforce_admins	read	<u>UAT</u> <u>(IAT</u>)	×
GET /repos/{owner}/{repo}/branches/{branch}/protection/required_pull_request_reviews	read	UAT LAT	×
GET /repos/{owner}/{repo}/branches/{branch}/protection/required_signatures	read	UAT LAT	×
GET /repos/{owner}/{repo}/branches/{branch}/protection/required_status_checks	read	UAT LAT	×
GET /repos/{owner}/{repo}/branches/{branch}/protection/r equired_status_checks/contexts	read	<u>UAT</u> <u>IAT</u>	×
GET /repos/{owner}/{repo}/branches/{branch}/protection/restrictions	read	(UAT) (IAT)	×
GET /repos/{owner}/{repo}/branches/{branch}/protection/restrictions/apps	read	<u>UAT</u> <u>IAT</u>	×
GET /repos/{owner}/{repo}/branches/{branch}/protection/restrictions/teams	read	<u>UAT</u> <u>IAT</u>	×
GET /repos/{owner}/{repo}/branches/{branch}/protection/restrictions/users	read	<u>UAT</u> <u>IAT</u>	×
GET /repos/{owner}/{repo}/interaction-limits	read	<u>UAT</u> <u>IAT</u>	×

<pre>GET /repos/{owner}/{repo}/invitations</pre>	read	(UAT) (IAT)	×
GET /repos/{owner}/{repo}/keys	read	<u>UAT</u> <u>IAT</u>	×
<pre>GET /repos/{owner}/{repo}/keys/{key_id}</pre>	read	<u>UAT</u> <u>IAT</u>	×
GET /repos/{owner}/{repo}/tags/protection	read	(UAT) (IAT)	×
GET /repos/{owner}/{repo}/teams	read	<u>UAT</u> <u>IAT</u>	×
GET /repos/{owner}/{repo}/traffic/clones	read	<u>UAT</u> <u>IAT</u>	×
GET /repos/{owner}/{repo}/traffic/popular/paths	read	<u>UAT</u> <u>IAT</u>	×
GET /repos/{owner}/{repo}/traffic/popular/referrers	read	<u>UAT</u> <u>IAT</u>	×
GET /repos/{owner}/{repo}/traffic/views	read	<u>UAT</u> <u>IAT</u>	×
GET /repos/{owner}/{repo}/vulnerability-alerts	read	<u>UAT</u> <u>IAT</u>	×
GET /user/repository_invitations	read	<u>UAT</u>	×

Repository permissions for "Checks" @

Endpoint	Access	Token types	Additional permissions
POST /repos/{owner}/{repo}/check-runs	write	<u>UAT</u> <u>IAT</u>	×
PATCH /repos/{owner}/{repo}/check-runs/{check_run_id}	write	<u>UAT</u> <u>IAT</u>	×
POST /repos/{owner}/{repo}/check- runs/{check_run_id}/rerequest	write	<u>UAT</u> <u>IAT</u>	×
POST /repos/{owner}/{repo}/check-suites	write	<u>UAT</u> <u>IAT</u>	×
PATCH /repos/{owner}/{repo}/check-suites/preferences	write	<u>UAT</u> <u>IAT</u>	×
POST /repos/{owner}/{repo}/check- suites/{check_suite_id}/rerequest	write	<u>UAT</u> <u>IAT</u>	×
POST			Repository

/repos/{owner}/{repo}/actions/runs/{run_ia}/penaing_deployments	read	UAT LAT	permissions for "Actions", Repository permissions for "Deployments"
<pre>GET /repos/{owner}/{repo}/check-runs/{check_run_id}</pre>	read	(UAT) (IAT)	×
<pre>GET /repos/{owner}/{repo}/check- runs/{check_run_id}/annotations</pre>	read	(UAT) (IAT)	×
<pre>GET /repos/{owner}/{repo}/check- suites/{check_suite_id}</pre>	read	(UAT) (IAT)	×
<pre>GET /repos/{owner}/{repo}/check- suites/{check_suite_id}/check-runs</pre>	read	(UAT) (IAT)	×
GET /repos/{owner}/{repo}/commits/{ref}/check-runs	read	(UAT) (IAT)	×
GET /repos/{owner}/{repo}/commits/{ref}/checksuites	read	<u>UAT</u> <u>IAT</u>	×

Repository permissions for "Code scanning alerts" ${\mathscr O}$

Endpoint	Access	Token types	Additional permissions
PATCH /repos/{owner}/{repo}/code- scanning/alerts/{alert_number}	write	(UAT) (IAT)	×
DELETE /repos/{owner}/{repo}/code-scanning/analyses/{analysis_id}	write	(UAT) (IAT)	×
POST /repos/{owner}/{repo}/code-scanning/sarifs	write	<u>UAT</u> <u>IAT</u>	×
GET /orgs/{org}/code-scanning/alerts	read	<u>UAT</u> <u>IAT</u>	×
GET /repos/{owner}/{repo}/code-scanning/alerts	read	(UAT) (IAT)	×
<pre>GET /repos/{owner}/{repo}/code- scanning/alerts/{alert_number}</pre>	read	(UAT) (IAT)	×
GET /repos/{owner}/{repo}/code- scanning/alerts/{alert_number}/instances	read	(UAT) (IAT)	×
GET /repos/{owner}/{repo}/code-scanning/analyses	read	(UAT) (IAT)	×
<pre>GET /repos/{owner}/{repo}/code- scanning/analyses/{analysis_id}</pre>	read	(UAT) (IAT)	×
GET /renos/fownerl/frenol/code-		TIAT	*



Repository permissions for "Codespaces lifecycle admin" ${\mathscr O}$

Endpoint	Access	Token types	Additional permissions
POST /orgs/{org}/members/{username}/codespaces/{codespace_name}/stop	write	UAT IAT	Organization permissions for "Organization codespaces"
POST /user/codespaces/{codespace_name}/exports	write	<u>UAT</u>	×
POST /user/codespaces/{codespace_name}/start	write	<u>UAT</u>	×
POST /user/codespaces/{codespace_name}/stop	write	<u>UAT</u>	*
GET /user/codespaces/{codespace_name}/exports/{export_i d}	read	<u>UAT</u>	×

Repository permissions for "Codespaces metadata"

Õ

Endpoint	Access	Token types	Additional permissions
GET /repos/{owner}/{repo}/codespaces/devcontainers	read	(UAT) (IAT)	×
GET /repos/{owner}/{repo}/codespaces/machines	read	<u>UAT</u> <u>IAT</u>	×
GET /user/codespaces/{codespace_name}/machines	read	<u>UAT</u>	×

Repository permissions for "Codespaces secrets" ∂

Endpoint	Access	Token types	Additional permissions
<pre>GET /repos/{owner}/{repo}/codespaces/secrets</pre>	write	<u>UAT</u> <u>IAT</u>	×
GET /repos/{owner}/{repo}/codespaces/secrets/public- key	write	<u>UAT</u> <u>IAT</u>	×
<pre>GET /repos/{owner}/{repo}/codespaces/secrets/{secret_na me}</pre>	write	<u>UAT</u> <u>IAT</u>	×
<pre>PUT /repos/{owner}/{repo}/codespaces/secrets/{secret_na me}</pre>	write	<u>UAT</u> <u>IAT</u>	Repository permissions for "Administration"

DELETE
/repos/{owner}/{repo}/codespaces/secrets/{secret_na
me}

write

<u>UAT</u> <u>IAT</u> Repository
permissions for
"Administration"

Repository permissions for "Codespaces" *₽*

Endpoint	Access	Token types	Additional permissions
<pre>DELETE /orgs/{org}/members/{username}/codespaces/{codes pace_name}</pre>	write	UAT LAT	Organization permissions for "Organization codespaces"
POST /repos/{owner}/{repo}/codespaces	write	<u>UAT</u>	×
GET /repos/{owner}/{repo}/codespaces/new	write	<u>UAT</u>	*
GET /repos/{owner}/{repo}/codespaces/permissions_check	write	<u>UAT</u>)	*
POST /repos/{owner}/{repo}/pulls/{pull_number}/codespace s	write	<u>UAT</u>)	×
POST /user/codespaces	write	<u>UAT</u>	×
PATCH /user/codespaces/{codespace_name}	write	<u>UAT</u>	×
DELETE /user/codespaces/{codespace_name}	write	<u>UAT</u>	×
POST /user/codespaces/{codespace_name}/publish	write	<u>UAT</u>	×
GET /orgs/{org}/codespaces	read	(UAT) (IAT)	Organization permissions for "Organization codespaces"
GET /orgs/{org}/members/{username}/codespaces	read	<u>UAT</u> <u>IAT</u>	Organization permissions for "Organization codespaces"
GET /repos/{owner}/{repo}/codespaces	read	<u>UAT</u>	×
GET /user/codespaces	read	<u>UAT</u>	×
<pre>GET /user/codespaces/{codespace_name}</pre>	read	<u>UAT</u>	×

Repository permissions for "Commit statuses" ₽

Endpoint	Access	Token types	Additional permissions
POST /repos/{owner}/{repo}/statuses/{sha}	write	(UAT) (IAT)	*

<pre>GET /repos/{owner}/{repo}/commits/{ref}/status</pre>	read	(<u>UAT</u>) (<u>IAT</u>)	×	
<pre>GET /repos/{owner}/{repo}/commits/{ref}/statuses</pre>	read	<u>UAT</u> <u>IAT</u>	×	

Repository permissions for "Contents" *⊗*

Endpoint	Access	Token types	Additional permissions
POST /repos/{owner}/{repo}/branches/{branch}/rename	write	<u>UAT</u> <u>IAT</u>	×
PATCH /repos/{owner}/{repo}/comments/{comment_id}	write	<u>UAT</u> <u>IAT</u>	×
DELETE /repos/{owner}/{repo}/comments/{comment_id}	write	UAT IAT	×
POST /repos/{owner}/{repo}/comments/{comment_id}/react ions	write	<u>UAT</u> <u>IAT</u>	×
DELETE /repos/{owner}/{repo}/comments/{comment_id}/react ions/{reaction_id}	write	<u>UAT</u> <u>IAT</u>	×
PUT /repos/{owner}/{repo}/contents/{path}	write	<u>UAT</u> <u>IAT</u>	×
DELETE /repos/{owner}/{repo}/contents/{path}	write	<u>UAT</u> <u>IAT</u>	×
POST /repos/{owner}/{repo}/dependency- graph/snapshots	write	<u>UAT</u> <u>IAT</u>	×
POST /repos/{owner}/{repo}/dispatches	write	<u>UAT</u> <u>IAT</u>	×
POST /repos/{owner}/{repo}/git/blobs	write	<u>UAT</u> <u>IAT</u>	×
POST /repos/{owner}/{repo}/git/commits	write	UAT IAT	×
POST /repos/{owner}/{repo}/git/refs	write	<u>UAT</u> <u>IAT</u>	Repository permissions for "Workflows"
PATCH /repos/{owner}/{repo}/git/refs/{ref}	write	(UAT) (IAT)	Repository permissions for "Workflows"
DELETE /repos/{owner}/{repo}/git/refs/{ref}	write	<u>UAT</u> (IAT)	×

POST /repos/{owner}/{repo}/git/tags	write	(UAT) (IAT)	×
POST /repos/{owner}/{repo}/git/trees	write	(UAT) (IAT)	×
PUT /repos/{owner}/{repo}/import	write	<u>UAT</u>	×
PATCH /repos/{owner}/{repo}/import	write	<u>UAT</u>	×
DELETE /repos/{owner}/{repo}/import	write	<u>UAT</u>	×
PATCH /repos/{owner}/{repo}/import/authors/{author_id}	write	<u>UAT</u>	×
PATCH /repos/{owner}/{repo}/import/lfs	write	<u>UAT</u>	*
POST /repos/{owner}/{repo}/merge-upstream	write	(UAT) (IAT)	×
POST /repos/{owner}/{repo}/merges	write	(UAT) (IAT)	×
PUT /repos/{owner}/{repo}/pulls/{pull_number}/merge	write	(UAT) (IAT)	*
POST /repos/{owner}/{repo}/releases	write	<u>UAT</u> <u>IAT</u>	×
PATCH /repos/{owner}/{repo}/releases/assets/{asset_id}	write	(<u>UAT</u>) (<u>IAT</u>)	×
<pre>DELETE /repos/{owner}/{repo}/releases/assets/{asset_id}</pre>	write	<u>UAT</u> <u>IAT</u>	×
POST /repos/{owner}/{repo}/releases/generate-notes	write	<u>UAT</u> <u>IAT</u>	×
PATCH /repos/{owner}/{repo}/releases/{release_id}	write	<u>UAT</u> <u>IAT</u>	×
DELETE /repos/{owner}/{repo}/releases/{release_id}	write	(IAT)	×
GET /repos/{owner}/{repo}/activity	read	UAT IAT	×
GET /repos/{owner}/{repo}/branches	read	(UAT) (IAT)	×
<pre>GET /repos/{owner}/{repo}/branches/{branch}</pre>	read	<u>UAT</u>) <u>[AT</u>)	×
GET /repos/{owner}/{repo}/code- scanning/codeql/databases	read	<u>UAT</u> <u>IAT</u>	×
GET /repos/{owner}/{repo}/code- scanning/codeql/databases/{language}	read	<u>UAT</u> <u>IAT</u>	×

GET /repos/{owner}/{repo}/codeowners/errors	read	<u>UAT</u> <u>IAT</u>	×
GET /repos/{owner}/{repo}/commits	read	(UAT) (IAT)	×
GET /repos/{owner}/{repo}/commits/{commit_sha}/branch es-where-head	read	<u>UAT</u> <u>IAT</u>	×
POST /repos/{owner}/{repo}/commits/{commit_sha}/comme nts	read	<u>UAT</u> <u>IAT</u>	×
<pre>GET /repos/{owner}/{repo}/commits/{ref}</pre>	read	<u>UAT</u> <u>IAT</u>	×
GET /repos/{owner}/{repo}/community/profile	read	<u>UAT</u> <u>IAT</u>	×
<pre>GET /repos/{owner}/{repo}/compare/{basehead}</pre>	read	(UAT) (IAT)	×
<pre>GET /repos/{owner}/{repo}/contents/{path}</pre>	read	(UAT) (IAT)	×
<pre>GET /repos/{owner}/{repo}/dependency- graph/compare/{basehead}</pre>	read	<u>UAT</u> <u>IAT</u>	Repository permissions for "Pull requests"
GET /repos/{owner}/{repo}/dependency-graph/sbom	read	(UAT) (IAT)	×
POST /repos/{owner}/{repo}/forks	read	<u>UAT</u> <u>IAT</u>	Repository permissions for "Administration"
<pre>GET /repos/{owner}/{repo}/git/blobs/{file_sha}</pre>	read	<u>UAT</u> <u>IAT</u>	×
<pre>GET /repos/{owner}/{repo}/git/commits/{commit_sha}</pre>	read	(UAT)	×
<pre>GET /repos/{owner}/{repo}/git/matching-refs/{ref}</pre>	read	UAT LAT	×
<pre>GET /repos/{owner}/{repo}/git/ref/{ref}</pre>	read	<u>UAT</u> <u>IAT</u>	×
<pre>GET /repos/{owner}/{repo}/git/tags/{tag_sha}</pre>	read	<u>UAT</u> <u>IAT</u>	×
<pre>GET /repos/{owner}/{repo}/git/trees/{tree_sha}</pre>	read	UAT LAT	×
GET /repos/{owner}/{repo}/import	read	<u>UAT</u>	*

<pre>GET /repos/{owner}/{repo}/import/authors</pre>	read	<u>UAT</u>	×
GET /repos/{owner}/{repo}/import/large_files	read	<u>UAT</u>	×
<pre>GET /repos/{owner}/{repo}/pulls/{pull_number}</pre>	read	(UAT) (IAT)	Repository permissions for "Pull requests"
GET /repos/{owner}/{repo}/releases	read	(UAT) (IAT)	×
<pre>GET /repos/{owner}/{repo}/releases/assets/{asset_id}</pre>	read	(UAT) (IAT)	×
GET /repos/{owner}/{repo}/releases/latest	read	(UAT) (IAT)	×
GET /repos/{owner}/{repo}/releases/tags/{tag}	read	(UAT) (IAT)	×
GET /repos/{owner}/{repo}/releases/{release_id}	read	(UAT) (IAT)	×
GET /repos/{owner}/{repo}/releases/{release_id}/assets	read	<u>UAT</u> <u>IAT</u>	×

Repository permissions for "Dependabot alerts" &

Endpoint	Access	Token types	Additional permissions
PATCH /repos/{owner}/{repo}/dependabot/alerts/{alert_numb er}	write	(UAT) (IAT)	×
GET /orgs/{org}/dependabot/alerts	read	(UAT) (IAT)	×
GET /repos/{owner}/{repo}/dependabot/alerts	read	<u>UAT</u> <u>IAT</u>	×
<pre>GET /repos/{owner}/{repo}/dependabot/alerts/{alert_numb er}</pre>	read	(UAT) (IAT)	×

Repository permissions for "Dependabot secrets" $\mathscr P$

Endpoint	Access	Token types	Additional permissions
<pre>PUT /repos/{owner}/{repo}/dependabot/secrets/{secret_na me}</pre>	write	(UAT) (IAT)	×
<pre>DELETE /repos/{owner}/{repo}/dependabot/secrets/{secret_na</pre>	write	(UAT)	×

me}			
GET /repos/{owner}/{repo}/dependabot/secrets	read	(UAT) (IAT)	×
GET /repos/{owner}/{repo}/dependabot/secrets/public- key	read	<u>UAT</u> <u>IAT</u>	×
GET /repos/{owner}/{repo}/dependabot/secrets/{secret_na me}	read	(UAT) (IAT)	×

Repository permissions for "Deployments" $\mathscr O$

Endpoint	Access	Token types	Additional permissions
POST /repos/{owner}/{repo}/actions/runs/{run_id}/deployment_protection_rule	write	(IAT)	*
POST /repos/{owner}/{repo}/deployments	write	UAT IAT	×
<pre>DELETE /repos/{owner}/{repo}/deployments/{deployment_id}</pre>	write	<u>UAT</u> (IAT)	×
POST /repos/{owner}/{repo}/deployments/{deployment_id}/ statuses	write	UAT IAT	*
POST /repos/{owner}/{repo}/actions/runs/{run_id}/pending_ deployments	read	(UAT) (IAT)	Repository permissions for "Actions", Repository permissions for "Checks"
GET /repos/{owner}/{repo}/deployments	read	UAT IAT	×
<pre>GET /repos/{owner}/{repo}/deployments/{deployment_id}</pre>	read	<u>UAT</u> <u>IAT</u>	×
GET /repos/{owner}/{repo}/deployments/{deployment_id}/ statuses	read	<u>UAT</u> <u>IAT</u>	×
GET /repos/{owner}/{repo}/deployments/{deployment_id}/ statuses/{status_id}	read	<u>UAT</u> <u>IAT</u>	×

Repository permissions for "Environments" &

Endpoint	Access	Token types	Additional permissions

PUT /repositories/{repository_id}/environments/{environme nt_name}/secrets/{secret_name}	write	<u>UAT</u> <u>IAT</u>	Repository permissions for "Secrets"
DELETE /repositories/{repository_id}/environments/{environme nt_name}/secrets/{secret_name}	write	<u>UAT</u> <u>IAT</u>	Repository permissions for "Secrets"
POST /repositories/{repository_id}/environments/{environments_nt_name}/variables	write	<u>UAT</u> <u>IAT</u>	Repository permissions for "Variables"
PATCH /repositories/{repository_id}/environments/{environment_name}/variables/{name}	write	<u>UAT</u> <u>IAT</u>	Repository permissions for "Variables"
DELETE /repositories/{repository_id}/environments/{environments_name}/variables/{name}	write	<u>UAT</u> <u>IAT</u>	Repository permissions for "Variables"
GET /repositories/{repository_id}/environments/{environment_name}/secrets	read	<u>UAT</u> <u>IAT</u>	Repository permissions for "Secrets"
GET /repositories/{repository_id}/environments/{environme nt_name}/secrets/public-key	read	<u>UAT</u> <u>IAT</u>	Repository permissions for "Secrets"
GET /repositories/{repository_id}/environments/{environment_name}/secrets/{secret_name}	read	<u>UAT</u> <u>IAT</u>	Repository permissions for "Secrets"
GET /repositories/{repository_id}/environments/{environments/qenvironmen	read	<u>UAT</u> <u>IAT</u>	Repository permissions for "Variables"
GET /repositories/{repository_id}/environments/{environme nt_name}/variables/{name}	read	<u>UAT</u> <u>IAT</u>	Repository permissions for "Variables"

Repository permissions for "Issues" ₽

Endpoint	Access	Token types	Additional permissions
POST /repos/{owner}/{repo}/issues	write	<u>UAT</u> <u>IAT</u>	×
PATCH /repos/{owner}/{repo}/issues/comments/{comment_id} }	write	<u>UAT</u> <u>IAT</u>	Repository permissions for "Pull requests"
<pre>DELETE /repos/{owner}/{repo}/issues/comments/{comment_id} }</pre>	write	<u>UAT</u> <u>IAT</u>	Repository permissions for "Pull requests"
POST /repos/{owner}/{repo}/issues/comments/{comment_id}/reactions	write	<u>UAT</u> <u>IAT</u>	×
<pre>DELETE /repos/{owner}/{repo}/issues/comments/{comment_id }/reactions/fraction_id}</pre>	write	(UAT) (IAT)	×

7/1 Hat	HOUS/KIPA	CHOIL	10.1 >

<pre>//reactions/{reaction_iu}</pre>			
PATCH /repos/{owner}/{repo}/issues/{issue_number}	write	(UAT) (IAT)	Repository permissions for "Pull requests"
POST /repos/{owner}/{repo}/issues/{issue_number}/assigne es	write	(UAT) (IAT)	Repository permissions for "Pull requests"
<u>DELETE</u> /repos/{owner}/{repo}/issues/{issue_number}/assigne es	write	<u>UAT</u> <u>IAT</u>	Repository permissions for "Pull requests"
POST /repos/{owner}/{repo}/issues/{issue_number}/comme nts	write	(UAT) (IAT)	Repository permissions for "Pull requests"
POST /repos/{owner}/{repo}/issues/{issue_number}/labels	write	(UAT) (IAT)	Repository permissions for "Pull requests"
<u>PUT</u> /repos/{owner}/{repo}/issues/{issue_number}/labels	write	(UAT) (IAT)	Repository permissions for "Pull requests"
<u>DELETE</u> /repos/{owner}/{repo}/issues/{issue_number}/labels	write	(UAT) (IAT)	Repository permissions for "Pull requests"
DELETE /repos/{owner}/{repo}/issues/{issue_number}/labels/{ name}	write	(UAT) (IAT)	Repository permissions for "Pull requests"
PUT /repos/{owner}/{repo}/issues/{issue_number}/lock	write	<u>UAT</u> <u>IAT</u>	Repository permissions for "Pull requests"
DELETE /repos/{owner}/{repo}/issues/{issue_number}/lock	write	(UAT) (IAT)	Repository permissions for "Pull requests"
POST /repos/{owner}/{repo}/issues/{issue_number}/reactions	write	(UAT) (IAT)	×
DELETE /repos/{owner}/{repo}/issues/{issue_number}/reactio ns/{reaction_id}	write	<u>UAT</u> <u>IAT</u>	×
POST /repos/{owner}/{repo}/labels	write	(UAT) (IAT)	Repository permissions for "Pull requests"
PATCH /repos/{owner}/{repo}/labels/{name}	write	(UAT) (IAT)	Repository permissions for "Pull requests"
DELETE /repos/{owner}/{repo}/labels/{name}	write	(UAT) (IAT)	Repository permissions for "Pull requests"
POST /repos/{owner}/{repo}/milestones	write	(UAT) (IAT)	Repository permissions for "Pull requests"

PATCH		(<u>UAT</u>)	Repository
/repos/{owner}/{repo}/milestones/{milestone_number	write	(IAT)	permissions for
1		IAL	"Pull requests"
DELETE		(<u>UAT</u>)	Repository
/repos/{owner}/{repo}/milestones/{milestone_number	write		permissions for
¥ .		(<u>IAT</u>)	"Pull requests"
GET /repos/{owner}/{repo}/assignees			Repository
<u>OET /Tepos/(owner)/(repo)/assignees</u>	read	(<u>UAT</u>)	permissions for
	read	(IAT)	"Pull requests"
<pre>GET /repos/{owner}/{repo}/assignees/{assignee}</pre>	read	<u>UAT</u>	Repository permissions for
	read	(IAT)	"Pull requests"
GET /repos/{owner}/{repo}/issues	read	(<u>UAT</u>)	×
		(IAT)	
GET /repos/{owner}/{repo}/issues/comments			Repository
,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,	read	(<u>UAT</u>)	permissions for
	. 534	(IAT)	"Pull requests"
GET		(UAT)	Repository
/repos/{owner}/{repo}/issues/comments/{comment_id	read		permissions for
).		(<u>IAT</u>)	"Pull requests"
GET			×
/repos/{owner}/{repo}/issues/comments/{comment_id_	read	(<u>UAT</u>)	•
}/reactions	rcuu	<u>IAT</u>	
GET /repos/{owner}/{repo}/issues/events		(<u>UAT</u>)	×
	read	(IAT)	
<pre>GET /repos/{owner}/{repo}/issues/events/{event_id}</pre>		(<u>UAT</u>)	Repository
	read	(IAT)	permissions for
			<u>"Pull requests"</u>
GET /repos/{owner}/{repo}/issues/{issue_number}		<u>UAT</u>	×
	read	(IAT)	
		<u> </u>	
<u>GET</u>		(<u>UAT</u>)	Repository
/repos/{owner}/{repo}/issues/{issue_number}/assigne	read		permissions for
<u>es/{assignee}</u>		(IAT)	<u>"Pull requests"</u>
			Danasitani
CET			Repository
	read	<u>UAT</u>	nermissions for
/repos/{owner}/{repo}/issues/{issue_number}/comme	read	<u>UAT</u> <u>IAT</u>	permissions for "Pull requests"
GET /repos/{owner}/{repo}/issues/{issue_number}/comme nts	read		permissions for "Pull requests"
/repos/{owner}/{repo}/issues/{issue_number}/comme nts GET			"Pull requests" Repository
/repos/{owner}/{repo}/issues/{issue_number}/comme nts GET	read	<u>IAT</u>	"Pull requests" Repository permissions for
/repos/{owner}/{repo}/issues/{issue_number}/comme		(IAT)	"Pull requests" Repository
/repos/{owner}/{repo}/issues/{issue_number}/comme nts GET		UAT LAT	"Pull requests" Repository permissions for
/repos/{owner}/{repo}/issues/{issue_number}/comme_nts GET /repos/{owner}/{repo}/issues/{issue_number}/events GET		UAT LAT	"Pull requests" Repository permissions for "Pull requests"
/repos/{owner}/{repo}/issues/{issue_number}/comme nts GET /repos/{owner}/{repo}/issues/{issue_number}/events GET	read	UAT LAT	"Pull requests" Repository permissions for "Pull requests" Repository
/repos/{owner}/{repo}/issues/{issue_number}/comme nts GET /repos/{owner}/{repo}/issues/{issue_number}/events GET /repos/{owner}/{repo}/issues/{issue_number}/labels	read	UAT LAT	"Pull requests" Repository permissions for "Pull requests" Repository permissions for "Pull requests"
/repos/{owner}/{repo}/issues/{issue_number}/comme nts GET /repos/{owner}/{repo}/issues/{issue_number}/events GET /repos/{owner}/{repo}/issues/{issue_number}/labels GET /repos/{owner}/{repo}/issues/{issue_number}/labels	read	UAT LAT	"Pull requests" Repository permissions for "Pull requests" Repository permissions for
/repos/{owner}/{repo}/issues/{issue_number}/comme nts GET /repos/{owner}/{repo}/issues/{issue_number}/events GET /repos/{owner}/{repo}/issues/{issue_number}/labels	read	UAT LAT LAT	"Pull requests" Repository permissions for "Pull requests" Repository permissions for "Pull requests"

<pre>GET /repos/{owner}/{repo}/issues/{issue_number}/timeline</pre>	read	<u>UAT</u> <u>IAT</u>	Repository permissions for "Pull requests"
GET /repos/{owner}/{repo}/labels	read	<u>UAT</u> <u>IAT</u>	Repository permissions for "Pull requests"
<pre>GET /repos/{owner}/{repo}/labels/{name}</pre>	read	<u>UAT</u> <u>IAT</u>	Repository permissions for "Pull requests"
GET /repos/{owner}/{repo}/milestones	read	<u>UAT</u> <u>IAT</u>	Repository permissions for "Pull requests"
GET /repos/{owner}/{repo}/milestones/{milestone_number} }	read	UAT IAT	Repository permissions for "Pull requests"
GET /repos/{owner}/{repo}/milestones/{milestone_number}/labels	read	<u>UAT</u> <u>IAT</u>	Repository permissions for "Pull requests"

Repository permissions for "Metadata" $\mathscr P$

POST /gists read U	fo	ser permissions or "Gists"
	IAT)	
PATCH /gists/{gist_id} read	10	ser permissions or "Gists"
DELETE /gists/{gist_id} read	IAT)	ser permissions or "Gists"
POST /gists/{gist_id}/comments read	ΙΔΤ)	ser permissions or "Gists"
GET /gists/{gist_id}/comments/{comment_id} read	IAT	*
PATCH /gists/{gist_id}/comments/{comment_id} read	IAT \	ser permissions or "Gists"
DELETE /gists/{gist_id}/comments/{comment_id} read	ΔΙ	ser permissions or "Gists"
POST /gists/{gist_id}/forks read		ser permissions or "Gists"
PUT /gists/{gist_id}/star read	ΙΔΙ)	ser permissions or "Gists"
DELETE /gists/{gist_id}/star read	ΙΔΙ)	ser permissions or "Gists"
GET /notifications read		ser permissions or "Notifications"

PUT /orgs/{org}/actions/permissions/repositories/{repositor y_id}	read	(UAT) (IAT)	Organization permissions for "Administration"
DELETE /orgs/{org}/actions/permissions/repositories/{repository_id}	read	(UAT) (IAT)	Organization permissions for "Administration"
PUT /orgs/{org}/actions/runner-groups/{runner_group_id}/repositories/{repository_id}	read	(UAT) (IAT)	Organization permissions for "Self-hosted runners"
<pre>DELETE /orgs/{org}/actions/runner- groups/{runner_group_id}/repositories/{repository_id}</pre>	read	UAT LAT	Organization permissions for "Self-hosted runners"
<pre>PUT /orgs/{org}/actions/secrets/{secret_name}/repositories /{repository_id}</pre>	read	<u>UAT</u> <u>IAT</u>	Organization permissions for "Secrets"
<pre>DELETE /orgs/{org}/actions/secrets/{secret_name}/repositories /{repository_id}</pre>	read	<u>UAT</u> <u>IAT</u>	Organization permissions for "Secrets"
PUT /orgs/{org}/actions/variables/{name}/repositories/{repository_id}	read	(UAT) (IAT)	Organization permissions for "Variables"
PUT /orgs/{org}/codespaces/secrets/{secret_name}/reposit ories/{repository_id}	read	<u>UAT</u> <u>IAT</u>	Organization permissions for "Organization codespaces secrets"
<pre>DELETE /orgs/{org}/codespaces/secrets/{secret_name}/reposit ories/{repository_id}</pre>	read	(UAT) (IAT)	Organization permissions for "Organization codespaces secrets"
PUT /orgs/{org}/dependabot/secrets/{secret_name}/reposit ories/{repository_id}	read	<u>UAT</u> <u>IAT</u>	Organization permissions for "Organization dependabot secrets"
<pre>DELETE /orgs/{org}/dependabot/secrets/{secret_name}/reposit ories/{repository_id}</pre>	read	<u>UAT</u> <u>IAT</u>	Organization permissions for "Organization dependabot secrets"
GET /orgs/{org}/repos	read	<u>UAT</u> <u>IAT</u>	×
<pre>GET /repos/{owner}/{repo}</pre>	read	<u>UAT</u> <u>IAT</u>	×
GET /repos/{owner}/{repo}/collaborators	read	<u>UAT</u>	×

		<u>INI</u>	
<pre>GET /repos/{owner}/{repo}/collaborators/{username}</pre>	read	(UAT) (IAT)	×
GET /repos/{owner}/{repo}/collaborators/{username}/per mission	read	(UAT) (IAT)	×
GET /repos/{owner}/{repo}/comments	read	<u>UAT</u> <u>IAT</u>	×
<pre>GET /repos/{owner}/{repo}/comments/{comment_id}</pre>	read	<u>UAT</u> <u>IAT</u>	×
<pre>GET /repos/{owner}/{repo}/comments/{comment_id}/react ions</pre>	read	(UAT) (IAT)	×
<pre>GET /repos/{owner}/{repo}/commits/{commit_sha}/comme nts</pre>	read	(UAT) (IAT)	×
<pre>GET /repos/{owner}/{repo}/contributors</pre>	read	<u>UAT</u> <u>IAT</u>	×
<pre>GET /repos/{owner}/{repo}/events</pre>	read	<u>UAT</u> <u>IAT</u>	×
GET /repos/{owner}/{repo}/forks	read	<u>UAT</u> <u>IAT</u>	×
GET /repos/{owner}/{repo}/languages	read	<u>UAT</u> <u>IAT</u>	×
GET /repos/{owner}/{repo}/license	read	<u>UAT</u> <u>IAT</u>	×
GET /repos/{owner}/{repo}/properties/values	read	<u>UAT</u> <u>IAT</u>	×
GET /repos/{owner}/{repo}/rules/branches/{branch}	read	<u>UAT</u>)	×
		<u>IAT</u>	
<pre>GET /repos/{owner}/{repo}/rulesets</pre>	read	<u>UAT</u> <u>IAT</u>	×
<pre>GET /repos/{owner}/{repo}/rulesets/{ruleset_id}</pre>	read	<u>UAT</u> <u>IAT</u>	×
GET /repos/{owner}/{repo}/stargazers	read	<u>UAT</u> <u>IAT</u>	×
GET /repos/{owner}/{repo}/stats/code_frequency	read	(UAT) (IAT)	×
<pre>GET /repos/{owner}/{repo}/stats/commit_activity</pre>	read	<u>UAT</u> <u>IAT</u>	×

GET /repos/{owner}/{repo}/stats/contributors	read	<u>UAT</u> <u>IAT</u>	×
GET /repos/{owner}/{repo}/stats/participation	read	<u>UAT</u> <u>IAT</u>	×
<pre>GET /repos/{owner}/{repo}/stats/punch_card</pre>	read	<u>UAT</u> <u>IAT</u>	×
GET /repos/{owner}/{repo}/subscribers	read	<u>UAT</u> <u>IAT</u>	×
GET /repos/{owner}/{repo}/tags	read	<u>UAT</u> <u>IAT</u>	×
GET /repos/{owner}/{repo}/topics	read	UAT IAT	×
POST /repos/{template_owner}/{template_repo}/generate	read	<u>UAT</u>	×
GET /repositories	read	<u>UAT</u> <u>IAT</u>	×
GET /search/labels	read	<u>UAT</u> <u>IAT</u>	×
PUT /user/codespaces/secrets/{secret_name}/repositories/{ repository_id}	read	<u>UAT</u>	User permissions for "Codespaces user secrets"
<pre>DELETE /user/codespaces/secrets/{secret_name}/repositories/{ repository_id}</pre>	read	<u>UAT</u>	User permissions for "Codespaces user secrets"
GET /user/installations/{installation_id}/repositories	read	<u>UAT</u>	×
GET /user/repos	read	<u>UAT</u>	×
GET /users/{username}/repos	read	<u>UAT</u> <u>IAT</u>	×

Repository permissions for "Pages" ∂

Endpoint	Access	Token types	Additional permissions
POST /repos/{owner}/{repo}/pages	write	<u>UAT</u> <u>IAT</u>	Repository permissions for "Administration"
PUT /repos/{owner}/{repo}/pages	write	(UAT) (IAT)	Repository permissions for "Administration"
DELETE /repos/{owner}/{repo}/pages	write	(UAT) (IAT)	Repository permissions for "Administration"

POST /repos/{owner}/{repo}/pages/builds	write	<u>UAT</u> <u>IAT</u>	×
POST /repos/{owner}/{repo}/pages/deployment	write	<u>UAT</u> <u>IAT</u>	×
GET /repos/{owner}/{repo}/pages/health	write	<u>UAT</u> <u>IAT</u>	Repository permissions for "Administration"
GET /repos/{owner}/{repo}/pages	read	<u>UAT</u> <u>IAT</u>	×
GET /repos/{owner}/{repo}/pages/builds	read	<u>UAT</u> <u>IAT</u>	×
GET /repos/{owner}/{repo}/pages/builds/latest	read	<u>UAT</u> <u>IAT</u>	×
<pre>GET /repos/{owner}/{repo}/pages/builds/{build_id}</pre>	read	<u>UAT</u> <u>IAT</u>	×

Repository permissions for "Projects" *∂*

Endpoint	Access	Token types	Additional permissions
PATCH /projects/columns/cards/{card_id}	write	<u>UAT</u> <u>IAT</u>	Organization permissions for "Projects"
DELETE /projects/columns/cards/{card_id}	write	<u>UAT</u> <u>IAT</u>	Organization permissions for "Projects"
POST /projects/columns/cards/{card_id}/moves	write	<u>UAT</u> <u>IAT</u>	Organization permissions for "Projects"
PATCH /projects/columns/{column_id}	write	<u>UAT</u> <u>IAT</u>	Organization permissions for "Projects"
DELETE /projects/columns/{column_id}	write	<u>UAT</u> <u>IAT</u>	Organization permissions for "Projects"
POST /projects/columns/{column_id}/cards	write	<u>UAT</u> <u>IAT</u>	Organization permissions for "Projects"
POST /projects/columns/{column_id}/moves	write	<u>UAT</u> <u>IAT</u>	Organization permissions for "Projects"
PATCH /projects/{project_id}	write	(UAT) (IAT)	Organization permissions for "Projects"

DELETE /projects/{project_id}	write	UAT IAT	Organization permissions for "Projects"
GET /projects/{project_id}/collaborators	write	<u>UAT</u> <u>IAT</u>	Organization permissions for "Projects"
<pre>PUT /projects/{project_id}/collaborators/{username}</pre>	write	<u>UAT</u> <u>IAT</u>	Organization permissions for "Projects"
<pre>DELETE /projects/{project_id}/collaborators/{username}</pre>	write	<u>UAT</u> <u>IAT</u>	Organization permissions for "Projects"
GET /projects/{project_id}/collaborators/{username}/permis sion	write	<u>UAT</u> <u>IAT</u>	Organization permissions for "Projects"
POST /projects/{project_id}/columns	write	<u>UAT</u> <u>IAT</u>	Organization permissions for "Projects"
POST /repos/{owner}/{repo}/projects	write	<u>UAT</u> <u>IAT</u>	×
GET /projects/columns/cards/{card_id}	read	<u>UAT</u> <u>IAT</u>	Organization permissions for "Projects"
GET /projects/columns/{column_id}	read	<u>UAT</u> <u>IAT</u>	Organization permissions for "Projects"
GET /projects/columns/{column_id}/cards	read	<u>UAT</u> <u>IAT</u>	Organization permissions for "Projects"
<pre>GET /projects/{project_id}</pre>	read	<u>UAT</u> <u>IAT</u>	Organization permissions for "Projects"
<pre>GET /projects/{project_id}/columns</pre>	read	<u>UAT</u> <u>IAT</u>	Organization permissions for "Projects"
GET /repos/{owner}/{repo}/projects	read	<u>UAT</u> <u>IAT</u>	*

Repository permissions for "Pull requests" ∂

Endpoint	Access	Token types	Additional permissions
PATCH /repos/{owner}/{repo}/issues/comments/{comment_id} }	write	<u>UAT</u> <u>IAT</u>	Repository permissions for "Issues"
DEI ETE			Popository

/repos/{owner}/{repo}/issues/comments/{comment_id}	write	(UAT) (IAT)	nepository permissions for "Issues"
PATCH /repos/{owner}/{repo}/issues/{issue_number}	write	<u>UAT</u> <u>IAT</u>	Repository permissions for "Issues"
POST /repos/{owner}/{repo}/issues/{issue_number}/assigne es	write	<u>UAT</u> <u>IAT</u>	Repository permissions for "Issues"
<pre>DELETE /repos/{owner}/{repo}/issues/{issue_number}/assigne es</pre>	write	<u>UAT</u> <u>IAT</u>	Repository permissions for "Issues"
POST /repos/{owner}/{repo}/issues/{issue_number}/comme nts	write	<u>UAT</u>	Repository permissions for "Issues"
POST /repos/{owner}/{repo}/issues/{issue_number}/labels	write	<u>UAT</u> <u>IAT</u>	Repository permissions for "Issues"
PUT /repos/{owner}/{repo}/issues/{issue_number}/labels	write	<u>UAT</u> <u>IAT</u>	Repository permissions for "Issues"
DELETE /repos/{owner}/{repo}/issues/{issue_number}/labels	write	<u>UAT</u> <u>IAT</u>	Repository permissions for "Issues"
<pre>DELETE /repos/{owner}/{repo}/issues/{issue_number}/labels/{ name}</pre>	write	<u>UAT</u> <u>IAT</u>	Repository permissions for "Issues"
<pre>PUT /repos/{owner}/{repo}/issues/{issue_number}/lock</pre>	write	<u>UAT</u> <u>IAT</u>	Repository permissions for "Issues"
<pre>DELETE /repos/{owner}/{repo}/issues/{issue_number}/lock</pre>	write	<u>UAT</u> <u>IAT</u>	Repository permissions for "Issues"
POST /repos/{owner}/{repo}/labels	write	<u>UAT</u> <u>IAT</u>	Repository permissions for "Issues"
PATCH /repos/{owner}/{repo}/labels/{name}	write	<u>UAT</u> <u>IAT</u>	Repository permissions for "Issues"
DELETE /repos/{owner}/{repo}/labels/{name}	write	<u>UAT</u> <u>IAT</u>	Repository permissions for "Issues"
POST /repos/{owner}/{repo}/milestones	write	<u>UAT</u> <u>IAT</u>	Repository permissions for "Issues"
PATCH /repos/{owner}/{repo}/milestones/{milestone_number} }	write	<u>UAT</u> <u>IAT</u>	Repository permissions for "Issues"
DELETE		<u>UAT</u>	Repository

<pre>/repos/{owner}/{repo}/milestones/{milestone_number}</pre>	write	(IAT)	permissions for "Issues"
POST /repos/{owner}/{repo}/pulls	write	<u>UAT</u> <u>IAT</u>	×
PATCH /repos/{owner}/{repo}/pulls/comments/{comment_id}	write	(UAT) (IAT)	×
DELETE /repos/{owner}/{repo}/pulls/comments/{comment_id}	write	(UAT) (IAT)	×
POST /repos/{owner}/{repo}/pulls/comments/{comment_id}/ reactions	write	(UAT) (IAT)	×
DELETE /repos/{owner}/{repo}/pulls/comments/{comment_id}/ reactions/{reaction_id}	write	UAT IAT	×
PATCH /repos/{owner}/{repo}/pulls/{pull_number}	write	<u>UAT</u> <u>IAT</u>	×
POST /repos/{owner}/{repo}/pulls/{pull_number}/comments	write	UAT LAT	×
POST /repos/{owner}/{repo}/pulls/{pull_number}/comments /{comment_id}/replies	write	UAT IAT	×
POST /repos/{owner}/{repo}/pulls/{pull_number}/requested_ reviewers	write	UAT IAT	×
<pre>DELETE /repos/{owner}/{repo}/pulls/{pull_number}/requested_ reviewers</pre>	write	(UAT) (IAT)	×
POST /repos/{owner}/{repo}/pulls/{pull_number}/reviews	write	(UAT) (IAT)	×
PUT /repos/{owner}/{repo}/pulls/{pull_number}/reviews/{r eview_id}	write	<u>UAT</u> <u>IAT</u>	×
<pre>DELETE /repos/{owner}/{repo}/pulls/{pull_number}/reviews/{r eview_id}</pre>	write	(UAT) (IAT)	×
<pre>PUT /repos/{owner}/{repo}/pulls/{pull_number}/reviews/{r eview_id}/dismissals</pre>	write	(UAT) (IAT)	×
POST /repos/{owner}/{repo}/pulls/{pull_number}/reviews/{review_id}/events	write	<u>UAT</u> <u>IAT</u>	×
PUT /repos/{owner}/{repo}/pulls/{pull_number}/update- branch	write	(UAT) (IAT)	×

GET /repos/{owner}/{repo}/assignees	read	(UAT) (IAT)	Repository permissions for "Issues"
<pre>GET /repos/{owner}/{repo}/assignees/{assignee}</pre>	read	(UAT) (IAT)	Repository permissions for "Issues"
<pre>GET /repos/{owner}/{repo}/commits/{commit_sha}/pulls</pre>	read	<u>UAT</u> <u>IAT</u>	×
<pre>GET /repos/{owner}/{repo}/dependency- graph/compare/{basehead}</pre>	read	<u>UAT</u> <u>IAT</u>	Repository permissions for "Contents"
GET /repos/{owner}/{repo}/issues/comments	read	<u>UAT</u> <u>IAT</u>	Repository permissions for "Issues"
<pre>GET /repos/{owner}/{repo}/issues/comments/{comment_id} }</pre>	read	(UAT) (IAT)	Repository permissions for "Issues"
<pre>GET /repos/{owner}/{repo}/issues/events/{event_id}</pre>	read	(UAT) (IAT)	Repository permissions for "Issues"
<pre>GET /repos/{owner}/{repo}/issues/{issue_number}/assigne es/{assignee}</pre>	read	(UAT) (IAT)	Repository permissions for "Issues"
<pre>GET /repos/{owner}/{repo}/issues/{issue_number}/comme nts</pre>	read	(UAT) (IAT)	Repository permissions for "Issues"
GET /repos/{owner}/{repo}/issues/{issue_number}/events	read	(UAT) (IAT)	Repository permissions for "Issues"
GET /repos/{owner}/{repo}/issues/{issue_number}/labels	read	(UAT) (IAT)	Repository permissions for "Issues"
<pre>GET /repos/{owner}/{repo}/issues/{issue_number}/timeline</pre>	read	(UAT) (IAT)	Repository permissions for "Issues"
GET /repos/{owner}/{repo}/labels	read	<u>UAT</u> <u>IAT</u>	Repository permissions for "Issues"
<pre>GET /repos/{owner}/{repo}/labels/{name}</pre>	read	(UAT) (IAT)	Repository permissions for "Issues"
GET /repos/{owner}/{repo}/milestones	read	(UAT) (IAT)	Repository permissions for "Issues"
GET /repos/{owner}/{repo}/milestones/{milestone_number} }	read	(UAT) (IAT)	Repository permissions for "Issues"
GET /renos/fowner}/freno}/milestones/fmilestone number	read	<u>UAT</u>	Repository nermissions for

//labels	rcuu	(IAT)	"Issues"
GET /repos/{owner}/{repo}/pulls	read	<u>UAT</u> <u>IAT</u>	×
GET /repos/{owner}/{repo}/pulls/comments	read	<u>UAT</u> <u>IAT</u>	×
GET /repos/{owner}/{repo}/pulls/comments/{comment_id}	read	<u>UAT</u> <u>IAT</u>	×
GET /repos/{owner}/{repo}/pulls/comments/{comment_id}/ reactions	read	<u>UAT</u>	×
<pre>GET /repos/{owner}/{repo}/pulls/{pull_number}</pre>	read	<u>UAT</u> <u>IAT</u>	Repository permissions for "Contents"
GET /repos/{owner}/{repo}/pulls/{pull_number}/comments	read	<u>UAT</u> <u>IAT</u>	×
GET /repos/{owner}/{repo}/pulls/{pull_number}/commits	read	<u>UAT</u> <u>IAT</u>	×
<pre>GET /repos/{owner}/{repo}/pulls/{pull_number}/files</pre>	read	<u>UAT</u> <u>IAT</u>	×
GET /repos/{owner}/{repo}/pulls/{pull_number}/merge	read	<u>UAT</u> <u>IAT</u>	×
GET /repos/{owner}/{repo}/pulls/{pull_number}/requested_ reviewers	read	<u>UAT</u> <u>IAT</u>	*
GET /repos/{owner}/{repo}/pulls/{pull_number}/reviews	read	<u>UAT</u> <u>IAT</u>	×
<pre>GET /repos/{owner}/{repo}/pulls/{pull_number}/reviews/{r eview_id}</pre>	read	<u>UAT</u> <u>IAT</u>	×
GET /repos/{owner}/{repo}/pulls/{pull_number}/reviews/{review_id}/comments	read	UAT IAT	×

Repository permissions for "Repository security advisories" 🔗

Endpoint	Access	Token types	Additional permissions
GET /orgs/{org}/security-advisories	write	(UAT) (IAT)	×
POST /repos/{owner}/{repo}/security-advisories	write	(UAT) (IAT)	×

POST /repos/{owner}/{repo}/security-advisories/reports	write	<u>UAT</u> <u>IAT</u>	×
PATCH /repos/{owner}/{repo}/security-advisories/{ghsa_id}	write	UAT IAT	*
POST /repos/{owner}/{repo}/security-advisories/{ghsa_id}/cve	write	UAT IAT	*
GET /repos/{owner}/{repo}/security-advisories	read	UAT IAT	×
<pre>GET /repos/{owner}/{repo}/security- advisories/{ghsa_id}</pre>	read	<u>UAT</u> <u>IAT</u>	×

Repository permissions for "Secret scanning alerts"

Endpoint	Access	Token types	Additional permissions
PATCH /repos/{owner}/{repo}/secret-scanning/alerts/{alert_number}	write	<u>UAT</u> <u>IAT</u>	×
GET /orgs/{org}/secret-scanning/alerts	read	(UAT) (IAT)	×
GET /repos/{owner}/{repo}/secret-scanning/alerts	read	(UAT) (IAT)	×
<pre>GET /repos/{owner}/{repo}/secret- scanning/alerts/{alert_number}</pre>	read	(UAT) (IAT)	×
GET /repos/{owner}/{repo}/secret-scanning/alerts/{alert_number}/locations	read	<u>UAT</u> <u>IAT</u>	×

Repository permissions for "Secrets" *₽*

Endpoint	Access	Token types	Additional permissions
<pre>PUT /repos/{owner}/{repo}/actions/secrets/{secret_name}</pre>	write	<u>UAT</u> <u>IAT</u>	×
DELETE /repos/{owner}/{repo}/actions/secrets/{secret_name}	write	UAT IAT	×
PUT /repositories/{repository_id}/environments/{environme nt_name}/secrets/{secret_name}	write	UAT IAT	Repository permissions for "Environments"
<pre>DELETE /repositories/{repository_id}/environments/{environme nt_name}/secrets/{secret_name}</pre>	write	UAT IAT	Repository permissions for "Environments"

GET /repos/{owner}/{repo}/actions/organization- secrets	read	(UAT) (IAT)	×
<pre>GET /repos/{owner}/{repo}/actions/secrets</pre>	read	<u>UAT</u> <u>IAT</u>	×
GET /repos/{owner}/{repo}/actions/secrets/public-key	read	<u>UAT</u> <u>IAT</u>	×
<pre>GET /repos/{owner}/{repo}/actions/secrets/{secret_name}</pre>	read	UAT IAT	×
GET /repositories/{repository_id}/environments/{environment_name}/secrets	read	<u>UAT</u> <u>IAT</u>	Repository permissions for "Environments"
GET /repositories/{repository_id}/environments/{environme nt_name}/secrets/public-key	read	(IAI)	Repository permissions for "Environments"
GET /repositories/{repository_id}/environments/{environments_name}/secrets/{secret_name}	read	<u>UAT</u> <u>IAT</u>	Repository permissions for "Environments"

Repository permissions for "Variables" $\mathscr {P}$

Endpoint	Access	Token types	Additional permissions
POST /repos/{owner}/{repo}/actions/variables	write	<u>UAT</u> <u>IAT</u>	×
PATCH /repos/{owner}/{repo}/actions/variables/{name}	write	<u>UAT</u> <u>IAT</u>	×
<pre>DELETE /repos/{owner}/{repo}/actions/variables/{name}</pre>	write	<u>UAT</u> <u>IAT</u>	×
POST /repositories/{repository_id}/environments/{environments/name}/variables	write	(UAT) (IAT)	Repository permissions for "Environments"
PATCH /repositories/{repository_id}/environments/{environments_name}/variables/{name}	write	(UAT) (IAT)	Repository permissions for "Environments"
<pre>DELETE /repositories/{repository_id}/environments/{environme nt_name}/variables/{name}</pre>	write	<u>UAT</u> <u>IAT</u>	Repository permissions for "Environments"
GET /repos/{owner}/{repo}/actions/organization- variables	read	<u>UAT</u> <u>IAT</u>	×
GET /repos/{owner}/{repo}/actions/variables	read	(UAT) (IAT)	×
<pre>GET /repos/{owner}/{repo}/actions/variables/{name}</pre>	read	UAT	×

		<u>IAI</u>	
GET /repositories/{repository_id}/environments/{environment_name}/variables	read	UAT IAT	Repository permissions for "Environments"
GET /repositories/{repository_id}/environments/{environme nt_name}/variables/{name}	read	UAT LAT	Repository permissions for "Environments"

Repository permissions for "Webhooks" 🔗

Endpoint	Access	Token types	Additional permissions
POST /repos/{owner}/{repo}/hooks	write	(UAT) (IAT)	×
PATCH /repos/{owner}/{repo}/hooks/{hook_id}	write	<u>UAT</u> <u>IAT</u>	×
DELETE /repos/{owner}/{repo}/hooks/{hook_id}	write	<u>UAT</u> <u>IAT</u>	×
PATCH /repos/{owner}/{repo}/hooks/{hook_id}/config	write	(UAT) (IAT)	×
POST /repos/{owner}/{repo}/hooks/{hook_id}/deliveries/{delivery_id}/attempts	write	<u>UAT</u> <u>(IAT</u>)	×
GET /repos/{owner}/{repo}/hooks	read	(UAT) (IAT)	×
<pre>GET /repos/{owner}/{repo}/hooks/{hook_id}</pre>	read	<u>UAT</u> <u>IAT</u>	×
<pre>GET /repos/{owner}/{repo}/hooks/{hook_id}/config</pre>	read	<u>UAT</u> <u>IAT</u>	×
GET /repos/{owner}/{repo}/hooks/{hook_id}/deliveries	read	<u>UAT</u> <u>IAT</u>	×
GET /repos/{owner}/{repo}/hooks/{hook_id}/deliveries/{del ivery_id}	read	<u>UAT</u> <u>IAT</u>	×
POST /repos/{owner}/{repo}/hooks/{hook_id}/pings	read	<u>UAT</u> <u>IAT</u>	×
POST /repos/{owner}/{repo}/hooks/{hook_id}/tests	read	<u>UAT</u> <u>IAT</u>	×

Repository permissions for "Workflows" &

Endpoint	Access	Token	Additional
		types	permissions

POST /repos/{owner}/{repo}/git/refs	write	<u>UAT</u> <u>IAT</u>	Repository permissions for "Contents"
PATCH /repos/{owner}/{repo}/git/refs/{ref}	write	<u>UAT</u> <u>IAT</u>	Repository permissions for "Contents"

User permissions for "Block another user" ∂

Endpoint	Access	Token types	Additional permissions
PUT /user/blocks/{username}	write	<u>UAT</u>	×
DELETE /user/blocks/{username}	write	<u>UAT</u>	×
GET /user/blocks	read	<u>UAT</u>	×
GET /user/blocks/{username}	read	<u>UAT</u>	×

User permissions for "Codespaces user secrets" ∂

Endpoint	Access	Token types	Additional permissions
PUT /user/codespaces/secrets/{secret_name}	write	(<u>UAT</u>)	×
DELETE /user/codespaces/secrets/{secret_name}	write	(<u>UAT</u>)	×
PUT /user/codespaces/secrets/{secret_name}/repositories	write	<u>UAT</u>	*
PUT /user/codespaces/secrets/{secret_name}/repositories/{ repository_id}	write	<u>UAT</u>	Repository permissions for "Metadata"
<pre>DELETE /user/codespaces/secrets/{secret_name}/repositories/{ repository_id}</pre>	write	<u>UAT</u>	Repository permissions for "Metadata"
GET /user/codespaces/secrets	read	<u>UAT</u>	×
GET /user/codespaces/secrets/public-key	read	<u>UAT</u>	×
GET /user/codespaces/secrets/{secret_name}	read	<u>UAT</u>	×
GET /user/codespaces/secrets/{secret_name}/repositories	read	<u>UAT</u>	×

User permissions for "Email addresses" ∂

Endpoint	Access	Token types	Additional permissions
PATCH /user/email/visibility	write	<u>UAT</u>	×

POST /user/emails	write	<u>UAT</u>	*
DELETE /user/emails	write	<u>UAT</u>	×
GET /user/emails	read	<u>UAT</u>	×
GET /user/public_emails	read	(<u>UAT</u>)	×

User permissions for "Followers" ₽

Endpoint	Access	Token types	Additional permissions
PUT /user/following/{username}	write	<u>UAT</u>	×
DELETE /user/following/{username}	write	<u>UAT</u>	×
GET /user/followers	read	<u>UAT</u>	×
GET /user/following	read	<u>UAT</u>	×
GET /user/following/{username}	read	<u>UAT</u>	×

User permissions for "GPG keys" ₽

Endpoint	Access	Token types	Additional permissions
POST /user/gpg_keys	write	<u>UAT</u>	×
DELETE /user/gpg_keys/{gpg_key_id}	write	<u>UAT</u>	×
GET /user/gpg_keys	read	<u>UAT</u>	×
GET /user/gpg_keys/{gpg_key_id}	read	<u>UAT</u>	×

User permissions for "Gists" ∂

Endpoint	Access	Token types	Additional permissions
POST /gists	write	<u>UAT</u>	Repository permissions for "Metadata"
PATCH /gists/{gist_id}	write	<u>UAT</u>	Repository permissions for "Metadata"
DELETE /gists/{gist_id}	write	<u>UAT</u>	Repository permissions for "Metadata"
POST /gists/{gist_id}/comments	write	<u>UAT</u>	Repository permissions for "Metadata"

PATCH /gists/{gist_id}/comments/{comment_id}	write	<u>UAT</u>	Repository permissions for "Metadata"
DELETE /gists/{gist_id}/comments/{comment_id}	write	<u>UAT</u>	Repository permissions for "Metadata"
POST /gists/{gist_id}/forks	write	<u>UAT</u>	Repository permissions for "Metadata"
PUT /gists/{gist_id}/star	write	(UAT)	Repository permissions for "Metadata"
DELETE /gists/{gist_id}/star	write	<u>UAT</u>	Repository permissions for "Metadata"

User permissions for "Git SSH keys" ∂

Endpoint	Access	Token types	Additional permissions
POST /user/keys	write	(<u>UAT</u>)	×
DELETE /user/keys/{key_id}	write	<u>UAT</u>	×
GET /user/keys	read	<u>UAT</u>	×
GET /user/keys/{key_id}	read	<u>UAT</u>	×
GET /users/{username}/keys	read	<u>UAT</u> <u>IAT</u>	×

User permissions for "Interaction limits" ${\mathscr O}$

Endpoint	Access	Token types	Additional permissions
PUT /user/interaction-limits	write	<u>UAT</u>	×
DELETE /user/interaction-limits	write	<u>UAT</u>	×
GET /user/interaction-limits	read	<u>UAT</u>	×

User permissions for "Notifications" ∂

Endpoint	Access	Token types	Additional permissions
GET /notifications	read	<u>UAT</u>)	Repository permissions for "Metadata"

User permissions for "Plan" ∂

Endpoint	Access	Token types	Additional permissions
GET /users/{username}/settings/billing/actions	read	<u>UAT</u>	×
GET /users/{username}/settings/billing/packages	read	<u>UAT</u>	×
GET /users/{username}/settings/billing/shared-storage	read	<u>UAT</u>	×

User permissions for "Profile" *∂*

Endpoint	Access	Token types	Additional permissions
PATCH /user	write	<u>UAT</u>	×
POST /user/social_accounts	write	<u>UAT</u>	×
DELETE /user/social_accounts	write	<u>UAT</u>	×

User permissions for "SSH signing keys" ${\mathscr O}$

Endpoint	Access	Token types	Additional permissions
POST /user/ssh_signing_keys	write	<u>UAT</u>	×
DELETE /user/ssh_signing_keys/{ssh_signing_key_id}	write	<u>UAT</u>	×
GET /user/ssh_signing_keys	read	<u>UAT</u>	×
GET /user/ssh_signing_keys/{ssh_signing_key_id}	read	<u>UAT</u>	×

User permissions for "Starring" ∂

Endpoint	Access	Token types	Additional permissions
PUT /user/starred/{owner}/{repo}	write	<u>UAT</u>	×
DELETE /user/starred/{owner}/{repo}	write	<u>UAT</u>	×
GET /user/starred	read	<u>UAT</u>	×
GET /user/starred/{owner}/{repo}	read	<u>UAT</u>	×
GET /users/{username}/starred	read	<u>UAT</u> <u>IAT</u>	×

User permissions for "Watching" &

Endpoint	Access	Token types	Additional permissions
GET /user/subscriptions	read	<u>UAT</u>	×
GET /users/{username}/subscriptions	read	<u>UAT</u> <u>IAT</u>	×

Legal

© 2023 GitHub, Inc. <u>Terms</u> <u>Privacy</u> <u>Status</u> <u>Pricing</u> <u>Expert services</u> <u>Blog</u>