



Secret scanning patterns

Lists of supported secrets and the partners that GitHub works with to prevent fraudulent use of secrets that were committed accidentally.

Secret scanning is available for organization-owned repositories in GitHub Enterprise Server if your enterprise has a license for GitHub Advanced Security. For more information, see "About secret scanning" and "About GitHub Advanced Security."

In this article

About secret scanning alerts

About push protection alerts

Supported secrets

Further reading

Note: Your site administrator must enable secret scanning for your GitHub Enterprise Server instance before you can use this feature. For more information, see "Configuring secret scanning for your appliance."

You may not be able to enable or disable secret scanning, if an enterprise owner has set a policy at the enterprise level. For more information, see "Enforcing policies for code security and analysis for your enterprise."

About secret scanning alerts @

When secret scanning is enabled, GitHub scans repositories for secrets issued by a large variety of service providers and generates secret scanning alerts.

You can see these alerts on the **Security** tab of the repository.

If access to a resource requires paired credentials, then secret scanning will create an alert only when both parts of the pair are detected in the same file. This ensures that the most critical leaks are not hidden behind information about partial leaks. Pair matching also helps reduce false positives since both elements of a pair must be used together to access the provider's resource.

If you use the REST API for secret scanning, you can use the Secret type to report on secrets from specific issuers. For more information, see "Secret scanning."

Note: You can also define custom secret scanning patterns for your repository, organization, or enterprise. For more information, see "<u>Defining custom patterns for secret scanning</u>."

About push protection alerts &

Push protection alerts are user alerts that are reported by push protection. Secret scanning as a push protection currently scans repositories for secrets issued by some

service providers.

If access to a resource requires paired credentials, then secret scanning will create an alert only when both parts of the pair are detected in the same file. This ensures that the most critical leaks are not hidden behind information about partial leaks. Pair matching also helps reduce false positives since both elements of a pair must be used together to access the provider's resource.

Older versions of certain tokens may not be supported by push protection as these tokens may generate a higher number of false positives than their most recent version. Push protection may also not apply to legacy tokens. For tokens such as Azure Storage Keys, GitHub only supports *recently created* tokens, not tokens that match the legacy patterns. For more information about push protection limitations, see "Troubleshooting secret scanning."

Supported secrets @

This table lists the secrets supported by secret scanning. You can see the types of alert that get generated for each token, as well as whether a validity check is performed on the token.

- **Provider**—name of the token provider.
- **Secret scanning alert**—token for which leaks are reported to users on GitHub. Applies to private repositories where GitHub Advanced Security and secret scanning enabled.
- **Push protection**—token for which leaks are reported to users on GitHub. Applies to repositories with secret scanning and push protection enabled.
- **Validity check**—token for which a validity check is implemented. Currently only applies to GitHub tokens.

Provider	Token	Secret scanning alert	Push protection	Validity check
Adafruit IO	adafruit_io_key	~	~	×
Adobe	adobe_device_to ken	~	~	×
Adobe	adobe_service_t oken	~	~	×
Adobe	adobe_short_live d_access_token	~	~	×
Aiven	aiven_auth_toke n	~	~	×
Aiven	aiven_service_pa ssword	~	~	×
Alibaba Cloud	alibaba_cloud_ac cess_key_id alibaba_cloud_ac cess_key_secret	~	~	×
Login with Amazon	amazon_oauth_cl ient_id amazon_oauth_cl ient_secret	~	~	×

Amazon Web Services (AWS)	aws_access_key_ id aws_secret_acce ss_key	~	~	×
Amazon Web Services (AWS)	aws_session_tok en aws_temporary_ access_key_id aws_secret_acce ss_key	~	~	×
Asana	asana_personal_ access_token	~	✓	×
Atlassian	atlassian_api_tok en	~	×	×
Atlassian	atlassian_jwt	~	×	×
Atlassian	bitbucket_server _personal_access _token	~	~	×
Azure	azure_active_dir ectory_applicatio n_secret	~	~	×
Azure	azure_batch_key _identifiable	~	~	×
Azure	azure_cache_for_ redis_access_key	~	~	×
Azure	azure_cosmosdb _key_identifiable	~	✓	×
Azure	azure_devops_pe rsonal_access_to ken	~	~	×
Azure	azure_function_k ey	~	~	×
Azure	azure_ml_web_s ervice_classic_id entifiable_key	~	~	×
Azure	azure_sas_token	~	×	×
Azure	azure_search_ad min_key	~	~	×
Azure	azure_search_qu ery_key	~	~	×
Azure	azure_managem ent_certificate	~	×	×
Azure	azure_sql_conne ction_string	~	×	×
Azure	azure_storage_a ccount_key	~	✓	×

Beamer	beamer_api_key	~	×	×
Canadian Digital Service	cds_canada_notif y_api_key	~	~	×
Checkout.com	checkout_produc tion_secret_key	~	~	×
Checkout.com	checkout_test_se cret_key	~	×	×
Chief Tools	chief_tools_token	~	~	×
Clojars	clojars_deploy_to ken	~	~	×
CloudBees CodeShip	codeship_creden tial	~	×	×
Contentful	contentful_perso nal_access_toke n	~	×	×
crates.io (Rust Foundation)	cratesio_api_tok en	~	~	×
Databricks	databricks_acces s_token	~	~	×
Defined	defined_networki ng_nebula_api_k ey	~	~	×
DevCycle	devcycle_client_ api_key	~	~	×
DevCycle	devcycle_mobile _api_key	~	~	×
DevCycle	devcycle_server_ api_key	~	~	×
DigitalOcean	digitalocean_oau th_token	~	~	×
DigitalOcean	digitalocean_per	~	~	×
	sonal_access_tok en			
DigitalOcean	digitalocean_refr esh_token	~	~	×
DigitalOcean	digitalocean_syst em_token	~	~	×
Discord	discord_api_toke n_v2	~	~	×
Discord	discord_bot_toke n	~	~	×
Doppler	doppler_audit_to	~	✓	×

レ	$\overline{}$	n	

	ken			
Doppler	doppler_cli_toke n	~	~	×
Doppler	doppler_personal _token	~	~	×
Doppler	doppler_scim_to ken	~	~	×
Doppler	doppler_service_ token	~	~	×
Doppler	doppler_service_ account_token	~	~	×
Dropbox	dropbox_access_ token	✓	×	×
Dropbox	dropbox_short_li ved_access_toke n	~	~	×
Duffel	duffel_live_acces s_token	~	~	×
Duffel	duffel_test_acces s_token	✓	×	×
Dynatrace	dynatrace_acces s_token	~	×	×
Dynatrace	dynatrace_intern al_token	~	×	×
EasyPost	easypost_produc tion_api_key	~	~	×
EasyPost	easypost_test_ap i_key	✓	×	×
еВау	ebay_production _client_id ebay_production _client_secret	~	×	×
еВау	ebay_sandbox_cl ient_id ebay_sandbox_cl ient_secret	~	×	×
Fastly	fastly_api_token	~	×	×
Figma	figma_pat	~	~	×
Finicity	finicity_app_key	~	×	×
Flutterwave	flutterwave_live_ api_secret_key	✓	~	×
Flutterwave	flutterwave_test_ api_secret_key	✓	×	×

Frame.io	frameio_develop er_token	~	×	×
Frame.io	frameio_jwt	~	×	×
FullStory	fullstory_api_key	~	~	×
GitHub	github_app_insta llation_access_to ken	~	~	~
GitHub	github_oauth_ac cess_token	~	~	~
GitHub	github_personal_ access_token	~	~	~
GitHub	github_refresh_t oken	~	~	~
GitHub	github_ssh_priva te_key	~	~	~
GitLab	gitlab_access_to ken	~	×	×
GoCardless	gocardless_live_ access_token	~	×	×
GoCardless	gocardless_sand box_access_toke n	~	×	×
Google	firebase_cloud_ messaging_serve r_key	~	×	×
Google	google_cloud_sto rage_service_acc ount_access_key _id google_cloud_sto rage_access_key _secret	~	~	×
Google	google_cloud_sto rage_user_acces s_key_id google_cloud_sto rage_access_key _secret	~	~	×
Google	google_oauth_ac cess_token	~	×	×
Google	google_oauth_cli ent_id google_oauth_cli ent_secret	~	~	×
Google	google_oauth_ref resh_token	~	×	×

Google Cloud	google_api_key	~	×	×
Google Cloud	google_cloud_pri vate_key_id	~	~	×
Grafana	grafana_cloud_a pi_key	~	~	×
Grafana	grafana_cloud_a pi_token	~	~	×
Grafana	grafana_project_ api_key	~	~	×
Grafana	grafana_project_ service_account_ token	~	~	×
HashiCorp	hashicorp_vault_ batch_token	~	~	×
HashiCorp	hashicorp_vault_ root_service_tok en	~	~	×
HashiCorp	hashicorp_vault_ service_token	~	~	×
Hashicorp Terraform	terraform_api_to ken	~	~	×
Highnote	highnote_rk_live_ key	~	~	×
Highnote	highnote_rk_test _key	~	~	×
Highnote	highnote_sk_live _key	~	~	×
Highnote	highnote_sk_test _key	~	~	×
Hubspot	hubspot_api_key	~	~	×
Hubspot	hubspot_api_per sonal_access_ke y	~	~	×
Intercom	intercom_access _token	~	~	×
Ionic	ionic_personal_a ccess_token	~	~	×
Ionic	ionic_refresh_tok en	~	~	×
JD Cloud	jd_cloud_access_ key	~	×	×
JFrog	jfrog_platform_a ccess_token	~	~	×

JFrog	jfrog_platform_a pi_key	~	~	×
Linear	linear_api_key	~	~	×
Linear	linear_oauth_acc ess_token	~	~	×
Lob	lob_live_api_key	~	×	×
Lob	lob_test_api_key	~	×	×
LocalStack	localstack_api_k ey	~	×	×
LogicMonitor	logicmonitor_bea rer_token	~	~	×
LogicMonitor	logicmonitor_lmv 1_access_key	~	~	×
Mailchimp	mailchimp_api_k ey	~	×	×
Mailgun	mailgun_api_key	~	×	×
Mapbox	mapbox_secret_ access_token	~	×	×
Mercury	mercury_non_pr oduction_api_tok en	~	×	×
Mercury	mercury_product ion_api_token	~	×	×
MessageBird	messagebird_api _key	~	×	×
Meta	facebook_access _token	~	×	×
Midtrans	midtrans_produc tion_server_key	~	~	×
Midtrans	midtrans_sandbo x_server_key	~	×	×
New Relic	new_relic_insight s_query_key	~	~	×
New Relic	new_relic_license _key	~	×	×
New Relic	new_relic_person al_api_key	~	√	×
New Relic	new_relic_rest_a pi_key	~	~	×
Notion	notion_integratio n_token	~	×	×

Notion	notion_oauth_cli ent_secret	~	×	×
npm	npm_access_tok en	~	~	×
NuGet	nuget_api_key	~	✓	×
Octopus Deploy	octopus_deploy_ api_key	~	×	×
Oculus	oculus_very_tiny _encrypted_sessi on	~	×	×
OneChronos	onechronos_api_ key	~	~	×
OneChronos	onechronos_eb_ api_key	~	~	×
OneChronos	onechronos_eb_ encryption_key	~	~	×
OneChronos	onechronos_oaut h_token	~	~	×
OneChronos	onechronos_refr esh_token	~	~	×
Onfido	onfido_live_api_t oken	~	~	×
Onfido	onfido_sandbox_ api_token	~	×	×
OpenAl	openai_api_key	~	~	×
OpenAl	openai_api_key_ v2	~	~	×
Palantir	palantir_jwt	~	~	×
Persona	persona_producti on_api_key	~	×	×
Persona	persona_sandbo x_api_key	~	×	×
PlanetScale	planetscale_data base_password	~	~	×
PlanetScale	planetscale_oaut h_token	~	~	×
PlanetScale	planetscale_servi ce_token	~	~	×
Plivo	plivo_auth_id plivo_auth_token	~	~	×
Postman	postman_api_key	✓	~	×

Postman	postman_collecti on_key	~	~	×
Prefect	prefect_server_a pi_key	~	~	×
Prefect	prefect_user_api _key	~	~	×
Proctorio	proctorio_consu mer_key	~	×	×
Proctorio	proctorio_linkage _key	~	×	×
Proctorio	proctorio_registr ation_key	~	×	×
Proctorio	proctorio_secret_ key	~	~	×
Pulumi	pulumi_access_t oken	~	×	×
РуРІ	pypi_api_token	✓	×	×
ReadMe	readmeio_api_ac cess_token	~	~	×
redirect.pizza	redirect_pizza_a pi_token	~	~	×
Rootly	rootly_api_key	~	~	×
RubyGems	rubygems_api_k ey	~	×	×
Samsara	samsara_api_tok en	~	~	×
Samsara	samsara_oauth_ access_token	~	~	×
Segment	segment_public_ api_token	~	✓	×
SendGrid	sendgrid_api_key	~	✓	×
Sendinblue	sendinblue_api_k ey	~	~	×
Sendinblue	sendinblue_smtp _key	~	~	×
Shippo	shippo_live_api_t oken	~	~	×
Shippo	shippo_test_api_t oken	~	×	×
Shopify	shopify_access_t oken	~	~	×

Shopify	shopify_app_clie nt_credentials	~	×	×
Shopify	shopify_app_clie nt_secret	~	×	×
Shopify	shopify_app_shar ed_secret	~	~	×
Shopify	shopify_custom_ app_access_toke n	~	×	×
Shopify	shopify_marketpl ace_token	~	×	×
Shopify	shopify_merchan t_token	~	×	×
Shopify	shopify_partner_ api_token	~	×	×
Shopify	shopify_private_ app_password	~	×	×
Slack	slack_api_token	~	~	×
Slack	slack_incoming_ webhook_url	~	×	×
Slack	slack_workflow_ webhook_url	~	×	×
Square	square_access_t oken	~	×	×
Square	square_productio n_application_se cret	~	×	×
Square	square_sandbox_ application_secr et	~	×	×
SSLMate	ssImate_api_key	~	×	×
SSLMate	sslmate_cluster_ secret	~	×	×
Stripe	stripe_live_restri cted_key	~	×	×
Stripe	stripe_api_key	~	✓	×
Stripe	stripe_legacy_api _key	~	×	×
Stripe	stripe_test_restri cted_key	~	×	×
Stripe	stripe_test_secre t_key	~	×	×

Stripe	stripe_webhook_ signing_secret	~	×	×
Supabase	supabase_servic e_key	~	×	×
Tableau	tableau_personal _access_token	~	×	×
Telegram	telegram_bot_to ken	~	×	×
Telnyx	telnyx_api_v2_ke y	~	~	×
Tencent Cloud	tencent_cloud_se cret_id	~	~	×
Tencent WeChat	tencent_wechat_ api_app_id	~	×	×
Twilio	twilio_access_tok en	~	~	×
Twilio	twilio_account_si d	~	~	×
Twilio	twilio_api_key	~	~	×
Typeform	typeform_person al_access_token	~	~	×
Uniwise	wiseflow_api_key	~	~	×
WakaTime	wakatime_pp_se cret	~	~	×
WakaTime	wakatime_oauth _access_token	~	~	×
WakaTime	wakatime_oauth _refresh_token	~	~	×
WorkOS	workos_producti on_api_key	~	~	×
WorkOS	workos_staging_ api_key	~	×	×
Yandex	yandex_iam_acc ess_secret	~	×	×
Yandex	yandex_cloud_ap i_key	~	×	×
Yandex	yandex_cloud_ia m_cookie	~	×	×
Yandex	yandex_cloud_ia m_token	~	×	×
Yandex	yandex_dictionar	~	×	×

	y_api_key			
Yandex	yandex_predicto r_api_key	~	×	×
Yandex	yandex_translate _api_key	~	×	×
Zuplo	zuplo_consumer_ api_key	~	~	×

Further reading ${\mathscr O}$

- "Securing your repository"
- "Keeping your account and data secure"
- "Secret scanning partner program" in the GitHub Enterprise Cloud documentation

Legal

© 2023 GitHub, Inc. <u>Terms</u> <u>Privacy</u> <u>Status</u> <u>Pricing</u> <u>Expert services</u> <u>Blog</u>