

This version of GitHub Enterprise was discontinued on 2023-03-15. No patch releases will be made, even for critical security issues. For better performance, improved security, and new features, [upgrade to the latest version of GitHub Enterprise](#). For help with the upgrade, [contact GitHub Enterprise support](#).

Error: Key already in use

In this article

Finding where the key has been used

Fixing the issue

Deploy keys

This error occurs when you try to [add a key](#) that's already been added to another account or repository.

Finding where the key has been used

To determine where the key has already been used, open a terminal and type the `ssh` command. Use the `-i` flag to provide the path to the key you want to check:

```
$ ssh -T -ai ~/.ssh/id_rsa git@HOSTNAME
# Connect to your GitHub Enterprise Server instance using a specific ssh key
> Hi USERNAME! You've successfully authenticated, but GitHub does not
> provide shell access.
```

The *username* in the response is the account on your GitHub Enterprise Server instance that the key is currently attached to. If the response looks something like "username/repo", the key has been attached to a repository as a [deploy key](#).

To force SSH to use only the key provided on the command line, use `-o` to add the `IdentitiesOnly=yes` option:

```
$ ssh -v -o "IdentitiesOnly=yes" -i ~/.ssh/id_rsa git@HOSTNAME
```

Fixing the issue

To resolve the issue, first remove the key from the other account or repository and then [add it to your account](#).

If you don't have permissions to transfer the key, and can't contact a user who does, remove the keypair and [generate a brand new one](#).

Deploy keys

Once a key has been attached to one repository as a deploy key, it cannot be used on another repository. If you're running into this error while setting up deploy keys, see "[Managing deploy keys](#)."

Legal