

# About private networking with GitHub-hosted runners

## In this article

About GitHub-hosted runners networking

Using an API Gateway with OIDC

Using WireGuard to create a network overlay

You can connect GitHub-hosted runners to resources on a private network, including package registries, secret managers, and other on-premises services.

**Note:** GitHub-hosted runners are not currently supported on GitHub Enterprise Server. You can see more information about planned future support on the [GitHub public roadmap](#).

## About GitHub-hosted runners networking

By default, GitHub-hosted runners have access to the public internet. However, you may also want these runners to access resources on your private network, such as a package registry, a secret manager, or other on-premise services.

GitHub-hosted runners are shared across all GitHub customers, so you will need a way of connecting your private network to just your runners while they are running your workflows. There are a few different approaches you could take to configure this access, each with different advantages and disadvantages.

## Using an API Gateway with OIDC

With GitHub Actions, you can use OpenID Connect (OIDC) tokens to authenticate your workflow outside of GitHub Actions. For more information, see "[Using an API gateway with OIDC](#)."

## Using WireGuard to create a network overlay

If you don't want to maintain separate infrastructure for an API Gateway, you can create an overlay network between your runner and a service in your private network, by running WireGuard in both places. For more information, see "[Using WireGuard to create a network overlay](#)."

## Legal