

**This version of GitHub Enterprise was discontinued on 2023-03-15.** No patch releases will be made, even for critical security issues. For better performance, improved security, and new features, [upgrade to the latest version of GitHub Enterprise](#). For help with the upgrade, [contact GitHub Enterprise support](#).

# Deploying PHP to Azure App Service

## In this article

- Introduction
- Prerequisites
- Creating the workflow
- Additional resources

You can deploy your PHP project to Azure App Service as part of your continuous deployment (CD) workflows.

**Note:** GitHub-hosted runners are not currently supported on GitHub Enterprise Server. You can see more information about planned future support on the [GitHub public roadmap](#).

## Introduction

This guide explains how to use GitHub Actions to build and deploy a PHP project to [Azure App Service](#).

## Prerequisites

Before creating your GitHub Actions workflow, you will first need to complete the following setup steps:

- 1 Create an Azure App Service plan.

For example, you can use the Azure CLI to create a new App Service plan:

Bash



```
az appservice plan create \
  --resource-group MY_RESOURCE_GROUP \
  --name MY_APP_SERVICE_PLAN \
  --is-linux
```

In the command above, replace `MY_RESOURCE_GROUP` with your pre-existing Azure Resource Group, and `MY_APP_SERVICE_PLAN` with a new name for the App Service plan.

See the Azure documentation for more information on using the [Azure CLI](#):

- For authentication, see "[Sign in with Azure CLI](#)."
- If you need to create a new resource group, see "[az group](#)."

## 2 Create a web app.

For example, you can use the Azure CLI to create an Azure App Service web app with a PHP runtime:

Bash

```
az webapp create \
  --name MY_WEBAPP_NAME \
  --plan MY_APP_SERVICE_PLAN \
  --resource-group MY_RESOURCE_GROUP \
  --runtime "php|7.4"
```

In the command above, replace the parameters with your own values, where `MY_WEBAPP_NAME` is a new name for the web app.

## 3 Configure an Azure publish profile and create an `AZURE_WEBAPP_PUBLISH_PROFILE` secret.

Generate your Azure deployment credentials using a publish profile. For more information, see "[Generate deployment credentials](#)" in the Azure documentation.

In your GitHub repository, create a secret named `AZURE_WEBAPP_PUBLISH_PROFILE` that contains the contents of the publish profile. For more information on creating secrets, see "[Encrypted secrets](#)."

## 4 Optionally, configure a deployment environment. Environments are used to describe a general deployment target like `production`, `staging`, or `development`. When a GitHub Actions workflow deploys to an environment, the environment is displayed on the main page of the repository. You can use environments to require approval for a job to proceed, restrict which branches can trigger a workflow, or limit access to secrets. For more information about creating environments, see "[Using environments for deployment](#)."

# Creating the workflow

Once you've completed the prerequisites, you can proceed with creating the workflow.

The following example workflow demonstrates how to build and deploy a PHP project to Azure App Service when there is a push to the `main` branch.

Ensure that you set `AZURE_WEBAPP_NAME` in the workflow `env` key to the name of the web app you created. If the path to your project is not the repository root, change `AZURE_WEBAPP_PACKAGE_PATH` to the path to your project. If you use a version of PHP other than `8.x`, change `PHP_VERSION` to the version that you use.

If you configured a deployment environment, change the value of `environment` to be the name of your environment. If you did not configure an environment, delete the `environment` key.

YAML

```
# This workflow uses actions that are not certified by GitHub.
# They are provided by a third-party and are governed by
# separate terms of service, privacy policy, and support
# documentation.

# GitHub recommends pinning actions to a commit SHA.
# To get a newer version, you will need to update the SHA.
```

# You can also reference a tag or branch, but the action may change without warning

name: Build and deploy PHP app to Azure Web App

env:

```
AZURE_WEBAPP_NAME: MY_WEBAPP_NAME    # set this to your application's name
AZURE_WEBAPP_PACKAGE_PATH: '.'        # set this to the path to your web app project
PHP_VERSION: '8.x'                   # set this to the PHP version to use
```

on:

```
push:
  branches:
    - main
```

jobs:

```
build:
  runs-on: ubuntu-latest
```

steps:

- uses: actions/checkout@v2
- name: Setup PHP
  - uses: shivammathur/setup-php@v2
  - with:
    - php-version: \${ env.PHP\_VERSION }
- name: Check if composer.json exists
  - id: check\_files
  - uses: andstor/file-existence-action@v2
  - with:
    - files: 'composer.json'
- name: Get Composer Cache Directory
  - id: composer-cache
  - if: steps.check\_files.outputs.files\_exists == 'true'
  - run: |
    - echo "::set-output name=dir::\$(composer config cache-files-dir)"
- name: Set up dependency caching for faster installs
  - uses: actions/cache@v2
  - if: steps.check\_files.outputs.files\_exists == 'true'
  - with:
    - path: \${ steps.composer-cache.outputs.dir }
    - key: \${ runner.os }-composer-\${ hashFiles('\*\*/composer.lock') }
    - restore-keys: |
      - \${ runner.os }-composer-
- name: Run composer install if composer.json exists
  - if: steps.check\_files.outputs.files\_exists == 'true'
  - run: composer validate --no-check-publish && composer install --prefer-dist
- name: Upload artifact for deployment job
  - uses: actions/upload-artifact@v2
  - with:
    - name: php-app
    - path: .

deploy:

```
runs-on: ubuntu-latest
needs: build
environment:
  name: 'production'
  url: ${ steps.deploy-to-webapp.outputs.webapp-url }
```

steps:

- name: Download artifact from build job
  - uses: actions/download-artifact@v2
  - with:
    - name: php-app
- name: 'Deploy to Azure Web App'

```
id: deploy-to-webapp
uses: azure/webapps-deploy@85270a1854658d167ab239bce43949edb336fa7c
with:
  app-name: ${ env.AZURE_WEBAPP_NAME }
  publish-profile: ${ secrets.AZURE_WEBAPP_PUBLISH_PROFILE }
  package: .
```

## Additional resources [↗](#)

---

The following resources may also be useful:

- For the original starter workflow, see [azure-webapps-php.yml](#) in the GitHub Actions [starter-workflows](#) repository.
- The action used to deploy the web app is the official Azure [Azure/webapps-deploy](#) action.
- For more examples of GitHub Action workflows that deploy to Azure, see the [actions-workflow-samples](#) repository.

### Legal

© 2023 GitHub, Inc. [Terms](#) [Privacy](#) [Status](#) [Pricing](#) [Expert services](#) [Blog](#)