

This version of GitHub Enterprise was discontinued on 2023-03-15. No patch releases will be made, even for critical security issues. For better performance, improved security, and new features, [upgrade to the latest version of GitHub Enterprise](#). For help with the upgrade, [contact GitHub Enterprise support](#).

Building and testing Xamarin applications

In this article

Introduction

Prerequisites

Building Xamarin.iOS apps

Building Xamarin.Android apps

Specifying a .NET version

You can create a continuous integration (CI) workflow in GitHub Actions to build and test your Xamarin application.

Note: GitHub-hosted runners are not currently supported on GitHub Enterprise Server. You can see more information about planned future support on the [GitHub public roadmap](#).

Introduction

This guide shows you how to create a workflow that performs continuous integration (CI) for your Xamarin project. The workflow you create will allow you to see when commits to a pull request cause build or test failures against your default branch; this approach can help ensure that your code is always healthy.

For a full list of available Xamarin SDK versions on the GitHub Actions-hosted macOS runners, see the README file for the version of macOS you want to use in the [GitHub Actions Runner Images repository](#).

Prerequisites

We recommend that you have a basic understanding of Xamarin, .NET Core SDK, YAML, workflow configuration options, and how to create a workflow file. For more information, see:

- "[Workflow syntax for GitHub Actions](#)"
- "[Getting started with .NET](#)"
- "[Learn Xamarin](#)"

Building Xamarin.iOS apps

The example below demonstrates how to change the default Xamarin SDK versions and

build a Xamarin.iOS application.

```
name: Build Xamarin.iOS app

on: [push]

jobs:
  build:

    runs-on: macos-latest

    steps:
      - uses: actions/checkout@v2
      - name: Set default Xamarin SDK versions
        run: |
          $VM_ASSETS/select-xamarin-sdk-v2.sh --mono=6.12 --ios=14.10

      - name: Set default Xcode 12.3
        run: |
          XCODE_ROOT=/Applications/Xcode_12.3.0.app
          echo "MD_APPLE_SDK_ROOT=$XCODE_ROOT" >> $GITHUB_ENV
          sudo xcode-select -s $XCODE_ROOT

      - name: Setup .NET Core SDK 5.0.x
        uses: actions/setup-dotnet@v1
        with:
          dotnet-version: '5.0.x'

      - name: Install dependencies
        run: nuget restore <sln_file_path>

      - name: Build
        run: msbuild <csproj_file_path> /p:Configuration=Debug /p:Platform=iPhoneSimu
```

Building Xamarin.Android apps [↗](#)

The example below demonstrates how to change default Xamarin SDK versions and build a Xamarin.Android application.

```
name: Build Xamarin.Android app

on: [push]

jobs:
  build:

    runs-on: macos-latest

    steps:
      - uses: actions/checkout@v2
      - name: Set default Xamarin SDK versions
        run: |
          $VM_ASSETS/select-xamarin-sdk-v2.sh --mono=6.10 --android=10.2

      - name: Setup .NET Core SDK 5.0.x
        uses: actions/setup-dotnet@v1
        with:
          dotnet-version: '5.0.x'

      - name: Install dependencies
        run: nuget restore <sln_file_path>

      - name: Build
        run: msbuild <csproj_file_path> /t:PackageForAndroid /p:Configuration=Debug
```

Specifying a .NET version

To use a preinstalled version of the .NET Core SDK on a GitHub-hosted runner, use the `setup-dotnet` action. This action finds a specific version of .NET from the tools cache on each runner, and adds the necessary binaries to `PATH`. These changes will persist for the remainder of the job.

The `setup-dotnet` action is the recommended way of using .NET with GitHub Actions, because it ensures consistent behavior across different runners and different versions of .NET. If you are using a self-hosted runner, you must install .NET and add it to `PATH`. For more information, see the [setup-dotnet](#) action.

Legal

© 2023 GitHub, Inc. [Terms](#) [Privacy](#) [Status](#) [Pricing](#) [Expert services](#) [Blog](#)