

pack packlist

In this article

- Synopsis
- Description
- Options

[Experimental] [Plumbing] Compute the set of files to be included in a QL query pack or library pack.

GitHub CodeQL is licensed on a per-user basis upon installation. You can use CodeQL only for certain tasks under the license restrictions. For more information, see "[About the CodeQL CLI](#)." If you have a GitHub Advanced Security license, you can use CodeQL for automated analysis, continuous integration, and continuous delivery. For more information, see "[About GitHub Advanced Security](#)."

This content describes the most recent release of the CodeQL CLI. For more information about this release, see <https://github.com/github/codeql-cli-binaries/releases>.

To see details of the options available for this command in an earlier release, run the command with the `--help` option in your terminal.

Synopsis

Shell

```
codeql pack packlist <options>... -- <dir>
```

Description

[Experimental] [Plumbing] Compute the set of files to be included in a QL query pack or library pack.

This command determines the set of files to be included in the pack based on the patterns specified in any `.gitignore` files present in the pack or in an ancestor directory.

Available since `v2.6.0`.

Options

Primary Options

`<dir>`

The root directory of the package.

`--format=<fmt>` [↗](#)

Select output format, either `text` (*default*) or `json`.

Common options [↗](#)

`-h, --help` [↗](#)

Show this help text.

`-J=<opt>` [↗](#)

[Advanced] Give option to the JVM running the command.

(Beware that options containing spaces will not be handled correctly.)

`-v, --verbose` [↗](#)

Incrementally increase the number of progress messages printed.

`-q, --quiet` [↗](#)

Incrementally decrease the number of progress messages printed.

`--verbosity=<level>` [↗](#)

[Advanced] Explicitly set the verbosity level to one of errors, warnings, progress, progress+, progress++, progress+++. Overrides `-v` and `-q`.

`--logdir=<dir>` [↗](#)

[Advanced] Write detailed logs to one or more files in the given directory, with generated names that include timestamps and the name of the running subcommand.

(To write a log file with a name you have full control over, instead give `--log-to-stderr` and redirect stderr as desired.)

Legal

© 2023 GitHub, Inc. [Terms](#) [Privacy](#) [Status](#) [Pricing](#) [Expert services](#) [Blog](#)