

bqrs diff

In this article

- Synopsis
- Description
- Options

Compute the difference between two result sets.


GitHub CodeQL is licensed on a per-user basis upon installation. You can use CodeQL only for certain tasks under the license restrictions. For more information, see "[About the CodeQL CLI](#)." If you have a GitHub Advanced Security license, you can use CodeQL for automated analysis, continuous integration, and continuous delivery. For more information, see "[About GitHub Advanced Security](#)."

This content describes the most recent release of the CodeQL CLI. For more information about this release, see <https://github.com/github/codeql-cli-binaries/releases>.

To see details of the options available for this command in an earlier release, run the command with the `--help` option in your terminal.

Synopsis

Shell



```
codeql bqrs diff <options>... -- <file1> <file2>
```

Description


Compute the difference between two result sets.

Options

Primary Options

`<file1>` 

[Mandatory] First BQRS file to compare.

`<file2>` 

[Mandatory] Second BQRS file to compare.

--left=<file> [↗](#)

Write rows only present in `file1` to this file.

--right=<file> [↗](#)

Write rows only present in `file2` to this file.

--both=<file> [↗](#)

Write rows present in both `file1` and `file2` to this file.

--retain-result-sets=<result-set>[,<result-set>...] [↗](#)

Comma-separated list of result set names to copy directly to the corresponding output instead of comparing. If `--both` is given, that output is taken from `file1`. Defaults to 'nodes,edges,subpaths' to simplify handling of path-problem results.

--[no-]compare-internal-ids [↗](#)

[Advanced] Include internal entity IDs in the comparison. Entity IDs are not comparable across databases, but for result sets that originate from the same database this can help distinguish entities with the same location and label.

Common options [↗](#)

-h, --help [↗](#)

Show this help text.

-J=<opt> [↗](#)

[Advanced] Give option to the JVM running the command.

(Beware that options containing spaces will not be handled correctly.)

-v, --verbose [↗](#)

Incrementally increase the number of progress messages printed.

-q, --quiet [↗](#)

Incrementally decrease the number of progress messages printed.

--verbosity=<level> [↗](#)

[Advanced] Explicitly set the verbosity level to one of errors, warnings, progress, progress+, progress++, progress+++. Overrides `-v` and `-q`.

--logdir=<dir> [↗](#)

[Advanced] Write detailed logs to one or more files in the given directory, with generated names that include timestamps and the name of the running subcommand.

(To write a log file with a name you have full control over, instead give `--log-to-stderr` and redirect stderr as desired.)

Legal