



## Audit log events for your enterprise

#### In this article

About audit log events for your enterprise business business\_advanced\_security business\_secret\_scanning business\_secret\_scanning\_automatic\_validity\_checks business\_secret\_scanning\_custom\_pattern business\_secret\_scanning\_custom\_pattern\_push\_protection business\_secret\_scanning\_push\_protection business secret scanning push protection custom message checks custom\_property\_definition custom\_property\_value discussion\_post discussion\_post\_reply enterprise enterprise\_announcement enterprise\_domain git hook integration integration\_installation ip allow list ip\_allow\_list\_entry oauth\_application oauth\_authorization organization\_domain org\_secret\_scanning\_automatic\_validity\_checks org\_secret\_scanning\_custom\_pattern packages protected\_branch public\_key pull\_request pull\_request\_review pull\_request\_review\_comment repo repository\_branch\_protection\_evaluation repository\_invitation repository\_ruleset repository\_secret\_scanning repository\_secret\_scanning\_automatic\_validity\_checks

repository\_secret\_scanning\_custom\_pattern

repository\_secret\_scanning\_custom\_pattern\_push\_protection

repository\_secret\_scanning\_push\_protection
restrict\_notification\_delivery
secret\_scanning
secret\_scanning\_alert
secret\_scanning\_new\_repos
secret\_scanning\_push\_protection
security\_key
ssh\_certificate\_authority
ssh\_certificate\_requirement
staff
team
team\_discussions
team\_sync\_tenant
two\_factor\_authentication
user

Learn about audit log events recorded for your enterprise.

#### Who can use this feature

Enterprise owners and site administrators can interact with the audit log.

#### Notes:

workflows

- This article contains the events available in the latest version of GitHub Enterprise Server. Some of the events may not be available in previous versions.
- This article contains the events that may appear in the enterprise settings, specifically. The audit log in the site admin dashboard may contain additional events not listed here.
- This article contains the events that may appear in the audit log for an enterprise. For the events that can appear in a user account's security log or the audit log for an organization, see "Security log events" and "Audit log events for your organization."

#### **About audit log events for your enterprise** *₽*

The name for each audit log entry is composed of a category of events, followed by an operation type. For example, the repo create entry refers to the create operation on the repo category. The reference information in this article is grouped by categories.

#### business &

Action	Description
business.add_admin	An enterprise owner was added to an enterprise.
business.add_organization	An organization was added to an enterprise.
business.advanced_security_policy_update	An enterprise owner created, updated, or removed a policy for GitHub Advanced Security.
business.clear_actions_settings	An enterprise owner or site administrator cleared GitHub Actions policy settings for an

enter	þι	ise.

business.clear_default_repository_permission	An enterprise owner cleared the base repository permission policy setting for an enterprise.
business.clear_members_can_create_repos	An enterprise owner cleared a restriction on repository creation in organizations in the enterprise.
business.create	An enterprise was created.
business.disable_source_ip_disclosure	Display of IP addresses within audit log events for the enterprise was disabled.
business.disable_two_factor_requirement	The requirement for members to have two- factor authentication enabled to access an enterprise was disabled.
business.enable_source_ip_disclosure	Display of IP addresses within audit log events for the enterprise was enabled.
business.enable_two_factor_requirement	The requirement for members to have two- factor authentication enabled to access an enterprise was enabled.
business.members_can_update_protected_branches.c .ear	An enterprise owner unset a policy for whether members of an enterprise can update protected branches on repositories for individual organizations. Organization owners can choose whether to allow updating protected branches settings.
business.members_can_update_protected_branches.d isable	The ability for enterprise members to update branch protection rules was disabled. Only enterprise owners can update protected branches.
business.members_can_update_protected_branches.e nable	The ability for enterprise members to update branch protection rules was enabled. Enterprise owners and members can update protected branches.
business.remove_admin	An enterprise owner was removed from an enterprise.
business.remove_organization	An organization was removed from an enterprise.
business.rename_slug	The slug for the enterprise URL was renamed.
business.set_actions_retention_limit	The retention period for GitHub Actions artifacts and logs was changed for an enterprise.
business.update_actions_settings	An enterprise owner or site administrator
	updated GitHub Actions policy settings for an enterprise.
business.update_default_repository_permission	The base repository permission setting was updated for all organizations in an enterprise.
business.update_member_repository_creation_permission	The repository creation setting was updated for an enterprise.
husinoss undata mamban manasitamu invitation non	The policy cotting for enterprise members

#### business\_advanced\_security &

Action	Description
business_advanced_security.disabled	GitHub Advanced Security was disabled for your enterprise.
<pre>business_advanced_security.disabled_for_new_repo s</pre>	GitHub Advanced Security was disabled for new repositories in your enterprise.
business_advanced_security.enabled	GitHub Advanced Security was enabled for your enterprise.
<pre>business_advanced_security.enabled_for_new_repo s</pre>	GitHub Advanced Security was enabled for new repositories in your enterprise.

#### business\_secret\_scanning ∂

0

Action	Description
business_secret_scanning.disable	Secret scanning was disabled for your enterprise.
business_secret_scanning.disabled_for_new_repos	Secret scanning was disabled for new repositories in your enterprise.
business_secret_scanning.enable	Secret scanning was enabled for your enterprise.
business_secret_scanning.enabled_for_new_repos	Secret scanning was enabled for new repositories in your enterprise.

#### business\_secret\_scanning\_automatic\_validity\_checks

Action	Description
<pre>business_secret_scanning_automatic_validity_chec ks.disabled</pre>	Automatic partner validation checks have been disabled at the business level
<pre>business_secret_scanning_automatic_validity_chec ks.enabled</pre>	Automatic partner validation checks have been enabled at the business level

## business\_secret\_scanning\_custom\_pattern $\mathscr O$

Action	Description
<pre>business_secret_scanning_custom_pattern.create</pre>	An enterprise-level custom pattern was created for secret scanning.
business_secret_scanning_custom_pattern.delete	An enterprise-level custom pattern was removed

	from secret scanning.
business_secret_scanning_custom_pattern.publish	An enterprise-level custom pattern was published for secret scanning.
business_secret_scanning_custom_pattern.update	Changes to an enterprise-level custom pattern were saved and a dry run was executed for secret scanning.

# $business\_secret\_scanning\_custom\_pattern\_push\_prot\\ ection \ \textit{@}$

Action	Description
<pre>business_secret_scanning_custom_pattern_push_pro tection.disabled</pre>	Push protection for a custom pattern for secret scanning was disabled for your enterprise.
<pre>business_secret_scanning_custom_pattern_push_pro tection.enabled</pre>	Push protection for a custom pattern for secret scanning was enabled for your enterprise.

#### business\_secret\_scanning\_push\_protection @

Action	Description
<pre>business_secret_scanning_push_protection.disabl e</pre>	Push protection for secret scanning was disabled for your enterprise.
<pre>business_secret_scanning_push_protection.disable d_for_new_repos</pre>	Push protection for secret scanning was disabled for new repositories in your enterprise.
business_secret_scanning_push_protection.enable	Push protection for secret scanning was enabled for your enterprise.
<pre>business_secret_scanning_push_protection.enabled _for_new_repos</pre>	Push protection for secret scanning was enabled for new repositories in your enterprise.

# business\_secret\_scanning\_push\_protection\_custom\_ message ∂

Action	Description
<pre>business_secret_scanning_push_protection_custom_ message.disable</pre>	The custom message triggered by an attempted push to a push-protected repository was disabled for your enterprise.
<pre>business_secret_scanning_push_protection_custom_ message.enable</pre>	The custom message triggered by an attempted push to a push-protected repository was enabled for your enterprise.
<pre>business_secret_scanning_push_protection_custom_ message.update</pre>	The custom message triggered by an attempted push to a push-protected repository was updated for your enterprise.

#### checks @

Action	Description
checks.auto_trigger_disabled	Automatic creation of check suites was disabled on a repository in the organization or enterprise.
checks.auto_trigger_enabled	Automatic creation of check suites was enabled on a repository in the organization or enterprise.

#### ${\bf custom\_property\_definition} \ {\mathscr O}$

Action	Description
<pre>custom_property_definition.create</pre>	A new custom property definition was created.
<pre>custom_property_definition.destroy</pre>	A custom property definition was deleted.
custom_property_definition.update	A custom property definition was updated.

## custom\_property\_value ∂

Action	Description
custom_property_value.create	A repository's custom property value was manually set for the first time.
custom_property_value.destroy	A repository's custom property value was deleted.
custom_property_value.update	A repository's custom property value was updated.

#### $\textbf{discussion\_post}~ \mathscr{O}$

Action	Description
discussion_post.destroy	Triggered when a team discussion post is deleted.
discussion_post.update	Triggered when a team discussion post is edited.

## discussion\_post\_reply ∂

Action	Description
discussion_post_reply.destroy	Triggered when a reply to a team discussion post is deleted.
discussion_post_reply.update	Triggered when a reply to a team discussion post is edited.

#### enterprise 🔗

Action	Description
<pre>enterprise.register_self_hosted_runner</pre>	A new GitHub Actions self-hosted runner was registered.
<pre>enterprise.remove_self_hosted_runner</pre>	A GitHub Actions self-hosted runner was removed.
enterprise.runner_group_created	A GitHub Actions self-hosted runner group was created.
enterprise.runner_group_removed	A GitHub Actions self-hosted runner group was removed.
enterprise.runner_group_runners_added	A GitHub Actions self-hosted runner was added to a group.
<pre>enterprise.runner_group_runners_updated</pre>	A GitHub Actions runner group's list of members was updated.
<pre>enterprise.runner_group_runner_removed</pre>	The REST API was used to remove a GitHub Actions self-hosted runner from a group.
enterprise.runner_group_updated	The configuration of a GitHub Actions self- hosted runner group was changed.
<pre>enterprise.self_hosted_runner_updated</pre>	The GitHub Actions runner application was updated. Can be viewed using the REST API and the UI; not visible in the JSON/CSV export.

# enterprise\_announcement ₽

Action	Description
<pre>enterprise_announcement.create</pre>	A global announcement banner was created for the enterprise.
<pre>enterprise_announcement.destroy</pre>	A global announcement banner was removed from the enterprise.
<pre>enterprise_announcement.update</pre>	A global announcement banner was updated for the enterprise.

# enterprise\_domain ∂

Action	Description
enterprise_domain.approve	A domain was approved for an enterprise.
enterprise_domain.create	A domain was added to an enterprise.
enterprise_domain.destroy	A domain was removed from an enterprise.
enterprise_domain.verify	A domain was verified for an enterprise.

Action	Description
git.clone	A repository was cloned.
git.fetch	Changes were fetched from a repository.
git.push	Changes were pushed to a repository.

#### hook 🔗

Action	Description
hook.config_changed	A hook's configuration was changed.
hook.create	A new hook was added.
hook.destroy	A hook was deleted.
hook.events_changed	A hook's configured events were changed.

# integration ${\mathscr O}$

Action	Description
integration.create	An integration was created.
integration.destroy	An integration was deleted.
integration.manager_added	A member of an enterprise or organization was added as an integration manager.
<pre>integration.manager_removed</pre>	A member of an enterprise or organization was removed from being an integration manager.
integration.transfer	Ownership of an integration was transferred to another user or organization.

# $integration\_installation \ {\mathscr O}$

Action	Description
<pre>integration_installation.create</pre>	An integration was installed.
<pre>integration_installation.destroy</pre>	An integration was uninstalled.
<pre>integration_installation.repositories_added</pre>	Repositories were added to an integration.
<pre>integration_installation.repositories_removed</pre>	Repositories were removed from an integration.
<pre>integration_installation.version_updated</pre>	Permissions for an integration were updated.

#### ip\_allow\_list ∂

Action	Description
<pre>ip_allow_list.disable</pre>	An IP allow list was disabled.
<pre>ip_allow_list.disable_for_installed_apps</pre>	An IP allow list was disabled for installed GitHub Apps.
<pre>ip_allow_list.disable_user_level_enforcement</pre>	IP allow list user level enforcement was disabled.
<pre>ip_allow_list.enable</pre>	An IP allow list was enabled.
<pre>ip_allow_list.enable_for_installed_apps</pre>	An IP allow list was enabled for installed GitHub Apps.
<pre>ip_allow_list.enable_user_level_enforcement</pre>	IP allow list user level enforcement was enabled.

# ip\_allow\_list\_entry ₽

Action	Description
<pre>ip_allow_list_entry.create</pre>	An IP address was added to an IP allow list.
<pre>ip_allow_list_entry.destroy</pre>	An IP address was deleted from an IP allow list.
<pre>ip_allow_list_entry.update</pre>	An IP address or its description was changed.

# $oauth\_application \ {\it \it P}$

Action	Description
oauth_application.create	An OAuth application was created.
oauth_application.destroy	An OAuth application was deleted.
oauth_application.reset_secret	The secret key for an OAuth application was reset.
oauth_application.revoke_tokens	Token(s) for an OAuth application were revoked.
oauth_application.transfer	An OAuth application was transferred from one account to another.
oauth_application.unsuspend	An OAuth application was unsuspended for a user or organization account.

# $oauth\_authorization \ \textit{@}$

Action	Description
oauth_authorization.create	An authorization for an OAuth application was created.
oauth_authorization.destroy	An authorization for an OAuth application was deleted.
acuth authorization undata	An authorization for an OAuth application was

#### org 🔗

Action	Description
org.accept_business_invitation	An invitation sent to an organization to join an enterprise was accepted.
org.add_billing_manager	A billing manager was added to an organization.
org.add_member	A user joined an organization.
org.advanced_security_disabled_for_new_repos	GitHub Advanced Security was disabled for new repositories in an organization.
org.advanced_security_disabled_on_all_repos	GitHub Advanced Security was disabled for all repositories in an organization.
org.advanced_security_enabled_for_new_repos	GitHub Advanced Security was enabled for new repositories in an organization.
org.advanced_security_enabled_on_all_repos	GitHub Advanced Security was enabled for all repositories in an organization.
org.advanced_security_policy_selected_member_disabled	An enterprise owner prevented GitHub Advanced Security features from being enabled for repositories owned by the organization.
org.advanced_security_policy_selected_member_enabled	An enterprise owner allowed GitHub Advanced Security features to be enabled for repositories owned by the organization.
org.async_delete	A user initiated a background job to delete an organization.
org.audit_log_export	An export of the organization audit log was created. If the export included a query, the log will list the query used and the number of audit log entries matching that query.
org.block_user	An organization owner blocked a user from accessing the organization's repositories.
org.cancel_business_invitation	An invitation for an organization to join an enterprise was revoked
org.cancel_invitation	An invitation sent to a user to join an organization was revoked.
org.codeql_disabled	Code scanning using the default setup was
	disabled for an organization.
org.codeql_enabled	Code scanning using the default setup was enabled for an organization.
org.config.disable_collaborators_only	The interaction limit for collaborators only for an organization was disabled.
org.config.disable_contributors_only	The interaction limit for prior contributors only for an organization was disabled

	ıvı alı urganizativn was ulsableu.
org.config.disable_sockpuppet_disallowed	The interaction limit for existing users only for an organization was disabled.
org.config.enable_collaborators_only	The interaction limit for collaborators only for an organization was enabled.
org.config.enable_contributors_only	The interaction limit for prior contributors only for an organization was enabled.
org.config.enable_sockpuppet_disallowed	The interaction limit for existing users only for an organization was enabled.
org.confirm_business_invitation	An invitation for an organization to join an enterprise was confirmed.
org.create	An organization was created.
org.delete	An organization was deleted by a user-initiated background job.
org.disable_member_team_creation_permission	Team creation was limited to owners.
<pre>org.disable_reader_discussion_creation_permissio n</pre>	An organization owner limited discussion creation to users with at least triage permission in an organization.
org.disable_saml	SAML single sign-on was disabled for an organization.
org.disable_two_factor_requirement	A two-factor authentication requirement was disabled for the organization.
org.display_commenter_full_name_disabled	An organization owner disabled the display of a commenter's full name in an organization.  Members cannot see a comment author's full name.
org.display_commenter_full_name_enabled	An organization owner enabled the display of a commenter's full name in an organization.  Members can see a comment author's full name.
org.enable_member_team_creation_permission	Team creation by members was allowed.
<pre>org.enable_reader_discussion_creation_permissio n</pre>	An organization owner allowed users with read access to create discussions in an organization
org.enable_saml	SAML single sign-on was enabled for the organization.
org.enable_two_factor_requirement	Two-factor authentication is now required for the organization.
org.integration_manager_added	An organization owner granted a member access to manage all GitHub Apps owned by an organization.
org.integration_manager_removed	An organization owner removed access to manage all GitHub Apps owned by an organization from an organization member.
org.invite_member	A new user was invited to join an organization.

org.invite_to_business	An organization was invited to join an enterprise.
org.members_can_update_protected_branches.disabl	The ability for enterprise members to update protected branches was disabled. Only enterprise owners can update protected branches.
org.members_can_update_protected_branches.enabl	The ability for enterprise members to update protected branches was enabled. Members of a organization can update protected branches.
org.recreate	An organization was restored.
org.register_self_hosted_runner	A new self-hosted runner was registered.
org.remove_billing_manager	A billing manager was removed from an organization, either manually or due to a two-factor authentication requirement.
org.remove_member	A member was removed from an organization, either manually or due to a two-factor authentication requirement.
org.remove_outside_collaborator	An outside collaborator was removed from an organization, either manually or due to a two-factor authentication requirement.
org.remove_self_hosted_runner	A self-hosted runner was removed.
org.rename	An organization was renamed.
org.restore_member	An organization member was restored.
org.runner_group_created	A self-hosted runner group was created.
org.runner_group_removed	A self-hosted runner group was removed.
org.runner_group_runners_added	A self-hosted runner was added to a group.
org.runner_group_runners_updated	A runner group's list of members was updated.
org.runner_group_runner_removed	The REST API was used to remove a self-hosted runner from a group.
org.runner_group_updated	The configuration of a self-hosted runner group was changed.
org.secret_scanning_custom_pattern_push_protecti on_disabled	Push protection for a custom pattern for secret scanning was disabled for an organization.
org.secret_scanning_custom_pattern_push_protection_enabled	Push protection for a custom pattern for secret scanning was enabled for an organization.
org.secret_scanning_push_protection_custom_messa ge_disabled	The custom message triggered by an attempted push to a push-protected repository was disabled for an organization.
org.secret_scanning_push_protection_custom_messa ge_enabled	The custom message triggered by an attempted push to a push-protected repository was enabled for an organization.
ora cocrat comming such protection custom mosco	The custom message triggered by an attemptor

org.secret_scanning_pusn_protection_custom_messa ge_updated	push to a push-protected repository was updated for an organization.
org.secret_scanning_push_protection_disable	Push protection for secret scanning was disabled.
org.secret_scanning_push_protection_enable	Push protection for secret scanning was enabled.
org.self_hosted_runner_updated	The runner application was updated. Can be viewed using the REST API and the UI; not visible in the JSON/CSV export.
org.set_actions_retention_limit	The retention period for GitHub Actions artifacts and logs in an organization was changed.
org.sso_response	A SAML single sign-on (SSO) response was generated when a member attempted to authenticate with your organization.
org.transform	A user account was converted into an organization.
org.unblock_user	A user was unblocked from an organization.
org.update_default_repository_permission	The default repository permission level for organization members was changed.
<pre>org.update_member_repository_creation_permissio n</pre>	The create repository permission for organization members was changed.
$\label{lem:condition} {\tt org.update\_member\_repository\_invitation\_permission}$	An organization owner changed the policy setting for organization members inviting outside collaborators to repositories.
org.update_saml_provider_settings	An organization's SAML provider settings were updated.
org.update_terms_of_service	An organization changed between the Standard Terms of Service and the GitHub Customer Agreement.

# $organization\_domain \ {\it \it P}$

Action	Description
organization_domain.approve	A domain was approved for an organization.
organization_domain.create	A domain was added to an organization.
organization_domain.destroy	A domain was removed from an organization.
organization_domain.verify	A domain was verified for an organization.

# $org\_secret\_scanning\_automatic\_validity\_checks \ \mathscr{O}$

Action	Description
org_secret_scanning_automatic_validity_checks.di	Automatic partner validation checks have been

sabled	disabled at the organization level
<pre>org_secret_scanning_automatic_validity_checks.en abled</pre>	Automatic partner validation checks have been enabled at the organization level

## org\_secret\_scanning\_custom\_pattern ∂

Action	Description
<pre>org_secret_scanning_custom_pattern.create</pre>	A custom pattern was created for secret scanning in an organization.
<pre>org_secret_scanning_custom_pattern.delete</pre>	A custom pattern was removed from secret scanning in an organization.
<pre>org_secret_scanning_custom_pattern.publish</pre>	A custom pattern was published for secret scanning in an organization.
<pre>org_secret_scanning_custom_pattern.update</pre>	Changes to a custom pattern were saved and a dry run was executed for secret scanning in an organization.

#### packages 🔗

Action	Description
packages.package_deleted	An entire package was deleted.
packages.package_published	A package was published or republished to an organization.
packages.package_version_deleted	A specific package version was deleted.
packages.package_version_published	A specific package version was published or republished to a package.

# $protected\_branch \ \mathscr{O}$

Action	Description
<pre>protected_branch.authorized_users_teams</pre>	The users, teams, or integrations allowed to bypass a branch protection were changed.
protected_branch.branch_allowances	A protected branch allowance was given to a specific user, team or integration.
protected_branch.create	Branch protection was enabled on a branch.
protected_branch.destroy	Branch protection was disabled on a branch.
<pre>protected_branch.dismissal_restricted_users_team s</pre>	Enforcement of restricting users and/or teams who can dismiss reviews was updated on a branch.
<pre>protected_branch.dismiss_stale_reviews</pre>	Enforcement of dismissing stale pull requests

	was upuateu on a pranch.
<pre>protected_branch.policy_override</pre>	A branch protection requirement was overridden by a repository administrator.
<pre>protected_branch.rejected_ref_update</pre>	A branch update attempt was rejected.
protected_branch.update_admin_enforced	Branch protection was enforced for repository administrators.
<pre>protected_branch.update_allow_deletions_enforcem ent_level</pre>	Branch deletion was enabled or disabled for a protected branch.
<pre>protected_branch.update_allow_force_pushes_enfor cement_level</pre>	Force pushes were enabled or disabled for a branch.
<pre>protected_branch.update_ignore_approvals_from_co ntributors</pre>	Ignoring of approvals from contributors to a pull request was enabled or disabled for a branch.
<pre>protected_branch.update_linear_history_requireme nt_enforcement_level</pre>	Required linear commit history was enabled or disabled for a branch.
<pre>protected_branch.update_lock_allows_fetch_and_me rge</pre>	Fork syncing was enabled or disabled for a read- only branch
<pre>protected_branch.update_lock_branch_enforcement_ level</pre>	The enforcement of a branch lock was updated.
<pre>protected_branch.update_name</pre>	A branch name pattern was updated for a branch.
<pre>protected_branch.update_pull_request_reviews_enf orcement_level</pre>	Enforcement of required pull request reviews was updated for a branch. Can be 0 (deactivated), 1 (non-admins), or 2 (everyone).
<pre>protected_branch.update_required_approving_revie w_count</pre>	Enforcement of the required number of approvals before merging was updated on a branch.
<pre>protected_branch.update_required_status_checks_e nforcement_level</pre>	Enforcement of required status checks was updated for a branch.
<pre>protected_branch.update_require_code_owner_revie w</pre>	Enforcement of required code owner review was updated for a branch.
<pre>protected_branch.update_require_last_push_approv al</pre>	Someone other than the person who pushed the last code-modifying commit to the branch must approve pull requests for the branch.
<pre>protected_branch.update_signature_requirement_en forcement_level</pre>	Enforcement of required commit signing was updated for a branch.
<pre>protected_branch.update_strict_required_status_c hecks_policy</pre>	Enforcement of required status checks was updated for a branch.

# public\_key 🔗

Action	Description
public_key.create	An SSH key was added to a user account or a deploy key was added to a repository.

<pre>public_key.delete</pre>	An SSH key was removed from a user account or a deploy key was removed from a repository.
<pre>public_key.unverification_failure</pre>	A user account's SSH key or a repository's deploy key was unable to be unverified.
<pre>public_key.unverify</pre>	A user account's SSH key or a repository's deploy key was unverified.
public_key.update	A user account's SSH key or a repository's deploy key was updated.
<pre>public_key.verification_failure</pre>	A user account's SSH key or a repository's deploy key was unable to be verified.
<pre>public_key.verify</pre>	A user account's SSH key or a repository's deploy key was verified.

# $pull\_request \ \mathscr{O}$

Action	Description
pull_request.close	A pull request was closed without being merged.
<pre>pull_request.converted_to_draft</pre>	A pull request was converted to a draft.
pull_request.create	A pull request was created.
<pre>pull_request.create_review_request</pre>	A review was requested on a pull request.
<pre>pull_request.indirect_merge</pre>	A pull request was considered merged because the pull request's commits were merged into the target branch.
pull_request.in_progress	A pull request was marked as in progress.
pull_request.merge	A pull request was merged.
<pre>pull_request.ready_for_review</pre>	A pull request was marked as ready for review.
<pre>pull_request.remove_review_request</pre>	A review request was removed from a pull request.
<pre>pull_request.reopen</pre>	A pull request was reopened after previously being closed.

# pull\_request\_review ∂

Action	Description
<pre>pull_request_review.delete</pre>	A review on a pull request was deleted.
<pre>pull_request_review.dismiss</pre>	A review on a pull request was dismissed.
<pre>pull_request_review.submit</pre>	A review on a pull request was submitted.

# pull\_request\_review\_comment @

Action	Description
<pre>pull_request_review_comment.create</pre>	A review comment was added to a pull request.
<pre>pull_request_review_comment.delete</pre>	A review comment on a pull request was deleted.
<pre>pull_request_review_comment.update</pre>	A review comment on a pull request was changed.

#### repo 🔗

Action	Description
repo.access	The visibility of a repository changed.
repo.add_member	A collaborator was added to a repository.
repo.add_topic	A topic was added to a repository.
repo.advanced_security_disabled	GitHub Advanced Security was disabled for a repository.
repo.advanced_security_enabled	GitHub Advanced Security was enabled for a repository.
repo.archived	A repository was archived.
repo.change_merge_setting	Pull request merge options were changed for a repository.
repo.codeql_disabled	Code scanning using the default setup was disabled for a repository.
repo.codeql_enabled	Code scanning using the default setup was enabled for a repository.
repo.code_scanning_analysis_deleted	Code scanning analysis for a repository was deleted.
repo.code_scanning_configuration_for_branch_dele	A code scanning configuration for a branch of a repository was deleted.
repo.config.disable_collaborators_only	The interaction limit for collaborators only was disabled.
repo.config.disable_contributors_only	The interaction limit for prior contributors only was disabled in a repository.
repo.config.disable_sockpuppet_disallowed	The interaction limit for existing users only was disabled in a repository.
repo.config.enable_collaborators_only	The interaction limit for collaborators only was enabled in a repository Users that are not collaborators or organization members were unable to interact with a repository for a set duration.

repo.config.enable_contributors_only	The interaction limit for prior contributors only was enabled in a repository Users that are not prior contributors, collaborators or organization members were unable to interact with a repository for a set duration.
<pre>repo.config.enable_sockpuppet_disallowed</pre>	The interaction limit for existing users was enabled in a repository New users aren't able to interact with a repository for a set duration Existing users of the repository, contributors, collaborators or organization members are able to interact with a repository.
repo.create	A repository was created.
repo.destroy	A repository was deleted.
repo.disk_archive	A repository was archived on disk.
repo.download_zip	A source code archive of a repository was downloaded as a ZIP file.
repo.override_unlock	The repository was unlocked.
repo.pages_cname	A GitHub Pages custom domain was modified in a repository.
repo.pages_create	A GitHub Pages site was created.
repo.pages_destroy	A GitHub Pages site was deleted.
repo.pages_https_redirect_disabled	HTTPS redirects were disabled for a GitHub Pages site.
repo.pages_https_redirect_disabled repo.pages_https_redirect_enabled	
	Pages site.  HTTPS redirects were enabled for a GitHub
repo.pages_https_redirect_enabled	Pages site.  HTTPS redirects were enabled for a GitHub Pages site.  A GitHub Pages site visibility was changed to
repo.pages_https_redirect_enabled repo.pages_private	Pages site.  HTTPS redirects were enabled for a GitHub Pages site.  A GitHub Pages site visibility was changed to private.  A GitHub Pages site visibility was changed to
repo.pages_https_redirect_enabled repo.pages_private repo.pages_public	Pages site.  HTTPS redirects were enabled for a GitHub Pages site.  A GitHub Pages site visibility was changed to private.  A GitHub Pages site visibility was changed to public.
repo.pages_https_redirect_enabled  repo.pages_private  repo.pages_public  repo.pages_source	Pages site.  HTTPS redirects were enabled for a GitHub Pages site.  A GitHub Pages site visibility was changed to private.  A GitHub Pages site visibility was changed to public.  A GitHub Pages source was modified.
repo.pages_https_redirect_enabled  repo.pages_private  repo.pages_public  repo.pages_source  repo.register_self_hosted_runner	Pages site.  HTTPS redirects were enabled for a GitHub Pages site.  A GitHub Pages site visibility was changed to private.  A GitHub Pages site visibility was changed to public.  A GitHub Pages source was modified.  A new self-hosted runner was registered.
repo.pages_https_redirect_enabled  repo.pages_private  repo.pages_public  repo.pages_source  repo.register_self_hosted_runner  repo.remove_member	Pages site.  HTTPS redirects were enabled for a GitHub Pages site.  A GitHub Pages site visibility was changed to private.  A GitHub Pages site visibility was changed to public.  A GitHub Pages source was modified.  A new self-hosted runner was registered.  A collaborator was removed from a repository.
repo.pages_https_redirect_enabled  repo.pages_private  repo.pages_public  repo.pages_source  repo.register_self_hosted_runner  repo.remove_member  repo.remove_self_hosted_runner	Pages site.  HTTPS redirects were enabled for a GitHub Pages site.  A GitHub Pages site visibility was changed to private.  A GitHub Pages site visibility was changed to public.  A GitHub Pages source was modified.  A new self-hosted runner was registered.  A collaborator was removed from a repository.  A self-hosted runner was removed.
repo.pages_https_redirect_enabled  repo.pages_private  repo.pages_public  repo.pages_source  repo.register_self_hosted_runner  repo.remove_member  repo.remove_self_hosted_runner	Pages site.  HTTPS redirects were enabled for a GitHub Pages site.  A GitHub Pages site visibility was changed to private.  A GitHub Pages site visibility was changed to public.  A GitHub Pages source was modified.  A new self-hosted runner was registered.  A collaborator was removed from a repository.  A self-hosted runner was removed.  A topic was removed from a repository.

	anu iogs in a repository was changeu.
repo.staff_unlock	An enterprise owner or GitHub staff (with permission from a repository administrator) temporarily unlocked the repository.
repo.transfer	A user accepted a request to receive a transferred repository.
repo.transfer_outgoing	A repository was transferred to another repository network.
repo.transfer_start	A user sent a request to transfer a repository to another user or organization.
repo.unarchived	A repository was unarchived.
repo.update_actions_access_settings	The setting to control how a repository was used by GitHub Actions workflows in other repositories was changed.
repo.update_actions_settings	A repository administrator changed GitHub Actions policy settings for a repository.
repo.update_member	A user's permission to a repository was changed.

# repository\_branch\_protection\_evaluation ∂

Action	Description
repository_branch_protection_evaluation.disable	Branch protections were disabled for the repository.
repository_branch_protection_evaluation.enable	Branch protections were enabled for this repository.

# repository\_invitation ∂

Action	Description
repository_invitation.accept	An invitation to join a repository was accepted.
repository_invitation.cancel	An invitation to join a repository was canceled.
repository_invitation.create	An invitation to join a repository was sent.
repository_invitation.reject	An invitation to join a repository was declined.

## repository\_ruleset ∂

on
ry ruleset was created.
ry ruleset was deleted.

#### repository\_secret\_scanning ∂

Action	Description
repository_secret_scanning.disable	Secret scanning was disabled for a repository.
repository_secret_scanning.enable	Secret scanning was enabled for a repository.

# repository\_secret\_scanning\_automatic\_validity\_chec ks ∂

Action	Description
<pre>repository_secret_scanning_automatic_validity_ch ecks.disabled</pre>	Automatic partner validation checks have been disabled at the repository level
<pre>repository_secret_scanning_automatic_validity_ch ecks.enabled</pre>	Automatic partner validation checks have been enabled at the repository level

#### repository\_secret\_scanning\_custom\_pattern ∂

Action	Description
<pre>repository_secret_scanning_custom_pattern.creat e</pre>	A custom pattern was created for secret scanning in a repository.
<pre>repository_secret_scanning_custom_pattern.delet e</pre>	A custom pattern was removed from secret scanning in a repository.
<pre>repository_secret_scanning_custom_pattern.publis h</pre>	A custom pattern was published for secret scanning in a repository.
<pre>repository_secret_scanning_custom_pattern.updat e</pre>	Changes to a custom pattern were saved and a dry run was executed for secret scanning in a repository.

# $repository\_secret\_scanning\_custom\_pattern\_push\_pr$ $otection \ \mathscr{O}$

Action	Description
<pre>repository_secret_scanning_custom_pattern_push_p rotection.disabled</pre>	Push protection for a custom pattern for secret scanning was disabled for your repository.
<pre>repository_secret_scanning_custom_pattern_push_p rotection.enabled</pre>	Push protection for a custom pattern for secret scanning was enabled for your repository.

## $repository\_secret\_scanning\_push\_protection \ {\it @}$

**Action** Description

${\tt repository\_secret\_scanning\_push\_protection.disab} \\ {\tt le}$	Secret scanning push protection was disabled for a repository.
<pre>repository_secret_scanning_push_protection.enabl e</pre>	Secret scanning push protection was enabled for a repository.

## $restrict\_notification\_delivery \ {\it \o}$

Action	Description
restrict_notification_delivery.disable	Email notification restrictions for an organization or enterprise were disabled.
restrict_notification_delivery.enable	Email notification restrictions for an organization or enterprise were enabled.

#### secret\_scanning ₽

Action	Description
secret_scanning.disable	Secret scanning was disabled for all existing repositories.
secret_scanning.enable	Secret scanning was enabled for all existing repositories.

## secret\_scanning\_alert ∂

Action	Description
secret_scanning_alert.create	GitHub detected a secret and created a secret scanning alert.
secret_scanning_alert.reopen	A seret scanning alert was reopened.
secret_scanning_alert.resolve	A seret scanning alert was resolved.

#### secret\_scanning\_new\_repos ∂

Action	Description
secret_scanning_new_repos.disable	Secret scanning was disabled for all new repositories.
secret_scanning_new_repos.enable	Secret scanning was enabled for all new repositories.

## secret\_scanning\_push\_protection ∂

Action	Description

Triggered when a user bypasses the push protection on a secret detected by secret scanning.

#### security\_key ∂

Action	Description
security_key.register	A security key was registered for an account.
security_key.remove	A security key was removed from an account.

#### ssh\_certificate\_authority ∂

Action	Description
ssh_certificate_authority.create	An SSH certificate authority for an organization or enterprise was created.
ssh_certificate_authority.destroy	An SSH certificate authority for an organization or enterprise was deleted.

#### ssh\_certificate\_requirement ∂

Action	Description
ssh_certificate_requirement.disable	The requirement for members to use SSH certificates to access an organization resources was disabled.
ssh_certificate_requirement.enable	The requirement for members to use SSH certificates to access an organization resources was enabled.

#### staff @

Action	Description
staff.set_domain_token_expiration	The verification code expiry time for an organization or enterprise domain was set.
staff.unverify_domain	An organization or enterprise domain was unverified.
staff.verify_domain	An organization or enterprise domain was verified.

#### team 🔗

Action	Description

team.add_member	A member of an organization was added to a team.
team.add_repository	A team was given access and permissions to a repository.
team.change_parent_team	A child team was created or a child team's parent was changed.
team.change_privacy	A team's privacy level was changed.
team.create	A new team is created.
team.demote_maintainer	A user was demoted from a team maintainer to a team member.
team.destroy	A team was deleted.
team.promote_maintainer	A user was promoted from a team member to a team maintainer.
team.remove_member	An organization member was removed from a team.
team.remove_repository	A repository was removed from a team's control.
team.rename	A team's name was changed.
team.update_repository_permission	A team's permission to a repository was changed.

# $\textbf{team\_discussions} \; \mathscr{O}$

Action	Description
team_discussions.clear	An organization owner cleared the setting to allow team discussions for an organization or enterprise.
team_discussions.disable	Team discussions were disabled for an organization.
team_discussions.enable	Team discussions were enabled for an organization.

#### team\_sync\_tenant ∂

Action	Description
<pre>team_sync_tenant.disabled</pre>	Team synchronization with a tenant was disabled.
team_sync_tenant.enabled	Team synchronization with a tenant was enabled.

## $two\_factor\_authentication \ \mathscr{D}$

Action	Description
<pre>two_factor_authentication.disabled</pre>	Two-factor authentication was disabled for a user account.
two_factor_authentication.enabled	Two-factor authentication was enabled for a user account.
$\label{two_factor_authentication.password_reset_fallbac} two\_factor\_authentication.password\_reset\_fallbac\\ k\_sms$	A one-time password code was sent to a user account fallback phone number.
${\tt two\_factor\_authentication.recovery\_codes\_regener}$ ated	Two factor recovery codes were regenerated for a user account.
two_factor_authentication.sign_in_fallback_sms	A one-time password code was sent to a user account fallback phone number.
two_factor_authentication.update_fallback	The two-factor authentication fallback for a user account was changed.

#### user 🔗

Action	Description
user.add_email	An email address was added to a user account.
user.async_delete	An asynchronous job was started to destroy a user account, eventually triggering a user.delete event.
user.audit_log_export	Audit log entries were exported.
user.block_user	A user was blocked by another user.
user.change_password	A user changed their password.
user.create	A new user account was created.
user.creation_rate_limit_exceeded	The rate of creation of user accounts, applications, issues, pull requests or other resources exceeded the configured rate limits, or too many users were followed too quickly.
user.delete	A user account was destroyed by an asynchronous job.
user.demote	A site administrator was demoted to an ordinary user account.
user.destroy	A user deleted his or her account, triggering user.async_delete.
user.failed_login	A user tried to sign in with an incorrect username, password, or two-factor authentication code.
user.flag_as_large_scale_contributor	A user account was flagged as a large scale contributor. Only contributions from public repositories the user owns will be shown in their contribution graph, in order to prevent timeouts.

user.forgot_password	A user requested a password reset.
user.hide_private_contributions_count	A user changed the visibility of their private contributions. The number of contributions to private repositories on the user's profile are now hidden.
user.login	A user signed in.
user.minimize_comment	A comment made by a user was minimized.
user.promote	An ordinary user account was promoted to a site administrator.
user.recreate	A user's account was restored.
user.remove_email	An email address was removed from a user account.
user.remove_large_scale_contributor_flag	A user account was no longer flagged as a large scale contributor.
user.rename	A username was changed.
user.report_content	Triggered when you report an issue or pull request, or a comment on an issue, pull request, or commit.
user.reset_password	A user reset their account password.
user.show_private_contributions_count	A user changed the visibility of their private contributions. The number of contributions to private repositories on the user's profile are now shown.
user.sign_in_from_unrecognized_device	A user signed in from an unrecognized device.
user.sign_in_from_unrecognized_device_and_location	A user signed in from an unrecognized device and location.
user.sign_in_from_unrecognized_location	A user signed in from an unrecognized location.
user.suspend	A user account was suspended.
user.two_factor_challenge_failure	A 2FA challenge issued for a user account failed.
user.two_factor_challenge_success	A 2FA challenge issued for a user account succeeded.
user.two_factor_recover	A user used their 2FA recovery codes.
user.two_factor_recovery_codes_downloaded	A user downloaded 2FA recovery codes for their account.
user.two_factor_recovery_codes_printed	A user printed 2FA recovery codes for their account.
user.two_factor_recovery_codes_viewed	A user viewed 2FA recovery codes for their account.
user.two_factor_requested	A user was prompted for a two-factor authentication code.
	A

user.unblock_user	A user was unblocked by another user.
user.unminimize_comment	A comment made by a user was unminimized.
user.unsuspend	A user account was unsuspended.

#### workflows @

Action	Description
workflows.approve_workflow_job	A workflow job was approved.
workflows.cancel_workflow_run	A workflow run was cancelled.
workflows.delete_workflow_run	A workflow run was deleted.
workflows.disable_workflow	A workflow was disabled.
workflows.enable_workflow	A workflow was enabled, after previously being disabled by disable_workflow.
workflows.reject_workflow_job	A workflow job was rejected.
workflows.rerun_workflow_run	A workflow run was re-run.

#### Legal

© 2023 GitHub, Inc. <u>Terms</u> <u>Privacy</u> <u>Status</u> <u>Pricing</u> <u>Expert services</u> <u>Blog</u>