

Viewing a file

In this article

Viewing or copying the raw file content

Viewing the line-by-line revision history for a file

Ignore commits in the blame view


Bypassing .git-blame-ignore-revs in the blame view



You can view raw file content or trace changes to lines in a file and discover how parts of the file evolved over time.

Viewing or copying the raw file content [↗](#)

With the raw view, you can view or copy the raw content of a file without any styling.

- 1 On GitHub.com, navigate to the main page of the repository.
- 2 Click the file that you want to view.
- 3 In the upper-right corner of the file view, click **Raw**.



- 4 Optionally, to copy the raw file content, in the upper-right corner of the file view, click . To download the raw file, click .


Viewing the line-by-line revision history for a file [↗](#)

Within the blame view, you can view the line-by-line revision history for an entire file.

Tip: On the command line, you can also use `git blame` to view the revision history of lines within a file. For more information, see [Git's git blame documentation](#).

- 1 On GitHub.com, navigate to the main page of the repository.
- 2 Click to open the file whose line history you want to view.
- 3 Above the file content, click **Blame**. This view gives you a line-by-line revision

history, with the code in a file separated by commit. Each commit lists the author, commit description, and commit date.

- 4 To see versions of a file before a particular commit, click . Alternatively, to see more detail about a particular commit, click the commit message.



- 5 To return to the raw code view, above the file content, click **Code**.
 - If you are viewing a Markdown file, above the file content, you can also click **Preview** to return to the view with Markdown formatting applied.

Ignore commits in the blame view [↗](#)


All revisions specified in the `.git-blame-ignore-revs` file, which must be in the root directory of your repository, are hidden from the blame view using Git's `git blame --ignore-revs-file` configuration setting. For more information, see [git blame --ignore-revs-file](#) in the Git documentation.

- 1 In the root directory of your repository, create a file named `.git-blame-ignore-revs`.
- 2 Add the commit hashes you want to exclude from the blame view to that file. We recommend the file to be structured as follows, including comments:

```
# .git-blame-ignore-revs
# Removed semi-colons from the entire codebase
a8940f7fbddf7fad9d7d50014d4e8d46baf30592
# Converted all JavaScript to TypeScript
69d029cec8337c616552756310748c4a507bd75a
```

- 3 Commit and push the changes.

Now when you visit the blame view, the listed revisions will not be included in the blame. You'll see an **Ignoring revisions in .git-blame-ignore-revs** banner indicating that some commits may be hidden:



This can be useful when a few commits make extensive changes to your code. You can use the file when running `git blame` locally as well:

```
git blame --ignore-revs-file .git-blame-ignore-revs
```

You can also configure your local git so it always ignores the revs in that file:

```
git config blame.ignoreRevsFile .git-blame-ignore-revs
```

Bypassing `.git-blame-ignore-revs` in the blame view [↗](#)

If the blame view for a file shows **Ignoring revisions in `.git-blame-ignore-revs`**, you can still bypass `.git-blame-ignore-revs` and see the normal blame view. In the URL, append a `~` to the SHA and the **Ignoring revisions in `.git-blame-ignore-revs`** banner will disappear.

Legal

© 2023 GitHub, Inc. [Terms](#) [Privacy](#) [Status](#) [Pricing](#) [Expert services](#) [Blog](#)