

Webhook events and payloads

In this article

About webhook events and payloads

branch_protection_rule

cache_sync

check_run

check_suite

code_scanning_alert

commit_comment

create

delete

dependabot_alert

deploy_key

deployment

deployment_protection_rule

deployment_review

deployment_status

discussion

discussion_comment

enterprise

fork

github_app_authorization

gollum

installation

installation_repositories

installation_target

issue_comment

issues

label

member

membership

meta

milestone

organization

package

page_build

personal_access_token_request

ping

project_card

project

project_column

projects_v2

projects_v2_item

public

pull_request

pull_request_review_comment
pull_request_review
pull_request_review_thread
push
registry_package
release
repository
repository_dispatch
repository_vulnerability_alert
secret_scanning_alert
secret_scanning_alert_location
security_advisory
security_and_analysis
sponsorship
star
status
team_add
team
user
watch
workflow_dispatch
workflow_job
workflow_run

Learn about when each webhook event occurs and what the payload contains.

About webhook events and payloads

You can create webhooks that subscribe to the events listed on this page. To limit the number of HTTP requests to your server, you should only subscribe to the specific events that you plan on handling. For more information, see "[Creating webhooks](#)."

Each webhook event on this page includes a description of the webhook properties for that event. If the event has multiple actions, the properties corresponding to each action are included.

Each event is only available to specific types of webhooks. For example, an organization webhook can subscribe to the `team` event, but a repository webhook cannot. The description of each webhook event lists the availability for that event. For more information, see "[Types of webhooks](#)."

Payload cap

Payloads are capped at 25 MB. If an event generates a larger payload, GitHub will not deliver a payload for that webhook event. This may happen, for example, on a `create` event if many branches or tags are pushed at once. We suggest monitoring your payload size to ensure delivery.

Delivery headers

HTTP POST payloads that are delivered to your webhook's configured URL endpoint will

contain several special headers:

- `X-GitHub-Hook-ID` : The unique identifier of the webhook.
- `X-GitHub-Event` : The name of the event that triggered the delivery.
- `X-GitHub-Delivery` : A globally unique identifier (GUID) to identify the delivery.
- `X-GitHub-Enterprise-Version` : The version of the GitHub Enterprise Server instance that sent the HTTP POST payload.
- `X-GitHub-Enterprise-Host` : The hostname of the GitHub Enterprise Server instance that sent the HTTP POST payload.
- `X-Hub-Signature` : This header is sent if the webhook is configured with a `secret` . This is the HMAC hex digest of the request body, and is generated using the SHA-1 hash function and the `secret` as the HMAC `key` . `X-Hub-Signature` is provided for compatibility with existing integrations. We recommend that you use the more secure `X-Hub-Signature-256` instead.
- `X-Hub-Signature-256` : This header is sent if the webhook is configured with a `secret` . This is the HMAC hex digest of the request body, and is generated using the SHA-256 hash function and the `secret` as the HMAC `key` . For more information, see "[Validating webhook deliveries](#)."
- `User-Agent` : This header will always have the prefix `GitHub-Hookshot/` .
- `X-GitHub-Hook-Installation-Target-Type` : The type of resource where the webhook was created.
- `X-GitHub-Hook-Installation-Target-ID` : The unique identifier of the resource where the webhook was created.

To see what each header might look like in a webhook payload, see "[Example webhook delivery](#)."

Example webhook delivery

You can choose to have payloads delivered in JSON format (`application/json`) or as URL-encoded data (`x-www-form-urlencoded`). Following is an example of a webhook POST request that uses the JSON format.

```
> POST /payload HTTP/2

> X-GitHub-Delivery: 72d3162e-cc78-11e3-81ab-4c9367dc0958
> X-GitHub-Enterprise-Version: 2.15.0
> X-GitHub-Enterprise-Host: example.com
> X-Hub-Signature: sha1=7d38cdd689735b008b3c702edd92eea23791c5f6
> X-Hub-Signature-256:
sha256=d57c68ca6f92289e6987922ff26938930f6e66a2d161ef06abdf1859230aa23c
> User-Agent: GitHub-Hookshot/044aadd
> Content-Type: application/json
> Content-Length: 6615
> X-GitHub-Event: issues
> X-GitHub-Hook-ID: 292430182
> X-GitHub-Hook-Installation-Target-ID: 79929171
> X-GitHub-Hook-Installation-Target-Type: repository

> {
>   "action": "opened",
>   "issue": {
>     "url": "http(s)://<em>HOSTNAME</em>/api/v3/repos/octocat/Hello-World/issues/1347",
>     "number": 1347,
>     ...
>   },
>   "repository": {
>     "id": 1296269,
>     "full_name": "octocat/Hello-World",
>     "owner": {
>       "login": "octocat",
```

```
>     "id": 1,
>     ...
>   },
>   ...
> },
> "sender": {
>   "login": "octocat",
>   "id": 1,
>   ...
> }
> }
```

branch_protection_rule

This event occurs when there is activity relating to branch protection rules. For more information, see "[About protected branches](#)." For information about the APIs to manage branch protection rules, see [the GraphQL documentation](#) or "[Branch protection](#)" in the REST API documentation.

To subscribe to this event, a GitHub App must have at least read-level access for the "Administration" repository permission.

Availability for branch_protection_rule

- Repositories
- Organizations
- GitHub Apps

Webhook payload object for branch_protection_rule

Action type: **created** ▾

A branch protection rule was created.

Webhook request body parameters

action string **Required**

Value: `created`

enterprise object

An enterprise on GitHub. Webhook payloads contain the `enterprise` property when the webhook is configured on an enterprise account or an organization that's part of an enterprise account. For more information, see "[About enterprise accounts](#)."

installation object

The GitHub App installation. Webhook payloads contain the `installation` property when the event is configured for and sent to a GitHub App. For more information, see "[Using webhooks with GitHub Apps](#)."

organization object

A GitHub organization. Webhook payloads contain the `organization` property when the webhook is configured for an organization, or when the event occurs from activity in a repository owned by an organization.

repository object **Required**

repository object **Required**

The repository on GitHub where the event occurred. Webhook payloads contain the `repository` property when the event occurs from activity in a repository.

rule object **Required**

The branch protection rule. Includes a `name` and all the [branch protection settings](#) applied to branches that match the name. Binary settings are boolean. Multi-level configurations are one of `off`, `non_admins`, or `everyone`. Actor and build lists are arrays of strings.

► Properties of `rule`

sender object **Required**

The GitHub user that triggered the event. This property is included in every webhook payload.

cache_sync

This event occurs when a Git ref has been successfully synced to a cache replica. For more information, see "[About repository caching](#)."

Availability for `cache_sync`

- Repositories
- Organizations
- GitHub Apps

Webhook payload object for `cache_sync`

Webhook request body parameters

after string **Required**

before string **Required**

cache_location string **Required**

enterprise object

An enterprise on GitHub. Webhook payloads contain the `enterprise` property when the webhook is configured on an enterprise account or an organization that's part of an enterprise account. For more information, see "[About enterprise accounts](#)."

installation object

The GitHub App installation. Webhook payloads contain the `installation` property when the event is configured for and sent to a GitHub App. For more information, see "[Using webhooks with GitHub Apps](#)."

organization object

A GitHub organization. Webhook payloads contain the `organization` property when the webhook is configured for an organization, or when the event occurs from activity in a repository owned by an organization.

ref string **Required**

repository object

The repository on GitHub where the event occurred. Webhook payloads contain the `repository` property when the event occurs from activity in a repository.

sender object

The GitHub user that triggered the event. This property is included in every webhook payload.

check_run

This event occurs when there is activity relating to a check run. For information about check runs, see "[Getting started with the Checks API](#)." For information about the APIs to manage check runs, see [the GraphQL API documentation](#) or "[Check Runs](#)" in the REST API documentation.

For activity relating to check suites, use the `check-suite` event.

To subscribe to this event, a GitHub App must have at least read-level access for the "Checks" repository permission. To receive the `rerequested` and `requested_action` event types, the app must have at least write-level access for the "Checks" permission. GitHub Apps with write-level access for the "Checks" permission are automatically subscribed to this webhook event.

Repository and organization webhooks only receive payloads for the `created` and `completed` event types in repositories.

Note: The API only looks for pushes in the repository where the check run was created. Pushes to a branch in a forked repository are not detected and return an empty `pull_requests` array and a `null` value for `head_branch`.

Availability for `check_run`

- Repositories
- Organizations
- GitHub Apps

Webhook payload object for `check_run`

Action type: **completed** ▾

A check run was completed, and a conclusion is available.

Webhook request body parameters

action string

Value: `completed`

check_run object **Required**

A check performed on the code of a given code change

► Properties of `check_run`

installation object

The GitHub App installation. Webhook payloads contain the `installation` property when the event is configured for and sent to a GitHub App. For more information, see "[Using webhooks with GitHub Apps](#)."

organization object

A GitHub organization. Webhook payloads contain the **organization** property when the webhook is configured for an organization, or when the event occurs from activity in a repository owned by an organization.

repository object **Required**

The repository on GitHub where the event occurred. Webhook payloads contain the **repository** property when the event occurs from activity in a repository.

sender object **Required**

The GitHub user that triggered the event. This property is included in every webhook payload.

check_suite

This event occurs when there is activity relating to a check suite. For information about check suites, see "[Getting started with the Checks API](#)." For information about the APIs to manage check suites, see [the GraphQL API documentation](#) or "[Check Suites](#)" in the REST API documentation.

For activity relating to check runs, use the **check_run** event.

To subscribe to this event, a GitHub App must have at least read-level access for the "Checks" permission. To receive the **requested** and **rerequested** event types, the app must have at least write-level access for the "Checks" permission. GitHub Apps with write-level access for the "Checks" permission are automatically subscribed to this webhook event.

Repository and organization webhooks only receive payloads for the **completed** event types in repositories.

Note: The API only looks for pushes in the repository where the check suite was created. Pushes to a branch in a forked repository are not detected and return an empty **pull_requests** array and a **null** value for **head_branch**.

Availability for **check_suite**

- Repositories
- Organizations
- GitHub Apps

Webhook payload object for **check_suite**

Action type: **completed** ▾

All check runs in a check suite have completed, and a conclusion is available.

Webhook request body parameters

action string **Required**

Value: **completed**

check_suite object **Required**

The [check_suite](#).

► Properties of `check_suite`

enterprise `object`

An enterprise on GitHub. Webhook payloads contain the `enterprise` property when the webhook is configured on an enterprise account or an organization that's part of an enterprise account. For more information, see "[About enterprise accounts](#)."

installation `object`

The GitHub App installation. Webhook payloads contain the `installation` property when the event is configured for and sent to a GitHub App. For more information, see "[Using webhooks with GitHub Apps](#)."

organization `object`

A GitHub organization. Webhook payloads contain the `organization` property when the webhook is configured for an organization, or when the event occurs from activity in a repository owned by an organization.

repository `object` **Required**

The repository on GitHub where the event occurred. Webhook payloads contain the `repository` property when the event occurs from activity in a repository.

sender `object` **Required**

The GitHub user that triggered the event. This property is included in every webhook payload.

code_scanning_alert

This event occurs when there is activity relating to code scanning alerts in a repository. For more information, see "[About code scanning](#)" and "[About code scanning alerts](#)." For information about the API to manage code scanning, see "[Code scanning](#)" in the REST API documentation.

To subscribe to this event, a GitHub App must have at least read-level access for the "Code scanning alerts" repository permission.

Availability for `code_scanning_alert`

- Repositories
- Organizations
- GitHub Apps

Webhook payload object for `code_scanning_alert`

Action type: **appeared_in_branch** ▼

A previously created code scanning alert appeared in another branch. This can happen when a branch is merged into or created from a branch with a pre-existing code scanning alert.

Webhook request body parameters

action `string` **Required**

Value: `appeared_in_branch`

alert `object` **Required**

The code scanning alert involved in the event.

► Properties of `alert`

`commit_oid` string **Required**

The commit SHA of the code scanning alert. When the action is `reopened_by_user` or `closed_by_user`, the event was triggered by the `sender` and this value will be empty.

`enterprise` object

An enterprise on GitHub. Webhook payloads contain the `enterprise` property when the webhook is configured on an enterprise account or an organization that's part of an enterprise account. For more information, see "[About enterprise accounts](#)."

`installation` object

The GitHub App installation. Webhook payloads contain the `installation` property when the event is configured for and sent to a GitHub App. For more information, see "[Using webhooks with GitHub Apps](#)."

`organization` object

A GitHub organization. Webhook payloads contain the `organization` property when the webhook is configured for an organization, or when the event occurs from activity in a repository owned by an organization.

`ref` string **Required**

The Git reference of the code scanning alert. When the action is `reopened_by_user` or `closed_by_user`, the event was triggered by the `sender` and this value will be empty.

`repository` object **Required**

The repository on GitHub where the event occurred. Webhook payloads contain the `repository` property when the event occurs from activity in a repository.

`sender` object **Required**

The GitHub user that triggered the event. This property is included in every webhook payload.

commit_comment

This event occurs when there is activity relating to commit comments. For more information about commit comments, see "[Commenting on a pull request](#)." For information about the APIs to manage commit comments, see [the GraphQL API documentation](#) or "[Commit comments](#)" in the REST API documentation.

For activity relating to comments on pull request reviews, use the `pull_request_review_comment` event. For activity relating to issue comments, use the `issue_comment` event. For activity relating to discussion comments, use the `discussion_comment` event.

To subscribe to this event, a GitHub App must have at least read-level access for the "Contents" repository permission.

Availability for `commit_comment`

- Repositories
- Organizations
- GitHub Apps

Webhook payload object for `commit_comment`

Someone commented on a commit.

Webhook request body parameters

action string **Required**

The action performed. Can be `created`.

Value: `created`

comment object **Required**

The [commit comment](#) resource.

► Properties of `comment`

enterprise object

An enterprise on GitHub. Webhook payloads contain the `enterprise` property when the webhook is configured on an enterprise account or an organization that's part of an enterprise account. For more information, see "[About enterprise accounts](#)."

installation object

The GitHub App installation. Webhook payloads contain the `installation` property when the event is configured for and sent to a GitHub App. For more information, see "[Using webhooks with GitHub Apps](#)."

organization object

A GitHub organization. Webhook payloads contain the `organization` property when the webhook is configured for an organization, or when the event occurs from activity in a repository owned by an organization.

repository object **Required**

The repository on GitHub where the event occurred. Webhook payloads contain the `repository` property when the event occurs from activity in a repository.

sender object **Required**

The GitHub user that triggered the event. This property is included in every webhook payload.

create

This event occurs when a Git branch or tag is created.

To subscribe to this event, a GitHub App must have at least read-level access for the "Contents" repository permission.

Notes:

- This event will not occur when more than three tags are created at once.
- Payloads are capped at 25 MB. If an event generates a larger payload, GitHub will not deliver a payload for that webhook event. This may happen, for example, if many branches or tags are pushed at once. We suggest monitoring your payload size to ensure delivery.

Availability for `create`

- Repositories
- Organizations
- GitHub Apps

Webhook payload object for `create`

Webhook request body parameters

description string or null **Required**

The repository's current description.

enterprise object

An enterprise on GitHub. Webhook payloads contain the `enterprise` property when the webhook is configured on an enterprise account or an organization that's part of an enterprise account. For more information, see "[About enterprise accounts](#)."

installation object

The GitHub App installation. Webhook payloads contain the `installation` property when the event is configured for and sent to a GitHub App. For more information, see "[Using webhooks with GitHub Apps](#)."

master_branch string **Required**

The name of the repository's default branch (usually `main`).

organization object

A GitHub organization. Webhook payloads contain the `organization` property when the webhook is configured for an organization, or when the event occurs from activity in a repository owned by an organization.

pusher_type string **Required**

The pusher type for the event. Can be either `user` or a deploy key.

ref string **Required**

The [git_ref](#) resource.

ref_type string **Required**

The type of Git ref object created in the repository.

Can be one of: `tag` , `branch`

repository object **Required**

The repository on GitHub where the event occurred. Webhook payloads contain the `repository` property when the event occurs from activity in a repository.

sender object **Required**

The GitHub user that triggered the event. This property is included in every webhook payload.

delete

This event occurs when a Git branch or tag is deleted. To subscribe to all pushes to a repository, including branch and tag deletions, use the [push](#) webhook event.

To subscribe to this event, a GitHub App must have at least read-level access for the

"Contents" repository permission.

Note: This event will not occur when more than three tags are deleted at once.

Availability for delete

- Repositories
- Organizations
- GitHub Apps

Webhook payload object for delete

Webhook request body parameters

enterprise object

An enterprise on GitHub. Webhook payloads contain the `enterprise` property when the webhook is configured on an enterprise account or an organization that's part of an enterprise account. For more information, see "[About enterprise accounts](#)."

installation object

The GitHub App installation. Webhook payloads contain the `installation` property when the event is configured for and sent to a GitHub App. For more information, see "[Using webhooks with GitHub Apps](#)."

organization object

A GitHub organization. Webhook payloads contain the `organization` property when the webhook is configured for an organization, or when the event occurs from activity in a repository owned by an organization.

pusher_type string **Required**

The pusher type for the event. Can be either `user` or a deploy key.

ref string **Required**

The `git_ref` resource.

ref_type string **Required**

The type of Git ref object deleted in the repository.

Can be one of: `tag` , `branch`

repository object **Required**

The repository on GitHub where the event occurred. Webhook payloads contain the `repository` property when the event occurs from activity in a repository.

sender object **Required**

The GitHub user that triggered the event. This property is included in every webhook payload.

dependabot_alert

This event occurs when there is activity relating to Dependabot alerts.

For more information about Dependabot alerts, see "[About Dependabot alerts](#)." For information about the API to manage Dependabot alerts, see "[Dependabot alerts](#)" in the REST API documentation.

To subscribe to this event, a GitHub App must have at least read-level access for the "Dependabot alerts" repository permission.

Note: Webhook events for Dependabot alerts are currently in beta and subject to change.

Availability for dependabot_alert

- Repositories
- Organizations
- GitHub Apps

Webhook payload object for dependabot_alert

Action type: **created** ▾

A manifest file change introduced a vulnerable dependency, or a GitHub Security Advisory was published and an existing dependency was found to be vulnerable.

Webhook request body parameters

action string **Required**
Value: `created`

alert object **Required**
A Dependabot alert.

► Properties of `alert`

installation object

The GitHub App installation. Webhook payloads contain the `installation` property when the event is configured for and sent to a GitHub App. For more information, see "[Using webhooks with GitHub Apps](#)."

organization object

A GitHub organization. Webhook payloads contain the `organization` property when the webhook is configured for an organization, or when the event occurs from activity in a repository owned by an organization.

enterprise object

An enterprise on GitHub. Webhook payloads contain the `enterprise` property when the webhook is configured on an enterprise account or an organization that's part of an enterprise account. For more information, see "[About enterprise accounts](#)."

repository object **Required**

The repository on GitHub where the event occurred. Webhook payloads contain the `repository` property when the event occurs from activity in a repository.

sender object **Required**

The GitHub user that triggered the event. This property is included in every webhook payload.

deploy_key

This event occurs when there is activity relating to deploy keys. For more information, see "[Managing deploy keys](#)." For information about the APIs to manage deploy keys, see [the GraphQL API documentation](#) or "[Deploy keys](#)" in the REST API documentation.

To subscribe to this event, a GitHub App must have at least read-level access for the "Deployments" repository permission.

Availability for `deploy_key`

- Repositories
- Organizations
- GitHub Apps

Webhook payload object for `deploy_key`

Action type: `created` ▾

A deploy key was created.

Webhook request body parameters

`action` string **Required**

Value: `created`

`enterprise` object

An enterprise on GitHub. Webhook payloads contain the `enterprise` property when the webhook is configured on an enterprise account or an organization that's part of an enterprise account. For more information, see "[About enterprise accounts](#)."

`installation` object

The GitHub App installation. Webhook payloads contain the `installation` property when the event is configured for and sent to a GitHub App. For more information, see "[Using webhooks with GitHub Apps](#)."

`key` object **Required**

The `deploy_key` resource.

► Properties of `key`

`organization` object

A GitHub organization. Webhook payloads contain the `organization` property when the webhook is configured for an organization, or when the event occurs from activity in a repository owned by an organization.

`repository` object **Required**

The repository on GitHub where the event occurred. Webhook payloads contain the `repository` property when the event occurs from activity in a repository.

`sender` object **Required**

The GitHub user that triggered the event. This property is included in every webhook payload.

deployment

This event occurs when there is activity relating to deployments. For more information, see "[About deployments](#)." For information about the APIs to manage deployments, see [the GraphQL API documentation](#) or "[Deployments](#)" in the REST API documentation.

For activity relating to deployment status, use the `deployment_status` event.

To subscribe to this event, a GitHub App must have at least read-level access for the "Deployments" repository permission.

Availability for `deployment`

- Repositories
- Organizations
- GitHub Apps

Webhook payload object for `deployment`

A deployment was created.

Webhook request body parameters

action	string	Required
Value:	created	
deployment	object	Required
The deployment .		
► Properties of <code>deployment</code>		
enterprise	object	
An enterprise on GitHub. Webhook payloads contain the <code>enterprise</code> property when the webhook is configured on an enterprise account or an organization that's part of an enterprise account. For more information, see " About enterprise accounts ."		
installation	object	
The GitHub App installation. Webhook payloads contain the <code>installation</code> property when the event is configured for and sent to a GitHub App. For more information, see " Using webhooks with GitHub Apps ."		
organization	object	
A GitHub organization. Webhook payloads contain the <code>organization</code> property when the webhook is configured for an organization, or when the event occurs from activity in a repository owned by an organization.		
repository	object	Required
The repository on GitHub where the event occurred. Webhook payloads contain the <code>repository</code> property when the event occurs from activity in a repository.		
sender	object	Required
The GitHub user that triggered the event. This property is included in every webhook payload.		
workflow	object or null	Required
► Properties of <code>workflow</code>		

workflow_run object or null **Required**

► Properties of **workflow_run**

deployment_protection_rule

This event occurs when there is activity relating to deployment protection rules. For more information, see "[Using environments for deployment](#)." For information about the API to manage deployment protection rules, see [the REST API documentation](#).

To subscribe to this event, a GitHub App must have at least read-level access for the "Deployments" repository permission.

Availability for deployment_protection_rule

- GitHub Apps

Webhook payload object for deployment_protection_rule

A deployment protection rule was requested for an environment.

Webhook request body parameters

action string

Value: **requested**

environment string

The name of the environment that has the deployment protection rule.

event string

The event that triggered the deployment protection rule.

deployment_callback_url string

The URL to review the deployment protection rule.

deployment object

A request for a specific ref(branch,sha,tag) to be deployed

► Properties of **deployment**

pull_requests array of objects

► Properties of **pull_requests**

repository object

The repository on GitHub where the event occurred. Webhook payloads contain the **repository** property when the event occurs from activity in a repository.

organization object

A GitHub organization. Webhook payloads contain the **organization** property when the webhook is configured for an organization, or when the event occurs from activity in a repository owned by an organization.

installation object

The GitHub App installation. Webhook payloads contain the `installation` property when the event is configured for and sent to a GitHub App. For more information, see "[Using webhooks with GitHub Apps](#)."

sender object

The GitHub user that triggered the event. This property is included in every webhook payload.

deployment_review

This event occurs when there is activity relating to deployment reviews. For more information, see "[About deployments](#)." For information about the APIs to manage deployments, see [the GraphQL API documentation](#) or "[Deployments](#)" in the REST API documentation.

For activity relating to deployment creation or deployment status, use the `deployment` or `deployment_status` event.

To subscribe to this event, a GitHub App must have at least read-level access for the "Deployments" repository permission.

Availability for deployment_review

- GitHub Apps

Webhook payload object for deployment_review

Action type: **approved** ▾

A deployment review was approved.

Webhook request body parameters

action string **Required**

Value: `approved`

approver object

► Properties of `approver`

comment string

enterprise object

An enterprise on GitHub. Webhook payloads contain the `enterprise` property when the webhook is configured on an enterprise account or an organization that's part of an enterprise account. For more information, see "[About enterprise accounts](#)."

installation object

The GitHub App installation. Webhook payloads contain the `installation` property when the event is configured for and sent to a GitHub App. For more information, see "[Using webhooks with GitHub Apps](#)."

organization object **Required**

organization object **Required**

A GitHub organization. Webhook payloads contain the `organization` property when the webhook is configured for an organization, or when the event occurs from activity in a repository owned by an organization.

repository object **Required**

The repository on GitHub where the event occurred. Webhook payloads contain the `repository` property when the event occurs from activity in a repository.

reviewers array of objects

► Properties of `reviewers`

sender object **Required**

The GitHub user that triggered the event. This property is included in every webhook payload.

since string **Required**

workflow_job_run object

► Properties of `workflow_job_run`

workflow_job_runs array of objects

► Properties of `workflow_job_runs`

workflow_run object or null **Required**

► Properties of `workflow_run`

deployment_status

This event occurs when there is activity relating to deployment statuses. For more information, see "[About deployments](#)." For information about the APIs to manage deployments, see [the GraphQL API documentation](#) or "[Deployments](#)" in the REST API documentation.

For activity relating to deployment creation, use the `deployment` event.

To subscribe to this event, a GitHub App must have at least read-level access for the "Deployments" repository permission.

Availability for `deployment_status`

- Repositories
- Organizations
- GitHub Apps

Webhook payload object for `deployment_status`

A new deployment status was created.

Webhook request body parameters

status string **Required**

action string **Required**

Value: `created`

check_run object or null

► Properties of `check_run`

deployment object **Required**

The [deployment](#).

► Properties of `deployment`

deployment_status object **Required**

The [deployment status](#).

► Properties of `deployment_status`

enterprise object

An enterprise on GitHub. Webhook payloads contain the `enterprise` property when the webhook is configured on an enterprise account or an organization that's part of an enterprise account. For more information, see "[About enterprise accounts](#)."

installation object

The GitHub App installation. Webhook payloads contain the `installation` property when the event is configured for and sent to a GitHub App. For more information, see "[Using webhooks with GitHub Apps](#)."

organization object

A GitHub organization. Webhook payloads contain the `organization` property when the webhook is configured for an organization, or when the event occurs from activity in a repository owned by an organization.

repository object **Required**

The repository on GitHub where the event occurred. Webhook payloads contain the `repository` property when the event occurs from activity in a repository.

sender object **Required**

The GitHub user that triggered the event. This property is included in every webhook payload.

workflow object or null

► Properties of `workflow`

workflow_run object or null

► Properties of `workflow_run`

discussion

This event occurs when there is activity relating to a discussion. For more information about discussions, see "[GitHub Discussions](#)." For information about the API to manage discussions, see [the GraphQL documentation](#).

For activity relating to a comment on a discussion, use the `discussion_comment` event.

To subscribe to this event, a GitHub App must have at least read-level access for the "Discussions" repository permission.

Note: Webhook events for GitHub Discussions are currently in beta and subject to change.

Availability for discussion

- Repositories
- Organizations
- GitHub Apps

Webhook payload object for discussion

Action type: answered ▾

A comment on the discussion was marked as the answer.

Webhook request body parameters

action string Required

Value: answered

answer object Required

► Properties of answer

discussion object Required

A Discussion in a repository.

► Properties of discussion

enterprise object

An enterprise on GitHub. Webhook payloads contain the `enterprise` property when the webhook is configured on an enterprise account or an organization that's part of an enterprise account. For more information, see "[About enterprise accounts](#)."

installation object

The GitHub App installation. Webhook payloads contain the `installation` property when the event is configured for and sent to a GitHub App. For more information, see "[Using webhooks with GitHub Apps](#)."

organization object

A GitHub organization. Webhook payloads contain the `organization` property when the webhook is configured for an organization, or when the event occurs from activity in a repository owned by an organization.

repository object Required

The repository on GitHub where the event occurred. Webhook payloads contain the `repository` property when the event occurs from activity in a repository.

sender object Required

The GitHub user that triggered the event. This property is included in every webhook payload.

discussion_comment

This event occurs when there is activity relating to a comment on a discussion. For more information about discussions, see "[GitHub Discussions](#)." For information about the API to manage discussions, see [the GraphQL documentation](#).

For activity relating to a discussion as opposed to comments on a discussion, use the `discussion` event.

To subscribe to this event, a GitHub App must have at least read-level access for the "Discussions" repository permission.

Note: Webhook events for GitHub Discussions are currently in beta and subject to change.

Availability for discussion_comment

- Repositories
- Organizations
- GitHub Apps

Webhook payload object for discussion_comment

Action type: `created` ▾

A comment on a discussion was created.

Webhook request body parameters

`action` string **Required**
Value: `created`

`comment` object **Required**

► Properties of `comment`

`discussion` object **Required**
A Discussion in a repository.

► Properties of `discussion`

`enterprise` object

An enterprise on GitHub. Webhook payloads contain the `enterprise` property when the webhook is configured on an enterprise account or an organization that's part of an enterprise account. For more information, see "[About enterprise accounts](#)."

`installation` object

The GitHub App installation. Webhook payloads contain the `installation` property when the event is configured for and sent to a GitHub App. For more information, see "[Using webhooks with GitHub Apps](#)."

`organization` object

A GitHub organization. Webhook payloads contain the `organization` property when the webhook is configured for an organization, or when the event occurs from activity in a repository owned by an

configured for an organization, or when the event occurs from activity in a repository owned by an organization.

repository object **Required**

The repository on GitHub where the event occurred. Webhook payloads contain the `repository` property when the event occurs from activity in a repository.

sender object **Required**

The GitHub user that triggered the event. This property is included in every webhook payload.

enterprise

This event occurs when there is activity relating to anonymous Git read access in an enterprise. For more information, see "[Enforcing repository management policies in your enterprise](#)."

Availability for enterprise

- Enterprises

Webhook payload object for enterprise

Action type: **anonymous_access_disabled** ▾

Anonymous Git read access was disabled.

Webhook request body parameters

action string **Required**

Value: `anonymous_access_disabled`

sender object

The GitHub user that triggered the event. This property is included in every webhook payload.

fork

This event occurs when someone forks a repository. For more information, see "[Fork a repo](#)." For information about the API to manage forks, see "[Forks](#)" in the REST API documentation.

To subscribe to this event, a GitHub App must have at least read-level access for the "Contents" repository permission.

Availability for fork

- Enterprises
- Repositories
- Organizations
- GitHub Apps

Webhook payload object for fork

Webhook request body parameters

enterprise object

An enterprise on GitHub. Webhook payloads contain the `enterprise` property when the webhook is configured on an enterprise account or an organization that's part of an enterprise account. For more information, see "[About enterprise accounts](#)."

forkee object **Required**

The created `repository` resource.

► Properties of `forkee`

installation object

The GitHub App installation. Webhook payloads contain the `installation` property when the event is configured for and sent to a GitHub App. For more information, see "[Using webhooks with GitHub Apps](#)."

organization object

A GitHub organization. Webhook payloads contain the `organization` property when the webhook is configured for an organization, or when the event occurs from activity in a repository owned by an organization.

repository object **Required**

The repository on GitHub where the event occurred. Webhook payloads contain the `repository` property when the event occurs from activity in a repository.

sender object **Required**

The GitHub user that triggered the event. This property is included in every webhook payload.

github_app_authorization

This event occurs when a user revokes their authorization of a GitHub App. For more information, see "[About apps](#)." For information about the API to manage GitHub Apps, see [the GraphQL API documentation](#) or "[Apps](#)" in the REST API documentation.

A GitHub App receives this webhook by default and cannot unsubscribe from this event.

Anyone can revoke their authorization of a GitHub App from their [GitHub account settings page](#). Revoking the authorization of a GitHub App does not uninstall the GitHub App. You should program your GitHub App so that when it receives this webhook, it stops calling the API on behalf of the person who revoked the token. If your GitHub App continues to use a revoked access token, it will receive the `401 Bad Credentials` error. For details about requests with a user access token, which require GitHub App authorization, see "[Authenticating with a GitHub App on behalf of a user](#)."

Availability for `github_app_authorization`

- GitHub Apps

Webhook payload object for `github_app_authorization`

Someone revoked their authorization of a GitHub App.

Webhook request body parameters

action string **Required**

Value: `revoked`

enterprise object

An enterprise on GitHub. Webhook payloads contain the `enterprise` property when the webhook is configured on an enterprise account or an organization that's part of an enterprise account. For more information, see "[About enterprise accounts](#)."

installation object

The GitHub App installation. Webhook payloads contain the `installation` property when the event is configured for and sent to a GitHub App. For more information, see "[Using webhooks with GitHub Apps](#)."

organization object

A GitHub organization. Webhook payloads contain the `organization` property when the webhook is configured for an organization, or when the event occurs from activity in a repository owned by an organization.

repository object

The repository on GitHub where the event occurred. Webhook payloads contain the `repository` property when the event occurs from activity in a repository.

sender object **Required**

The GitHub user that triggered the event. This property is included in every webhook payload.

gollum

This event occurs when someone creates or updates a wiki page. For more information, see "[About wikis](#)."

To subscribe to this event, a GitHub App must have at least read-level access for the "Contents" repository permission.

Availability for `gollum`

- Repositories
- Organizations
- GitHub Apps

Webhook payload object for `gollum`

Webhook request body parameters

enterprise object

An enterprise on GitHub. Webhook payloads contain the `enterprise` property when the webhook is configured on an enterprise account or an organization that's part of an enterprise account. For more information, see "[About enterprise accounts](#)."

installation object

The GitHub App installation. Webhook payloads contain the `installation` property when the event is configured for and sent to a GitHub App. For more information, see "[Using webhooks with GitHub Apps](#)."

organization object

organization object

A GitHub organization. Webhook payloads contain the `organization` property when the webhook is configured for an organization, or when the event occurs from activity in a repository owned by an organization.

pages array of objects **Required**

The pages that were updated.

► Properties of `pages`

repository object **Required**

The repository on GitHub where the event occurred. Webhook payloads contain the `repository` property when the event occurs from activity in a repository.

sender object **Required**

The GitHub user that triggered the event. This property is included in every webhook payload.

installation

This event occurs when there is activity relating to a GitHub App installation. All GitHub Apps receive this event by default. You cannot manually subscribe to this event.

For more information about GitHub Apps, see "[About apps](#)." For information about the APIs to manage GitHub Apps, see [the GraphQL API documentation](#) or "[Apps](#)" in the REST API documentation.

Availability for `installation`

- GitHub Apps

Webhook payload object for `installation`

Action type: **created** ▾

Someone installed a GitHub App on a user or organization account.

Webhook request body parameters

action string **Required**

Value: `created`

enterprise object

An enterprise on GitHub. Webhook payloads contain the `enterprise` property when the webhook is configured on an enterprise account or an organization that's part of an enterprise account. For more information, see "[About enterprise accounts](#)."

installation object **Required**

Installation

organization object

A GitHub organization. Webhook payloads contain the `organization` property when the webhook is configured for an organization, or when the event occurs from activity in a repository owned by an organization.

organization

repositories array of objects

An array of repository objects that the installation can access.

► Properties of **repositories**

repository object

The repository on GitHub where the event occurred. Webhook payloads contain the **repository** property when the event occurs from activity in a repository.

requester object or null

► Properties of **requester**

sender object **Required**

The GitHub user that triggered the event. This property is included in every webhook payload.

installation_repositories

This event occurs when there is activity relating to which repositories a GitHub App installation can access. All GitHub Apps receive this event by default. You cannot manually subscribe to this event.

For more information about GitHub Apps, see "[About apps](#)." For information about the APIs to manage GitHub Apps, see [the GraphQL API documentation](#) or "[Apps](#)" in the REST API documentation.

Availability for **installation_repositories**

- GitHub Apps

Webhook payload object for **installation_repositories**

Action type: **added** ▾

A GitHub App installation was granted access to one or more repositories.

Webhook request body parameters

action string **Required**

Value: **added**

enterprise object

An enterprise on GitHub. Webhook payloads contain the **enterprise** property when the webhook is configured on an enterprise account or an organization that's part of an enterprise account. For more information, see "[About enterprise accounts](#)."

installation object **Required**

Installation

organization object

A GitHub organization. Webhook payloads contain the **organization** property when the webhook is configured for an organization, or when the event occurs from activity in a repository owned by an

configured for an organization, or when the event occurs from activity in a repository owned by an organization.

repositories_added array of objects **Required**

An array of repository objects, which were added to the installation.

► Properties of **repositories_added**

repositories_removed array of objects **Required**

An array of repository objects, which were removed from the installation.

► Properties of **repositories_removed**

repository object

The repository on GitHub where the event occurred. Webhook payloads contain the **repository** property when the event occurs from activity in a repository.

repository_selection string **Required**

Describe whether all repositories have been selected or there's a selection involved

Can be one of: **all** , **selected**

requester object or null **Required**

► Properties of **requester**

sender object **Required**

The GitHub user that triggered the event. This property is included in every webhook payload.

installation_target [↗](#)

This event occurs when there is activity relating to the user or organization account that a GitHub App is installed on. For more information, see "[About apps](#)." For information about the APIs to manage GitHub Apps, see [the GraphQL API documentation](#) or "[Apps](#)" in the REST API documentation.

Availability for **installation_target**

- GitHub Apps

Webhook payload object for **installation_target**

Somebody renamed the user or organization account that a GitHub App is installed on.

Webhook request body parameters

account object **Required**

► Properties of **account**

action string **Required**

Value: **renamed**

changes object **Required**

► Properties of **changes**

enterprise object

An enterprise on GitHub. Webhook payloads contain the **enterprise** property when the webhook is configured on an enterprise account or an organization that's part of an enterprise account. For more information, see "[About enterprise accounts](#)."

installation object **Required**

The GitHub App installation. Webhook payloads contain the **installation** property when the event is configured for and sent to a GitHub App. For more information, see "[Using webhooks with GitHub Apps](#)."

organization object

A GitHub organization. Webhook payloads contain the **organization** property when the webhook is configured for an organization, or when the event occurs from activity in a repository owned by an organization.

repository object

The repository on GitHub where the event occurred. Webhook payloads contain the **repository** property when the event occurs from activity in a repository.

sender object

The GitHub user that triggered the event. This property is included in every webhook payload.

target_type string **Required**

issue_comment

This event occurs when there is activity relating to a comment on an issue or pull request. For more information about issues and pull requests, see "[About issues](#)" and "[About pull requests](#)." For information about the APIs to manage issue comments, see [the GraphQL documentation](#) or "[Issue comments](#)" in the REST API documentation.

For activity relating to an issue as opposed to comments on an issue, use the **issue** event. For activity related to pull request reviews or pull request review comments, use the **pull_request_review** or **pull_request_review_comment** events. For more information about the different types of pull request comments, see "[Working with comments](#)."

To subscribe to this event, a GitHub App must have at least read-level access for the "Issues" repository permission.

Availability for **issue_comment**

- Repositories
- Organizations
- GitHub Apps

Webhook payload object for **issue_comment**

Action type: **created** ▾

A comment on an issue or pull request was created.

Webhook request body parameters

action string **Required**

Value: `created`

comment object **Required**

The [comment](#) itself.

► Properties of `comment`

enterprise object

An enterprise on GitHub. Webhook payloads contain the `enterprise` property when the webhook is configured on an enterprise account or an organization that's part of an enterprise account. For more information, see "[About enterprise accounts](#)."

installation object

The GitHub App installation. Webhook payloads contain the `installation` property when the event is configured for and sent to a GitHub App. For more information, see "[Using webhooks with GitHub Apps](#)."

issue object **Required**

The [issue](#) the comment belongs to.

► Properties of `issue`

organization object

A GitHub organization. Webhook payloads contain the `organization` property when the webhook is configured for an organization, or when the event occurs from activity in a repository owned by an organization.

repository object **Required**

The repository on GitHub where the event occurred. Webhook payloads contain the `repository` property when the event occurs from activity in a repository.

sender object **Required**

The GitHub user that triggered the event. This property is included in every webhook payload.

issues

This event occurs when there is activity relating to an issue. For more information about issues, see "[About issues](#)." For information about the APIs to manage issues, see [the GraphQL documentation](#) or "[Issues](#)" in the REST API documentation.

For activity relating to a comment on an issue, use the `issue_comment` event.

To subscribe to this event, a GitHub App must have at least read-level access for the "Issues" repository permission.

Availability for `issues`

- Repositories
- Organizations
- GitHub Apps

Webhook payload object for `issues`

Action type: `assigned` ▾

An issue was assigned to a user.

Webhook request body parameters

action string **Required**

The action that was performed.

Value: `assigned`

assignee object or null

► Properties of `assignee`

enterprise object

An enterprise on GitHub. Webhook payloads contain the `enterprise` property when the webhook is configured on an enterprise account or an organization that's part of an enterprise account. For more information, see "[About enterprise accounts](#)."

installation object

The GitHub App installation. Webhook payloads contain the `installation` property when the event is configured for and sent to a GitHub App. For more information, see "[Using webhooks with GitHub Apps](#)."

issue object **Required**

The [issue](#) itself.

► Properties of `issue`

organization object

A GitHub organization. Webhook payloads contain the `organization` property when the webhook is configured for an organization, or when the event occurs from activity in a repository owned by an organization.

repository object **Required**

The repository on GitHub where the event occurred. Webhook payloads contain the `repository` property when the event occurs from activity in a repository.

sender object **Required**

The GitHub user that triggered the event. This property is included in every webhook payload.

label

This event occurs when there is activity relating to labels. For more information, see "[Managing labels](#)." For information about the APIs to manage labels, see [the GraphQL documentation](#) or "[Labels](#)" in the REST API documentation.

If you want to receive an event when a label is added to or removed from an issue, pull request, or discussion, use the `labeled` or `unlabeled` action type for the `issues`, `pull_request`, or `discussion` events instead.

To subscribe to this event, a GitHub App must have at least read-level access for the

"Metadata" repository permission.

Availability for `label`

- Repositories
- Organizations
- GitHub Apps

Webhook payload object for `label`

Action type: `created` ▾

A label was created.

Webhook request body parameters

`action` string **Required**

Value: `created`

`enterprise` object

An enterprise on GitHub. Webhook payloads contain the `enterprise` property when the webhook is configured on an enterprise account or an organization that's part of an enterprise account. For more information, see "[About enterprise accounts](#)."

`installation` object

The GitHub App installation. Webhook payloads contain the `installation` property when the event is configured for and sent to a GitHub App. For more information, see "[Using webhooks with GitHub Apps](#)."

`label` object **Required**

► Properties of `label`

`organization` object

A GitHub organization. Webhook payloads contain the `organization` property when the webhook is configured for an organization, or when the event occurs from activity in a repository owned by an organization.

`repository` object **Required**

The repository on GitHub where the event occurred. Webhook payloads contain the `repository` property when the event occurs from activity in a repository.

`sender` object

The GitHub user that triggered the event. This property is included in every webhook payload.

member

This event occurs when there is activity relating to collaborators in a repository. For more information, see "[Adding outside collaborators to repositories in your organization](#)." For more information about the API to manage repository collaborators, see [the GraphQL API documentation](#) or "[Collaborators](#)" in the REST API documentation.

To subscribe to this event, a GitHub App must have at least read-level access for the

"Members" organization permission.

Availability for member

- Enterprises
- Repositories
- Organizations
- GitHub Apps

Webhook payload object for member

Action type: **added** ▾

A GitHub user accepted an invitation to a repository.

Webhook request body parameters

action string **Required**

Value: `added`

changes object

► Properties of `changes`

enterprise object

An enterprise on GitHub. Webhook payloads contain the `enterprise` property when the webhook is configured on an enterprise account or an organization that's part of an enterprise account. For more information, see "[About enterprise accounts](#)."

installation object

The GitHub App installation. Webhook payloads contain the `installation` property when the event is configured for and sent to a GitHub App. For more information, see "[Using webhooks with GitHub Apps](#)."

member object or null **Required**

► Properties of `member`

organization object

A GitHub organization. Webhook payloads contain the `organization` property when the webhook is configured for an organization, or when the event occurs from activity in a repository owned by an organization.

repository object **Required**

The repository on GitHub where the event occurred. Webhook payloads contain the `repository` property when the event occurs from activity in a repository.

sender object **Required**

The GitHub user that triggered the event. This property is included in every webhook payload.

membership

This event occurs when there is activity relating to team membership. For more

information, see "[About teams](#)." For more information about the APIs to manage team memberships, see [the GraphQL API documentation](#) or "[Team members](#)" in the REST API documentation.

To subscribe to this event, a GitHub App must have at least read-level access for the "Members" organization permission.

Availability for membership

- Organizations
- Enterprises
- GitHub Apps

Webhook payload object for membership

Action type: **added** ▾

An organization member was added to a team.

Webhook request body parameters

action string **Required**

Value: `added`

enterprise object

An enterprise on GitHub. Webhook payloads contain the `enterprise` property when the webhook is configured on an enterprise account or an organization that's part of an enterprise account. For more information, see "[About enterprise accounts](#)."

installation object

The GitHub App installation. Webhook payloads contain the `installation` property when the event is configured for and sent to a GitHub App. For more information, see "[Using webhooks with GitHub Apps](#)."

member object or null **Required**

► Properties of `member`

organization object **Required**

A GitHub organization. Webhook payloads contain the `organization` property when the webhook is configured for an organization, or when the event occurs from activity in a repository owned by an organization.

repository object

The repository on GitHub where the event occurred. Webhook payloads contain the `repository` property when the event occurs from activity in a repository.

scope string **Required**

The scope of the membership. Currently, can only be `team`.

Value: `team`

sender object or null **Required**

team object **Required**

Groups of organization members that gives permissions on specified repositories.

Group of organization members that gives permissions on specified repositories.

► Properties of `team`

meta

This event occurs when there is activity relating to a webhook itself.

To subscribe to this event, a GitHub App must have at least read-level access for the "Meta" app permission.

Availability for `meta`

- GitHub Marketplace
- Enterprises
- Repositories
- Organizations
- GitHub Apps

Webhook payload object for `meta`

The webhook was deleted.

Webhook request body parameters

action `string` Required

Value: `deleted`

enterprise `object`

An enterprise on GitHub. Webhook payloads contain the `enterprise` property when the webhook is configured on an enterprise account or an organization that's part of an enterprise account. For more information, see "[About enterprise accounts](#)."

hook `object` Required

The modified webhook. This will contain different keys based on the type of webhook it is: repository, organization, business, app, or GitHub Marketplace.

► Properties of `hook`

hook_id `integer` Required

The id of the modified webhook.

installation `object`

The GitHub App installation. Webhook payloads contain the `installation` property when the event is configured for and sent to a GitHub App. For more information, see "[Using webhooks with GitHub Apps](#)."

organization `object`

A GitHub organization. Webhook payloads contain the `organization` property when the webhook is configured for an organization, or when the event occurs from activity in a repository owned by an organization.

repository `object`

The repository on GitHub where the event occurred. Webhook payloads contain the `repository`

property when the event occurs from activity in a repository.

sender object

The GitHub user that triggered the event. This property is included in every webhook payload.

milestone

This event occurs when there is activity relating to milestones. For more information, see "[About milestones](#)." For information about the APIs to manage milestones, see [the GraphQL documentation](#) or "[Milestones](#)" in the REST API documentation.

If you want to receive an event when an issue or pull request is added to or removed from a milestone, use the `milestoned` or `demilestoned` action type for the `issues` or `pull_request` events instead.

To subscribe to this event, a GitHub App must have at least read-level access for the "Issues" or "Pull requests" repository permissions.

Availability for milestone

- Repositories
- Organizations
- GitHub Apps

Webhook payload object for milestone

Action type: **closed** ▾

A milestone was closed.

Webhook request body parameters

action string **Required**

Value: `closed`

enterprise object

An enterprise on GitHub. Webhook payloads contain the `enterprise` property when the webhook is configured on an enterprise account or an organization that's part of an enterprise account. For more information, see "[About enterprise accounts](#)."

installation object

The GitHub App installation. Webhook payloads contain the `installation` property when the event is configured for and sent to a GitHub App. For more information, see "[Using webhooks with GitHub Apps](#)."

milestone object **Required**

A collection of related issues and pull requests.

► Properties of `milestone`

organization object

A GitHub organization. Webhook payloads contain the `organization` property when the webhook is configured for an organization, or when the event occurs from activity in a repository owned by an organization.

organization.

repository object **Required**

The repository on GitHub where the event occurred. Webhook payloads contain the `repository` property when the event occurs from activity in a repository.

sender object **Required**

The GitHub user that triggered the event. This property is included in every webhook payload.

organization

This event occurs when there is activity relating to an organization and its members. For more information, see "[About organizations](#)." For information about the APIs to manage organizations, see [the GraphQL documentation](#) or "[Organizations](#)" in the REST API documentation.

If you want to receive an event when a non-member is blocked or unblocked from an organization, use the `org_block` event instead.

To subscribe to this event, a GitHub App must have at least read-level access for the "Members" organization permission.

Availability for organization

- Organizations
- Enterprises
- GitHub Apps

Webhook payload object for organization

Action type: **deleted** ▾

An organization was deleted.

Webhook request body parameters

action string **Required**

Value: `deleted`

enterprise object

An enterprise on GitHub. Webhook payloads contain the `enterprise` property when the webhook is configured on an enterprise account or an organization that's part of an enterprise account. For more information, see "[About enterprise accounts](#)."

installation object

The GitHub App installation. Webhook payloads contain the `installation` property when the event is configured for and sent to a GitHub App. For more information, see "[Using webhooks with GitHub Apps](#)."

membership object

The membership between the user and the organization. Not present when the action is `member_invited`.

► Properties of `membership`

organization object **Required**

A GitHub organization. Webhook payloads contain the `organization` property when the webhook is configured for an organization, or when the event occurs from activity in a repository owned by an organization.

repository object

The repository on GitHub where the event occurred. Webhook payloads contain the `repository` property when the event occurs from activity in a repository.

sender object **Required**

The GitHub user that triggered the event. This property is included in every webhook payload.

package

This event occurs when there is activity relating to GitHub Packages. For more information, see "[Introduction to GitHub Packages](#)." For information about the APIs to manage GitHub Packages, see [the GraphQL API documentation](#) or "[Packages](#)" in the REST API documentation.

To install this event on a GitHub App, the app must have at least read-level access for the "Packages" repository permission.

Availability for package

- Repositories
- Organizations
- GitHub Apps

Webhook payload object for package

Action type: **published** ▾

A package was published to a registry.

Webhook request body parameters

action string **Required**

Value: `published`

enterprise object

An enterprise on GitHub. Webhook payloads contain the `enterprise` property when the webhook is configured on an enterprise account or an organization that's part of an enterprise account. For more information, see "[About enterprise accounts](#)."

installation object

The GitHub App installation. Webhook payloads contain the `installation` property when the event is configured for and sent to a GitHub App. For more information, see "[Using webhooks with GitHub Apps](#)."

organization object

A GitHub organization. Webhook payloads contain the `organization` property when the webhook is configured for an organization, or when the event occurs from activity in a repository owned by an organization.

package object **Required**

Information about the package.

► Properties of **package**

repository object

The repository on GitHub where the event occurred. Webhook payloads contain the **repository** property when the event occurs from activity in a repository.

sender object **Required**

The GitHub user that triggered the event. This property is included in every webhook payload.

page_build

This event occurs when there is an attempted build of a GitHub Pages site. This event occurs regardless of whether the build is successful. For more information, see "[Configuring a publishing source for your GitHub Pages site](#)." For information about the API to manage GitHub Pages, see "[Pages](#)" in the REST API documentation.

To subscribe to this event, a GitHub App must have at least read-level access for the "Pages" repository permission.

Availability for **page_build**

- Repositories
- Organizations
- GitHub Apps

Webhook payload object for **page_build**

Webhook request body parameters

build object **Required**

The [List GitHub Pages builds](#) itself.

► Properties of **build**

enterprise object

An enterprise on GitHub. Webhook payloads contain the **enterprise** property when the webhook is configured on an enterprise account or an organization that's part of an enterprise account. For more information, see "[About enterprise accounts](#)."

id integer **Required**

installation object

The GitHub App installation. Webhook payloads contain the **installation** property when the event is configured for and sent to a GitHub App. For more information, see "[Using webhooks with GitHub Apps](#)."

organization object

A GitHub organization. Webhook payloads contain the **organization** property when the webhook is configured for an organization, or when the event occurs from activity in a repository owned by an organization.

organization

repository object **Required**

The repository on GitHub where the event occurred. Webhook payloads contain the **repository** property when the event occurs from activity in a repository.

sender object **Required**

The GitHub user that triggered the event. This property is included in every webhook payload.

personal_access_token_request

This event occurs when there is activity relating to a request for a fine-grained personal access token to access resources that belong to a resource owner that requires approval for token access. For more information, see "[Creating a personal access token](#)."

To subscribe to this event, a GitHub App must have at least read-level access for the "Personal access token requests" organization permission.

Note: Fine-grained PATs are in public beta. Related APIs, events, and functionality are subject to change.

Availability for personal_access_token_request

- GitHub Apps

Webhook payload object for personal_access_token_request

Action type: **approved** ▾

A fine-grained personal access token request was approved.

Webhook request body parameters

action string **Required**

Value: **approved**

personal_access_token_request object **Required**

Details of a Personal Access Token Request.

► Properties of **personal_access_token_request**

organization object **Required**

A GitHub organization. Webhook payloads contain the **organization** property when the webhook is configured for an organization, or when the event occurs from activity in a repository owned by an organization.

sender object **Required**

The GitHub user that triggered the event. This property is included in every webhook payload.

installation object **Required**

The GitHub App installation. Webhook payloads contain the **installation** property when the event is configured for and sent to a GitHub App. For more information, see "[Using webhooks with GitHub Apps](#)."

ping

This event occurs when you create a new webhook. The ping event is a confirmation from GitHub that you configured the webhook correctly.

Availability for ping

- Repositories
- Organizations
- GitHub Apps
- Enterprises
- GitHub Marketplace

Webhook payload object for ping

Webhook request body parameters

hook object

The webhook that is being pinged

► Properties of hook

hook_id integer

The ID of the webhook that triggered the ping.

organization object

A GitHub organization. Webhook payloads contain the `organization` property when the webhook is configured for an organization, or when the event occurs from activity in a repository owned by an organization.

repository object

The repository on GitHub where the event occurred. Webhook payloads contain the `repository` property when the event occurs from activity in a repository.

sender object

The GitHub user that triggered the event. This property is included in every webhook payload.

zen string

Random string of GitHub zen.

project_card

This event occurs when there is activity relating to a card on a classic project. For more information, see "[About projects \(classic\)](#)." For information about the API to manage classic projects, see [the GraphQL API documentation](#) or "[Projects \(classic\)](#)" in the REST API documentation.

For activity relating to a project or a column on a project, use the `project` and `project_column` event. For activity relating to Projects instead of Projects (classic), use the `projects_v2` event instead.

To subscribe to this event, a GitHub App must have at least read-level access for the

"Projects" repository or organization permission.

Availability for project_card

- Repositories
- Organizations
- GitHub Apps

Webhook payload object for project_card

Action type: **converted** ▾

A note in a classic project was converted to an issue.

Webhook request body parameters

action string **Required**

Value: converted

changes object **Required**

► Properties of changes

enterprise object

An enterprise on GitHub. Webhook payloads contain the enterprise property when the webhook is configured on an enterprise account or an organization that's part of an enterprise account. For more information, see "[About enterprise accounts](#)."

installation object

The GitHub App installation. Webhook payloads contain the installation property when the event is configured for and sent to a GitHub App. For more information, see "[Using webhooks with GitHub Apps](#)."

organization object

A GitHub organization. Webhook payloads contain the organization property when the webhook is configured for an organization, or when the event occurs from activity in a repository owned by an organization.

project_card object **Required**

► Properties of project_card

repository object

The repository on GitHub where the event occurred. Webhook payloads contain the repository property when the event occurs from activity in a repository.

sender object **Required**

The GitHub user that triggered the event. This property is included in every webhook payload.

project

This event occurs when there is activity relating to a classic project. For more information, see "[About projects \(classic\)](#)." For information about the API to manage

classic projects, see [the GraphQL API documentation](#) or "[Projects \(classic\)](#)" in the REST API documentation.

For activity relating to a card or column on a project, use the `project_card` and `project_column` event. For activity relating to Projects instead of Projects (classic), use the `projects_v2` event instead.

To subscribe to this event, a GitHub App must have at least read-level access for the "Projects" repository or organization permission.

Availability for `project`

- Repositories
- Organizations
- GitHub Apps

Webhook payload object for `project`

Action type: `closed` ▾

A classic project was closed.

Webhook request body parameters

`action` string **Required**

Value: `closed`

`enterprise` object

An enterprise on GitHub. Webhook payloads contain the `enterprise` property when the webhook is configured on an enterprise account or an organization that's part of an enterprise account. For more information, see "[About enterprise accounts](#)."

`installation` object

The GitHub App installation. Webhook payloads contain the `installation` property when the event is configured for and sent to a GitHub App. For more information, see "[Using webhooks with GitHub Apps](#)."

`organization` object

A GitHub organization. Webhook payloads contain the `organization` property when the webhook is configured for an organization, or when the event occurs from activity in a repository owned by an organization.

`project` object **Required**

► Properties of `project`

`repository` object

The repository on GitHub where the event occurred. Webhook payloads contain the `repository` property when the event occurs from activity in a repository.

`sender` object **Required**

The GitHub user that triggered the event. This property is included in every webhook payload.

project_column

This event occurs when there is activity relating to a column on a classic project. For more information, see "[About projects \(classic\)](#)." For information about the API to manage classic projects, see [the GraphQL API documentation](#) or "[Projects \(classic\)](#)" in the REST API documentation.

For activity relating to a project or a card on a project, use the `project` and `project_card` event. For activity relating to Projects instead of Projects (classic), use the `projects_v2` event instead.

To subscribe to this event, a GitHub App must have at least read-level access for the "Projects" repository or organization permission.

Availability for project_column

- Repositories
- Organizations
- GitHub Apps

Webhook payload object for project_column

Action type: `created` ▾

A column was added to a classic project.

Webhook request body parameters

action string **Required**

Value: `created`

enterprise object

An enterprise on GitHub. Webhook payloads contain the `enterprise` property when the webhook is configured on an enterprise account or an organization that's part of an enterprise account. For more information, see "[About enterprise accounts](#)."

installation object

The GitHub App installation. Webhook payloads contain the `installation` property when the event is configured for and sent to a GitHub App. For more information, see "[Using webhooks with GitHub Apps](#)."

organization object

A GitHub organization. Webhook payloads contain the `organization` property when the webhook is configured for an organization, or when the event occurs from activity in a repository owned by an organization.

project_column object **Required**

► Properties of `project_column`

repository object

The repository on GitHub where the event occurred. Webhook payloads contain the `repository` property when the event occurs from activity in a repository.

sender object

The GitHub user that triggered the event. This property is included in every webhook payload.

projects_v2

This event occurs when there is activity relating to an organization-level project. For more information, see "[About Projects](#)." For information about the Projects API, see [the GraphQL documentation](#).

For activity relating to a item on a project, use the `projects_v2_item` event. For activity relating to Projects (classic), use the `project` , `project_card` , and `project_column` events instead.

To subscribe to this event, a GitHub App must have at least read-level access for the "Projects" organization permission.

Note: Webhook events for projects are currently in beta and subject to change. To share feedback about projects webhooks with GitHub, see the [Projects webhook feedback discussion](#).

Availability for `projects_v2`

- Organizations

Webhook payload object for `projects_v2`

Action type: `closed` ▾

A project in the organization was closed.

Webhook request body parameters

`action` string **Required**

Value: `closed`

`installation` object

The GitHub App installation. Webhook payloads contain the `installation` property when the event is configured for and sent to a GitHub App. For more information, see "[Using webhooks with GitHub Apps](#)."

`organization` object **Required**

A GitHub organization. Webhook payloads contain the `organization` property when the webhook is configured for an organization, or when the event occurs from activity in a repository owned by an organization.

`projects_v2` object **Required**

A projects v2 project

► Properties of `projects_v2`

`sender` object **Required**

The GitHub user that triggered the event. This property is included in every webhook payload.

projects_v2_item

This event occurs when there is activity relating to an item on an organization-level project. For more information, see "[About Projects](#)." For information about the Projects API, see [the GraphQL documentation](#).

For activity relating to a project (instead of an item on a project), use the `projects_v2` event. For activity relating to Projects (classic), use the `project` , `project_card` , and `project_column` events instead.

To subscribe to this event, a GitHub App must have at least read-level access for the "Projects" organization permission.

Note: Webhook events for projects are currently in beta and subject to change. To share feedback about projects webhooks with GitHub, see the [Projects webhook feedback discussion](#).

Availability for `projects_v2_item`

- Organizations

Webhook payload object for `projects_v2_item`

Action type: **archived** ▾

An item on an organization project was archived. For more information, see "[Archiving items from your project](#)."

Webhook request body parameters

action string **Required**
Value: `archived`

changes object **Required**

► Properties of `changes`

installation object

The GitHub App installation. Webhook payloads contain the `installation` property when the event is configured for and sent to a GitHub App. For more information, see "[Using webhooks with GitHub Apps](#)."

organization object **Required**

A GitHub organization. Webhook payloads contain the `organization` property when the webhook is configured for an organization, or when the event occurs from activity in a repository owned by an organization.

projects_v2_item object **Required**

An item belonging to a project

► Properties of `projects_v2_item`

sender object **Required**

The GitHub user that triggered the event. This property is included in every webhook payload.

This event occurs when repository visibility changes from private to public. For more information, see "[Setting repository visibility](#)."

To subscribe to this event, a GitHub App must have at least read-level access for the "Metadata" repository permission.

Availability for `public`

- Repositories
- Organizations
- GitHub Apps

Webhook payload object for `public`

Webhook request body parameters

`enterprise` object

An enterprise on GitHub. Webhook payloads contain the `enterprise` property when the webhook is configured on an enterprise account or an organization that's part of an enterprise account. For more information, see "[About enterprise accounts](#)."

`installation` object

The GitHub App installation. Webhook payloads contain the `installation` property when the event is configured for and sent to a GitHub App. For more information, see "[Using webhooks with GitHub Apps](#)."

`organization` object

A GitHub organization. Webhook payloads contain the `organization` property when the webhook is configured for an organization, or when the event occurs from activity in a repository owned by an organization.

`repository` object **Required**

The repository on GitHub where the event occurred. Webhook payloads contain the `repository` property when the event occurs from activity in a repository.

`sender` object **Required**

The GitHub user that triggered the event. This property is included in every webhook payload.

pull_request

This event occurs when there is activity on a pull request. For more information, see "[About pull requests](#)." For information about the APIs to manage pull requests, see [the GraphQL API documentation](#) or "[Pulls](#)" in the REST API documentation.

For activity related to pull request reviews, pull request review comments, pull request comments, or pull request review threads, use the `pull_request_review`, `pull_request_review_comment`, `issue_comment`, or `pull_request_review_thread` events instead.

To subscribe to this event, a GitHub App must have at least read-level access for the "Pull requests" repository permission.

Availability for `pull_request`

- Repositories

- Organizations
- GitHub Apps

Webhook payload object for pull_request

Action type: **assigned** ▾

A pull request was assigned to a user.

Webhook request body parameters

action string **Required**

Value: assigned

assignee object or null **Required**

► Properties of assignee

enterprise object

An enterprise on GitHub. Webhook payloads contain the `enterprise` property when the webhook is configured on an enterprise account or an organization that's part of an enterprise account. For more information, see "[About enterprise accounts](#)."

installation object

The GitHub App installation. Webhook payloads contain the `installation` property when the event is configured for and sent to a GitHub App. For more information, see "[Using webhooks with GitHub Apps](#)."

number integer **Required**

The pull request number.

organization object

A GitHub organization. Webhook payloads contain the `organization` property when the webhook is configured for an organization, or when the event occurs from activity in a repository owned by an organization.

pull_request object **Required**

► Properties of pull_request

repository object **Required**

The repository on GitHub where the event occurred. Webhook payloads contain the `repository` property when the event occurs from activity in a repository.

sender object **Required**

The GitHub user that triggered the event. This property is included in every webhook payload.

pull_request_review_comment

This event occurs when there is activity relating to a pull request review comment. A pull request review comment is a comment on a pull request's diff. For more information, see "[Commenting on a pull request](#)." For information about the APIs to manage pull request

review comments, see [the GraphQL API documentation](#) or "[Pull request review comments](#)" in the REST API documentation.

For activity related to pull request reviews, pull request comments, or pull request review threads, use the `pull_request_review`, `issue_comment`, or `pull_request_review_thread` events instead.

To subscribe to this event, a GitHub App must have at least read-level access for the "Pull requests" repository permission.

Availability for `pull_request_review_comment`

- Repositories
- Organizations
- GitHub Apps

Webhook payload object for `pull_request_review_comment`

Action type: `created` ▾

A comment on a pull request diff was created.

Webhook request body parameters

`action` string **Required**

Value: `created`

`comment` object **Required**

The [comment](#) itself.

► Properties of `comment`

`enterprise` object

An enterprise on GitHub. Webhook payloads contain the `enterprise` property when the webhook is configured on an enterprise account or an organization that's part of an enterprise account. For more information, see "[About enterprise accounts](#)."

`installation` object

The GitHub App installation. Webhook payloads contain the `installation` property when the event is configured for and sent to a GitHub App. For more information, see "[Using webhooks with GitHub Apps](#)."

`organization` object

A GitHub organization. Webhook payloads contain the `organization` property when the webhook is configured for an organization, or when the event occurs from activity in a repository owned by an organization.

`pull_request` object **Required**

► Properties of `pull_request`

`repository` object **Required**

The repository on GitHub where the event occurred. Webhook payloads contain the `repository` property when the event occurs from activity in a repository.

property when the event occurs from activity in a repository.

sender object **Required**

The GitHub user that triggered the event. This property is included in every webhook payload.

pull_request_review

This event occurs when there is activity relating to a pull request review. A pull request review is a group of pull request review comments in addition to a body comment and a state. For more information, see "[About pull request reviews](#)." For information about the APIs to manage pull request reviews, see [the GraphQL API documentation](#) or "[Pull request reviews](#)" in the REST API documentation.

For activity related to pull request review comments, pull request comments, or pull request review threads, use the `pull_request_review_comment`, `issue_comment`, or `pull_request_review_thread` events instead.

To subscribe to this event, a GitHub App must have at least read-level access for the "Pull requests" repository permission.

Availability for pull_request_review

- Repositories
- Organizations
- GitHub Apps

Webhook payload object for pull_request_review

Action type: **dismissed** ▾

A review on a pull request was dismissed.

Webhook request body parameters

action string **Required**

Value: `dismissed`

enterprise object

An enterprise on GitHub. Webhook payloads contain the `enterprise` property when the webhook is configured on an enterprise account or an organization that's part of an enterprise account. For more information, see "[About enterprise accounts](#)."

installation object

The GitHub App installation. Webhook payloads contain the `installation` property when the event is configured for and sent to a GitHub App. For more information, see "[Using webhooks with GitHub Apps](#)."

organization object

A GitHub organization. Webhook payloads contain the `organization` property when the webhook is configured for an organization, or when the event occurs from activity in a repository owned by an organization.

pull_request object **Required**

► Properties of `pull_request`

repository object **Required**

The repository on GitHub where the event occurred. Webhook payloads contain the `repository` property when the event occurs from activity in a repository.

review object **Required**

The review that was affected.

► Properties of `review`

sender object **Required**

The GitHub user that triggered the event. This property is included in every webhook payload.

pull_request_review_thread

This event occurs when there is activity relating to a comment thread on a pull request. For more information, see "[About pull request reviews](#)." For information about the APIs to manage pull request reviews, see [the GraphQL API documentation](#) or "[Pull request review comments](#)" in the REST API documentation.

For activity related to pull request review comments, pull request comments, or pull request reviews, use the `pull_request_review_comment`, `issue_comment`, or `pull_request_review` events instead.

To subscribe to this event, a GitHub App must have at least read-level access for the "Pull requests" repository permission.

Availability for `pull_request_review_thread`

- Repositories
- Organizations
- GitHub Apps

Webhook payload object for `pull_request_review_thread`

Action type: **resolved** ▾

A comment thread on a pull request was marked as resolved.

Webhook request body parameters

action string **Required**

Value: `resolved`

enterprise object

An enterprise on GitHub. Webhook payloads contain the `enterprise` property when the webhook is configured on an enterprise account or an organization that's part of an enterprise account. For more information, see "[About enterprise accounts](#)."

installation object

The GitHub App installation. Webhook payloads contain the `installation` property when the event is configured for and sent to a GitHub App. For more information, see "[Using webhooks with GitHub Apps](#)."

organization object

A GitHub organization. Webhook payloads contain the `organization` property when the webhook is configured for an organization, or when the event occurs from activity in a repository owned by an organization.

pull_request object **Required**

► Properties of `pull_request`

repository object **Required**

The repository on GitHub where the event occurred. Webhook payloads contain the `repository` property when the event occurs from activity in a repository.

sender object

The GitHub user that triggered the event. This property is included in every webhook payload.

thread object **Required**

► Properties of `thread`

push

This event occurs when there is a push to a repository branch. This includes when a commit is pushed, when a commit tag is pushed, when a branch is deleted, when a tag is deleted, or when a repository is created from a template. To subscribe to only branch and tag deletions, use the [delete](#) webhook event.

To subscribe to this event, a GitHub App must have at least read-level access for the "Contents" repository permission.

Note: An event will not be created when more than three tags are pushed at once.

Availability for `push`

- Repositories
- Organizations
- GitHub Apps

Webhook payload object for `push`

Webhook request body parameters

after string **Required**

The SHA of the most recent commit on `ref` after the push.

base_ref string or null **Required**

before string **Required**

The SHA of the most recent commit on `ref` before the push.

commits array of objects **Required**

An array of commit objects describing the pushed commits. (Pushed commits are all commits that

are included in the `compare` between the `before` commit and the `after` commit.) The array includes a maximum of 20 commits. If necessary, you can use the [Commits API](#) to fetch additional commits. This limit is applied to timeline events only and isn't applied to webhook deliveries.

► Properties of `commits`

compare string **Required**

URL that shows the changes in this `ref` update, from the `before` commit to the `after` commit. For a newly created `ref` that is directly based on the default branch, this is the comparison between the head of the default branch and the `after` commit. Otherwise, this shows all commits until the `after` commit.

created boolean **Required**

Whether this push created the `ref`.

deleted boolean **Required**

Whether this push deleted the `ref`.

enterprise object

An enterprise on GitHub. Webhook payloads contain the `enterprise` property when the webhook is configured on an enterprise account or an organization that's part of an enterprise account. For more information, see "[About enterprise accounts](#)."

forced boolean **Required**

Whether this push was a force push of the `ref`.

head_commit object or null **Required**

► Properties of `head_commit`

installation object

The GitHub App installation. Webhook payloads contain the `installation` property when the event is configured for and sent to a GitHub App. For more information, see "[Using webhooks with GitHub Apps](#)."

organization object

A GitHub organization. Webhook payloads contain the `organization` property when the webhook is configured for an organization, or when the event occurs from activity in a repository owned by an organization.

pusher object **Required**

Metaproperties for Git author/committer information.

► Properties of `pusher`

ref string **Required**

The full git ref that was pushed. Example: `refs/heads/main` or `refs/tags/v3.14.1`.

repository object **Required**

A git repository

sender object

The GitHub user that triggered the event. This property is included in every webhook payload.

registry_package

This event occurs when there is activity relating to GitHub Packages. For more information, see "[Introduction to GitHub Packages](#)." For information about the APIs to manage GitHub Packages, see [the GraphQL API documentation](#) or "[Packages](#)" in the REST API documentation.

To install this event on a GitHub App, the app must have at least read-level access for the "Packages" repository permission.

Note: GitHub recommends that you use the newer `package` event instead.

Availability for registry_package

- Repositories
- Organizations
- GitHub Apps

Webhook payload object for registry_package

Action type: **published** ▾

A package was published to a registry.

Webhook request body parameters

action string **Required**

Value: `published`

enterprise object

An enterprise on GitHub. Webhook payloads contain the `enterprise` property when the webhook is configured on an enterprise account or an organization that's part of an enterprise account. For more information, see "[About enterprise accounts](#)."

installation object

The GitHub App installation. Webhook payloads contain the `installation` property when the event is configured for and sent to a GitHub App. For more information, see "[Using webhooks with GitHub Apps](#)."

organization object

A GitHub organization. Webhook payloads contain the `organization` property when the webhook is configured for an organization, or when the event occurs from activity in a repository owned by an organization.

registry_package object **Required**

► Properties of `registry_package`

repository object

The repository on GitHub where the event occurred. Webhook payloads contain the `repository` property when the event occurs from activity in a repository.

sender object **Required**

The GitHub user that triggered the event. This property is included in every webhook payload.

release

This event occurs when there is activity relating to releases. For more information, see "[About releases](#)." For information about the APIs to manage releases, see [the GraphQL API documentation](#) or "[Releases](#)" in the REST API documentation.

To subscribe to this event, a GitHub App must have at least read-level access for the "Contents" repository permission.

Availability for release

- Repositories
- Organizations
- GitHub Apps

Webhook payload object for release

Action type: **created** ▾

A draft was saved, or a release or pre-release was published without previously being saved as a draft.

Webhook request body parameters

action string **Required**

Value: `created`

enterprise object

An enterprise on GitHub. Webhook payloads contain the `enterprise` property when the webhook is configured on an enterprise account or an organization that's part of an enterprise account. For more information, see "[About enterprise accounts](#)."

installation object

The GitHub App installation. Webhook payloads contain the `installation` property when the event is configured for and sent to a GitHub App. For more information, see "[Using webhooks with GitHub Apps](#)."

organization object

A GitHub organization. Webhook payloads contain the `organization` property when the webhook is configured for an organization, or when the event occurs from activity in a repository owned by an organization.

release object **Required**

The [release](#) object.

► Properties of `release`

repository object **Required**

The repository on GitHub where the event occurred. Webhook payloads contain the `repository` property when the event occurs from activity in a repository.

sender object **Required**

The GitHub user that triggered the event. This property is included in every webhook payload.

repository

This event occurs when there is activity relating to repositories. For more information, see "[About repositories](#)." For information about the APIs to manage repositories, see [the GraphQL documentation](#) or "[Repositories](#)" in the REST API documentation.

To subscribe to this event, a GitHub App must have at least read-level access for the "Metadata" repository permission.

Availability for repository

- GitHub Apps
- Enterprises
- Organizations
- Repositories

Webhook payload object for repository

Action type: **anonymous_access_disabled** ▾

Someone disabled anonymous Git read access to the repository. For more information, see "[Enabling anonymous Git read access for a repository](#)."

Webhook request body parameters

action string **Required**

Value: `anonymous_access_disabled`

enterprise object

An enterprise on GitHub. Webhook payloads contain the `enterprise` property when the webhook is configured on an enterprise account or an organization that's part of an enterprise account. For more information, see "[About enterprise accounts](#)."

installation object

The GitHub App installation. Webhook payloads contain the `installation` property when the event is configured for and sent to a GitHub App. For more information, see "[Using webhooks with GitHub Apps](#)."

organization object

A GitHub organization. Webhook payloads contain the `organization` property when the webhook is configured for an organization, or when the event occurs from activity in a repository owned by an organization.

repository object

The repository on GitHub where the event occurred. Webhook payloads contain the `repository` property when the event occurs from activity in a repository.

sender object

The GitHub user that triggered the event. This property is included in every webhook payload.

repository_dispatch

This event occurs when a GitHub App sends a `POST` request to `/repos/{owner}/{repo}/dispatches` . For more information, see [the REST API documentation for creating a repository dispatch event](#).

To subscribe to this event, a GitHub App must have at least read-level access for the "Contents" repository permission.

Availability for repository_dispatch

- GitHub Apps

Webhook payload object for repository_dispatch

The `event_type` that was specified in the `POST /repos/{owner}/{repo}/dispatches` request body.

Webhook request body parameters

action string **Required**

Value: `sample.collected`

branch string **Required**

client_payload object or null **Required**

enterprise object

An enterprise on GitHub. Webhook payloads contain the `enterprise` property when the webhook is configured on an enterprise account or an organization that's part of an enterprise account. For more information, see "[About enterprise accounts](#)."

installation object **Required**

The GitHub App installation. Webhook payloads contain the `installation` property when the event is configured for and sent to a GitHub App. For more information, see "[Using webhooks with GitHub Apps](#)."

organization object

A GitHub organization. Webhook payloads contain the `organization` property when the webhook is configured for an organization, or when the event occurs from activity in a repository owned by an organization.

repository object **Required**

The repository on GitHub where the event occurred. Webhook payloads contain the `repository` property when the event occurs from activity in a repository.

sender object **Required**

The GitHub user that triggered the event. This property is included in every webhook payload.

repository_vulnerability_alert

This event occurs when there is activity relating to a security vulnerability alert in a repository.

Note: This event is deprecated. Use the `dependabot_alert` event instead.

Availability for repository_vulnerability_alert

- Repositories
- Organizations

Webhook payload object for repository_vulnerability_alert

Action type: **create** ▾

A repository vulnerability alert was created.

Webhook request body parameters

action string **Required**

Value: `create`

alert object **Required**

► Properties of `alert`

enterprise object

An enterprise on GitHub. Webhook payloads contain the `enterprise` property when the webhook is configured on an enterprise account or an organization that's part of an enterprise account. For more information, see "[About enterprise accounts](#)."

installation object

The GitHub App installation. Webhook payloads contain the `installation` property when the event is configured for and sent to a GitHub App. For more information, see "[Using webhooks with GitHub Apps](#)."

organization object

A GitHub organization. Webhook payloads contain the `organization` property when the webhook is configured for an organization, or when the event occurs from activity in a repository owned by an organization.

repository object **Required**

The repository on GitHub where the event occurred. Webhook payloads contain the `repository` property when the event occurs from activity in a repository.

sender object **Required**

The GitHub user that triggered the event. This property is included in every webhook payload.

secret_scanning_alert

This event occurs when there is activity relating to a secret scanning alert. For more information about secret scanning, see "[About secret scanning](#)." For information about the API to manage secret scanning alerts, see "[Secret scanning](#)" in the REST API documentation.

For activity relating to secret scanning alert locations, use the `secret_scanning_alert_location` event.

To subscribe to this event, a GitHub App must have at least read-level access for the "Secret scanning alerts" repository permission.

Availability for secret_scanning_alert

- Repositories
- Organizations
- GitHub Apps

Webhook payload object for `secret_scanning_alert`

Action type: `created` ▾

A secret scanning alert was created.

Webhook request body parameters

action string **Required**

Value: `created`

alert object **Required**

► Properties of `alert`

enterprise object

An enterprise on GitHub. Webhook payloads contain the `enterprise` property when the webhook is configured on an enterprise account or an organization that's part of an enterprise account. For more information, see "[About enterprise accounts](#)."

installation object

The GitHub App installation. Webhook payloads contain the `installation` property when the event is configured for and sent to a GitHub App. For more information, see "[Using webhooks with GitHub Apps](#)."

organization object

A GitHub organization. Webhook payloads contain the `organization` property when the webhook is configured for an organization, or when the event occurs from activity in a repository owned by an organization.

repository object **Required**

The repository on GitHub where the event occurred. Webhook payloads contain the `repository` property when the event occurs from activity in a repository.

sender object

The GitHub user that triggered the event. This property is included in every webhook payload.

`secret_scanning_alert_location` 🔗

This event occurs when there is activity relating to the locations of a secret in a secret scanning alert.

For more information about secret scanning, see "[About secret scanning](#)." For information about the API to manage secret scanning alerts, see "[Secret scanning](#)" in the REST API documentation.

For activity relating to secret scanning alerts, use the `secret_scanning_alert` event.

To subscribe to this event, a GitHub App must have at least read-level access for the "Secret scanning alerts" repository permission.

Availability for `secret_scanning_alert_location`

- Repositories
- Organizations
- GitHub Apps

Webhook payload object for `secret_scanning_alert_location`

A new instance of a previously detected secret was detected in a repository, and the location of the secret was added to the existing alert.

Webhook request body parameters

action string

Value: `created`

alert object **Required**

► Properties of `alert`

installation object

The GitHub App installation. Webhook payloads contain the `installation` property when the event is configured for and sent to a GitHub App. For more information, see "[Using webhooks with GitHub Apps](#)."

location object **Required**

► Properties of `location`

organization object

A GitHub organization. Webhook payloads contain the `organization` property when the webhook is configured for an organization, or when the event occurs from activity in a repository owned by an organization.

repository object **Required**

The repository on GitHub where the event occurred. Webhook payloads contain the `repository` property when the event occurs from activity in a repository.

sender object **Required**

The GitHub user that triggered the event. This property is included in every webhook payload.

security_advisory

This event occurs when there is activity relating to a security advisory that was reviewed by GitHub. A GitHub-reviewed security advisory provides information about security-related vulnerabilities in software on GitHub. For more information about security advisories, see "[About GitHub Security Advisories for repositories](#)." For information about the API to manage security advisories, see [the GraphQL documentation](#).

GitHub Dependabot alerts are also powered by the security advisory dataset. For more information, see "[About Dependabot alerts](#)."

Availability for `security_advisory`

- GitHub Apps

Webhook payload object for `security_advisory`

Action type: **published** ▾

A security advisory was published to the GitHub community.

Webhook request body parameters

action string **Required**

Value: `published`

enterprise object

An enterprise on GitHub. Webhook payloads contain the `enterprise` property when the webhook is configured on an enterprise account or an organization that's part of an enterprise account. For more information, see "[About enterprise accounts](#)."

installation object

The GitHub App installation. Webhook payloads contain the `installation` property when the event is configured for and sent to a GitHub App. For more information, see "[Using webhooks with GitHub Apps](#)."

organization object

A GitHub organization. Webhook payloads contain the `organization` property when the webhook is configured for an organization, or when the event occurs from activity in a repository owned by an organization.

repository object

The repository on GitHub where the event occurred. Webhook payloads contain the `repository` property when the event occurs from activity in a repository.

security_advisory object **Required**

The details of the security advisory, including summary, description, and severity.

► Properties of `security_advisory`

sender object

The GitHub user that triggered the event. This property is included in every webhook payload.

security_and_analysis

This event occurs when code security and analysis features are enabled or disabled for a repository. For more information, see "[GitHub security features](#)."

To subscribe to this event, a GitHub App must have at least read-level access for the "Administration" repository permission.

Availability for `security_and_analysis`

- Repositories

- Organizations
- GitHub Apps

Webhook payload object for security_and_analysis

Webhook request body parameters

changes object **Required**

► Properties of changes

enterprise object

An enterprise on GitHub. Webhook payloads contain the `enterprise` property when the webhook is configured on an enterprise account or an organization that's part of an enterprise account. For more information, see "[About enterprise accounts](#)."

installation object

The GitHub App installation. Webhook payloads contain the `installation` property when the event is configured for and sent to a GitHub App. For more information, see "[Using webhooks with GitHub Apps](#)."

organization object

A GitHub organization. Webhook payloads contain the `organization` property when the webhook is configured for an organization, or when the event occurs from activity in a repository owned by an organization.

repository object **Required**

Full Repository

sender object

The GitHub user that triggered the event. This property is included in every webhook payload.

sponsorship

This event occurs when there is activity relating to a sponsorship listing. For more information, see "[About GitHub Sponsors](#)." For information about the API to manage sponsors, see [the GraphQL documentation](#).

You can only create a sponsorship webhook on GitHub.com. For more information, see "[Configuring webhooks for events in your sponsored account](#)."

Availability for sponsorship

- Sponsored accounts

Webhook payload object for sponsorship

Action type: **cancelled** ▼

A sponsorship was cancelled and the last billing cycle has ended.

This event is only sent when a recurring (monthly) sponsorship is cancelled; it is not sent for one-time sponsorships.

Webhook request body parameters

action string **Required**

Value: cancelled

enterprise object

An enterprise on GitHub. Webhook payloads contain the **enterprise** property when the webhook is configured on an enterprise account or an organization that's part of an enterprise account. For more information, see "[About enterprise accounts](#)."

installation object

The GitHub App installation. Webhook payloads contain the **installation** property when the event is configured for and sent to a GitHub App. For more information, see "[Using webhooks with GitHub Apps](#)."

organization object

A GitHub organization. Webhook payloads contain the **organization** property when the webhook is configured for an organization, or when the event occurs from activity in a repository owned by an organization.

repository object

The repository on GitHub where the event occurred. Webhook payloads contain the **repository** property when the event occurs from activity in a repository.

sender object **Required**

The GitHub user that triggered the event. This property is included in every webhook payload.

sponsorship object **Required**

► Properties of **sponsorship**

star

This event occurs when there is activity relating to repository stars. For more information about stars, see "[Saving repositories with stars](#)." For information about the APIs to manage stars, see [the GraphQL documentation](#) or "[Starring](#)" in the REST API documentation.

To subscribe to this event, a GitHub App must have at least read-level access for the "Metadata" repository permission.

Availability for **star**

- Repositories
- Organizations
- GitHub Apps

Webhook payload object for **star**

Action type: **created** ▾

Someone starred a repository.

Webhook request body parameters

action string **Required**

Value: `created`

enterprise object

An enterprise on GitHub. Webhook payloads contain the `enterprise` property when the webhook is configured on an enterprise account or an organization that's part of an enterprise account. For more information, see "[About enterprise accounts](#)."

installation object

The GitHub App installation. Webhook payloads contain the `installation` property when the event is configured for and sent to a GitHub App. For more information, see "[Using webhooks with GitHub Apps](#)."

organization object

A GitHub organization. Webhook payloads contain the `organization` property when the webhook is configured for an organization, or when the event occurs from activity in a repository owned by an organization.

repository object **Required**

The repository on GitHub where the event occurred. Webhook payloads contain the `repository` property when the event occurs from activity in a repository.

sender object **Required**

The GitHub user that triggered the event. This property is included in every webhook payload.

starred_at string or null **Required**

The time the star was created. This is a timestamp in ISO 8601 format: `YYYY-MM-DDTHH:MM:SSZ` . Will be `null` for the `deleted` action.

status

This event occurs when the status of a Git commit changes. For example, commits can be marked as `error` , `failure` , `pending` , or `success` . For more information, see "[About status checks](#)." For information about the APIs to manage commit statuses, see [the GraphQL documentation](#) or "[Commit statuses](#)" in the REST API documentation.

To subscribe to this event, a GitHub App must have at least read-level access for the "Commit statuses" repository permission.

Availability for `status`

- Repositories
- Organizations
- GitHub Apps

Webhook payload object for `status`

Webhook request body parameters

avatar_url string or null

branches array of objects **Required**

An array of branch objects containing the status' SHA. Each branch contains the given SHA, but the SHA may or may not be the head of the branch. The array includes a maximum of 10 branches.

► Properties of **branches**

commit object **Required**

► Properties of **commit**

context string **Required**

created_at string **Required**

description string or null **Required**

The optional human-readable description added to the status.

enterprise object

An enterprise on GitHub. Webhook payloads contain the **enterprise** property when the webhook is configured on an enterprise account or an organization that's part of an enterprise account. For more information, see "[About enterprise accounts](#)."

id integer **Required**

The unique identifier of the status.

installation object

The GitHub App installation. Webhook payloads contain the **installation** property when the event is configured for and sent to a GitHub App. For more information, see "[Using webhooks with GitHub Apps](#)."

name string **Required**

organization object

A GitHub organization. Webhook payloads contain the **organization** property when the webhook is configured for an organization, or when the event occurs from activity in a repository owned by an organization.

repository object **Required**

The repository on GitHub where the event occurred. Webhook payloads contain the **repository** property when the event occurs from activity in a repository.

sender object **Required**

The GitHub user that triggered the event. This property is included in every webhook payload.

sha string **Required**

The Commit SHA.

state string **Required**

The new state. Can be **pending**, **success**, **failure**, or **error**.

Can be one of: **pending**, **success**, **failure**, **error**

target_url string or null **Required**

The optional link added to the status.

updated_at string **Required**

team_add

This event occurs when a team is added to a repository. For more information, see "[Managing teams and people with access to your repository](#)."

For activity relating to teams, see the `teams` event.

To subscribe to this event, a GitHub App must have at least read-level access for the "Members" organization permission.

Availability for `team_add`

- Repositories
- Organizations
- GitHub Apps

Webhook payload object for `team_add`

Webhook request body parameters

enterprise object

An enterprise on GitHub. Webhook payloads contain the `enterprise` property when the webhook is configured on an enterprise account or an organization that's part of an enterprise account. For more information, see "[About enterprise accounts](#)."

installation object

The GitHub App installation. Webhook payloads contain the `installation` property when the event is configured for and sent to a GitHub App. For more information, see "[Using webhooks with GitHub Apps](#)."

organization object

A GitHub organization. Webhook payloads contain the `organization` property when the webhook is configured for an organization, or when the event occurs from activity in a repository owned by an organization.

repository object **Required**

The repository on GitHub where the event occurred. Webhook payloads contain the `repository` property when the event occurs from activity in a repository.

sender object **Required**

The GitHub user that triggered the event. This property is included in every webhook payload.

team object **Required**

Groups of organization members that gives permissions on specified repositories.

► Properties of `team`

team

This event occurs when there is activity relating to teams in an organization. For more information, see "[About teams](#)."

To subscribe to this event, a GitHub App must have at least read-level access for the "Members" organization permission.

Availability for team

- Organizations
- Enterprises
- GitHub Apps

Webhook payload object for team

Action type: **added_to_repository** ▾

A team was granted access to a repository.

Webhook request body parameters

action string **Required**

Value: `added_to_repository`

enterprise object

An enterprise on GitHub. Webhook payloads contain the `enterprise` property when the webhook is configured on an enterprise account or an organization that's part of an enterprise account. For more information, see "[About enterprise accounts](#)."

installation object

The GitHub App installation. Webhook payloads contain the `installation` property when the event is configured for and sent to a GitHub App. For more information, see "[Using webhooks with GitHub Apps](#)."

organization object **Required**

A GitHub organization. Webhook payloads contain the `organization` property when the webhook is configured for an organization, or when the event occurs from activity in a repository owned by an organization.

repository object

A git repository

sender object

The GitHub user that triggered the event. This property is included in every webhook payload.

team object **Required**

Groups of organization members that gives permissions on specified repositories.

► Properties of `team`

user

This event occurs when there is activity relating to user accounts in an enterprise.

Availability for user

- Enterprises

Webhook payload object for user

Action type: **created** ▾

A user account was added to the enterprise.

Webhook request body parameters

action string **Required**

Value: `created`

enterprise object

An enterprise on GitHub. Webhook payloads contain the `enterprise` property when the webhook is configured on an enterprise account or an organization that's part of an enterprise account. For more information, see "[About enterprise accounts](#)."

installation object

The GitHub App installation. Webhook payloads contain the `installation` property when the event is configured for and sent to a GitHub App. For more information, see "[Using webhooks with GitHub Apps](#)."

organization object

A GitHub organization. Webhook payloads contain the `organization` property when the webhook is configured for an organization, or when the event occurs from activity in a repository owned by an organization.

repository object

The repository on GitHub where the event occurred. Webhook payloads contain the `repository` property when the event occurs from activity in a repository.

sender object

The GitHub user that triggered the event. This property is included in every webhook payload.

user object or null

► Properties of `user`

watch

This event occurs when there is activity relating to watching, or subscribing to, a repository. For more information about watching, see "[Managing your subscriptions](#)." For information about the APIs to manage watching, see "[Watching](#)" in the REST API documentation.

To subscribe to this event, a GitHub App must have at least read-level access for the "Metadata" repository permission.

Availability for watch

- Repositories

- Organizations
- GitHub Apps

Webhook payload object for watch

Someone started watching the repository.

Webhook request body parameters

action string **Required**

Value: started

enterprise object

An enterprise on GitHub. Webhook payloads contain the `enterprise` property when the webhook is configured on an enterprise account or an organization that's part of an enterprise account. For more information, see "[About enterprise accounts](#)."

installation object

The GitHub App installation. Webhook payloads contain the `installation` property when the event is configured for and sent to a GitHub App. For more information, see "[Using webhooks with GitHub Apps](#)."

organization object

A GitHub organization. Webhook payloads contain the `organization` property when the webhook is configured for an organization, or when the event occurs from activity in a repository owned by an organization.

repository object **Required**

The repository on GitHub where the event occurred. Webhook payloads contain the `repository` property when the event occurs from activity in a repository.

sender object **Required**

The GitHub user that triggered the event. This property is included in every webhook payload.

workflow_dispatch

This event occurs when a GitHub Actions workflow is manually triggered. For more information, see "[Manually running a workflow](#)."

For activity relating to workflow runs, use the `workflow_run` event.

To subscribe to this event, a GitHub App must have at least read-level access for the "Contents" repository permission.

Availability for workflow_dispatch

- GitHub Apps

Webhook payload object for workflow_dispatch

Webhook request body parameters

enterprise object

An enterprise on GitHub. Webhook payloads contain the `enterprise` property when the webhook is

An enterprise on GitHub. Webhook payloads contain the `enterprise` property when the webhook is configured on an enterprise account or an organization that's part of an enterprise account. For more information, see "[About enterprise accounts](#)."

inputs object or null **Required**

installation object

The GitHub App installation. Webhook payloads contain the `installation` property when the event is configured for and sent to a GitHub App. For more information, see "[Using webhooks with GitHub Apps](#)."

organization object

A GitHub organization. Webhook payloads contain the `organization` property when the webhook is configured for an organization, or when the event occurs from activity in a repository owned by an organization.

ref string **Required**

repository object **Required**

The repository on GitHub where the event occurred. Webhook payloads contain the `repository` property when the event occurs from activity in a repository.

sender object **Required**

The GitHub user that triggered the event. This property is included in every webhook payload.

workflow string **Required**

workflow_job

This event occurs when there is activity relating to a job in a GitHub Actions workflow. For more information, see "[Using jobs in a workflow](#)." For information about the API to manage workflow jobs, see "[Workflow jobs](#)" in the REST API documentation.

For activity relating to a workflow run instead of a job in a workflow run, use the `workflow_run` event.

To subscribe to this event, a GitHub App must have at least read-level access for the "Actions" repository permission.

Availability for workflow_job

- Enterprises
- Repositories
- Organizations
- GitHub Apps

Webhook payload object for workflow_job

Action type: **completed** ▾

A job in a workflow run finished. This event occurs when a job in a workflow is completed, regardless of whether the job was successful or unsuccessful.

Webhook request body parameters

action string **Required**

Value: `completed`

enterprise object

An enterprise on GitHub. Webhook payloads contain the `enterprise` property when the webhook is configured on an enterprise account or an organization that's part of an enterprise account. For more information, see "[About enterprise accounts](#)."

installation object

The GitHub App installation. Webhook payloads contain the `installation` property when the event is configured for and sent to a GitHub App. For more information, see "[Using webhooks with GitHub Apps](#)."

organization object

A GitHub organization. Webhook payloads contain the `organization` property when the webhook is configured for an organization, or when the event occurs from activity in a repository owned by an organization.

repository object **Required**

The repository on GitHub where the event occurred. Webhook payloads contain the `repository` property when the event occurs from activity in a repository.

sender object **Required**

The GitHub user that triggered the event. This property is included in every webhook payload.

workflow_job object **Required**

► Properties of `workflow_job`

deployment object

A request for a specific ref(branch,sha,tag) to be deployed

► Properties of `deployment`

workflow_run

This event occurs when there is activity relating to a run of a GitHub Actions workflow. For more information, see "[About workflows](#)." For information about the APIs to manage workflow runs, see [the GraphQL documentation](#) or "[Workflow runs](#)" in the REST API documentation.

For activity relating to a job in a workflow run, use the `workflow_job` event.

To subscribe to this event, a GitHub App must have at least read-level access for the "Actions" repository permission.

Availability for `workflow_run`

- Enterprises
- Repositories
- Organizations
- GitHub Apps

Webhook payload object for workflow_run

Action type: **completed** ▾

A workflow run finished. This event occurs when a workflow run is completed, regardless of whether the workflow was successful or unsuccessful.

Webhook request body parameters

action string **Required**

Value: `completed`

enterprise object

An enterprise on GitHub. Webhook payloads contain the `enterprise` property when the webhook is configured on an enterprise account or an organization that's part of an enterprise account. For more information, see "[About enterprise accounts](#)."

installation object

The GitHub App installation. Webhook payloads contain the `installation` property when the event is configured for and sent to a GitHub App. For more information, see "[Using webhooks with GitHub Apps](#)."

organization object

A GitHub organization. Webhook payloads contain the `organization` property when the webhook is configured for an organization, or when the event occurs from activity in a repository owned by an organization.

repository object **Required**

The repository on GitHub where the event occurred. Webhook payloads contain the `repository` property when the event occurs from activity in a repository.

sender object **Required**

The GitHub user that triggered the event. This property is included in every webhook payload.

workflow object or null **Required**

► Properties of `workflow`

workflow_run object **Required**

► Properties of `workflow_run`

Legal