> The REST API is now versioned. For more information, see "About API versioning."

Review requests

Use the REST API to interact with review requests.

About review requests 🔗

Pull request authors and repository owners and collaborators can request a pull request review from anyone with write access to the repository. Each requested reviewer will receive a notification asking them to review the pull request.

Get all requested reviewers for a pull request 🔗

✓ Works with GitHub Apps

Gets the users or teams whose review is requested for a pull request. Once a requested reviewer submits a review, they are no longer considered a requested reviewer. Their review will instead be returned by the List reviews for a pull request operation.

Parameters for "Get all requested reviewers for a pull request"

Headers

`accept`   string

Setting to `application/vnd.github+json` is recommended.

Path parameters

`owner`   string   Required

The account owner of the repository. The name is not case sensitive.

`repo`   string   Required

The name of the repository without the `.git` extension. The name is not case sensitive.

`pull_number`   integer   Required

The number that identifies the pull request.

HTTP response status codes for "Get all requested reviewers for a pull request"

Status code	Description
`200`	OK

Code samples for "Get all requested reviewers for a pull request"

GET `/repos/{owner}/{repo}/pulls/{pull_number}/requested_reviewers`

cURL	JavaScript	GitHub CLI	

```
curl -L \ -H "Accept: application/vnd.github+json" \ -H "Authorization: Bearer <YOUR-TOKEN>" \ -H "X-GitHub-Api-Version: 2022-11-28"
\ http(s)://HOSTNAME/api/v3/repos/OWNER/REPO/pulls/PULL_NUMBER/requested_reviewers
```

Response

Example response	Response schema

Status: 200

{ "users": [{ "login": "octocat", "id": 1, "node_id": "MDQ6VXNlcjE=", "avatar_url": "https://github.com/images/error/octocat_happy.gif", "gravatar_id": "", "url": "https://HOSTNAME/users/octocat", "html_url": "https://github.com/octocat", "followers_url": "https://HOSTNAME/users/octocat/followers", "following_url": "https://HOSTNAME/users/octocat/following{/other_user}", "gists_url": "https://HOSTNAME/users/octocat/gists{/gist_id}", "starred_url": "https://HOSTNAME/users/octocat/starred{/owner}{/repo}", "subscriptions_url": "https://HOSTNAME/users/octocat/subscriptions", "organizations_url": "https://HOSTNAME/users/octocat/orgs", "repos_url":

Request reviewers for a pull request 🔗

✅ Works with [GitHub Apps](#)

Requests reviews for a pull request from a given set of users and/or teams. This endpoint triggers [notifications](#). Creating content too quickly using this endpoint may result in secondary rate limiting. See "[Secondary rate limits](#)" and "[Dealing with secondary rate limits](#)" for details.

Parameters for "Request reviewers for a pull request"

Headers

accept string

Setting to `application/vnd.github+json` is recommended.

Path parameters

owner string   Required

The account owner of the repository. The name is not case sensitive.

repo string   Required

The name of the repository without the `.git` extension. The name is not case sensitive.

pull_number integer   Required

The number that identifies the pull request.

Body parameters

`reviewers` array of strings

An array of user `login` s that will be requested.

`team_reviewers` array of strings

An array of team `slug` s that will be requested.

HTTP response status codes for "Request reviewers for a pull request"

Status code	Description
`201`	Created
`403`	Forbidden
`422`	Unprocessable Entity if user is not a collaborator

Code samples for "Request reviewers for a pull request"

POST `/repos/{owner}/{repo}/pulls/{pull_number}/requested_reviewers`

| cURL | JavaScript | GitHub CLI |

```
curl -L \ -X POST \ -H "Accept: application/vnd.github+json" \ -H "Authorization: Bearer <YOUR-TOKEN>" \ -H "X-GitHub-Api-Version:
2022-11-28" \ http(s)://HOSTNAME/api/v3/repos/OWNER/REPO/pulls/PULL_NUMBER/requested_reviewers \ -d '{"reviewers":
["octocat","hubot","other_user"],"team_reviewers":["justice-league"]}'
```

Response

| Example response | Response schema |

Status: 201

```
{ "url": "https://HOSTNAME/repos/octocat/Hello-World/pulls/1347", "id": 1, "node_id": "MDExOlB1bGxSZXF1ZXN0MQ==", "html_url":
"https://github.com/octocat/Hello-World/pull/1347", "diff_url": "https://github.com/octocat/Hello-World/pull/1347.diff",
"patch_url": "https://github.com/octocat/Hello-World/pull/1347.patch", "issue_url": "https://HOSTNAME/repos/octocat/Hello-
World/issues/1347", "commits_url": "https://HOSTNAME/repos/octocat/Hello-World/pulls/1347/commits", "review_comments_url":
"https://HOSTNAME/repos/octocat/Hello-World/pulls/1347/comments", "review_comment_url": "https://HOSTNAME/repos/octocat/Hello-
World/pulls/comments{/number}", "comments_url": "https://HOSTNAME/repos/octocat/Hello-World/issues/1347/comments", "statuses_url":
```

Remove requested reviewers from a pull request 🔗

✅ Works with [GitHub Apps](#)

Removes review requests from a pull request for a given set of users and/or teams.

Parameters for "Remove requested reviewers from a pull request"

Headers

accept string

Setting to `application/vnd.github+json` is recommended.

Path parameters

owner string   Required

The account owner of the repository. The name is not case sensitive.

repo string   Required

The name of the repository without the `.git` extension. The name is not case sensitive.

pull_number integer   Required

The number that identifies the pull request.

Body parameters

reviewers array of strings   Required

An array of user `login` s that will be removed.

team_reviewers array of strings

An array of team `slug` s that will be removed.

HTTP response status codes for "Remove requested reviewers from a pull request"

Status code	Description
200	OK
422	Validation failed, or the endpoint has been spammed.

Code samples for "Remove requested reviewers from a pull request"

DELETE /repos/{owner}/{repo}/pulls/{pull_number}/requested_reviewers

cURL   JavaScript   GitHub CLI

```
curl -L \ -X DELETE \ -H "Accept: application/vnd.github+json" \ -H "Authorization: Bearer <YOUR-TOKEN>" \ -H "X-GitHub-Api-Version:
2022-11-28" \ http(s)://HOSTNAME/api/v3/repos/OWNER/REPO/pulls/PULL_NUMBER/requested_reviewers \ -d '{"reviewers":
["octocat","hubot","other_user"],"team_reviewers":["justice-league"]}'
```

Response

Example response   Response schema

Status: 200

```
{ "url": "https://HOSTNAME/repos/octocat/Hello-World/pulls/1347", "id": 1, "node_id": "MDExOlB1bGxSZXF1ZXN0MQ==", "html_url":
"https://github.com/octocat/Hello-World/pull/1347", "diff_url": "https://github.com/octocat/Hello-World/pull/1347.diff",
"patch_url": "https://github.com/octocat/Hello-World/pull/1347.patch", "issue_url": "https://HOSTNAME/repos/octocat/Hello-
World/issues/1347", "commits_url": "https://HOSTNAME/repos/octocat/Hello-World/pulls/1347/commits", "review_comments_url":
"https://HOSTNAME/repos/octocat/Hello-World/pulls/1347/comments", "review_comment_url": "https://HOSTNAME/repos/octocat/Hello-
World/pulls/comments{/number}", "comments_url": "https://HOSTNAME/repos/octocat/Hello-World/issues/1347/comments", "statuses_url":
```

world/pulls/comments{/number}", "comments_url": "https://HOSTNAME/repos/octocat/Hello-World/issues/1347/comments", "statuses_url

Legal

© 2023 GitHub, Inc.   [Terms](#)   [Privacy](#)   [Status](#)   [Pricing](#)   [Expert services](#)   [Blog](#)