

The REST API is now versioned. For more information, see "[About API versioning](#)."

Team discussion comments

Use the REST API to get, create, edit, and delete discussion comments on a [team discussion](#) post.

The team discussions and team discussion comments endpoints will be deprecated on 2023-11-28 in favor of GitHub Discussions. For more information about GitHub Discussions, see "[GitHub Discussions documentation](#)."

List discussion comments

✔ Works with [GitHub Apps](#)

List all comments on a team discussion. OAuth access tokens require the `read:discussion` [scope](#).

Note: You can also specify a team by `org_id` and `team_id` using the route `GET /organizations/{org_id}/team/{team_id}/discussions/{discussion_number}/comments`.

Parameters for "List discussion comments"

Headers

`accept` string

Setting to `application/vnd.github+json` is recommended.

Path parameters

`org` string **Required**

The organization name. The name is not case sensitive.

`team_slug` string **Required**

The slug of the team name.

`discussion_number` integer **Required**

The number that identifies the discussion.

Query parameters

`direction` string

The direction to sort the results by.

Default: `desc`

Can be one of: `asc`, `desc`

per_page integer

The number of results per page (max 100).

Default: 30

page integer

Page number of the results to fetch.

Default: 1

HTTP response status codes for "List discussion comments"

Status code	Description
200	OK

Code samples for "List discussion comments"

GET /orgs/{org}/teams/{team_slug}/discussions/{discussion_number}/comments

cURL

JavaScript

GitHub CLI

```
curl -L \ -H "Accept: application/vnd.github+json" \ -H "Authorization: Bearer <YOUR-TOKEN>" \ -H "X-GitHub-API-Version: 2022-11-28" \ https://api.github.com/orgs/ORG/teams/TEAM_SLUG/discussions/DISCUSSION_NUMBER/comments
```

Response

Example response

Response schema

Status: 200

```
[ { "author": { "login": "octocat", "id": 1, "node_id": "MDQ6VXNlcjE=", "avatar_url": "https://github.com/images/error/octocat_happy.gif", "gravatar_id": "", "url": "https://api.github.com/users/octocat", "html_url": "https://github.com/octocat", "followers_url": "https://api.github.com/users/octocat/followers", "following_url": "https://api.github.com/users/octocat/following{/other_user}", "gists_url": "https://api.github.com/users/octocat/gists{/gist_id}", "starred_url": "https://api.github.com/users/octocat/starred{/owner}/{repo}", "subscriptions_url": "https://api.github.com/users/octocat/subscriptions", "organizations_url": "https://api.github.com/users/octocat/orgs",
```

Create a discussion comment

Works with [GitHub Apps](#)

Creates a new comment on a team discussion. OAuth access tokens require the `write:discussion` [scope](#).

This endpoint triggers [notifications](#). Creating content too quickly using this endpoint may result in secondary rate limiting. See "[Secondary rate limits](#)" and "[Dealing with secondary rate limits](#)" for details.

Note: You can also specify a team by `org_id` and `team_id` using the route `POST /organizations/{org_id}/team/{team_id}/discussions/{discussion_number}/comments`.

Parameters for "Create a discussion comment"

Headers

accept string

Setting to `application/vnd.github+json` is recommended.

Path parameters

org string **Required**

The organization name. The name is not case sensitive.

team_slug string **Required**

The slug of the team name.

discussion_number integer **Required**

The number that identifies the discussion.

Body parameters

body string **Required**

The discussion comment's body text.

HTTP response status codes for "Create a discussion comment"

Status code	Description
201	Created

Code samples for "Create a discussion comment"

POST /orgs/{org}/teams/{team_slug}/discussions/{discussion_number}/comments

cURL

JavaScript

GitHub CLI

```
curl -L \ -X POST \ -H "Accept: application/vnd.github+json" \ -H "Authorization: Bearer <YOUR-TOKEN>" \ -H "X-GitHub-API-Version: 2022-11-28" \ https://api.github.com/orgs/ORG/teams/TEAM_SLUG/discussions/DISCUSSION_NUMBER/comments \ -d '{"body":"Do you like apples?"}'
```

Response

Example response

Response schema

Status: 201

```
{ "author": { "login": "octocat", "id": 1, "node_id": "MDQ6VXNlcjE=", "avatar_url": "https://github.com/images/error/octocat_happy.gif", "gravatar_id": "", "url": "https://api.github.com/users/octocat", "html_url": "https://github.com/octocat", "followers_url": "https://api.github.com/users/octocat/followers", "following_url": "https://api.github.com/users/octocat/following{/other_user}", "gists_url": "https://api.github.com/users/octocat/gists{/gist_id}", "starred_url": "https://api.github.com/users/octocat/starred{/owner}/{/repo}", "subscriptions_url": "https://api.github.com/users/octocat/subscriptions", "organizations_url": "https://api.github.com/users/octocat/orgs",
```

Get a discussion comment

✔ Works with [GitHub Apps](#)

Get a specific comment on a team discussion. OAuth access tokens require the `read:discussion` [scope](#).

Note: You can also specify a team by `org_id` and `team_id` using the route `GET /organizations/{org_id}/team/{team_id}/discussions/{discussion_number}/comments/{comment_number}`.

Parameters for "Get a discussion comment"

Headers

accept string
Setting to `application/vnd.github+json` is recommended.

Path parameters

org string **Required**
The organization name. The name is not case sensitive.

team_slug string **Required**
The slug of the team name.

discussion_number integer **Required**
The number that identifies the discussion.

comment_number integer **Required**
The number that identifies the comment.

HTTP response status codes for "Get a discussion comment"

Status code	Description
200	OK

Code samples for "Get a discussion comment"

GET `/orgs/{org}/teams/{team_slug}/discussions/{discussion_number}/comments/{comment_number}`

cURLJavaScriptGitHub CLI

```
curl -L \ -H "Accept: application/vnd.github+json" \ -H "Authorization: Bearer <YOUR-TOKEN>" \ -H "X-GitHub-API-Version: 2022-11-28" \ https://api.github.com/orgs/ORG/teams/TEAM_SLUG/discussions/DISCUSSION_NUMBER/comments/COMMENT_NUMBER
```

Response

Example response	Response schema
Status: 200	
<pre>{ "author": { "login": "octocat", "id": 1, "node_id": "MDQ6VXNlcjE=", "avatar_url": "https://github.com/images/error/octocat_happy.gif", "gravatar_id": "", "url": "https://api.github.com/users/octocat", "html_url": "https://github.com/octocat", "followers_url": "https://api.github.com/users/octocat/followers", "following_url": "https://api.github.com/users/octocat/following{/other_user}", "gists_url": "https://api.github.com/users/octocat/gists{/gist_id}", "starred_url": "https://api.github.com/users/octocat/starred{/owner}/{repo}", "subscriptions_url": "https://api.github.com/users/octocat/subscriptions", "organizations_url": "https://api.github.com/users/octocat/orgs",</pre>	

Update a discussion comment

✔ Works with [GitHub Apps](#)

Edits the body text of a discussion comment. OAuth access tokens require the `write:discussion` [scope](#).

Note: You can also specify a team by `org_id` and `team_id` using the route `PATCH /organizations/{org_id}/team/{team_id}/discussions/{discussion_number}/comments/{comment_number}`.

Parameters for "Update a discussion comment"

Headers

accept string
Setting to `application/vnd.github+json` is recommended.

Path parameters

org string **Required**
The organization name. The name is not case sensitive.

team_slug string **Required**
The slug of the team name.

discussion_number integer **Required**
The number that identifies the discussion.

comment_number integer **Required**
The number that identifies the comment.

Body parameters

body string **Required**
The discussion comment's body text.

HTTP response status codes for "Update a discussion comment"

Status code	Description
200	OK

Code samples for "Update a discussion comment"

PATCH

/orgs/{org}/teams/{team_slug}/discussions/{discussion_number}/comments/{comment_number}

cURL

JavaScript

GitHub CLI

```
curl -L \ -X PATCH \ -H "Accept: application/vnd.github+json" \ -H "Authorization: Bearer <YOUR-TOKEN>" \ -H "X-GitHub-API-Version: 2022-11-28" \ https://api.github.com/orgs/ORG/teams/TEAM_SLUG/discussions/DISCUSSION_NUMBER/comments/COMMENT_NUMBER \ -d '{"body":"Do you like pineapples?"}'
```

Response

Example response

Response schema

Status: 200

```
{ "author": { "login": "octocat", "id": 1, "node_id": "MDQ6VXNlcjE=", "avatar_url": "https://github.com/images/error/octocat_happy.gif", "gravatar_id": "", "url": "https://api.github.com/users/octocat", "html_url": "https://github.com/octocat", "followers_url": "https://api.github.com/users/octocat/followers", "following_url": "https://api.github.com/users/octocat/following{/other_user}", "gists_url": "https://api.github.com/users/octocat/gists{/gist_id}", "starred_url": "https://api.github.com/users/octocat/starred{/owner}/{repo}", "subscriptions_url": "https://api.github.com/users/octocat/subscriptions", "organizations_url": "https://api.github.com/users/octocat/orgs",
```

Delete a discussion comment

✔ Works with [GitHub Apps](#)

Deletes a comment on a team discussion. OAuth access tokens require the `write:discussion` [scope](#).

Note: You can also specify a team by `org_id` and `team_id` using the route `DELETE /organizations/{org_id}/team/{team_id}/discussions/{discussion_number}/comments/{comment_number}`.

Parameters for "Delete a discussion comment"

Headers

accept

string

Setting to `application/vnd.github+json` is recommended.

Path parameters

org

string

Required

The organization name. The name is not case sensitive.

team_slug

string

Required

The slug of the team name.

discussion_number

integer

Required

The number that identifies the discussion.

The number that identifies the discussion.

`comment_number` integer Required

The number that identifies the comment.

HTTP response status codes for "Delete a discussion comment"

Status code	Description
204	No Content

Code samples for "Delete a discussion comment"

`DELETE` /orgs/{org}/teams/{team_slug}/discussions/{discussion_number}/comments/{comment_number}

cURL

JavaScript

GitHub CLI

```
curl -L \ -X DELETE \ -H "Accept: application/vnd.github+json" \ -H "Authorization: Bearer <YOUR-TOKEN>" \ -H "X-GitHub-API-Version: 2022-11-28" \ https://api.github.com/orgs/ORG/teams/TEAM_SLUG/discussions/DISCUSSION_NUMBER/comments/COMMENT_NUMBER
```

Response

Status: 204

List discussion comments (Legacy)

✔ Works with [GitHub Apps](#)

Deprecation Notice: This endpoint route is deprecated and will be removed from the Teams API. We recommend migrating your existing code to use the new [List discussion comments](#) endpoint.

List all comments on a team discussion. OAuth access tokens require the `read:discussion` [scope](#).

Parameters for "List discussion comments (Legacy)"

Headers

`accept` string

Setting to `application/vnd.github+json` is recommended.

Path parameters

`team_id` integer Required

The unique identifier of the team.

`discussion_number` integer Required

The number that identifies the discussion.

The number that identifies the discussion.

Query parameters

direction string

The direction to sort the results by.

Default: `desc`

Can be one of: `asc`, `desc`

per_page integer

The number of results per page (max 100).

Default: `30`

page integer

Page number of the results to fetch.

Default: `1`

HTTP response status codes for "List discussion comments (Legacy)"

Status code

Description

`200`

OK

Code samples for "List discussion comments (Legacy)"

GET /teams/{team_id}/discussions/{discussion_number}/comments

cURL JavaScript GitHub CLI



```
curl -L \ -H "Accept: application/vnd.github+json" \ -H "Authorization: Bearer <YOUR-TOKEN>" \ -H "X-GitHub-API-Version: 2022-11-28" \ https://api.github.com/teams/TEAM_ID/discussions/DISCUSSION_NUMBER/comments
```

Response

Example response

Response schema

Status: 200

```
[ { "author": { "login": "octocat", "id": 1, "node_id": "MDQ6VXNlcjE=", "avatar_url": "https://github.com/images/error/octocat_happy.gif", "gravatar_id": "", "url": "https://api.github.com/users/octocat", "html_url": "https://github.com/octocat", "followers_url": "https://api.github.com/users/octocat/followers", "following_url": "https://api.github.com/users/octocat/following{/other_user}", "gists_url": "https://api.github.com/users/octocat/gists{/gist_id}", "starred_url": "https://api.github.com/users/octocat/starred{/owner}/{repo}", "subscriptions_url": "https://api.github.com/users/octocat/subscriptions", "organizations_url": "https://api.github.com/users/octocat/orgs",
```

Create a discussion comment (Legacy)

✔ Works with [GitHub Apps](#)

Deprecation Notice: This endpoint route is deprecated and will be removed from the Teams API. We recommend

migrating your existing code to use the new [Create a discussion comment](#) endpoint.

Creates a new comment on a team discussion. OAuth access tokens require the `write:discussion` [scope](#).

This endpoint triggers [notifications](#). Creating content too quickly using this endpoint may result in secondary rate limiting. See "[Secondary rate limits](#)" and "[Dealing with secondary rate limits](#)" for details.

Parameters for "Create a discussion comment (Legacy)"

Headers

`accept` string

Setting to `application/vnd.github+json` is recommended.

Path parameters

`team_id` integer **Required**

The unique identifier of the team.

`discussion_number` integer **Required**

The number that identifies the discussion.

Body parameters

`body` string **Required**

The discussion comment's body text.

HTTP response status codes for "Create a discussion comment (Legacy)"

Status code	Description
201	Created

Code samples for "Create a discussion comment (Legacy)"

`POST` `/teams/{team_id}/discussions/{discussion_number}/comments`

`cURL`

`JavaScript`

`GitHub CLI`

```
curl -L \ -X POST \ -H "Accept: application/vnd.github+json" \ -H "Authorization: Bearer <YOUR-TOKEN>" \ -H "X-GitHub-API-Version: 2022-11-28" \ https://api.github.com/teams/TEAM_ID/discussions/DISCUSSION_NUMBER/comments \ -d '{"body":"Do you like apples?"}'
```

Response

`Example response`

`Response schema`

Status: 201

```
{ "author": { "login": "octocat", "id": 1, "node_id": "MDQ6VXNlcjE=", "avatar_url": "https://github.com/images/error/octocat_happy.gif", "gravatar_id": "", "url": "https://api.github.com/users/octocat", "html_url":
```

```
"https://github.com/octocat", "followers_url": "https://api.github.com/users/octocat/followers", "following_url":
"https://api.github.com/users/octocat/following{/other_user}", "gists_url": "https://api.github.com/users/octocat/gists{/gist_id}",
"starred_url": "https://api.github.com/users/octocat/starred{/owner}/{repo}", "subscriptions_url":
"https://api.github.com/users/octocat/subscriptions", "organizations_url": "https://api.github.com/users/octocat/orgs",
```

Get a discussion comment (Legacy)

✔ Works with [GitHub Apps](#)

Deprecation Notice: This endpoint route is deprecated and will be removed from the Teams API. We recommend migrating your existing code to use the new [Get a discussion comment](#) endpoint.

Get a specific comment on a team discussion. OAuth access tokens require the `read:discussion` [scope](#).

Parameters for "Get a discussion comment (Legacy)"

Headers

accept string

Setting to `application/vnd.github+json` is recommended.

Path parameters

team_id integer **Required**

The unique identifier of the team.

discussion_number integer **Required**

The number that identifies the discussion.

comment_number integer **Required**

The number that identifies the comment.

HTTP response status codes for "Get a discussion comment (Legacy)"

Status code	Description
200	OK

Code samples for "Get a discussion comment (Legacy)"

GET /teams/{team_id}/discussions/{discussion_number}/comments/{comment_number}

cURLJavaScriptGitHub CLI

```
curl -L \ -H "Accept: application/vnd.github+json" \ -H "Authorization: Bearer <YOUR-TOKEN>" \ -H "X-GitHub-API-Version: 2022-11-28" \
https://api.github.com/teams/TEAM_ID/discussions/DISCUSSION_NUMBER/comments/COMMENT_NUMBER
```



Response

Example response	Response schema
Status: 200	
<pre>{ "author": { "login": "octocat", "id": 1, "node_id": "MDQ6VXNlcjE=", "avatar_url": "https://github.com/images/error/octocat_happy.gif", "gravatar_id": "", "url": "https://api.github.com/users/octocat", "html_url": "https://github.com/octocat", "followers_url": "https://api.github.com/users/octocat/followers", "following_url": "https://api.github.com/users/octocat/following{/other_user}", "gists_url": "https://api.github.com/users/octocat/gists{/gist_id}", "starred_url": "https://api.github.com/users/octocat/starred{/owner}/{/repo}", "subscriptions_url": "https://api.github.com/users/octocat/subscriptions", "organizations_url": "https://api.github.com/users/octocat/orgs",</pre>	

Update a discussion comment (Legacy)

✔ Works with [GitHub Apps](#)

Deprecation Notice: This endpoint route is deprecated and will be removed from the Teams API. We recommend migrating your existing code to use the new [Update a discussion comment](#) endpoint.

Edits the body text of a discussion comment. OAuth access tokens require the `write:discussion` [scope](#).

Parameters for "Update a discussion comment (Legacy)"

Headers

accept string
Setting to `application/vnd.github+json` is recommended.

Path parameters

team_id integer **Required**
The unique identifier of the team.

discussion_number integer **Required**
The number that identifies the discussion.

comment_number integer **Required**
The number that identifies the comment.

Body parameters

body string **Required**
The discussion comment's body text.

HTTP response status codes for "Update a discussion comment (Legacy)"

Status code	Description
200	OK

Code samples for "Update a discussion comment (Legacy)"

PATCH /teams/{team_id}/discussions/{discussion_number}/comments/{comment_number}

cURL JavaScript GitHub CLI



```
curl -L \ -X PATCH \ -H "Accept: application/vnd.github+json" \ -H "Authorization: Bearer <YOUR-TOKEN>" \ -H "X-GitHub-API-Version: 2022-11-28" \ https://api.github.com/teams/TEAM_ID/discussions/DISCUSSION_NUMBER/comments/COMMENT_NUMBER \ -d '{"body":"Do you like pineapples?"}'
```

Response

Example response

Response schema

Status: 200

```
{ "author": { "login": "octocat", "id": 1, "node_id": "MDQ6VXNlcjE=", "avatar_url": "https://github.com/images/error/octocat_happy.gif", "gravatar_id": "", "url": "https://api.github.com/users/octocat", "html_url": "https://github.com/octocat", "followers_url": "https://api.github.com/users/octocat/followers", "following_url": "https://api.github.com/users/octocat/following{/other_user}", "gists_url": "https://api.github.com/users/octocat/gists{/gist_id}", "starred_url": "https://api.github.com/users/octocat/starred{/owner}/{/repo}", "subscriptions_url": "https://api.github.com/users/octocat/subscriptions", "organizations_url": "https://api.github.com/users/octocat/orgs",
```

Delete a discussion comment (Legacy)

✔ Works with [GitHub Apps](#)

Deprecation Notice: This endpoint route is deprecated and will be removed from the Teams API. We recommend migrating your existing code to use the new [Delete a discussion comment](#) endpoint.

Deletes a comment on a team discussion. OAuth access tokens require the `write:discussion` [scope](#).

Parameters for "Delete a discussion comment (Legacy)"

Headers

accept string

Setting to `application/vnd.github+json` is recommended.

Path parameters

team_id integer **Required**

The unique identifier of the team.

discussion_number integer **Required**

The number that identifies the discussion.

comment_number integer **Required**

The number that identifies the comment.

HTTP response status codes for "Delete a discussion comment (Legacy)"

Status code	Description
204	No Content

Code samples for "Delete a discussion comment (Legacy)"

DELETE

/teams/{team_id}/discussions/{discussion_number}/comments/{comment_number}

cURL

JavaScript

GitHub CLI

```
curl -L \ -X DELETE \ -H "Accept: application/vnd.github+json" \ -H "Authorization: Bearer <YOUR-TOKEN>" \ -H "X-GitHub-API-Version: 2022-11-28" \ https://api.github.com/teams/TEAM_ID/discussions/DISCUSSION_NUMBER/comments/COMMENT_NUMBER
```

Response

Status: 204

Legal