

Managing an individual's access to an organization repository

In this article

About access to organization repositories

Managing an individual's access to an organization repository

Further reading

You can manage a person's access to a repository owned by your organization.

Who can use this feature

People with admin access to a repository can manage access to the repository.

About access to organization repositories

When you remove a collaborator from a repository in your organization, the collaborator loses read and write access to the repository. If the repository is private and the collaborator has forked the repository, then their fork is also deleted, but the collaborator will still retain any local clones of your repository.

Warning:

- If you remove a person's access to a private repository, any of their forks of that private repository are deleted. Local clones of the private repository are retained. If a team's access to a private repository is revoked or a team with access to a private repository is deleted, and team members do not have access to the repository through another team, private forks of the repository will be deleted.
- When [LDAP Sync is enabled](#), if you remove a person from a repository, they will lose access but their forks will not be deleted. If the person is added to a team with access to the original organization repository within three months, their access to the forks will be automatically restored on the next sync.
- You are responsible for ensuring that people who have lost access to a repository delete any confidential information or intellectual property.
- People with admin permissions to a private or internal repository can disallow forking of that repository, and organization owners can disallow forking of any private or internal repository in an organization. For more information, see "[Managing the forking policy for your organization](#)" and "[Managing the forking policy for your repository](#)."

Managing an individual's access to an organization repository

You can give a person access to a repository or change a person's level of access to a repository in your repository settings. For more information, see "[Managing teams and people with access to your repository](#)."

Further reading

- ["Repository roles for an organization"](#)

Legal