Q



The REST API is now versioned. For more information, see "About API versioning."

# Repository autolinks

Use the REST API to add autolinks to external resources.

# About repository autolinks &

To help streamline your workflow, you can use the REST API to add autolinks to external resources like JIRA issues and Zendesk tickets. For more information, see "Configuring autolinks to reference external resources."

GitHub Apps require repository administration permissions with read or write access to use these endpoints.

# List all autolinks of a repository @

Works with <u>GitHub Apps</u>

This returns a list of autolinks configured for the given repository.

Information about autolinks are only available to repository administrators.

### Parameters for "List all autolinks of a repository"

#### **Headers**

accept string

Setting to application/vnd.github+json is recommended.

### Path parameters

owner string Required

The account owner of the repository. The name is not case sensitive.

repo string Required

The name of the repository without the .git extension. The name is not case sensitive.

### **Query parameters**

page integer

Page number of the results to fetch.

Default: 1

Status code Description

200 OK

# Code samples for "List all autolinks of a repository"



### Response

```
Example response Response schema

Status: 200

[ { "id": 1, "key_prefix": "TICKET-", "url_template": "https://example.com/TICKET?query=<num>", "is_alphanumeric": true } ]
```

# Create an autolink reference for a repository &

Works with GitHub Apps

Users with admin access to the repository can create an autolink.

# Parameters for "Create an autolink reference for a repository"

### **Headers**

accept string
Setting to application/vnd.github+json is recommended.

## Path parameters

owner string Required

The account owner of the repository. The name is not case sensitive.

repo string Required

The name of the repository without the <code>.git</code> extension. The name is not case sensitive.

### **Body parameters**

### key\_prefix string Required

This prefix appended by certain characters will generate a link any time it is found in an issue, pull request, or commit.

# url\_template string Required

The URL must contain <num> for the reference number. <num> matches different characters depending on the value of is alphanumeric.

### is\_alphanumeric boolean

Whether this autolink reference matches alphanumeric characters. If true, the <num> parameter of the url\_template matches alphanumeric characters A-Z (case insensitive), 0-9, and -. If false, this autolink reference only matches numeric characters.

Default: true

## HTTP response status codes for "Create an autolink reference for a repository"

Status code	Description
201	Created
422	Validation failed, or the endpoint has been spammed.

### Code samples for "Create an autolink reference for a repository"



# response

```
Example response Response schema

Status: 201

{ "id": 1, "key_prefix": "TICKET-", "url_template": "https://example.com/TICKET?query=<num>", "is_alphanumeric": true }
```

# Get an autolink reference of a repository &

# Works with <u>GitHub Apps</u>

This returns a single autolink reference by ID that was configured for the given repository.

Information about autolinks are only available to repository administrators.

### Parameters for "Get an autolink reference of a repository"

#### **Headers**

accept string

Setting to application/vnd.github+json is recommended.

### Path parameters

owner string Required

The account owner of the repository. The name is not case sensitive.

repo string Required

The name of the repository without the .git extension. The name is not case sensitive.

autolink id integer Required

The unique identifier of the autolink.

# HTTP response status codes for "Get an autolink reference of a repository"

Status code	Description
200	OK
404	Resource not found

## Code samples for "Get an autolink reference of a repository"



### Response

```
Example response Response schema

Status: 200

{ "id": 1, "key_prefix": "TICKET-", "url_template": "https://example.com/TICKET?query=<num>", "is_alphanumeric": true }
```

# Delete an autolink reference from a repository &

### Works with <u>GitHub Apps</u>

This deletes a single autolink reference by ID that was configured for the given repository.

Information about autolinks are only available to repository administrators.

### Parameters for "Delete an autolink reference from a repository"

#### Headers

accept string

Setting to application/vnd.github+json is recommended.

#### Path parameters

owner string Required

The account owner of the repository. The name is not case sensitive.

repo string Required

The name of the repository without the .git extension. The name is not case sensitive.

autolink\_id integer Required

The unique identifier of the autolink.

## HTTP response status codes for "Delete an autolink reference from a repository"

Status code	Description
204	No Content
404	Resource not found

## Code samples for "Delete an autolink reference from a repository"



### Response

Status: 204

# Legal

© 2023 GitHub, Inc. <u>Terms</u> <u>Privacy</u> <u>Status</u> <u>Pricing</u> <u>Expert services</u> <u>Blog</u>