

The REST API is now versioned. For more information, see "[About API versioning](#)."

# Team discussions

Use the REST API to get, create, edit, and delete discussion posts on a team's page.

The team discussions and team discussion comments endpoints will be deprecated on 2023-11-28 in favor of GitHub Discussions. For more information about GitHub Discussions, see "[GitHub Discussions documentation](#)."

## List discussions

✔ Works with [GitHub Apps](#)

List all discussions on a team's page. OAuth access tokens require the `read:discussion` [scope](#).

**Note:** You can also specify a team by `org_id` and `team_id` using the route `GET /organizations/{org_id}/team/{team_id}/discussions`.

### Parameters for "List discussions"

#### Headers

**accept** string

Setting to `application/vnd.github+json` is recommended.

#### Path parameters

**org** string **Required**

The organization name. The name is not case sensitive.

**team\_slug** string **Required**

The slug of the team name.

#### Query parameters

**direction** string

The direction to sort the results by.

Default: `desc`

Can be one of: `asc`, `desc`

**per\_page** integer

The number of results per page (max 100).

Default: `30`

Default: 1

**page** integer

Page number of the results to fetch.

Default: 1

**pinned** string

Pinned discussions only filter

## HTTP response status codes for "List discussions"

Status code	Description
200	OK

## Code samples for "List discussions"

**GET** /orgs/{org}/teams/{team\_slug}/discussions

cURL JavaScript GitHub CLI



```
curl -L \ -H "Accept: application/vnd.github+json" \ -H "Authorization: Bearer <YOUR-TOKEN>" \ -H "X-GitHub-Api-Version: 2022-11-28" \ https://api.github.com/orgs/ORG/teams/TEAM_SLUG/discussions
```

## Response

Example response Response schema

Status: 200

```
[ { "author": { "login": "octocat", "id": 1, "node_id": "MDQ6VXNlcjE=", "avatar_url": "https://github.com/images/error/octocat_happy.gif", "gravatar_id": "", "url": "https://api.github.com/users/octocat", "html_url": "https://github.com/octocat", "followers_url": "https://api.github.com/users/octocat/followers", "following_url": "https://api.github.com/users/octocat/following{/other_user}", "gists_url": "https://api.github.com/users/octocat/gists{/gist_id}", "starred_url": "https://api.github.com/users/octocat/starred{/owner}/{repo}", "subscriptions_url": "https://api.github.com/users/octocat/subscriptions", "organizations_url": "https://api.github.com/users/octocat/orgs",
```

## Create a discussion

✔ Works with [GitHub Apps](#)

Creates a new discussion post on a team's page. OAuth access tokens require the `write:discussion` [scope](#).

This endpoint triggers [notifications](#). Creating content too quickly using this endpoint may result in secondary rate limiting. See "[Secondary rate limits](#)" and "[Dealing with secondary rate limits](#)" for details.

**Note:** You can also specify a team by `org_id` and `team_id` using the route `POST /organizations/{org_id}/team/{team_id}/discussions`.

## Parameters for "Create a discussion"

Headers

**accept** string

Setting to `application/vnd.github+json` is recommended.

Path parameters

**org** string **Required**

The organization name. The name is not case sensitive.

**team\_slug** string **Required**

The slug of the team name.

Body parameters

**title** string **Required**

The discussion post's title.

**body** string **Required**

The discussion post's body text.

**private** boolean

Private posts are only visible to team members, organization owners, and team maintainers. Public posts are visible to all members of the organization. Set to `true` to create a private post.

Default: `false`

HTTP response status codes for "Create a discussion"

Status code	Description
201	Created

Code samples for "Create a discussion"

**POST** `/orgs/{org}/teams/{team_slug}/discussions`

cURL

JavaScript

GitHub CLI



```
curl -L \ -X POST \ -H "Accept: application/vnd.github+json" \ -H "Authorization: Bearer <YOUR-TOKEN>" \ -H "X-GitHub-API-Version: 2022-11-28" \ https://api.github.com/orgs/ORG/teams/TEAM_SLUG/discussions \ -d '{"title":"Our first team post","body":"Hi! This is an area for us to collaborate as a team."}'
```

Response

Example response

Response schema

Status: 201

```
{ "author": { "login": "octocat", "id": 1, "node_id": "MDQ6VXNlcjE=", "avatar_url": "https://github.com/images/error/octocat_happy.gif", "gravatar_id": "", "url": "https://api.github.com/users/octocat", "html_url": "https://github.com/octocat", "followers_url": "https://api.github.com/users/octocat/followers", "following_url": "https://api.github.com/users/octocat/following{other_user}", "gists_url": "https://api.github.com/users/octocat/gists{gist_id}",
```

```
"starred_url": "https://api.github.com/users/octocat/starred{/owner}/{repo}", "subscriptions_url":
"https://api.github.com/users/octocat/subscriptions", "organizations_url": "https://api.github.com/users/octocat/orgs",
```

## Get a discussion

✔ Works with [GitHub Apps](#)

Get a specific discussion on a team's page. OAuth access tokens require the `read:discussion` [scope](#).

**Note:** You can also specify a team by `org_id` and `team_id` using the route `GET /organizations/{org_id}/team/{team_id}/discussions/{discussion_number}` .

### Parameters for "Get a discussion"

#### Headers

**accept** string  
Setting to `application/vnd.github+json` is recommended.

#### Path parameters

**org** string **Required**  
The organization name. The name is not case sensitive.

**team\_slug** string **Required**  
The slug of the team name.

**discussion\_number** integer **Required**  
The number that identifies the discussion.


### HTTP response status codes for "Get a discussion"

Status code	Description
200	OK

### Code samples for "Get a discussion"

GET /orgs/{org}/teams/{team\_slug}/discussions/{discussion\_number}

cURLJavaScriptGitHub CLI



curl -L \ -H "Accept: application/vnd.github+json" \ -H "Authorization: Bearer <YOUR-TOKEN>" \ -H "X-GitHub-API-Version: 2022-11-28" \ https://api.github.com/orgs/ORG/teams/TEAM\_SLUG/discussions/DISCUSSION\_NUMBER

#### Response

Example responseResponse schema

```
Status: 200

{ "author": { "login": "octocat", "id": 1, "node_id": "MDQ6VXNlcjE=", "avatar_url":
"https://github.com/images/error/octocat_happy.gif", "gravatar_id": "", "url": "https://api.github.com/users/octocat", "html_url":
"https://github.com/octocat", "followers_url": "https://api.github.com/users/octocat/followers", "following_url":
"https://api.github.com/users/octocat/following{/other_user}", "gists_url": "https://api.github.com/users/octocat/gists{/gist_id}",
"starred_url": "https://api.github.com/users/octocat/starred{/owner}/{repo}", "subscriptions_url":
"https://api.github.com/users/octocat/subscriptions", "organizations_url": "https://api.github.com/users/octocat/orgs",
```

## Update a discussion

✔ Works with [GitHub Apps](#)

Edits the title and body text of a discussion post. Only the parameters you provide are updated. OAuth access tokens require the `write:discussion` [scope](#).

**Note:** You can also specify a team by `org_id` and `team_id` using the route `PATCH /organizations/{org_id}/team/{team_id}/discussions/{discussion_number}` .

### Parameters for "Update a discussion"

#### Headers

**accept** string  
Setting to `application/vnd.github+json` is recommended.

#### Path parameters

**org** string **Required**  
The organization name. The name is not case sensitive.

**team\_slug** string **Required**  
The slug of the team name.

**discussion\_number** integer **Required**  
The number that identifies the discussion.

#### Body parameters

**title** string  
The discussion post's title.

**body** string  
The discussion post's body text.

### HTTP response status codes for "Update a discussion"

Status code	Description
200	OK

Code samples for "Update a discussion"

PATCH

/orgs/{org}/teams/{team\_slug}/discussions/{discussion\_number}

cURL

JavaScript

GitHub CLI

curl -L \ -X PATCH \ -H "Accept: application/vnd.github+json" \ -H "Authorization: Bearer <YOUR-TOKEN>" \ -H "X-GitHub-API-Version: 2022-11-28" \ https://api.github.com/orgs/ORG/teams/TEAM\_SLUG/discussions/DISCUSSION\_NUMBER \ -d '{"title":"Welcome to our first team post"}'

Response

Example response

Response schema

Status: 200

{ "author": { "login": "octocat", "id": 1, "node\_id": "MDQ6VXNlcjE=", "avatar\_url": "https://github.com/images/error/octocat\_happy.gif", "gravatar\_id": "", "url": "https://api.github.com/users/octocat", "html\_url": "https://github.com/octocat", "followers\_url": "https://api.github.com/users/octocat/followers", "following\_url": "https://api.github.com/users/octocat/following{/other\_user}", "gists\_url": "https://api.github.com/users/octocat/gists{/gist\_id}", "starred\_url": "https://api.github.com/users/octocat/starred{/owner}/{repo}", "subscriptions\_url": "https://api.github.com/users/octocat/subscriptions", "organizations\_url": "https://api.github.com/users/octocat/orgs",

Delete a discussion

✔ Works with [GitHub Apps](#)

Delete a discussion from a team's page. OAuth access tokens require the `write:discussion` [scope](#).

**Note:** You can also specify a team by `org_id` and `team_id` using the route `DELETE /organizations/{org_id}/team/{team_id}/discussions/{discussion_number}` .

Parameters for "Delete a discussion"

Headers

`accept` string  
Setting to `application/vnd.github+json` is recommended.

Path parameters

`org` string **Required**  
The organization name. The name is not case sensitive.

`team_slug` string **Required**  
The slug of the team name.

`discussion_number` integer **Required**  
The number that identifies the discussion.

## HTTP response status codes for "Delete a discussion"

Status code	Description
204	No Content

## Code samples for "Delete a discussion"

DELETE

/orgs/{org}/teams/{team\_slug}/discussions/{discussion\_number}

cURL

JavaScript

GitHub CLI

```
curl -L \ -X DELETE \ -H "Accept: application/vnd.github+json" \ -H "Authorization: Bearer <YOUR-TOKEN>" \ -H "X-GitHub-API-Version: 2022-11-28" \ https://api.github.com/orgs/ORG/teams/TEAM_SLUG/discussions/DISCUSSION_NUMBER
```

## Response

Status: 204

## List discussions (Legacy)

✔ Works with [GitHub Apps](#)

**Deprecation Notice:** This endpoint route is deprecated and will be removed from the Teams API. We recommend migrating your existing code to use the new [List discussions](#) endpoint.

List all discussions on a team's page. OAuth access tokens require the `read:discussion` [scope](#).

## Parameters for "List discussions (Legacy)"

### Headers

**accept** string

Setting to `application/vnd.github+json` is recommended.

### Path parameters

**team\_id** integer **Required**

The unique identifier of the team.

### Query parameters

**direction** string

The direction to sort the results by.

Default: `desc`

Can be one of: `asc` , `desc`

**per\_page** integer

The number of results per page (max 100).

Default: 30

**page** integer

Page number of the results to fetch.

Default: 1

HTTP response status codes for "List discussions (Legacy)"

Status code	Description
200	OK

Code samples for "List discussions (Legacy)"

GET

/teams/{team\_id}/discussions

cURL

JavaScriptGitHub CLI

```
curl -L \ -H "Accept: application/vnd.github+json" \ -H "Authorization: Bearer <YOUR-TOKEN>" \ -H "X-GitHub-API-Version: 2022-11-28" \ https://api.github.com/teams/TEAM_ID/discussions
```

Response

Example response

Response schema

Status: 200

```
[ { "author": { "login": "octocat", "id": 1, "node_id": "MDQ6VXNlcjE=", "avatar_url": "https://github.com/images/error/octocat_happy.gif", "gravatar_id": "", "url": "https://api.github.com/users/octocat", "html_url": "https://github.com/octocat", "followers_url": "https://api.github.com/users/octocat/followers", "following_url": "https://api.github.com/users/octocat/following{/other_user}", "gists_url": "https://api.github.com/users/octocat/gists{/gist_id}", "starred_url": "https://api.github.com/users/octocat/starred{/owner}/{repo}", "subscriptions_url": "https://api.github.com/users/octocat/subscriptions", "organizations_url": "https://api.github.com/users/octocat/orgs",
```

Create a discussion (Legacy)

Works with [GitHub Apps](#)

**Deprecation Notice:** This endpoint route is deprecated and will be removed from the Teams API. We recommend migrating your existing code to use the new [Create a discussion](#) endpoint.

Creates a new discussion post on a team's page. OAuth access tokens require the `write:discussion` [scope](#).

This endpoint triggers [notifications](#). Creating content too quickly using this endpoint may result in secondary rate limiting. See "[Secondary rate limits](#)" and "[Dealing with secondary rate limits](#)" for details.

Parameters for "Create a discussion (Legacy)"



Headers

**accept** string

Setting to `application/vnd.github+json` is recommended.

Path parameters

**team\_id** integer **Required**

The unique identifier of the team.

Body parameters

**title** string **Required**

The discussion post's title.

**body** string **Required**

The discussion post's body text.

**private** boolean

Private posts are only visible to team members, organization owners, and team maintainers. Public posts are visible to all members of the organization. Set to `true` to create a private post.

Default: `false`

HTTP response status codes for "Create a discussion (Legacy)"

Status code	Description
201	Created

Code samples for "Create a discussion (Legacy)"

POST /teams/{team\_id}/discussions

cURL

JavaScript

GitHub CLI

```
curl -L \ -X POST \ -H "Accept: application/vnd.github+json" \ -H "Authorization: Bearer <YOUR-TOKEN>" \ -H "X-GitHub-API-Version: 2022-11-28" \ https://api.github.com/teams/TEAM_ID/discussions \ -d '{"title":"Our first team post","body":"Hi! This is an area for us to collaborate as a team."}'
```

Response

Example response

Response schema

Status: 201

```
{ "author": { "login": "octocat", "id": 1, "node_id": "MDQ6VXNlcjE=", "avatar_url": "https://github.com/images/error/octocat_happy.gif", "gravatar_id": "", "url": "https://api.github.com/users/octocat", "html_url": "https://github.com/octocat", "followers_url": "https://api.github.com/users/octocat/followers", "following_url": "https://api.github.com/users/octocat/following{/other_user}", "gists_url": "https://api.github.com/users/octocat/gists{/gist_id}", "starred_url": "https://api.github.com/users/octocat/starred{/owner}/{/repo}", "subscriptions_url": "https://api.github.com/users/octocat/subscriptions", "organizations_url": "https://api.github.com/users/octocat/orgs",
```

# Get a discussion (Legacy)

✔ Works with [GitHub Apps](#)

**Deprecation Notice:** This endpoint route is deprecated and will be removed from the Teams API. We recommend migrating your existing code to use the new [Get a discussion](#) endpoint.

Get a specific discussion on a team's page. OAuth access tokens require the `read:discussion` [scope](#).

## Parameters for "Get a discussion (Legacy)"

### Headers

**accept** string  
Setting to `application/vnd.github+json` is recommended.

### Path parameters

**team\_id** integer **Required**  
The unique identifier of the team.

**discussion\_number** integer **Required**  
The number that identifies the discussion.

## HTTP response status codes for "Get a discussion (Legacy)"

Status code	Description
200	OK

## Code samples for "Get a discussion (Legacy)"


GET

/teams/{team\_id}/discussions/{discussion\_number}

cURL

JavaScript

GitHub CLI



```
curl -L \ -H "Accept: application/vnd.github+json" \ -H "Authorization: Bearer <YOUR-TOKEN>" \ -H "X-GitHub-API-Version: 2022-11-28" \ https://api.github.com/teams/TEAM_ID/discussions/DISCUSSION_NUMBER
```

### Response

Example response

Response schema

Status: 200

```
{ "author": { "login": "octocat", "id": 1, "node_id": "MDQ6VXNlcjE=", "avatar_url": "https://github.com/images/error/octocat_happy.gif", "gravatar_id": "", "url": "https://api.github.com/users/octocat", "html_url": "https://github.com/octocat", "followers_url": "https://api.github.com/users/octocat/followers", "following_url": "https://api.github.com/users/octocat/following{other_user}", "gists_url": "https://api.github.com/users/octocat/gists{gist_id}", "starred_url": "https://api.github.com/users/octocat/starred{owner}/{repo}", "subscriptions_url": "https://api.github.com/users/octocat/subscriptions", "organizations url": "https://api.github.com/users/octocat/orgs",
```

# Update a discussion (Legacy)

✔ Works with [GitHub Apps](#)

**Deprecation Notice:** This endpoint route is deprecated and will be removed from the Teams API. We recommend migrating your existing code to use the new [Update a discussion](#) endpoint.

Edits the title and body text of a discussion post. Only the parameters you provide are updated. OAuth access tokens require the `write:discussion` [scope](#).

## Parameters for "Update a discussion (Legacy)"

### Headers

**accept** string

Setting to `application/vnd.github+json` is recommended.

### Path parameters

**team\_id** integer **Required**

The unique identifier of the team.

**discussion\_number** integer **Required**

The number that identifies the discussion.

### Body parameters

**title** string

The discussion post's title.

**body** string

The discussion post's body text.

## HTTP response status codes for "Update a discussion (Legacy)"

Status code	Description
200	OK

## Code samples for "Update a discussion (Legacy)"

**PATCH** /teams/{team\_id}/discussions/{discussion\_number}

cURL   JavaScript   GitHub CLI



```
curl -L \ -X PATCH \ -H "Accept: application/vnd.github+json" \ -H "Authorization: Bearer <YOUR-TOKEN>" \ -H "X-GitHub-API-Version: 2022-11-28" \ https://api.github.com/teams/TEAM_ID/discussions/DISCUSSION_NUMBER \ -d '{"title":"Welcome to our first team post"}'
```

Response

Example responseResponse schema

Status: 200

```
{ "author": { "login": "octocat", "id": 1, "node_id": "MDQ6VXNlcjE=", "avatar_url": "https://github.com/images/error/octocat_happy.gif", "gravatar_id": "", "url": "https://api.github.com/users/octocat", "html_url": "https://github.com/octocat", "followers_url": "https://api.github.com/users/octocat/followers", "following_url": "https://api.github.com/users/octocat/following{/other_user}", "gists_url": "https://api.github.com/users/octocat/gists{/gist_id}", "starred_url": "https://api.github.com/users/octocat/starred{/owner}/{repo}", "subscriptions_url": "https://api.github.com/users/octocat/subscriptions", "organizations_url": "https://api.github.com/users/octocat/orgs",
```

## Delete a discussion (Legacy)

✔ Works with [GitHub Apps](#)

**Deprecation Notice:** This endpoint route is deprecated and will be removed from the Teams API. We recommend migrating your existing code to use the new [Delete a discussion](#) endpoint.

Delete a discussion from a team's page. OAuth access tokens require the `write:discussion` [scope](#).

### Parameters for "Delete a discussion (Legacy)"

Headers

`accept` string

Setting to `application/vnd.github+json` is recommended.

Path parameters

`team_id` integer **Required**

The unique identifier of the team.

`discussion_number` integer **Required**

The number that identifies the discussion.

### HTTP response status codes for "Delete a discussion (Legacy)"

Status code	Description
204	No Content

### Code samples for "Delete a discussion (Legacy)"

DELETE

`/teams/{team_id}/discussions/{discussion_number}`

cURLJavaScriptGitHub CLI

curl -L \ -X DELETE \ -H "Accept: application/vnd.github+json" \ -H "Authorization: Bearer <YOUR-TOKEN>" \ -H "X-GitHub-API-Version: 2022-11-28" \ https://api.github.com/teams/TEAM\_ID/discussions/DISCUSSION\_NUMBER

Response

Status: 204

Legal