

Ex No: 3

**Date: 13/02/24**

## **DEVELOP A LEXICAL ANALYZER TO RECOGNIZE TOKENS USING LEX TOOL**

### **AIM:**

To implement the program to identify C keywords, identifiers, operators, and statements like [], {} using LEX tool.

### **ALGORITHM**

- Define patterns for C keywords, identifiers, operators, and end statements using regular expressions. Use %option noyywrap to disable the default behavior of yywrap.
- Utilize regular expressions to match patterns for C keywords, identifiers, operators, and end statements. Associate each pattern with an action to be executed when matched.
- Define actions to print corresponding token categories for matched patterns. Handle special cases like function declarations, numeric literals, and processor directives separately.
- Open the input file (sample.c in this case) for reading. Start lexical analysis using yylex() to scan the input and apply defined rules.
- Increment a counter (n) each time a newline character is encountered. Print the total number of lines at the end of the program execution.

### **PROGRAM**

```
%option noyywrap
letter [a-zA-Z]
digit [0-9]
id [_a-zA-Z]
AO [+|-|/|%|*]
RO [<|>|<=|>|=|==]
pp [#]
%{
int n=0;
}%

%%

"void" printf("%s return type\n",yytext);
{letter}*([[]] printf("%s Function\n",yytext);
"int"|"float"|"if"|"else" printf("%s keywords\n",yytext);
"printf" printf("%s keywords\n",yytext);
```

```

{id}({id}|{digit})* printf("%s Identifier\n",yytext);
{digit} {digit}* printf("%d Numbers\n",yytext);
{AO} printf("%s Arithmetic Operators\n",yytext); {RO} printf("%s Relational
Operators\n",yytext);

```

6

```

{pp} {letter}*[<]{letter}*[{.}]{letter}[>] printf("%s processor
Directive\n",yytext); [\n] n++;
"."|","|"}|{"|";" printf("%s others\n",yytext);


```

```

%%
int main()
{
    yyin=fopen("sample.c","r");
    yylex();
    printf("No of Lines %d\n",n);
}

```

## OUTPUT:



```

[root@fedora student]# vi 307_exp3.1
[root@fedora student]# lex 307_exp3.1
[root@fedora student]# cc lex.yy.c
[root@fedora student]# ./a.out
#include<stdio.h> void main)f int a,b; }
#include<stdio.h> processor Directive
void return type
main() Function
{ others
int keywords
a Identifier
, others
b Identifier
; others
} others

```

**RESULT:** To implement the program to identify C keywords, identifiers, operators, end statements like [], {} using LEX tool has been verified