

Problem Scenario:

Loudacre Inc. is a leading electronics retailer

- More than 1,000 brick and mortar stores
- Dualcore also has a thriving e-commerce Web site

Loudacre has hired you to help find value in its data

- You will process and analyse data from internal and external sources
- Identify opportunities to increase revenue
- Find new ways to reduce costs
- Help other departments achieve their goals

Ques 1: List all the databases in the RDBMS

```
sqoop list-databases --connect jdbc:mysql://localhost/ --username training  
--password training
```

Ques 2: Make a directory on HDFS named as /Loudacre

```
hdfs dfs -mkdir /Loudacre
```

Ques 3: Import accounts, accountdevice, webpage into the directory /Loudacre separately

```
sqoop import --connect jdbc:mysql://localhost/loudacre --username training  
--password training --table accounts --target-dir /Loudacre/accounts
```

```
sqoop import --connect jdbc:mysql://localhost/loudacre --username training  
--password training --table accountdevice --target-dir /Loudacre/accountdevice
```

```
sqoop import --connect jdbc:mysql://localhost/loudacre --username training  
--password training --table webpage --target-dir /Loudacre/webpage
```

Ques 4: Import table accounts in /user/training changing the mappers to 10 and changing the field terminator to ‘.’. Also split them on the basis of state.

```
sqoop import --connect jdbc:mysql://localhost/loudacre --username training
--password training --table accounts --target-dir /user/training/accounts -m 10
--fields-terminated-by ':' --split-by state
```

Ques 5: Import the Complete names of people having accounts in Loudacre
ex: firstname <space> last_name
ex: Britney Spears

```
sqoop import --connect jdbc:mysql://localhost/loudacre --username training
--password training --table accounts --columns "first_name,last_name"
--fields-terminated-by ' ' --target-dir /Loudacre/complete_names
```

Ques 6: Import only those records where device_id is between 10 and 50 in table accountdevice.

```
sqoop import --connect jdbc:mysql://localhost/loudacre --username training
--password training --table accountdevice --where "device_id BETWEEN 10 AND
50" --target-dir /Loudacre/accountdevice_q6
```

Ques 7: Copy the acct_num from the table customerservicerep where customer name is Roger Miller.

```
sqoop import --connect jdbc:mysql://localhost/loudacre --username training
--password training --table customerservicerep --columns "acct_num" --where
"cs_name='Roger Miller'" --target-dir /Loudacre/roger_acct
```