Security and Access Policy

NovaTech Solutions | Fictional sample document created for a technical assignment.

Authentication

Internal services must use multi-factor authentication (MFA) wherever it is supported. Employees must never share passwords or approve an MFA prompt they did not initiate. If a device used for authentication is lost, the employee should contact the support team and their manager.

Access requests

Access must follow least privilege: users receive only the permissions needed for their assigned duties. A request should name the system, requested role, business reason, and expected duration. The system owner approves access to production data. Temporary elevated access should expire at the end of the approved period.

Incident reporting

A suspected security incident should be reported to Security Operations as soon as possible, ideally within one hour of discovery. The report should include the time noticed, affected service, observed behaviour, and actions already taken. Employees should preserve relevant logs and avoid deleting evidence.

Credential storage

Secrets belong in the approved secret manager or deployment environment settings. They must not be committed to source control, placed in screenshots, or pasted into public issue trackers. Rotate a credential if it may have been exposed. The security team records the incident and tracks the remediation.

Device requirements

Devices that access internal tools should use a supported operating system, screen lock, and current security updates. Unattended devices must be locked. Unapproved removable storage should not be used for company information.

Operational examples

Example: Record the relevant timestamp, owner, observed impact, and next action before escalating a service issue.

Example: If the evidence is incomplete, state what is known and what remains unverified rather than guessing.

These examples are illustrative and do not override the policy statements above.