00:00–00:35, 35 seconds

- Introduce the paper and coauthors. The study examines archived Portuguese-to-English workplace survey translations.
- The central question is how to interpret automated audit results when many answers are short or repeated.
- Lead into the practical reason for translating these answers into English.

Source: camera-ready article, title and author block. Logos are the official assets shared with the poster.

Translation audits for short survey responses

00:35–01:35, 60 seconds

- Workplace surveys collect open answers about strengths, improvements and well-being. Translation makes these answers accessible to English-centered analysis tools.
- Brief answers can be reasonable translations while offering very little distinctive information. Repetition adds to the ambiguity.
- Ask the audience to keep three conditions in mind: response length, repeated wording and the vocabulary covered by the diagnostic resources.
- This study evaluates the archived pairs. The translation workflow's row-level model history is incomplete.

Source: camera-ready article, Introduction and Translation Workflow and Provenance. The diagram contains conceptual labels only.

Four cohorts, three prompt families

01:35–02:35, 60 seconds

- The corpus covers four Brazilian workplace survey cohorts from 2023 to 2025. There are 44,118 response pairs from 14,706 survey-specific records.
- These records describe participation within each survey. A person answering across years cannot be linked across cohorts.
- Every retained record has three answers, one per prompt family. One third of the pairs therefore come from mental-health or well-being prompts, whose wording varies by cohort.
- The chart shows the cohort sizes. The analysis retained short and repeated answers because they are part of the operational setting.

Source: camera-ready article, Table 1 and Appendix A.

Three audit views

02:35–03:40, 65 seconds

- All pairs enter three parallel audit views. Read them as separate questions rather than as stages feeding a combined score.
- Qwen3-Embedding-4B tests paired-text recovery. The 8B version provides a model-scale sensitivity check.
- COMETKiwi DA-XL estimates quality from the Portuguese source and English translation, without a human reference translation.
- Lingua supplies language flags, and EmoAtlas supplies language-specific affective-lexicon diagnostics. Coverage helps explain which responses yield a profile.

Source: camera-ready article, Figure 2 and Computational Provenance. Qwen3, COMETKiwi and EmoAtlas references are on the backup reference slide.

What rank-one recovery measures

03:40–04:45, 65 seconds

- A query asks the encoder to find its counterpart among all 44,118 texts in the other language. Queries receive a retrieval instruction, while candidates are encoded without one.
- Rank-one recovery counts a match when the first candidate is the paired target or any candidate with exactly the same normalized target text.
- Semantically similar answers with different normalized wording remain competing candidates. This is a demanding corpus-level identification task.
- The overall rates are 71.80 percent for English queries and 73.37 percent for Portuguese queries. The next slide shows what this average conceals.

Source: camera-ready article, Instruction-Conditioned Paired-Text Retrieval and Table 2. Diagram is schematic and contains no response text.

Retrieval rises sharply with response length

04:45–06:15, 90 seconds

- Orient the audience. The horizontal axis uses Portuguese source length, with four prespecified bands. The vertical axis shows correct rank-one recovery.
- Blue is an English query searching Portuguese candidates. Dashed gray is a Portuguese query searching English candidates.
- One- or two-word responses have recovery rates of about 8 to 13 percent. Responses longer than twenty words reach about 98 to 99 percent.
- Error bars are 95 percent cluster-bootstrap intervals from 2,000 resamples. All length groups use the same full candidate corpus.
- This is an association between length and recoverability in this corpus. Bilingual judgments would connect individual misses to translation quality.

Source: camera-ready article, Figure 1.

Quality estimates follow a different pattern

06:15–07:25, 70 seconds

- This plot keeps the same length bands and shows mean COMETKiwi scores on their model scale.
- The mean is highest for the three-to-five-word group, then falls for the longer groups. Retrieval continued to rise across those groups.
- The disagreement is informative. Retrieval measures distinguishability among candidates, while COMETKiwi estimates quality using learned source–translation relations.
- The study has automated criteria rather than bilingual human ratings. Those ratings would be the next step for calibration in this setting.

Source: camera-ready article, Retrieval Varies Sharply with Response Length and Discussion. Exact means are 0.6414, 0.7798, 0.7526 and 0.7152. Display labels round to three decimals.

Emotion-lexicon coverage

07:25–08:25, 60 seconds

- The blue portion shows responses for which the language-specific lexicon returns zero emotion coverage: 24.67 percent in Portuguese and 23.48 percent in English.
- Zero coverage describes the resource's output. A response can carry meaning or emotion beyond the vocabulary recognized by the lexicon.
- Empty affective profiles affect distance calculations mechanically. The paper therefore also reports comparisons conditional on nonzero profiles in both languages.
- This is a resource-coverage constraint to carry into interpretation, especially when translated text supports mental-health research.

Source: camera-ready article, Language and Affective Coverage. Gray bar segments are the complements of the reported zero-coverage rates.

Scope and validation

08:25–09:20, 55 seconds

- The findings describe one Portuguese–English workplace-survey corpus. Encoder comparisons remain within the Qwen3 family.
- Translation provenance is incomplete, so these findings characterize archived outputs rather than an identifiable translation-system configuration.
- The next validation step is bilingual assessment sampled across lengths and prompt families. This would help relate retrieval and estimated quality to translation accuracy and emotional or cultural meaning.
- Public code contains frozen configurations and synthetic tests. Confidential response data limit full independent reproduction.

Source: camera-ready article, Discussion, Limitations and Ethics Statement. Human validation is proposed future work, not a completed analysis.

09:20–10:00, 40 seconds

- Return to the central message. For brief and repeated survey responses, the audit needs separate views of how distinguishable a response is, its estimated translation quality and the coverage of the diagnostic resources.
- A retrieval miss can arise from ambiguity in the candidate corpus. COMETKiwi and lexical coverage contribute different evidence.
- Thank the audience. The QR code links to the public analysis repository, and the email is available for follow-up.

Source: camera-ready article, Conclusion. Code URL was verified public when preparing the presentation.

Encoder sensitivity

Backup, outside the ten-minute talk

- Use if asked about dependence on the encoder. Relative to 4B, the 8B encoder changes English-to-Portuguese R@1 by -2.37 percentage points, and Portuguese-to-English R@1 by $+1.47$ points.
- The paired 95 percent intervals are [-2.68, -2.08] and [1.19, 1.76] percentage points.
- These comparisons test model scale within Qwen3. Other encoder families remain an extension.

Source: camera-ready article, Appendix C.

Selected references

Backup, outside the ten-minute talk

Main method references used in the presentation. The camera-ready article contains the full bibliography and immutable model revisions.

Slide design adapts the author's slidesThesisSemanticDriftQualification repository. Institutional and conference logos are the shared official assets.