



# REST API Specification

interact.io

Mr. Michael Zirngibl

**V2.0**

Created by: interact.io Scrum Team

Following changes have been made in order to create the current version:

[illegible]

## Table of contents

|            |   |    |
|------------|---|----|
| 1          | About this Document.....                                | 6  |
| 2          | API Specification .....                                 | 7  |
| 2.1        | Prerequisites.....                                      | 7  |
| 2.2        | General API Pattern.....                                | 7  |
| 2.3        | Overview.....   | 7  |
| 2.4        | Push Notifications (Server → Device) .....              | 10 |
| 2.4.1      | Push an Interaction Notification.....                   | 10 |
| 2.4.2      | Push an Interaction Notification (via APN) .....        | 11 |
| 2.4.3      | Push a Synchronize Hint Message .....                   | 12 |
| 2.5        | API Calls .....   | 13 |
| 2.5.1      | Authentication.....                                     | 13 |
| 2.5.1.1    | Login.....  | 13 |
| 2.5.1.2    | Logout.....   | 15 |
| 2.5.2      | Trigger Device → Server .....                           | 16 |
| 2.5.2.1    | Trigger an Event .....                                  | 16 |
| 2.5.2.2    | Register a Trigger Device .....                         | 18 |
| 2.5.2.3    | Read a Trigger Token.....                               | 19 |
| 2.5.3      | Device (Web Portal, CSR resp.) → Server.....            | 20 |
| 2.5.3.1    | Basic CRUD functions .....                              | 20 |
| 2.5.3.1.1  | Read a List of Activities.....                          | 20 |
| 2.5.3.1.2  | Create Person Contact .....                             | 22 |
| 2.5.3.1.3  | Create Organization Contact .....                       | 25 |
| 2.5.3.1.4  | Read a List of Contacts .....                           | 27 |
| 2.5.3.1.5  | Read a List of Contacts Associated with a Contact ..... | 29 |
| 2.5.3.1.6  | Read a Person Contact.....                              | 31 |
| 2.5.3.1.7  | Read an Organization Contact.....                       | 34 |
| 2.5.3.1.8  | Update a Person Contact.....                            | 37 |
| 2.5.3.1.9  | Update an Organization Contact.....                     | 40 |
| 2.5.3.1.10 | Delete Contacts.....                                    | 43 |
| 2.5.3.1.11 | Delete a Contact.....                                   | 44 |
| 2.5.3.1.12 | Upload a contact picture .....                          | 45 |
| 2.5.3.1.13 | Read a Picture.....                                     | 46 |
| 2.5.3.1.14 | Read a List of Pictures Associated with a Contact ..... | 47 |
| 2.5.3.1.15 | Update a contact picture .....                          | 48 |
| 2.5.3.1.16 | Delete Pictures .....                                   | 49 |
| 2.5.3.1.17 | Delete Picture.....                                     | 50 |
| 2.5.3.1.18 | Create Note Associated with a Contact .....             | 51 |
| 2.5.3.1.19 | Read a List of Notes .....                              | 52 |
| 2.5.3.1.20 | Read a List of Notes Associated with a Contact .....    | 53 |
| 2.5.3.1.21 | Update a Note .....                                     | 54 |
| 2.5.3.1.22 | Delete Notes.....                                       | 55 |
| 2.5.3.1.23 | Delete a Note.....                                      | 56 |
| 2.5.3.1.24 | Read a List of Profiles Associated with a Contact ..... | 57 |

|            |  |     |
|------------|--|-----|
| 2.5.3.1.25 | Read a List of Search Terms Associated with a Contact .....  | 59  |
| 2.5.3.1.26 | Read a List of Tags .....                                    | 60  |
| 2.5.3.1.27 | Read a List of Tags Associated with a Contact .....          | 61  |
| 2.5.3.1.28 | Read a List of Interactions.....                             | 62  |
| 2.5.3.1.29 | Read a List of Interactions Associated with a Contact.....   | 64  |
| 2.5.3.1.30 | Read an Interaction .....                                    | 66  |
| 2.5.3.1.31 | Update an Interaction.....                                   | 68  |
| 2.5.3.1.32 | Create Basicinfo.....  | 70  |
| 2.5.3.1.33 | Update a Basicinfo .....                                     | 70  |
| 2.5.3.1.34 | Create Task.....   | 72  |
| 2.5.3.1.35 | Read a List of Tasks .....                                   | 74  |
| 2.5.3.1.36 | Read a List of Tasks Associated with a Contact .....         | 76  |
| 2.5.3.1.37 | Read a Task .....  | 78  |
| 2.5.3.1.38 | Update a Task.....   | 80  |
| 2.5.3.1.39 | Delete Tasks .....   | 81  |
| 2.5.3.1.40 | Delete a Task .....  | 83  |
| 2.5.3.1.41 | Create a Tasklist .....                                      | 84  |
| 2.5.3.1.42 | Read a List of Tasklists .....                               | 85  |
| 2.5.3.1.43 | Read a Tasklist .....  | 87  |
| 2.5.3.1.44 | Update a Tasklist .....                                      | 89  |
| 2.5.3.1.45 | Delete a Tasklist .....                                      | 90  |
| 2.5.3.1.46 | Create Deal.....   | 91  |
| 2.5.3.1.47 | Read a List of Deals .....                                   | 93  |
| 2.5.3.1.48 | Read a List of Deals Associated with a Contact .....         | 94  |
| 2.5.3.1.49 | Read a Deal .....  | 96  |
| 2.5.3.1.50 | Update a Deal.....   | 97  |
| 2.5.3.1.51 | Delete Deals .....   | 99  |
| 2.5.3.1.52 | Delete a Deal .....  | 100 |
| 2.5.3.1.53 | Create User.....   | 101 |
| 2.5.3.1.54 | Read a List of Users .....                                   | 102 |
| 2.5.3.1.55 | Read a User .....  | 103 |
| 2.5.3.1.56 | Delete Users .....   | 104 |
| 2.5.3.1.57 | Delete a User .....  | 105 |
| 2.5.3.1.58 | Create a Company .....                                       | 106 |
| 2.5.3.1.59 | Read a List Companies.....                                   | 107 |
| 2.5.3.1.60 | Read a Company .....   | 109 |
| 2.5.3.1.61 | Delete Companies.....  | 111 |
| 2.5.3.1.62 | Create a Group .....   | 112 |
| 2.5.3.1.63 | Read a List of Groups Associated with a Company.....         | 113 |
| 2.5.3.1.64 | Read a Group .....   | 115 |
| 2.5.3.1.65 | Update a Group.....  | 117 |
| 2.5.3.1.66 | Delete Groups .....  | 118 |
| 2.5.3.1.67 | Delete a Group .....   | 119 |
| 2.5.3.1.68 | Register a Device.....                                       | 120 |
| 2.5.3.1.69 | Read a List of Devices .....                                 | 121 |
| 2.5.3.1.70 | Update a Device .....  | 122 |
| 2.5.3.1.71 | Delete a Device .....  | 123 |
| 2.5.3.1.72 | Create a Custom Field .....                                  | 124 |
| 2.5.3.1.73 | Read a List of Custom Fields Associated with a Company ..... | 125 |
| 2.5.3.1.74 | Read a Custom Field .....                                    | 126 |

|            |  |     |
|------------|--|-----|
| 2.5.3.1.75 | Update a Custom Field .....                                | 127 |
| 2.5.3.1.76 | Delete Custom Fields .....                                 | 128 |
| 2.5.3.2    | Extended functions.....                                    | 129 |
| 2.5.3.2.1  | Synchronize Offline Data.....                              | 129 |
| 2.5.3.2.2  | Wipe-out a User Account.....                               | 131 |
| 2.5.3.2.3  | Read a List of Contact Groups From an External System..... | 132 |
| 2.5.3.2.4  | Import Person Contacts.....                                | 133 |
| 2.5.3.2.5  | Find Duplicates of Basicinfos.....                         | 135 |
| 2.5.3.2.6  | Get Conflicted Contacts .....                              | 136 |
| 2.5.3.2.7  | Merge Contact Data.....                                    | 137 |
| 2.5.3.2.8  | Share Contact With Group(s) .....                          | 139 |
| 2.5.3.2.9  | Assign User Roles .....                                    | 140 |
| 2.5.3.2.10 | Assign User Groups.....                                    | 142 |
| 2.5.3.2.11 | Reset User Password.....                                   | 144 |
| 2.5.3.2.12 | Change a User password .....                               | 145 |
| 2.6        | Error codes.....   | 146 |
| 3          | Index of tables.....                                       | 149 |
| 4          | Attachments .....  | 153 |

# 1 About this Document

This document describes the REST API of the interact.io platform. For basic understanding we distinguish 3 types of components:

1. The Trigger Device that triggers the actual event,
2. The Server and
3. The Device that is the end user application.

In the [Overview](#) chapter you will find a general overview of all provided API calls. Each of these API calls is documented in a chapter below. The documentation of each API call is based on a table format and is structured in the following way:

|                          |  |                   |           |
|--------------------------|--|-------------------|-----------|
| <b>Title</b>             | <The name of the API call>   |                   |           |
| <b>URL</b>               | <The URL structure – path only, no root url.>  |                   |           |
| <b>Header attributes</b> | <Header attributes with names and values>  |                   |           |
| <b>Method</b>            | <The request type - DELETE   GET   POST   PUT>   |                   |           |
| <b>URL parameters</b>    | <URL parameters if exist, specified in accordance with name mentioned in URL section>  |                   |           |
|                          | <Parameter name = Parameter data type>   | <Required marker> | <Example> |
| <b>Data</b>              | <Payload for POST and PUT requests with data types, optional attributes and nodes are in lighter color>  |                   |           |
| <b>Success response</b>  | <HTTP return code and response data with data types, optional attributes and nodes are in lighter color. The <i>entity</i> attribute contains the whole object.> |                   |           |
| <b>Error response</b>    | <Possible HTTP return codes and response data with data types, optional attributes and nodes are in lighter color>   |                   |           |
| <b>Code example</b>      | <AJAX example to make life easier and more predictable ;-)>  |                   |           |
| <b>Notes</b>             | <Section where all uncertainties and commentary go.>   |                   |           |

Table 1 API call documentation template

In case one of the sections does not apply to a particular API call, the table cell value is *none*.

## 2 API Specification

Note: The Server's root URL is <https://api.interact.io/v2>.

### 2.1 Prerequisites

The character set used for encoding response data and decoding request data is UTF-8.

### 2.2 General API Pattern

In general the following simple pattern is used in the API:

- Nouns are used as resource names.
- Verbs (http methods) are used to operate on entities.

CRUD (**C**reate-**R**ead-**U**ppdate-**D**ele) operations are represented by the http methods PUT, GET, POST and DELETE. Entities are defined by integer IDs.

| Resource          | PUT<br>create                     | GET<br>read                 | POST<br>update  | DELETE<br>delete                     |
|-------------------|-----------------------------------|-----------------------------|---|--------------------------------------|
| /v2/foos          | Create new foo                    | List foos                   | Bulk update foos  | Delete foos                          |
| /v2/foos/:id      | ERROR                             | Show foo                    | If exists update foo,<br>If not exists ERROR              | Delete foo if exists                 |
| /v2/foos/:id/bars | Create new bars associated to foo | Show bars associated to foo | Associate all bars to foo and replace former associations | Delete associations from foo to bars |

Table 2 General API pattern

In addition there are some extended functions available. These functions are represented by a query parameter named *cmd*.

The API is able to respond to GET requests in "JSON with padding" format (JSONP). This function is represented by a query parameter named *callback*. See <http://www.json-p.org/> for further informations.

### 2.3 Overview

| API call            | PUT | GET | POST | DELETE |
|---------------------|-----|-----|------|--------|
| /v2/activities      |     | X   |      |        |
| /v2/admin/companies | X   | X   |      | X      |

|                                      |   |   |   |   |
|--------------------------------------|---|---|---|---|
| /v2/admin/companies/:id              |   | X |   |   |
| /v2/admin/companies/:id/customFields |   | X |   |   |
| /v2/admin/companies/:id/groups       |   | X |   |   |
| /v2/admin/customFields               | X |   |   | X |
| /v2/admin/customFields/:id           |   | X | X |   |
| /v2/admin/groups                     | X |   |   | X |
| /v2/admin/groups/:id                 |   | X | X | X |
| /v2/admin/users                      | X | X |   | X |
| /v2/admin/users/:id                  |   | X | X | X |
| /v2/admin/users/:id/groups           |   |   | X |   |
| /v2/admin/users/:id/roles            |   |   | X |   |
| /v2/basicInfos                       | X |   |   |   |
| /v2/basicInfos/:id                   |   |   | X |   |
| /v2/cleanup                          |   | X |   |   |
| /v2/contacts                         | X | X | X | X |
| /v2/contacts/:id                     |   | X | X | X |
| /v2/contacts/:id/contacts            |   | X |   |   |
| /v2/contacts/:id/deals               |   | X |   |   |
| /v2/contacts/:id/interactions        |   | X |   |   |
| /v2/contacts/:id/notes               |   | X |   |   |
| /v2/contacts/:id/pictures            |   | X |   |   |
| /v2/contacts/:id/profiles            |   | X |   |   |
| /v2/contacts/:id/searchTerms         |   | X |   |   |
| /v2/contacts/:id/tags                |   | X |   |   |
| /v2/contacts/:id/tasks               |   | X |   |   |
| /v2/deals                            | X | X |   | X |
| /v2/deals/:id                        |   | X | X | X |



|                      |   |   |   |   |
|----------------------|---|---|---|---|
| /v2/devices          | X | X |   |   |
| /v2/devices/:id      |   |   | X | X |
| /v2/import           |   |   | X |   |
| /v2/interactions     | X | X |   |   |
| /v2/interactions/:id |   | X | X |   |
| /v2/login            |   |   | X |   |
| /v2/logout           |   |   | X |   |
| /v2/myAccount        |   |   | X |   |
| /v2/notes            | X | X |   | X |
| /v2/notes/:id        |   |   | X | X |
| /v2/pictures         | X |   |   | X |
| /v2/pictures/:id     |   | X | X | X |
| /v2/sync             |   | X |   |   |
| /v2/tags             |   | X |   |   |
| /v2/tasks            | X | X |   | X |
| /v2/tasks/:id        |   | X | X | X |
| /v2/taskLists        | X | X |   |   |
| /v2/taskLists/:id    |   | X | X | X |
| /v2/triggerDevices   | X | X |   |   |

Table 3 API call overview

## 2.4 Push Notifications (Server → Device)

### 2.4.1 Push an Interaction Notification

|                     |  |
|---------------------|--|
| <b>Title</b>        | Notify Device about interaction  |
| <b>Data</b>         | <pre>{   "type" : &lt;enum(call-incoming,call-outgoing,sms-incoming,sms-outgoing)&gt;,   "data" : &lt;alphanumeric&gt;,   "match" :     {       "contactId" : &lt;integer&gt;,       "contactName" : &lt;alphanumeric&gt;,       "contactType" : &lt;alphanumeric&gt;,       "basicInfoId" : &lt;integer&gt;     },   "tentatives" : [     {       "contactId" : &lt;integer&gt;,       "contactName" : &lt;alphanumeric&gt;,       "contactType" : &lt;alphanumeric&gt;,       "basicInfoId" : &lt;integer&gt;     }   ]   "interactionId" : &lt;integer&gt; }</pre>  |
| <b>Code example</b> | <pre>var ws = new WebSocket(   "ws://" + window.location.host + "/interact- server/socket?deviceId=s243df35fd6g43&amp;authToken=bTIgh4uUt5rj6T"); ws.onmessage = function(event) {   console.log(event.data); };</pre>   |
| <b>Notes</b>        | <p>This is actually not an API call but a push notification from the Server to the Device. To receive push notifications the Device must have established a websocket connection to the Server with the <i>deviceId</i> and a valid <i>authToken</i> as parameters.</p> <p>The attribute <i>match</i> is set only when <i>data</i> is associated to a known contact in the database.</p> <p>If <i>match</i> is not set, <i>tentatives</i> may be set. A tentative match may represent a contact. In this case all attributes of the tentative match will be set. If the tentative match represents a basicinfo not assigned to a contact, only the <i>tentatives[i].basicInfoId</i> attribute will be set and the <i>tentatives[i].contactName</i> attribute will be set to "Unknown".</p> |

Table 4 Push interaction notification

## 2.4.2 Push an Interaction Notification (via APN)

|              |  |
|--------------|--|
| <b>Title</b> | Notify Apple Device about interaction  |
| <b>Data</b>  | <pre>{   "aps" :   {     "alert" : &lt;alphanumeric&gt;   },   "data" : &lt;alphanumeric&gt;,   "type" : &lt;enum(call-incoming,call-outgoing,sms-incoming,sms-outgoing)&gt; }</pre>   |
| <b>Notes</b> | <p>This is actually not an API call but a push notification from the Server to an Apple Device. To receive push notifications the Device must have enabled Apple Push Notifications.</p> <p>The alert message has the following form:</p> <p>"&lt;Incoming   Outgoing&gt; &lt;call   chat message   email   sms&gt; &lt;from   to&gt;<br/>&lt;contactname (phonenumber)   phonenumber&gt;"</p> |

Table 5 Push interaction notification (via APN)

### 2.4.3 Push a Synchronize Hint Message

|                     |  |
|---------------------|--|
| <b>Title</b>        | Notify Device that cloud synchronization should be performed   |
| <b>Data</b>         | <pre>{   "message" : "cloud synchronization recommended",   "lastSyncTime" : &lt;integer&gt; }</pre>   |
| <b>Code example</b> | <pre>var ws = new WebSocket(   "ws://" + window.location.host + "/interact- server/socket?deviceId=s243df35fd6g43&amp;authToken=bTIgh4uUt5rj6T"); ws.onmessage = function(event) {   console.log(event.data); };</pre>   |
| <b>Notes</b>        | <p>This is actually not an API call but a push notification from the Server to the Device. To receive push notifications the Device must have established a websocket connection to the Server with the <i>deviceId</i> and a valid <i>authToken</i> as parameters.</p> <p>When a Device establishes a websocket connection the Server checks for changes in the cloud DB occurred since the last time the Device was synchronized. If there were no changes, no push notification is sent at all. Otherwise the server sends the last determined sync time of the Device in the <i>lastSyncTime</i> attribute. This time is represented by the number of milliseconds since the standard base time known as "the epoch", namely January 1, 1970, 00:00:00 GMT. Then the device is supposed to {Synchronize Offline Data}.</p> |

Table 6 Push synchronization hint

## 2.5 API Calls

### 2.5.1 Authentication

Authentication is required for all other API calls.

#### 2.5.1.1 Login

|                          |   |
|--------------------------|---|
| <b>Title</b>             | Login and authenticate for further API calls  |
| <b>URL</b>               | /v2/login   |
| <b>Header attributes</b> | none  |
| <b>Method</b>            | POST  |
| <b>URL parameters</b>    | none  |
| <b>Data</b>              | <pre>{   "username" : &lt;alphanumeric&gt;,   "password" : &lt;alphanumeric&gt;,   "scope" : &lt;enum(csr,device app, trigger app, web portal)&gt; }</pre>  |
| <b>Success response</b>  | <div>Code: 200 OK</div> <pre>{   "user" :   {     "id" : &lt;integer&gt;,     "active" : true,     "email" : &lt;alphanumeric&gt;,     "companyId" : &lt;integer&gt;,     "groups" :     [       {         "id" : &lt;integer&gt;,         "name" : &lt;alphanumeric&gt;       }     ],     "roles" : [&lt;alphanumeric&gt;]   },   "token" :   {     "authToken" : &lt;alphanumeric&gt;,     "expires" : &lt;integer&gt;   } }</pre> |
| <b>Error response</b>    | <div>Code: 400 BAD REQUEST</div> <div>Code: 401 UNAUTHORIZED</div> <pre>{"code" : &lt;integer&gt;, "error" : &lt;integer&gt;, "devmsg" : &lt;alphanumeric&gt;}</pre>  |
| <b>Code example</b>      | <pre>\$.ajax({   type : "POST",   url : "/v2/login",   dataType : "json",   contentType : "application/json",   data : JSON.stringify({     "username" : "test@interact.io",</pre>  |

|              |   |
|--------------|---|
|              | <pre>"password" : "iwonttellyou", "scope" : "device app" }), success : function(data) {   console.log(data); }, error : function(data) {   console.log(data); } });</pre>   |
| <b>Notes</b> | <p>The <i>authToken</i> returned can be used for further API calls and must be passed in the header attribute of the request. The <i>expires</i> field indicates the time when this token will be invalidated. This time is represented by the number of milliseconds since the standard base time known as "the epoch", namely January 1, 1970, 00:00:00 GMT. Note that the token will be renewed with every API call.</p> |

Table 7 Login

### 2.5.1.2 Logout

|                          |   |
|--------------------------|---|
| <b>Title</b>             | Logout and invalidate the authentication token  |
| <b>URL</b>               | /v2/logout  |
| <b>Header attributes</b> | none  |
| <b>Method</b>            | POST  |
| <b>URL parameters</b>    | none  |
| <b>Data</b>              | <pre>{   "authToken" : &lt;alphanumeric&gt; }</pre>   |
| <b>Success response</b>  | Code: 200 OK  |
|                          | <pre>{"code" : 200, "devmsg" : "success"}</pre>   |
| <b>Error response</b>    | Code: 400 BAD REQUEST   |
|                          | <pre>{"code" : &lt;integer&gt;, "error" : &lt;integer&gt;, "devmsg" : &lt;alphanumeric&gt;}</pre>   |
| <b>Code example</b>      | <pre>\$.ajax({   type : "POST",   url : "/v2/logout",   dataType : "json",   contentType : "application/json",   data : JSON.stringify({     "authToken" : "gfUH43trfdkjg34"   }),   success : function(data) {     console.log(data);   },   error : function(data) {     console.log(data);   } });</pre> |
| <b>Notes</b>             | none  |

Table 8 Logout

## 2.5.2 Trigger Device → Server

### 2.5.2.1 Trigger an Event

|                          |  |                  |                                     |
|--------------------------|--|------------------|-------------------------------------|
| <b>Title</b>             | Trigger an interaction event   |                  |                                     |
| <b>URL</b>               | /v2/interactions   |                  |                                     |
| <b>Header attributes</b> | <b>Attribute</b>   | <b>Required?</b> | <b>Example</b>                      |
|                          | triggerToken   | yes              | triggerToken=fSDAF8439fdsRdsfG5dfTf |
| <b>Method</b>            | PUT  |                  |                                     |
| <b>URL parameters</b>    | none   |                  |                                     |
| <b>Data</b>              | <pre>{   "data" : &lt;alphanumeric&gt;,   "externalSystem" :     {       "name" : &lt;alphanumeric&gt;,       "threadId" : &lt;alphanumeric&gt;,       "entityId" : &lt;alphanumeric&gt;     },   "receiverId" : &lt;alphanumeric&gt;,   "time" : &lt;integer&gt;,   "type" : &lt;enum(call-incoming,call-outgoing,email-incoming,email-outgoing,im-incoming,im-outgoing,sms-incoming,sms-outgoing)&gt; }</pre>                        |                  |                                     |
| <b>Success response</b>  | Code: 201 CREATED  |                  |                                     |
|                          | <pre>{"code" : 201, "entity" : &lt;interaction&gt;, "devmsg" : "success"}</pre>  |                  |                                     |
| <b>Error response</b>    | Code: 401 UNAUTHORIZED<br>Code: 400 BAD REQUEST  |                  |                                     |
|                          | <pre>{"code" : &lt;integer&gt;, "error" : &lt;integer&gt;, "devmsg" : &lt;alphanumeric&gt;}</pre>  |                  |                                     |
| <b>Code example</b>      | <pre>\$.ajax({   type : "PUT",   url : "/v2/interactions",   headers : {triggerToken : "fSDAF8439fdsRdsfG5dfTf"},   dataType : "json",   contentType : "application/json",   data : JSON.stringify({     "type" : "call-incoming",     "data" : "555-12345",     "receiverId" : "john.doe@interact.io",   }),   success : function(data) {     console.log(data);   },   error : function(data) {     console.log(data);   } });</pre> |                  |                                     |
| <b>Notes</b>             | <p>The given <i>triggerToken</i> must be a valid token retrieved by “Register a Trigger Device”, otherwise the error response will be sent. If the owner of the Trigger Device has registered another Device which is connected to the Server, this second Device will receive a notification about the trigger event. (see “Push an Interaction Notification”)</p>  |                  |                                     |



|  |   |
|--|---|
|  | <p>If the <i>externalSystem</i> entity is given at least one of <i>externalSystem.threadId</i> or <i>externalSystem.entityId</i> must be given. While the <i>threadId</i> is meant to reference the interaction parent (e.g. the im-conversation id) the <i>entityId</i> is meant to reference the concrete interaction message (e.g. im-message id) inside that parent.</p> <p>The <i>time</i> attribute defines when the event occurred. It is represented by the number of milliseconds since the standard base time known as "the epoch", namely January 1, 1970, 00:00:00 GMT.</p> |
|--|---|

Table 9 Trigger event

## 2.5.2.2 Register a Trigger Device

|                          |  |                  |                            |
|--------------------------|--|------------------|----------------------------|
| <b>Title</b>             | Register a new trigger device for interactions.  |                  |                            |
| <b>URL</b>               | /v2/triggerDevices   |                  |                            |
| <b>Header attributes</b> | <b>Attribute</b>   | <b>Required?</b> | <b>Example</b>             |
|                          | authToken  | Yes              | authToken=gfUH43trfdkjpg34 |
| <b>Method</b>            | PUT  |                  |                            |
| <b>URL Parameters</b>    | none   |                  |                            |
| <b>Data</b>              | <pre>{   "deviceId" : &lt;alphanumeric&gt; }</pre>   |                  |                            |
| <b>Success response</b>  | Code: 201 CREATED  |                  |                            |
|                          | <pre>{"code" : 201, "entity" : &lt;trigger-device&gt;, "devmsg" : "success"}</pre>   |                  |                            |
| <b>Error response</b>    | Code: 400 BAD REQUEST<br>Code: 401 UNAUTHORIZED<br>Code: 403 FORBIDDEN   |                  |                            |
|                          | <pre>{"code" : &lt;integer&gt;, "error" : &lt;integer&gt;, "devmsg" : &lt;alphanumeric&gt;}</pre>  |                  |                            |
| <b>Code example</b>      | <pre>\$.ajax({   type : "PUT",   url : "/v2/triggerDevices",   headers : {authToken : "gfUH43trfdkjpg34"},   dataType : "json",   contentType : "application/json",   data : JSON.stringify({     "deviceId" : "2155341-13582-5-38"   }),   success : function(data) {     console.log(data);   },   error : function(data) {     console.log(data);   } });</pre> |                  |                            |
| <b>Notes</b>             | <p>The <i>deviceId</i> should be the IMEI of the Trigger Device. The most important attribute of the returned trigger-device entity is the <i>triggerToken</i> attribute. This token represents a permanent token which allows the Trigger Device to sending notifications to the Server. See "Trigger an Event".</p>  |                  |                            |

Table 10 Register a trigger device

### 2.5.2.3 Read a Trigger Token

|                          |  |                  |                           |
|--------------------------|--|------------------|---------------------------|
| <b>Title</b>             | Read the trigger token for a registered trigger Device.  |                  |                           |
| <b>URL</b>               | /v2/triggerDevices?deviceId=id   |                  |                           |
| <b>Header attributes</b> | <b>Attribute</b>   | <b>Required?</b> | <b>Example</b>            |
|                          | authToken  | Yes              | authToken=gfUH43trfdkjg34 |
| <b>Method</b>            | GET  |                  |                           |
| <b>URL Parameters</b>    | <b>Attribute</b>   | <b>Required?</b> | <b>Example</b>            |
|                          | id : <alphanumeric>  | Yes              | deviceId=353092051071645  |
| <b>Data</b>              | None   |                  |                           |
| <b>Success response</b>  | Code: 200 OK   |                  |                           |
|                          | {"triggerToken" : <alphanumeric>}  |                  |                           |
| <b>Error response</b>    | Code: 400 BAD REQUEST<br>Code: 401 UNAUTHORIZED<br>Code: 403 FORBIDDEN   |                  |                           |
|                          | {"code" : <integer>, "error" : <integer>, "devmsg" : <alphanumeric>}   |                  |                           |
| <b>Code example</b>      | <pre>\$.ajax({   type : "GET",   url : "/v2/triggerDevices?deviceId=353092051071645",   headers : {authToken : "gfUH43trfdkjg34"},   dataType : "json",   contentType : "application/json",   success : function(data) {     console.log(data);   },   error : function(data) {     console.log(data);   } });</pre> |                  |                           |
| <b>Notes</b>             | The <i>deviceId</i> must be the id given when the trigger device was registered, e.g. the IMEI of the mobile phone.  |                  |                           |

Table 11 Read the Trigger Token of a Trigger Device

## 2.5.3 Device (Web Portal, CSR resp.) → Server

### 2.5.3.1 Basic CRUD functions

Basic CRUD functions are represented by the http methods PUT, GET, POST and DELETE.

#### 2.5.3.1.1 Read a List of Activities

|                          |   |                  |                           |
|--------------------------|---|------------------|---------------------------|
| <b>Title</b>             | Retrieve a list of activities   |                  |                           |
| <b>URL</b>               | /v2/activities?offset=:offset&limit=:limit&callback=:callback   |                  |                           |
| <b>Header attributes</b> | <b>Attribute</b>  | <b>Required?</b> | <b>Example</b>            |
|                          | authToken   | yes              | authToken=gfUH43trfdkjg34 |
| <b>Method</b>            | GET   |                  |                           |
| <b>URL parameters</b>    | <b>Parameter</b>  | <b>Required?</b> | <b>Example</b>            |
|                          | offset : <integer>  | no               | ?offset=5                 |
|                          | limit : <integer>   | no               | &limit=25                 |
|                          | callback : <string>   | no               | &callback=jsonpcballback  |
| <b>Data</b>              | none  |                  |                           |
| <b>Success response</b>  | Code: 200 OK  |                  |                           |
|                          | <pre>{   "totalLength" : &lt;integer&gt;,   "length" : &lt;integer&gt;,   "startIndex" : &lt;integer&gt;,   "data": [     {       "action" : enum(insert,update,delete),       "entity" :         {           "oldState" : &lt;object&gt;,           "newState" : &lt;object&gt;         },       "entityId" : &lt;integer&gt;,       "entityType" : enum(note,interaction),       "relatedTo" :         {           "id" : &lt;integer&gt;,           "displayName" : &lt;alphanumeric&gt;         },       "time" : &lt;integer&gt;     }   ] }</pre> |                  |                           |
| <b>Error response</b>    | Code: 401 UNAUTHORIZED  |                  |                           |
|                          | {"code" : 401, "error" : <integer>, "devmsg" : <alphanumeric>}  |                  |                           |
| <b>Code example</b>      | <pre>\$.ajax({   type : "GET",   url : "/v2/activities",   headers : {authToken : "gfUH43trfdkjg34"},   dataType : "json",   success : function(data) {</pre>   |                  |                           |

|              |  |
|--------------|--|
|              | <pre>console.log(data); }, error : function(data) {   console.log(data); } });</pre>   |
| <b>Notes</b> | <p>The <i>time</i> attribute holds the date when the activity was saved in the db. This date is represented by the number of milliseconds since the standard base time known as "the epoch", namely January 1, 1970, 00:00:00 GMT.</p> <p>According to the value of the <i>entityType</i> attribute the attributes <i>entity.oldState</i> and <i>entity.newState</i> will differ. E.g. if <i>entityType</i> is 'note' the state attributes will hold note objects.</p> <p>If <i>action</i> is 'delete' the <i>entity.newState</i> attribute will not be set. On the other hand if <i>action</i> is 'insert' the <i>entity.oldState</i> attribute will not be set.</p> <p>The <i>relatedTo</i> attribute represents the user who performed the action.</p> <p><i>offset</i> and <i>limit</i> parameters are used for pagination. If at least one of them is provided, the response will contain the start index and the according length.</p> |

Table 12 Activities list request

### 2.5.3.1.2 Create Person Contact

|                          |  |                  |                           |
|--------------------------|--|------------------|---------------------------|
| <b>Title</b>             | Create given person contact  |                  |                           |
| <b>URL</b>               | /v2/contacts   |                  |                           |
| <b>Header attributes</b> | <b>Attribute</b>   | <b>Required?</b> | <b>Example</b>            |
|                          | authToken  | yes              | authToken=gfUH43trfdkjg34 |
| <b>Method</b>            | PUT  |                  |                           |
| <b>URL parameters</b>    | none   |                  |                           |
| <b>Data</b>              | <pre>{   "contactType" : "person",   "title" : &lt;alphanumeric&gt;,   "lastName" : &lt;alphanumeric&gt;,   "firstName" : &lt;alphanumeric&gt;,   "middleName" : &lt;alphanumeric&gt;,   "gender" : &lt;enum(f,m)&gt;,   "profession" : &lt;alphanumeric&gt;,   "hot" : &lt;boolean&gt;,   "basicInfos" :     [{       "id" : &lt;integer&gt;,       "type" : &lt;enum(email,fax,mobile,phone,website)&gt;,       "subtype" : &lt;enum(home,work,other)&gt;,       "identifier" : &lt;alphanumeric&gt;,       "value" : &lt;alphanumeric&gt;,       "excluded" : &lt;boolean&gt;     }],   "addresses" :     [{       "id" : &lt;integer&gt;,       "addressLine1" : &lt;alphanumeric&gt;,       "addressLine2" : &lt;alphanumeric&gt;,       "addressLine3" : &lt;alphanumeric&gt;,       "addressType" : &lt;enum(home,work,other)&gt;,       "postCode" : &lt;alphanumeric&gt;,       "city" : &lt;alphanumeric&gt;,       "country" : &lt;alphanumeric&gt;     }],   "relatedTo" : [&lt;integer&gt;],   "tags" : [&lt;alphanumeric&gt;],   "searchTerms" : [&lt;alphanumeric&gt;],   "profiles" :     {       "facebook" :         {           "connected" : &lt;boolean&gt;,           "username" : &lt;alphanumeric&gt;,           "url" : &lt;alphanumeric&gt;         },       "aim" :         {           "connected" : &lt;boolean&gt;,           "username" : &lt;alphanumeric&gt;,           "url" : &lt;alphanumeric&gt;         },       "gplus" :         {           "connected" : &lt;boolean&gt;,           "username" : &lt;alphanumeric&gt;,           "url" : &lt;alphanumeric&gt;         },       "gtalk" :         {           "connected" : &lt;boolean&gt;,           "username" : &lt;alphanumeric&gt;,           "url" : &lt;alphanumeric&gt;         },       "icq" :     }</pre> |                  |                           |

|                         |  |
|-------------------------|--|
|                         | <pre> {   "connected" : &lt;boolean&gt;,   "username" : &lt;alphanumeric&gt;,   "url" : &lt;alphanumeric&gt; }, "jabber" : {   "connected" : &lt;boolean&gt;,   "username" : &lt;alphanumeric&gt;,   "url" : &lt;alphanumeric&gt; }, "linkedIn" : {   "connected" : &lt;boolean&gt;,   "username" : &lt;alphanumeric&gt;,   "url" : &lt;alphanumeric&gt; }, "skype" : {   "connected" : &lt;boolean&gt;,   "username" : &lt;alphanumeric&gt;,   "url" : &lt;alphanumeric&gt; }, "twitter" : {   "connected" : &lt;boolean&gt;,   "username" : &lt;alphanumeric&gt;,   "url" : &lt;alphanumeric&gt; }, "xing" : {   "connected" : &lt;boolean&gt;,   "username" : &lt;alphanumeric&gt;,   "url" : &lt;alphanumeric&gt; } } </pre> |
| <b>Success response</b> | Code: 201 CREATED  |
|                         | <pre> {"code" : 201, "entity" : &lt;contact&gt;, "devmsg" : "success"} </pre>  |
| <b>Error response</b>   | Code: 400 BAD REQUEST<br>Code: 401 UNAUTHORIZED<br>Code: 403 FORBIDDEN   |
|                         | <pre> {"code" : &lt;integer&gt;, "error" : &lt;integer&gt;, "devmsg" : &lt;alphanumeric&gt;} </pre>  |
| <b>Code example</b>     | <pre> \$.ajax({   type : "PUT",   url : "/v2/contacts",   headers : {authToken : "gfUH43trfdkjg34"},   dataType : "json",   contentType : "application/json",   data : JSON.stringify({     "firstName" : "John",     "contactType" : "person",     "basicInfos" : [{       "id" : 498,       "type" : "phone",       "value" : "02332667998"     }, {       "type" : "fax",       "value" : "023326670"     }, {       "type" : "website",       "identifier" : "instagram",       "value" : "http://instagram.com/instagram"     }   ] }),   success : function(data) {     console.log(data);   },   error : function(data) {     console.log(data);   } }); </pre>   |

|              |   |
|--------------|---|
|              | <pre>}<br/>});</pre>  |
| <b>Notes</b> | At least the <i>lastName</i> or <i>firstName</i> attribute has to be set. |

Table 13 Person creation



### 2.5.3.1.3 Create Organization Contact

|                          |   |                  |                           |
|--------------------------|---|------------------|---------------------------|
| <b>Title</b>             | Create given organization contact   |                  |                           |
| <b>URL</b>               | /v2/contacts  |                  |                           |
| <b>Header attributes</b> | <b>Attribute</b>  | <b>Required?</b> | <b>Example</b>            |
|                          | authToken   | yes              | authToken=gfUH43trfdkjg34 |
| <b>Method</b>            | PUT   |                  |                           |
| <b>URL parameters</b>    | none  |                  |                           |
| <b>Data</b>              | <pre>{   "contactType" : "organization",   "organizationName" : &lt;alphanumeric&gt;,   "business" : &lt;alphanumeric&gt;,   "hot" : &lt;boolean&gt;,   "basicInfos" :     [{       "id" : &lt;integer&gt;,       "type" : &lt;enum(email,fax,mobile,phone,website)&gt;,       "subtype" : &lt;enum(home,work,other)&gt;,       "identifier" : &lt;alphanumeric&gt;,       "value" : &lt;alphanumeric&gt;,       "excluded" : &lt;boolean&gt;     }],   "addresses" :     [{       "id" : &lt;integer&gt;,       "addressLine1" : &lt;alphanumeric&gt;,       "addressLine2" : &lt;alphanumeric&gt;,       "addressLine3" : &lt;alphanumeric&gt;,       "addressType" : &lt;enum(home,work,other)&gt;,       "postCode" : &lt;alphanumeric&gt;,       "city" : &lt;alphanumeric&gt;,       "country" : &lt;alphanumeric&gt;     }],   "relatedTo" : [&lt;integer&gt;],   "tags" : [&lt;alphanumeric&gt;],   "searchTerms" : [&lt;alphanumeric&gt;],   "profiles" :     {       "facebook" :         {           "connected" : &lt;boolean&gt;,           "username" : &lt;alphanumeric&gt;,           "url" : &lt;alphanumeric&gt;         },       "aim" :         {           "connected" : &lt;boolean&gt;,           "username" : &lt;alphanumeric&gt;,           "url" : &lt;alphanumeric&gt;         },       "gplus" :         {           "connected" : &lt;boolean&gt;,           "username" : &lt;alphanumeric&gt;,           "url" : &lt;alphanumeric&gt;         },       "gtalk" :         {           "connected" : &lt;boolean&gt;,           "username" : &lt;alphanumeric&gt;,           "url" : &lt;alphanumeric&gt;         },       "icq" :         {           "connected" : &lt;boolean&gt;,           "username" : &lt;alphanumeric&gt;,           "url" : &lt;alphanumeric&gt;         },       "jabber" :         { </pre> |                  |                           |

|                         |   |
|-------------------------|---|
|                         | <pre>         "connected" : &lt;boolean&gt;,         "username" : &lt;alphanumeric&gt;,         "url" : &lt;alphanumeric&gt;       },       "linkedIn" :       {         "connected" : &lt;boolean&gt;,         "username" : &lt;alphanumeric&gt;,         "url" : &lt;alphanumeric&gt;       },       "skype" :       {         "connected" : &lt;boolean&gt;,         "username" : &lt;alphanumeric&gt;,         "url" : &lt;alphanumeric&gt;       },       "twitter" :       {         "connected" : &lt;boolean&gt;,         "username" : &lt;alphanumeric&gt;,         "url" : &lt;alphanumeric&gt;       },       "xing" :       {         "connected" : &lt;boolean&gt;,         "username" : &lt;alphanumeric&gt;,         "url" : &lt;alphanumeric&gt;       }     }   } } </pre> |
| <b>Success response</b> | Code: 201 CREATED   |
|                         | <pre> {"code" : 201, "entity" : &lt;contact&gt;, "devmsg" : "success"} </pre>   |
| <b>Error response</b>   | Code: 400 BAD REQUEST<br>Code: 401 UNAUTHORIZED<br>Code: 403 FORBIDDEN  |
|                         | <pre> {"code" : &lt;integer&gt;, "error" : &lt;integer&gt;, "devmsg" : &lt;alphanumeric&gt;} </pre>   |
| <b>Code example</b>     | <pre> \$.ajax({   type : "PUT",   url : "/v2/contacts",   headers : { authToken : "gfUH43trfdkkg34" },   dataType : "json",   contentType : "application/json",   data : JSON.stringify({     "organizationName" : "xaimed",     "contactType" : "organization",     "basicInfos" : [{       "id" : 498,       "type" : "phone",       "value" : "02332667998"     }, {       "type" : "fax",       "value" : "023326670"     }   ] }),   success : function(data) {     console.log(data);   },   error : function(data) {     console.log(data);   } }); </pre>   |
| <b>Notes</b>            | At least <i>organizationName</i> attribute has to be set.   |

Table 14 Organization creation

#### 2.5.3.1.4 Read a List of Contacts

|                          |  |                  |                            |
|--------------------------|--|------------------|----------------------------|
| <b>Title</b>             | Retrieve a list of contacts  |                  |                            |
| <b>URL</b>               | /v2/contacts?projection=:proj&offset=:offset&limit=:limit&callback=:callback   |                  |                            |
| <b>Header attributes</b> | <b>Attribute</b>   | <b>Required?</b> | <b>Example</b>             |
|                          | authToken  | yes              | authToken=gfUH43trfdkjpg34 |
| <b>Method</b>            | GET  |                  |                            |
| <b>URL parameters</b>    | <b>Parameter</b>   | <b>Required?</b> | <b>Example</b>             |
|                          | proj : <enum(thin,base,flat)>  | no               | ?projection=thin           |
|                          | offset : <integer>   | no               | &offset=5                  |
|                          | limit : <integer>  | no               | &limit=25                  |
|                          | callback : <string>  | no               | &callback=jsonpcallback    |
| <b>Data</b>              | none   |                  |                            |
| <b>Success response</b>  | Code: 200 OK   |                  |                            |
|                          | <pre>{   "data" : [&lt;contact&gt;],   "length" : &lt;integer&gt;,   "startIndex" : &lt;integer&gt;,   "totalLength" : &lt;integer&gt; }</pre>   |                  |                            |
| <b>Error response</b>    | Code: 400 BAD REQUEST<br>Code: 401 UNAUTHORIZED<br>Code: 403 FORBIDDEN   |                  |                            |
|                          | <pre>{"code" : &lt;integer&gt;, "error" : &lt;integer&gt;, "devmsg" : &lt;alphanumeric&gt;}</pre>  |                  |                            |
| <b>Code example</b>      | <pre>\$.ajax({   type : "GET",   url : "/v2/contacts?offset=5&amp;limit=10",   headers : { authToken : "gfUH43trfdkjpg34" },   dataType : "json",   success : function(data) {     console.log(data);   },   error : function(data) {     console.log(data);   } });</pre>   |                  |                            |
| <b>Notes</b>             | <p><i>offset</i> and <i>limit</i> parameters are used for pagination. If both are specified, the response will contain according <i>length</i> and <i>startIndex</i> attributes as well as an additional <i>totalLength</i> attribute to indicate whether there are more contacts available.</p> <p>If <i>projection</i> is not specified the default is <i>base</i>.</p> <p>If <i>projection</i> is <i>thin</i>, the <i>extra</i> attribute of the contact objects contains the organization name if <i>contactType</i> is <i>person</i> and the person contact is member of EXACTLY one organization. It contains the number of organizations if <i>contactType</i> is <i>person</i> and the person contact is member of MORE THAN one organizations. Vice</p> |                  |                            |

|  |  |
|--|--|
|  | <p>versa, it contains the person name if <i>contactType</i> is organization and the organization contact has EXACTLY one person contact assigned to it – or contains the number of person contacts if <i>contactType</i> is organization and the organization has MORE THAN one person contacts assigned to it. The attribute is not defined or empty if neither of the conditions above matches.</p> <p>If projection is <i>base</i>, the contact objects are returned as described in <a href="#">Read a Person Contact</a>, <a href="#">Read an Organization Contact</a> resp.</p> <p>Otherwise, if projection is <i>flat</i> the return data is very similar to projection <i>base</i> but more flatten.</p> |
|--|--|

Table 15 Contact list request

### 2.5.3.1.5 Read a List of Contacts Associated with a Contact

|                          |  |                  |                           |
|--------------------------|--|------------------|---------------------------|
| <b>Title</b>             | Retrieve a list of contacts related to a particular contact  |                  |                           |
| <b>URL</b>               | /v2/contacts/:id/contacts?projection=:proj&callback=:callback  |                  |                           |
| <b>Header attributes</b> | <b>Attribute</b>   | <b>Required?</b> | <b>Example</b>            |
|                          | authToken  | yes              | authToken=gfUH43trfdkjg34 |
| <b>Method</b>            | GET  |                  |                           |
| <b>URL parameters</b>    | <b>Parameter</b>   | <b>Required?</b> | <b>Example</b>            |
|                          | id : <integer>   | yes              | /23/                      |
|                          | proj : <enum(thin,base,flat)>  | no               | ?projection=thin          |
|                          | callback : <string>  | no               | &callback=jsonpcallback   |
| <b>Data</b>              | none   |                  |                           |
| <b>Success response</b>  | Code: 200 OK   |                  |                           |
|                          | { "data" : [<contact>] }   |                  |                           |
| <b>Error response</b>    | Code: 400 BAD REQUEST<br>Code: 401 UNAUTHORIZED<br>Code: 403 FORBIDDEN   |                  |                           |
|                          | { "code" : <integer>, "error" : <integer>, "devmsg" : <alphanumeric> }   |                  |                           |
| <b>Code example</b>      | <pre>\$.ajax({   type : "GET",   url : "/v2/contacts/23/contacts?projection=thin",   headers : {authToken : "gfUH43trfdkjg34"},   dataType : "json",   success : function(data) {     console.log(data);   },   error : function(data) {     console.log(data);   } });</pre>  |                  |                           |
| <b>Notes</b>             | <p>If <i>projection</i> is not specified the default is <i>base</i>.</p> <p>If <i>projection</i> is <i>thin</i>, the <i>extra</i> attribute of the contact objects contains the organization name if <i>contactType</i> is <i>person</i> and the person contact is member of EXACTLY one organization. It contains the number of organizations if <i>contactType</i> is <i>person</i> and the person contact is member of MORE THAN one organizations. Vice versa, it contains the person name if <i>contactType</i> is <i>organization</i> and the organization contact has EXACTLY one person contact assigned to it – or contains the number of person contacts if <i>contactType</i> is <i>organization</i> and the organization</p> |                  |                           |

|  |   |
|--|---|
|  | <p>has MORE THAN one person contacts assigned to it. The attribute is not defined or empty if neither of the conditions above matches.</p> <p>If projection is <i>base</i>, the contact objects are returned as described in <a href="#">Read a Person Contact</a>, <a href="#">Read an Organization Contact</a> resp.</p> <p>Otherwise, if projection is <i>flat</i> the return data is very similar to projection <i>base</i> but more flatten.</p> |
|--|---|

Table 16 Contacts list request - associated with another contact

### 2.5.3.1.6 Read a Person Contact

|                          |  |                  |                           |
|--------------------------|--|------------------|---------------------------|
| <b>Title</b>             | Retrieve detail information of a person contact  |                  |                           |
| <b>URL</b>               | /v2/contacts/:id?projection=:proj&callback=:callback   |                  |                           |
| <b>Header attributes</b> | <b>Attribute</b>   | <b>Required?</b> | <b>Example</b>            |
|                          | authToken  | yes              | authToken=gfUH43trfdkjg34 |
| <b>Method</b>            | GET  |                  |                           |
| <b>URL parameters</b>    | <b>Parameter</b>   | <b>Required?</b> | <b>Example</b>            |
|                          | id : <integer>   | yes              | /47                       |
|                          | proj : <enum(thin,base,flat)>  | no               | ?projection=base          |
|                          | callback : <string>  | no               | &callback=jsonpcallback   |
| <b>Data</b>              | none   |                  |                           |
| <b>Success response</b>  | Code: 200 OK   |                  |                           |
|                          | Content for projection <i>base</i> :<br><br><pre>{   "id" : &lt;integer&gt;,   "version" : &lt;integer&gt;,   "contactType" : "person",   "title" : &lt;alphanumeric&gt;,   "lastName" : &lt;alphanumeric&gt;,   "firstName" : &lt;alphanumeric&gt;,   "middleName" : &lt;alphanumeric&gt;,   "profession" : &lt;alphanumeric&gt;,   "gender" : &lt;enum(m,f)&gt;,   "hot" : &lt;boolean&gt;,   "basicInfos" :     [{       "id" : &lt;integer&gt;,       "type" : &lt;enum(email,fax,mobile,phone,website)&gt;,       "subtype" : &lt;enum(home,work,other)&gt;,       "identifier" : &lt;alphanumeric&gt;,       "value" : &lt;alphanumeric&gt;,       "excluded" : &lt;boolean&gt;     }],   "addresses" :     [{       "id" : &lt;integer&gt;,       "addressLine1" : &lt;alphanumeric&gt;,       "addressLine2" : &lt;alphanumeric&gt;,       "addressLine3" : &lt;alphanumeric&gt;,       "addressType" : &lt;enum(home,work,other)&gt;,       "postCode" : &lt;alphanumeric&gt;,       "city" : &lt;alphanumeric&gt;,       "country" : &lt;alphanumeric&gt;     }],   "deals" : [&lt;integer&gt;],   "notes" : [&lt;integer&gt;],   "tags" : [&lt;alphanumeric&gt;],   "tasks" : [&lt;integer&gt;],   "interactions" : [&lt;integer&gt;],   "relatedTo" : [&lt;integer&gt;],   "pictures" :     [{       "type" : &lt;alphanumeric&gt;,       "url" : &lt;alphanumeric&gt;     }],   "searchTerms" : [&lt;alphanumeric&gt;],   "profiles" :     {       "facebook" :</pre> |                  |                           |

|                |  |
|----------------|--|
|                | <pre> {   "connected" : &lt;boolean&gt;,   "username" : &lt;alphanumeric&gt;,   "url" : &lt;alphanumeric&gt; }, "aim" : {   "connected" : &lt;boolean&gt;,   "username" : &lt;alphanumeric&gt;,   "url" : &lt;alphanumeric&gt; }, "gplus" : {   "connected" : &lt;boolean&gt;,   "username" : &lt;alphanumeric&gt;,   "url" : &lt;alphanumeric&gt; }, "gtalk" : {   "connected" : &lt;boolean&gt;,   "username" : &lt;alphanumeric&gt;,   "url" : &lt;alphanumeric&gt; }, "icq" : {   "connected" : &lt;boolean&gt;,   "username" : &lt;alphanumeric&gt;,   "url" : &lt;alphanumeric&gt; }, "jabber" : {   "connected" : &lt;boolean&gt;,   "username" : &lt;alphanumeric&gt;,   "url" : &lt;alphanumeric&gt; }, "linkedIn" : {   "connected" : &lt;boolean&gt;,   "username" : &lt;alphanumeric&gt;,   "url" : &lt;alphanumeric&gt; }, "skype" : {   "connected" : &lt;boolean&gt;,   "username" : &lt;alphanumeric&gt;,   "url" : &lt;alphanumeric&gt; }, "twitter" : {   "connected" : &lt;boolean&gt;,   "username" : &lt;alphanumeric&gt;,   "url" : &lt;alphanumeric&gt; }, "xing" : {   "connected" : &lt;boolean&gt;,   "username" : &lt;alphanumeric&gt;,   "url" : &lt;alphanumeric&gt; } } </pre> |
| Error response | <p>Code: 400 BAD REQUEST</p> <p>Code: 401 UNAUTHORIZED</p> <p>Code: 403 FORBIDDEN</p>  |
|                | <pre> {"code" : &lt;integer&gt;, "error" : &lt;integer&gt;, "devmsg" : &lt;alphanumeric&gt;} </pre>  |
| Code example   | <pre> \$.ajax({   type : "GET",   url : "/v2/contacts/47",   headers : {authToken : "gfUH43trfdkjg34"},   dataType : "json",   success : function(data) {     console.log(data);   }, </pre>   |



|              |   |
|--------------|---|
|              | <pre>error : function(data) {<br/>  console.log(data);<br/>}<br/>});</pre>  |
| <b>Notes</b> | <p>The attributes <i>deals</i>, <i>notes</i>, <i>tasks</i>, <i>interactions</i> and <i>relatedTo</i> contain comma-separated lists of ids.</p> <p>At least the <i>lastName</i> or <i>firstName</i> attribute will be set.</p> <p>The structure for attribute <i>picture</i> depends on the value of the <i>projection</i> http query parameter:</p> <ul style="list-style-type: none"><li>• base: "pictures" : [{"type" : &lt;alphanumeric&gt;,"url" : &lt;alphanumeric&gt;}]</li><li>• flat: "pictures" : [&lt;alphanumeric&gt;]</li><li>• thin: "picture" : &lt;alphanumeric&gt;</li></ul> <p>When projection <i>thin</i> is used, the <i>picture</i> attribute holds the default picture only.</p> |

Table 17 Preson contact request

### 2.5.3.1.7 Read an Organization Contact

|                          |   |                  |                           |
|--------------------------|---|------------------|---------------------------|
| <b>Title</b>             | Retrieve detail information of an organization contact  |                  |                           |
| <b>URL</b>               | /v2/contacts/:id?projection=:proj&callback=:callback  |                  |                           |
| <b>Header attributes</b> | <b>Attribute</b>  | <b>Required?</b> | <b>Example</b>            |
|                          | authToken   | yes              | authToken=gfUH43trfdkjg34 |
| <b>Method</b>            | GET   |                  |                           |
| <b>URL parameters</b>    | <b>Parameter</b>  | <b>Required?</b> | <b>Example</b>            |
|                          | id : <integer>  | yes              | /22                       |
|                          | proj : <enum(thin,base,flat)>   | no               | ?projection=base          |
|                          | callback : <string>   | no               | &callback=jsonpcallback   |
| <b>Data</b>              | none  |                  |                           |
| <b>Success response</b>  | Code: 200 OK  |                  |                           |
|                          | <p>Content for projection <i>base</i>:</p> <pre>{   "id" : &lt;integer&gt;,   "version" : &lt;integer&gt;,   "contactType" : "organization",   "organizationName" : &lt;alphanumeric&gt;,   "business" : &lt;alphanumeric&gt;,   "hot" : &lt;boolean&gt;,   "basicInfos" :     [{       "id" : &lt;integer&gt;,       "type" : &lt;enum(email,fax,mobile,phone,website)&gt;,       "subtype" : &lt;enum(home,work,other)&gt;,       "identifier" : &lt;alphanumeric&gt;,       "value" : &lt;alphanumeric&gt;,       "excluded" : &lt;boolean&gt;     }],   "addresses" :     [{       "id" : &lt;integer&gt;,       "addressLine1" : &lt;alphanumeric&gt;,       "addressLine2" : &lt;alphanumeric&gt;,       "addressLine3" : &lt;alphanumeric&gt;,       "addressType" : &lt;enum(home,work,other)&gt;,       "postCode" : &lt;alphanumeric&gt;,       "city" : &lt;alphanumeric&gt;,       "country" : &lt;alphanumeric&gt;     }],   "deals" : [&lt;integer&gt;],   "notes" : [&lt;integer&gt;],   "tags" : [&lt;alphanumeric&gt;],   "tasks" : [&lt;integer&gt;],   "interactions" : [&lt;integer&gt;],   "relatedTo" : [&lt;integer&gt;],   "pictures" :     [{       "type" : &lt;alphanumeric&gt;,       "url" : &lt;alphanumeric&gt;     }],   "searchTerms" : [&lt;alphanumeric&gt;],   "profiles" :     {       "facebook" :         {           "connected" : &lt;boolean&gt;,           "username" : &lt;alphanumeric&gt;,           "url" : &lt;alphanumeric&gt;         }     } }</pre> |                  |                           |

|                |   |
|----------------|---|
|                | <pre>     },     "aim" :     {         "connected" : &lt;boolean&gt;,         "username" : &lt;alphanumeric&gt;,         "url" : &lt;alphanumeric&gt;     },     "gplus" :     {         "connected" : &lt;boolean&gt;,         "username" : &lt;alphanumeric&gt;,         "url" : &lt;alphanumeric&gt;     },     "gtalk" :     {         "connected" : &lt;boolean&gt;,         "username" : &lt;alphanumeric&gt;,         "url" : &lt;alphanumeric&gt;     },     "icq" :     {         "connected" : &lt;boolean&gt;,         "username" : &lt;alphanumeric&gt;,         "url" : &lt;alphanumeric&gt;     },     "jabber" :     {         "connected" : &lt;boolean&gt;,         "username" : &lt;alphanumeric&gt;,         "url" : &lt;alphanumeric&gt;     },     "linkedIn" :     {         "connected" : &lt;boolean&gt;,         "username" : &lt;alphanumeric&gt;,         "url" : &lt;alphanumeric&gt;     },     "skype" :     {         "connected" : &lt;boolean&gt;,         "username" : &lt;alphanumeric&gt;,         "url" : &lt;alphanumeric&gt;     },     "twitter" :     {         "connected" : &lt;boolean&gt;,         "username" : &lt;alphanumeric&gt;,         "url" : &lt;alphanumeric&gt;     },     "xing" :     {         "connected" : &lt;boolean&gt;,         "username" : &lt;alphanumeric&gt;,         "url" : &lt;alphanumeric&gt;     } } </pre> |
| Error response | <p>Code: 400 BAD REQUEST</p> <p>Code: 401 UNAUTHORIZED</p> <p>Code: 403 FORBIDDEN</p>   |
|                | <pre> {"code" : &lt;integer&gt;, "error" : &lt;integer&gt;, "devmsg" : &lt;alphanumeric&gt;} </pre>   |
| Code example   | <pre> \$.ajax({   type : "GET",   url : "/v2/contacts/22",   headers : {authToken : "gfUH43trfdkjg34"},   dataType : "json",   success : function(data) {     console.log(data);   },   error : function(data) {     console.log(data);   } }); </pre>  |

|              |   |
|--------------|---|
| <b>Notes</b> | <p>The attributes <i>deals</i>, <i>notes</i>, <i>tasks</i>, <i>interactions</i> and <i>relatedTo</i> contain comma-separated lists of ids.</p> <p>The structure for attribute <i>picture</i> depends on the value of the <i>projection</i> http query parameter:</p> <ul style="list-style-type: none"><li>• base: "pictures" : [{"type" : &lt;alphanumeric&gt;, "url" : &lt;alphanumeric&gt;}]</li><li>• flat: "pictures" : [&lt;alphanumeric&gt;]</li><li>• thin: "picture" : &lt;alphanumeric&gt;</li></ul> <p>When projection <i>thin</i> is used, the <i>picture</i> attribute holds the first picture only.</p> |
|--------------|---|

Table 18 Organization request

### 2.5.3.1.8 Update a Person Contact

|                          |  |                  |                           |
|--------------------------|--|------------------|---------------------------|
| <b>Title</b>             | Update a particular person contact   |                  |                           |
| <b>URL</b>               | /v2/contacts/:id   |                  |                           |
| <b>Header attributes</b> | <b>Attribute</b>   | <b>Required?</b> | <b>Example</b>            |
|                          | authToken  | Yes              | authToken=gfUH43trfdkjg34 |
| <b>Method</b>            | POST   |                  |                           |
| <b>URL parameters</b>    | <b>Parameter</b>   | <b>Required?</b> | <b>Example</b>            |
|                          | id : <integer>   | yes              | /285                      |
| <b>Data</b>              | <pre>{   "version" : &lt;integer&gt;,   "title" : &lt;alphanumeric&gt;,   "lastName" : &lt;alphanumeric&gt;,   "firstName" : &lt;alphanumeric&gt;,   "gender" : &lt;enum(f,m)&gt;,   "middleName" : &lt;alphanumeric&gt;,   "profession" : &lt;alphanumeric&gt;,   "hot" : &lt;boolean&gt;,   "basicInfos" :   [     {       "id" : &lt;integer&gt;,       "type" : &lt;enum(email,fax,mobile,phone,website)&gt;,       "subtype" : &lt;enum(home,work,other)&gt;,       "identifier" : &lt;alphanumeric&gt;,       "value" : &lt;alphanumeric&gt;,       "excluded" : &lt;boolean&gt;     }   ],   "addresses" :   [     {       "id" : &lt;integer&gt;,       "addressLine1" : &lt;alphanumeric&gt;,       "addressLine2" : &lt;alphanumeric&gt;,       "addressLine3" : &lt;alphanumeric&gt;,       "addressType" : &lt;enum(home,work,other)&gt;,       "postCode" : &lt;alphanumeric&gt;,       "city" : &lt;alphanumeric&gt;,       "country" : &lt;alphanumeric&gt;     }   ],   "relatedTo" : [&lt;integer&gt;],   "tags" : [&lt;alphanumeric &gt;],   "searchTerms" : [&lt;alphanumeric &gt;],   "profiles" :   {     "facebook" :     {       "connected" : &lt;boolean&gt;,       "username" : &lt;alphanumeric&gt;,       "url" : &lt;alphanumeric&gt;     },     "aim" :     {       "connected" : &lt;boolean&gt;,       "username" : &lt;alphanumeric&gt;,       "url" : &lt;alphanumeric&gt;     },     "gplus" :     {       "connected" : &lt;boolean&gt;,       "username" : &lt;alphanumeric&gt;,       "url" : &lt;alphanumeric&gt;     },     "gtalk" :     {       "connected" : &lt;boolean&gt;,       "username" : &lt;alphanumeric&gt;,       "url" : &lt;alphanumeric&gt;     }   } }</pre> |                  |                           |

|                  |  |
|------------------|--|
|                  | <pre> "icq" : {   "connected" : &lt;boolean&gt;,   "username" : &lt;alphanumeric&gt;,   "url" : &lt;alphanumeric&gt; }, "jabber" : {   "connected" : &lt;boolean&gt;,   "username" : &lt;alphanumeric&gt;,   "url" : &lt;alphanumeric&gt; }, "linkedIn" : {   "connected" : &lt;boolean&gt;,   "username" : &lt;alphanumeric&gt;,   "url" : &lt;alphanumeric&gt; }, "skype" : {   "connected" : &lt;boolean&gt;,   "username" : &lt;alphanumeric&gt;,   "url" : &lt;alphanumeric&gt; }, "twitter" : {   "connected" : &lt;boolean&gt;,   "username" : &lt;alphanumeric&gt;,   "url" : &lt;alphanumeric&gt; }, "xing" : {   "connected" : &lt;boolean&gt;,   "username" : &lt;alphanumeric&gt;,   "url" : &lt;alphanumeric&gt; } } </pre> |
| Success response | Code: 200 OK   |
|                  | <pre>{"code" : 200, "entity" : &lt;contact&gt;, "devmsg" : "success"}</pre>  |
| Error response   | Code: 400 BAD REQUEST<br>Code: 401 UNAUTHORIZED<br>Code: 403 FORBIDDEN<br>Code: 409 CONFLICT   |
|                  | <pre>{"code" : &lt;integer&gt;, "error" : &lt;integer&gt;, "devmsg" : &lt;alphanumeric&gt;}</pre>  |
| Code example     | <pre> \$.ajax({   type : "POST",   url : "/v2/contacts/285",   headers : {authToken : "gfUH43trfdkjpg34"},   dataType : "json",   contentType : "application/json",   data : JSON.stringify({     "version" : 12,     "firstName" : "Remo",     "basicInfos" : [{       "id" : 46,       "type" : "mobile",       "value" : "+4917134455667"     }, {       "type" : "phone",       "value" : "033056434239"     }, {       "type" : "website",       "value" : "http://instagram.com/instagram",       "identifier" : "instagram"     }]   }) }), success : function(data) {   console.log(data); } </pre>  |

|              |  |
|--------------|--|
|              | <pre>    },<br/>    error : function(data) {<br/>        console.log(data);<br/>    }<br/>});</pre>  |
| <b>Notes</b> | <p>Attribute values of <i>basicInfo.type</i> and <i>basicInfo.value</i> must not be empty (and thus are not allowed to be deleted).</p> <p>Updating <i>firstName</i> and <i>lastName</i> to an empty string is also not allowed.</p> <p>In the case of a version conflict the error response is a 409 Conflict with the devmsg "version conflict".</p> |

Table 19 Person update

### 2.5.3.1.9 Update an Organization Contact

|                          |  |                  |                           |
|--------------------------|--|------------------|---------------------------|
| <b>Title</b>             | Update a particular organization contact   |                  |                           |
| <b>URL</b>               | /v2/contacts/:id   |                  |                           |
| <b>Header attributes</b> | <b>Attribute</b>   | <b>Required?</b> | <b>Example</b>            |
|                          | authToken  | yes              | authToken=gfUH43trfdkjg34 |
| <b>Method</b>            | POST   |                  |                           |
| <b>URL parameters</b>    | <b>Parameter</b>   | <b>Required?</b> | <b>Example</b>            |
|                          | id : <integer>   | yes              | /1243                     |
| <b>Data</b>              | <pre>{   "version" : &lt;integer&gt;,   "name" : &lt;alphanumeric&gt;,   "business" : &lt;alphanumeric&gt;,   "hot" : &lt;boolean&gt;,   "basicInfos" :     [{       "id" : &lt;integer&gt;,       "type" : &lt;enum(email,fax,mobile,phone,website)&gt;,       "subtype" : &lt;enum(home,work,other)&gt;,       "identifier" : &lt;alphanumeric&gt;,       "value" : &lt;alphanumeric&gt;,       "excluded" : &lt;boolean&gt;     }],   "addresses" :     [{       "id" : &lt;integer&gt;,       "addressLine1" : &lt;alphanumeric&gt;,       "addressLine2" : &lt;alphanumeric&gt;,       "addressLine3" : &lt;alphanumeric&gt;,       "addressType" : &lt;enum(home,work,other)&gt;,       "postCode" : &lt;alphanumeric&gt;,       "city" : &lt;alphanumeric&gt;,       "country" : &lt;alphanumeric&gt;     }],   "relatedTo" : [&lt;integer&gt;],   "tags" : [&lt;alphanumeric&gt;],   "searchTerms" : [&lt;alphanumeric&gt;],   "profiles" :     {       "facebook" :         {           "connected" : &lt;boolean&gt;,           "username" : &lt;alphanumeric&gt;,           "url" : &lt;alphanumeric&gt;         },       "aim" :         {           "connected" : &lt;boolean&gt;,           "username" : &lt;alphanumeric&gt;,           "url" : &lt;alphanumeric&gt;         },       "gplus" :         {           "connected" : &lt;boolean&gt;,           "username" : &lt;alphanumeric&gt;,           "url" : &lt;alphanumeric&gt;         },       "gtalk" :         {           "connected" : &lt;boolean&gt;,           "username" : &lt;alphanumeric&gt;,           "url" : &lt;alphanumeric&gt;         },       "icq" :         {           "connected" : &lt;boolean&gt;, </pre> |                  |                           |



|                  |   |
|------------------|---|
|                  | <pre>         "username" : &lt;alphanumeric&gt;,         "url" : &lt;alphanumeric&gt;       },       "jabber" :       {         "connected" : &lt;boolean&gt;,         "username" : &lt;alphanumeric&gt;,         "url" : &lt;alphanumeric&gt;       },       "linkedIn" :       {         "connected" : &lt;boolean&gt;,         "username" : &lt;alphanumeric&gt;,         "url" : &lt;alphanumeric&gt;       },       "skype" :       {         "connected" : &lt;boolean&gt;,         "username" : &lt;alphanumeric&gt;,         "url" : &lt;alphanumeric&gt;       },       "twitter" :       {         "connected" : &lt;boolean&gt;,         "username" : &lt;alphanumeric&gt;,         "url" : &lt;alphanumeric&gt;       },       "xing" :       {         "connected" : &lt;boolean&gt;,         "username" : &lt;alphanumeric&gt;,         "url" : &lt;alphanumeric&gt;       }     }   } } </pre> |
| Success response | Code: 200 OK  |
|                  | <pre> {"code" : 200, "entity" : &lt;contact&gt;, "devmsg" : "success"} </pre>   |
| Error response   | Code: 400 BAD REQUEST<br>Code: 401 UNAUTHORIZED<br>Code: 403 FORBIDDEN<br>Code: 409 CONFLICT  |
|                  | <pre> {"code" : &lt;integer&gt;, "error" : &lt;integer&gt;, "devmsg" : &lt;alphanumeric&gt;} </pre>   |
| Code example     | <pre> \$.ajax({   type : "POST",   url : /v2/contacts/1243 ",   headers : {authToken : "gfUH43trfdkjg34"},   dataType : "json",   contentType : "application/json",   data : JSON.stringify({     "version" : 21,     "name" : "TU Berlin",     "basicInfos" : [{       "id" : 189,       "type" : " phone",       "value" : "0303140"     }]   }),   success : function(data) {     console.log(data);   },   error : function(data) {     console.log(data);   } }); </pre>   |
| Notes            | Attribute values of <i>basicInfo.type</i> and <i>basicInfo.value</i> must not be empty (and thus are not allowed to be deleted).  |

|  |   |
|--|---|
|  | Updating <i>organizationName</i> to an empty string is also not allowed.<br>In the case that of a version conflict the error response is a 409 Conflict with the devmsg "version conflict". |
|--|---|

Table 20 Organization update

### 2.5.3.1.10 Delete Contacts

|                          |   |                  |                           |
|--------------------------|---|------------------|---------------------------|
| <b>Title</b>             | Delete contacts with the given ids  |                  |                           |
| <b>URL</b>               | /v2/contacts?ids=:ids   |                  |                           |
| <b>Header attributes</b> | <b>Attribute</b>  | <b>Required?</b> | <b>Example</b>            |
|                          | authToken   | yes              | authToken=gfUH43trfdkjg34 |
| <b>Method</b>            | DELETE  |                  |                           |
| <b>URL parameters</b>    | <b>Parameter</b>  | <b>Required?</b> | <b>Example</b>            |
|                          | ids : [<integer>]   | Yes              | ids=1,3,45,6              |
| <b>Data</b>              | none  |                  |                           |
| <b>Success response</b>  | Code: 200 OK  |                  |                           |
|                          | {"code" : 204, "devmsg" : "success"}  |                  |                           |
| <b>Error response</b>    | Code: 400 BAD REQUEST<br>Code: 401 UNAUTHORIZED<br>Code: 403 FORBIDDEN  |                  |                           |
|                          | {"code" : <integer>, "error" : <integer>, "devmsg" : <alphanumeric>}  |                  |                           |
| <b>Code example</b>      | <pre>\$.ajax({   type : "DELETE",   url : "/v2/contacts?ids=1,3,45,6",   headers : {authToken : "gfUH43trfdkjg34"},   dataType : "json",   success : function(data) {     console.log(data);   },   error : function(data) {     console.log(data);   } });</pre> |                  |                           |
| <b>Notes</b>             | none  |                  |                           |

Table 21 Contact(s) deletion

### 2.5.3.1.11 Delete a Contact

|                          |   |                  |                           |
|--------------------------|---|------------------|---------------------------|
| <b>Title</b>             | Delete a particular person or organization contact  |                  |                           |
| <b>URL</b>               | /v2/contacts/:id  |                  |                           |
| <b>Header attributes</b> | <b>Attribute</b>  | <b>Required?</b> | <b>Example</b>            |
|                          | authToken   | yes              | authToken=gfUH43trfdkjg34 |
| <b>Method</b>            | DELETE  |                  |                           |
| <b>URL parameters</b>    | <b>Parameter</b>  | <b>Required?</b> | <b>Example</b>            |
|                          | id : <integer>  | yes              | /12                       |
| <b>Data</b>              | none  |                  |                           |
| <b>Success response</b>  | Code: 200 OK  |                  |                           |
|                          | { "code" : 204, "devmsg" : "success" }  |                  |                           |
| <b>Error response</b>    | Code: 400 BAD REQUEST<br>Code: 401 UNAUTHORIZED<br>Code: 403 FORBIDDEN  |                  |                           |
|                          | { "code" : <integer>, "error" : <integer>, "devmsg" : <alphanumeric> }  |                  |                           |
| <b>Code example</b>      | <pre>\$.ajax({   type : "DELETE",   url : "/v2/contacts/12",   headers : {authToken : "gfUH43trfdkjg34"},   dataType : "json",   success : function(data) {     console.log(data);   },   error : function(data) {     console.log(data);   } });</pre> |                  |                           |
| <b>Notes</b>             | none  |                  |                           |

Table 22 Contact deletion

### 2.5.3.1.12 Upload a contact picture

|                          |   |                  |                           |
|--------------------------|---|------------------|---------------------------|
| <b>Title</b>             | Provides uploading pictures for contacts  |                  |                           |
| <b>URL</b>               | /v2/pictures  |                  |                           |
| <b>Header attributes</b> | <b>Attribute</b>  | <b>Required?</b> | <b>Example</b>            |
|                          | authToken   | yes              | authToken=gfUH43trfdkjg34 |
| <b>Method</b>            | PUT   |                  |                           |
| <b>URL parameters</b>    | none  |                  |                           |
| <b>Data</b>              | <pre>{   "contactId" : &lt;integer&gt;,   "base64" : &lt;base64string&gt;,   "isDefault" : &lt;boolean&gt; }</pre>  |                  |                           |
| <b>Success response</b>  | Code: 200 OK  |                  |                           |
|                          | {"code" : 201, "devmsg" : "success", "entity" : <picture>}  |                  |                           |
| <b>Error response</b>    | Code: 400 BAD REQUEST<br>Code: 401 UNAUTHORIZED<br>Code: 403 FORBIDDEN  |                  |                           |
|                          | {"code" : <integer>, "error" : <integer>, "devmsg" : <alphanumeric>}  |                  |                           |
| <b>Code example</b>      | <pre>\$.ajax({   type : "PUT",   url : "/v2/pictures",   headers : {authToken : "gfUH43trfdkjg34"},   dataType : "json",   data : JSON.stringify({     "contactId" : 41,     "base64" : "DDgF4g833gSq3FKl9d8lEWshf+rh1//9k="   }),   success : function(data) {     console.log(data);   },   error : function(data) {     console.log(data);   } });</pre> |                  |                           |
| <b>Notes</b>             | none  |                  |                           |

Table 23 Picture upload

### 2.5.3.1.13 Read a Picture

|                          |   |                  |                                 |
|--------------------------|---|------------------|---------------------------------|
| <b>Title</b>             | Retrieve data of a particular picture   |                  |                                 |
| <b>URL</b>               | /v2/pictures/:id?callback=:callback   |                  |                                 |
| <b>Header attributes</b> | <b>Attribute</b>  | <b>Required?</b> | <b>Example</b>                  |
|                          | authToken   | yes              | authToken=gfUH43trfdkjg34       |
| <b>Method</b>            | GET   |                  |                                 |
| <b>URL parameters</b>    | <b>Parameter</b>  | <b>Required?</b> | <b>Example</b>                  |
|                          | id : <integer><br>callback : <string>   | Yes<br>No        | /751<br>?callback=jsonpcallback |
| <b>Data</b>              | none  |                  |                                 |
| <b>Success response</b>  | Code: 200 OK  |                  |                                 |
|                          | <pre>{   "id" : &lt;integer&gt;,   "isDefault" : &lt;boolean&gt;,   "type" : &lt;enum(facebook,google,gravatar,interact,twitter)&gt;,   "url" : &lt;alphanumeric&gt; }</pre>  |                  |                                 |
| <b>Error response</b>    | Code: 400 BAD REQUEST<br>Code: 401 UNAUTHORIZED<br>Code: 403 FORBIDDEN  |                  |                                 |
|                          | <pre>{"code" : &lt;integer&gt;, "error" : &lt;integer&gt;, "devmsg" : &lt;alphanumeric&gt;}</pre>   |                  |                                 |
| <b>Code example</b>      | <pre>\$.ajax({   type : "GET",   url : "/v2/pictures/751",   headers : {authToken : "gfUH43trfdkjg34"},   dataType : "json",   success : function(data) {     console.log(data);   },   error : function(data) {     console.log(data);   } });</pre> |                  |                                 |
| <b>Notes</b>             | none  |                  |                                 |

Table 24 Picture request

### 2.5.3.1.14 Read a List of Pictures Associated with a Contact

|                          |   |                  |                                   |
|--------------------------|---|------------------|-----------------------------------|
| <b>Title</b>             | Retrieve a list of pictures associated with a particular contact  |                  |                                   |
| <b>URL</b>               | /v2/contacts/:id/pictures?callback=:callback  |                  |                                   |
| <b>Header attributes</b> | <b>Attribute</b>  | <b>Required?</b> | <b>Example</b>                    |
|                          | authToken   | yes              | authToken=gfUH43trfdkjg34         |
| <b>Method</b>            | GET   |                  |                                   |
| <b>URL parameters</b>    | <b>Parameter</b>  | <b>Required?</b> | <b>Example</b>                    |
|                          | id : <integer><br>callback : <string>   | Yes<br>No        | /23/<br>?callback=myjsonpcallback |
| <b>Data</b>              | none  |                  |                                   |
| <b>Success response</b>  | Code: 200 OK  |                  |                                   |
|                          | <pre>[{   "id" : &lt;integer&gt;,   "isDefault" : &lt;boolean&gt;,   "type" : &lt;alphanumeric&gt;,   "url" : &lt;alphanumeric&gt; }]</pre>   |                  |                                   |
| <b>Error response</b>    | Code: 400 BAD REQUEST<br>Code: 401 UNAUTHORIZED<br>Code: 403 FORBIDDEN  |                  |                                   |
|                          | <pre>{"code" : &lt;integer&gt;, "error" : &lt;integer&gt;, "devmsg" : &lt;alphanumeric&gt;}</pre>   |                  |                                   |
| <b>Code example</b>      | <pre>\$.ajax({   type : "GET",   url : "/v2/contacts/23/pictures",   headers : {authToken : "gfUH43trfdkjg34"},   dataType : "json",   success : function(data) {     console.log(data);   },   error : function(data) {     console.log(data);   } });</pre> |                  |                                   |
| <b>Notes</b>             | none  |                  |                                   |

Table 25 Picture list request – associated with a contact

### 2.5.3.1.15 Update a contact picture

|                          |   |                  |                           |
|--------------------------|---|------------------|---------------------------|
| <b>Title</b>             | Allows updating pictures for contacts   |                  |                           |
| <b>URL</b>               | /v2/pictures/:id  |                  |                           |
| <b>Header attributes</b> | <b>Attribute</b>  | <b>Required?</b> | <b>Example</b>            |
|                          | authToken   | yes              | authToken=gfUH43trfdkjg34 |
| <b>Method</b>            | POST  |                  |                           |
| <b>URL parameters</b>    | <b>Parameter</b>  | <b>Required?</b> | <b>Example</b>            |
|                          | id : <integer>  | yes              | /85                       |
| <b>Data</b>              | <pre>{   "base64" : &lt;base64string&gt;,   "isDefault" : &lt;boolean&gt; }</pre>   |                  |                           |
| <b>Success response</b>  | Code: 200 OK  |                  |                           |
|                          | {"code" : 200, "devmsg" : "success", "entity" : <picture>}  |                  |                           |
| <b>Error response</b>    | Code: 400 BAD REQUEST<br>Code: 401 UNAUTHORIZED<br>Code: 403 FORBIDDEN  |                  |                           |
|                          | {"code" : <integer>, "error" : <integer>, "devmsg" : <alphanumeric>}  |                  |                           |
| <b>Code example</b>      | <pre>\$.ajax({   type : "POST",   url : "/v2/pictures/85",   headers : {authToken : "gfUH43trfdkjg34"},   dataType : "json",   data : JSON.stringify({     "base64" : "DDgF4g833gSq3FKl9d8lEWshf+rh1//9k="   }),   success : function(data) {     console.log(data);   },   error : function(data) {     console.log(data);   } });</pre> |                  |                           |
| <b>Notes</b>             | If the picture specified by the given id is not an uploaded picture but a picture from an external system (e.g. facebook, twitter, ...) the <i>base64</i> attribute must not be given.  |                  |                           |

Table 26 Picture update



### 2.5.3.1.16 Delete Pictures

|                          |  |                  |                           |
|--------------------------|--|------------------|---------------------------|
| <b>Title</b>             | Delete pictures with the given ids   |                  |                           |
| <b>URL</b>               | /v2/pictures?ids=:ids  |                  |                           |
| <b>Header attributes</b> | <b>Attribute</b>   | <b>Required?</b> | <b>Example</b>            |
|                          | authToken  | yes              | authToken=gfUH43trfdkjg34 |
| <b>Method</b>            | DELETE   |                  |                           |
| <b>URL parameters</b>    | <b>Parameter</b>   | <b>Required?</b> | <b>Example</b>            |
|                          | ids : [<integer>]  | Yes              | ids=12,435,98             |
| <b>Data</b>              | none   |                  |                           |
| <b>Success response</b>  | Code: 200 OK   |                  |                           |
|                          | { "code" : 204, "devmsg" : "success" }   |                  |                           |
| <b>Error response</b>    | Code: 400 BAD REQUEST<br>Code: 401 UNAUTHORIZED<br>Code: 403 FORBIDDEN   |                  |                           |
|                          | { "code" : <integer>, "error" : <integer>, "devmsg" : <alphanumeric> }   |                  |                           |
| <b>Code example</b>      | <pre>\$.ajax({   type : "DELETE",   url : "/v2/pictures?ids=12,435,98",   headers : {authToken : "gfUH43trfdkjg34"},   dataType : "json",   success : function(data) {     console.log(data);   },   error : function(data) {     console.log(data);   } });</pre> |                  |                           |
| <b>Notes</b>             | If any picture specified by the ids parameter is not an uploaded picture but a picture from an external system (e.g. facebook, twitter, ...) it can not be deleted.  |                  |                           |

Table 27 Pictures deletion

### 2.5.3.1.17 Delete Picture

|                          |   |                  |                           |
|--------------------------|---|------------------|---------------------------|
| <b>Title</b>             | Delete a particular picture   |                  |                           |
| <b>URL</b>               | /v2/pictures/:id  |                  |                           |
| <b>Header attributes</b> | <b>Attribute</b>  | <b>Required?</b> | <b>Example</b>            |
|                          | authToken   | yes              | authToken=gfUH43trfdkjg34 |
| <b>Method</b>            | DELETE  |                  |                           |
| <b>URL parameters</b>    | <b>Parameter</b>  | <b>Required?</b> | <b>Example</b>            |
|                          | id : <integer>  | Yes              | /98                       |
| <b>Data</b>              | none  |                  |                           |
| <b>Success response</b>  | Code: 200 OK  |                  |                           |
|                          | { "code" : 204, "devmsg" : "success" }  |                  |                           |
| <b>Error response</b>    | Code: 400 BAD REQUEST<br>Code: 401 UNAUTHORIZED<br>Code: 403 FORBIDDEN  |                  |                           |
|                          | { "code" : <integer>, "error" : <integer>, "devmsg" : <alphanumeric> }  |                  |                           |
| <b>Code example</b>      | <pre>\$.ajax({   type : "DELETE",   url : "/v2/pictures/98",   headers : {authToken : "gfUH43trfdkjg34"},   dataType : "json",   success : function(data) {     console.log(data);   },   error : function(data) {     console.log(data);   } });</pre> |                  |                           |
| <b>Notes</b>             | If the picture specified by the id parameter is not an uploaded picture but a picture from an external system (e.g. facebook, twitter, ...) it can not be deleted.  |                  |                           |

Table 28 Picture deletion

### 2.5.3.1.18 Create Note Associated with a Contact

|                          |   |                  |                           |
|--------------------------|---|------------------|---------------------------|
| <b>Title</b>             | Create given note   |                  |                           |
| <b>URL</b>               | /v2/notes   |                  |                           |
| <b>Header attributes</b> | <b>Attribute</b>  | <b>Required?</b> | <b>Example</b>            |
|                          | authToken   | yes              | authToken=gfUH43trfdkjg34 |
| <b>Method</b>            | PUT   |                  |                           |
| <b>URL parameters</b>    | <b>Parameter</b>  | <b>Required?</b> | <b>Example</b>            |
|                          | id : <integer>  | yes              | /312/                     |
| <b>Data</b>              | <pre>{   "message" : &lt;alphanumeric&gt;,   "relatedTo" :     {       "id" : &lt;integer&gt;,       "type" : "contact"     } }</pre>   |                  |                           |
| <b>Success response</b>  | Code: 201 CREATED   |                  |                           |
|                          | {"code" : 201, "entity" : <note>, "devmsg" : "success"}   |                  |                           |
| <b>Error response</b>    | Code: 400 BAD REQUEST<br>Code: 401 UNAUTHORIZED<br>Code: 403 FORBIDDEN  |                  |                           |
|                          | {"code" : <integer>, "error" : <integer>, "devmsg" : <alphanumeric>}  |                  |                           |
| <b>Code example</b>      | <pre>\$.ajax({   type : "PUT",   url : "/v2/notes",   headers : {authToken : "gfUH43trfdkjg34"},   dataType : "json",   contentType : "application/json",   data : JSON.stringify({     "message" : "deadline postponed",     "relatedTo" : {       "id" : 327,       "type" : "contact"     }   }) }, success : function(data) {   console.log(data); }, error : function(data) {   console.log(data); } });</pre> |                  |                           |
| <b>Notes</b>             | none  |                  |                           |

Table 29 Notes creation

### 2.5.3.1.19 Read a List of Notes

|                          |   |                  |                           |
|--------------------------|---|------------------|---------------------------|
| <b>Title</b>             | Retrieve a list of all notes created by the system user   |                  |                           |
| <b>URL</b>               | /v2/notes?callback=:callback  |                  |                           |
| <b>Header attributes</b> | <b>Attribute</b>  | <b>Required?</b> | <b>Example</b>            |
|                          | authToken   | yes              | authToken=gfUH43trfdkjg34 |
| <b>Method</b>            | GET   |                  |                           |
| <b>URL parameters</b>    | <b>Parameter</b>  | <b>Required?</b> | <b>Example</b>            |
|                          | callback : <string>   | no               | ?callback=jsonpcallback   |
| <b>Data</b>              | none  |                  |                           |
| <b>Success response</b>  | Code: 200 OK  |                  |                           |
|                          | <pre>[{   "id" : &lt;integer&gt;,   "timestamp" : &lt;integer&gt;,   "message" : &lt;alphanumeric&gt;,   "relatedTo" :     {       "id" : &lt;integer&gt;,       "type" : &lt;enum(contact,deal)&gt;,       "displayName" : &lt;alphanumeric&gt;     } }]</pre> |                  |                           |
| <b>Error response</b>    | Code: 401 UNAUTHORIZED  |                  |                           |
|                          | Code: 403 FORBIDDEN   |                  |                           |
|                          | {"code" : <integer>, "error" : <integer>, "devmsg" : <alphanumeric>}  |                  |                           |
| <b>Code example</b>      | <pre>\$.ajax({   type : "GET",   url : "/v2/notes",   headers : {authToken : "gfUH43trfdkjg34"},   dataType : "json",   success : function(data) {     console.log(data);   },   error : function(data) {     console.log(data);   } });</pre>                  |                  |                           |
| <b>Notes</b>             | The <i>timestamp</i> attribute holds the date when the note was last updated. This date is represented by the number of milliseconds since the standard base time known as "the epoch", namely January 1, 1970, 00:00:00 GMT.                                   |                  |                           |

Table 30 Note list request

### 2.5.3.1.20 Read a List of Notes Associated with a Contact

|                          |  |                  |                                 |
|--------------------------|--|------------------|---------------------------------|
| <b>Title</b>             | Retrieve a list of notes associated with a particular contact  |                  |                                 |
| <b>URL</b>               | /v2/contacts/:id/notes?callback=:callback  |                  |                                 |
| <b>Header attributes</b> | <b>Attribute</b>   | <b>Required?</b> | <b>Example</b>                  |
|                          | authToken  | yes              | authToken=gfUH43trfdkjg34       |
| <b>Method</b>            | GET  |                  |                                 |
| <b>URL parameters</b>    | <b>Parameter</b>   | <b>Required?</b> | <b>Example</b>                  |
|                          | id : <integer><br>callback : <string>  | Yes<br>no        | /23/<br>?callback=jsonpcallback |
| <b>Data</b>              | none   |                  |                                 |
| <b>Success response</b>  | Code: 200 OK   |                  |                                 |
|                          | <pre>[{   "id" : &lt;integer&gt;,   "timestamp" : &lt;integer&gt;,   "message" : &lt;alphanumeric&gt; }]</pre>   |                  |                                 |
| <b>Error response</b>    | Code: 400 BAD REQUEST<br>Code: 401 UNAUTHORIZED<br>Code: 403 FORBIDDEN   |                  |                                 |
|                          | <pre>{"code" : &lt;integer&gt;, "error" : &lt;integer&gt;, "devmsg" : &lt;alphanumeric&gt;}</pre>  |                  |                                 |
| <b>Code example</b>      | <pre>\$.ajax({   type : "GET",   url : "/v2/contacts/23/notes",   headers : {authToken : "gfUH43trfdkjg34"},   dataType : "json",   success : function(data) {     console.log(data);   },   error : function(data) {     console.log(data);   } });</pre> |                  |                                 |
| <b>Notes</b>             | The <i>timestamp</i> attribute holds the date when the note was last updated. This date is represented by the number of milliseconds since the standard base time known as "the epoch", namely January 1, 1970, 00:00:00 GMT.                              |                  |                                 |

Table 31 Note list request – associated with a contact

### 2.5.3.1.21 Update a Note

|                          |   |                  |                           |
|--------------------------|---|------------------|---------------------------|
| <b>Title</b>             | Update a particular note  |                  |                           |
| <b>URL</b>               | /v2/notes/:id   |                  |                           |
| <b>Header attributes</b> | <b>Attribute</b>  | <b>Required?</b> | <b>Example</b>            |
|                          | authToken   | yes              | authToken=gfUH43trfdkjg34 |
| <b>Method</b>            | POST  |                  |                           |
| <b>URL parameters</b>    | <b>Parameter</b>  | <b>Required?</b> | <b>Example</b>            |
|                          | id : <integer>  | yes              | /184                      |
| <b>Data</b>              | <pre>{   "message" : &lt;alphanumeric&gt; }</pre>   |                  |                           |
| <b>Success response</b>  | Code: 200 OK  |                  |                           |
|                          | {"code" : 200, "entity" : <note>, "devmsg" : "success"}   |                  |                           |
| <b>Error response</b>    | Code: 400 BAD REQUEST<br>Code: 401 UNAUTHORIZED<br>Code: 403 FORBIDDEN  |                  |                           |
|                          | {"code" : <integer>, "error" : <integer>, "devmsg" : <alphanumeric>}  |                  |                           |
| <b>Code example</b>      | <pre>\$.ajax({   type : "POST",   url : "/v2/notes/184",   headers : {authToken : "gfUH43trfdkjg34"},   dataType : "json",   contentType : "application/json",   data : JSON.stringify({     "message" : "Don't forget to ask for address data."   }),   success : function(data) {     console.log(data);   },   error : function(data) {     console.log(data);   } });</pre> |                  |                           |
| <b>Notes</b>             | none  |                  |                           |

Table 32 Note update

### 2.5.3.1.22 Delete Notes

|                          |  |                  |                           |
|--------------------------|--|------------------|---------------------------|
| <b>Title</b>             | Delete notes with the given ids  |                  |                           |
| <b>URL</b>               | /v2/notes?ids=:ids   |                  |                           |
| <b>Header attributes</b> | <b>Attribute</b>   | <b>Required?</b> | <b>Example</b>            |
|                          | authToken  | yes              | authToken=gfUH43trfdkjg34 |
| <b>Method</b>            | DELETE   |                  |                           |
| <b>URL parameters</b>    | <b>Parameter</b>   | <b>Required?</b> | <b>Example</b>            |
|                          | ids : [<integer>]  | Yes              | ids=12,435,98             |
| <b>Data</b>              | none   |                  |                           |
| <b>Success response</b>  | Code: 200 OK   |                  |                           |
|                          | { "code" : 204, "devmsg" : "success" }   |                  |                           |
| <b>Error response</b>    | Code: 400 BAD REQUEST<br>Code: 401 UNAUTHORIZED<br>Code: 403 FORBIDDEN   |                  |                           |
|                          | { "code" : <integer>, "error" : <integer>, "devmsg" : <alphanumeric> }   |                  |                           |
| <b>Code example</b>      | <pre>\$.ajax({   type : "DELETE",   url : "/v2/notes?ids=1,3,45,6",   headers : {authToken : "gfUH43trfdkjg34"},   dataType : "json",   success : function(data) {     console.log(data);   },   error : function(data) {     console.log(data);   } });</pre> |                  |                           |
| <b>Notes</b>             | none   |                  |                           |

Table 33 Notes deletion

### 2.5.3.1.23 Delete a Note

|                          |  |                  |                           |
|--------------------------|--|------------------|---------------------------|
| <b>Title</b>             | Delete a particular note.  |                  |                           |
| <b>URL</b>               | /v2/notes/:id  |                  |                           |
| <b>Header attributes</b> | <b>Attribute</b>   | <b>Required?</b> | <b>Example</b>            |
|                          | authToken  | yes              | authToken=gfUH43trfdkjg34 |
| <b>Method</b>            | DELETE   |                  |                           |
| <b>URL parameters</b>    | <b>Parameter</b>   | <b>Required?</b> | <b>Example</b>            |
|                          | id : <integer>   | yes              | /12                       |
| <b>Data</b>              | none   |                  |                           |
| <b>Success response</b>  | Code: 200 OK   |                  |                           |
|                          | { "code" : 204, "devmsg" : "success" }   |                  |                           |
| <b>Error response</b>    | Code: 400 BAD REQUEST<br>Code: 401 UNAUTHORIZED<br>Code: 403 FORBIDDEN   |                  |                           |
|                          | { "code" : <integer>, "error" : <integer>, "devmsg" : <alphanumeric> }   |                  |                           |
| <b>Code example</b>      | <pre>\$.ajax({   type : "DELETE",   url : "/v2/notes/12",   headers : {authToken : "gfUH43trfdkjg34"},   dataType : "json",   success : function(data) {     console.log(data);   },   error : function(data) {     console.log(data);   } });</pre> |                  |                           |
| <b>Notes</b>             | none   |                  |                           |

Table 34 Note deletion



### 2.5.3.1.24 Read a List of Profiles Associated with a Contact

|                          |   |                  |                                  |
|--------------------------|---|------------------|----------------------------------|
| <b>Title</b>             | Retrieve a list of social profiles and IMs associated with a particular contact   |                  |                                  |
| <b>URL</b>               | /v2/contacts/:id/profiles?callback=:callback  |                  |                                  |
| <b>Header attributes</b> | <b>Attribute</b>  | <b>Required?</b> | <b>Example</b>                   |
|                          | authToken   | yes              | authToken=gfUH43trfdkjg34        |
| <b>Method</b>            | GET   |                  |                                  |
| <b>URL parameters</b>    | <b>Parameter</b>  | <b>Required?</b> | <b>Example</b>                   |
|                          | id : <integer><br>callback : <string>   | Yes<br>No        | /471/<br>?callback=jsonpcallback |
| <b>Data</b>              | None  |                  |                                  |
| <b>Success response</b>  | Code: 200 OK  |                  |                                  |
|                          | <pre>{   "facebook" :   {     "connected" : &lt;boolean&gt;,     "username" : &lt;alphanumeric&gt;,     "url" : &lt;alphanumeric&gt;   },   "aim" :   {     "connected" : &lt;boolean&gt;,     "username" : &lt;alphanumeric&gt;,     "url" : &lt;alphanumeric&gt;   },   "gplus" :   {     "connected" : &lt;boolean&gt;,     "username" : &lt;alphanumeric&gt;,     "url" : &lt;alphanumeric&gt;   },   "gtalk" :   {     "connected" : &lt;boolean&gt;,     "username" : &lt;alphanumeric&gt;,     "url" : &lt;alphanumeric&gt;   },   "icq" :   {     "connected" : &lt;boolean&gt;,     "username" : &lt;alphanumeric&gt;,     "url" : &lt;alphanumeric&gt;   },   "jabber" :   {     "connected" : &lt;boolean&gt;,     "username" : &lt;alphanumeric&gt;,     "url" : &lt;alphanumeric&gt;   },   "linkedIn" :   {     "connected" : &lt;boolean&gt;,     "username" : &lt;alphanumeric&gt;,     "url" : &lt;alphanumeric&gt;   },   "skype" :   {     "connected" : &lt;boolean&gt;,     "username" : &lt;alphanumeric&gt;,     "url" : &lt;alphanumeric&gt;   }, }</pre> |                  |                                  |

|                |   |
|----------------|---|
|                | <pre> "twitter" : {   "connected" : &lt;boolean&gt;,   "username" : &lt;alphanumeric&gt;,   "url" : &lt;alphanumeric&gt; }, "xing" : {   "connected" : &lt;boolean&gt;,   "username" : &lt;alphanumeric&gt;,   "url" : &lt;alphanumeric&gt; } } </pre>            |
| Error response | <p>Code: 400 BAD REQUEST</p> <p>Code: 401 UNAUTHORIZED</p> <p>Code: 403 FORBIDDEN</p>   |
|                | <pre> {"code" : &lt;integer&gt;, "error" : &lt;integer&gt;, "devmsg" : &lt;alphanumeric&gt;} </pre>   |
| Code example   | <pre> \$.ajax({   type : "GET",   url : "/v2/contacts/471/profiles",   headers : {authToken : "gfUH43trfdkjpg34"},   dataType : "json",   success : function(data) {     console.log(data);   },   error : function(data) {     console.log(data);   } }); </pre> |
| Notes          | none  |

Table 35 Profiles list request – associated with a contact

### 2.5.3.1.25 Read a List of Search Terms Associated with a Contact

|                          |  |                  |                                 |
|--------------------------|--|------------------|---------------------------------|
| <b>Title</b>             | Retrieve a list of search terms associated with a particular contact   |                  |                                 |
| <b>URL</b>               | /v2/contacts/:id/searchTerms?callback=:callback  |                  |                                 |
| <b>Header attributes</b> | <b>Attribute</b>   | <b>Required?</b> | <b>Example</b>                  |
|                          | authToken  | yes              | authToken=gfUH43trfdkjg34       |
| <b>Method</b>            | GET  |                  |                                 |
| <b>URL parameters</b>    | <b>Parameter</b>   | <b>Required?</b> | <b>Example</b>                  |
|                          | id : <integer><br>callback : <string>  | Yes<br>No        | /65/<br>?callback=jsonpcallback |
| <b>Data</b>              | none   |                  |                                 |
| <b>Success response</b>  | Code: 200 OK   |                  |                                 |
|                          | [<alphanumeric>]   |                  |                                 |
| <b>Error response</b>    | Code: 400 BAD REQUEST<br>Code: 401 UNAUTHORIZED<br>Code: 403 FORBIDDEN   |                  |                                 |
|                          | { "code" : <integer>, "error" : <integer>, "devmsg" : <alphanumeric> }   |                  |                                 |
| <b>Code example</b>      | <pre>\$.ajax({   type : "GET",   url : "/v2/contacts/65/searchTerms",   headers : {authToken : "gfUH43trfdkjg34"},   dataType : "json",   success : function(data) {     console.log(data);   },   error : function(data) {     console.log(data);   } });</pre> |                  |                                 |
| <b>Notes</b>             | none   |                  |                                 |

Table 36 Search term list request – associated with a contact

### 2.5.3.1.26 Read a List of Tags

|  |   |                  |                           |
|--|---|------------------|---------------------------|
| <b>Title</b>                               | Retrieve a list of all tags used by the system user   |                  |                           |
| <b>URL</b>                                 | /v2/tags?callback=:callback   |                  |                           |
| <b>Header attributes</b>                   | <b>Attribute</b>  | <b>Required?</b> | <b>Example</b>            |
|  | authToken   | yes              | authToken=gfUH43trfdkjg34 |
| <b>Method</b>                              | GET   |                  |                           |
| <b>URL parameters</b>                      | <b>Parameter</b>  | <b>Required?</b> | <b>Example</b>            |
|  | callback : <string>   | no               | ?callback=jsonpcallback   |
| <b>Data</b>                                | none  |                  |                           |
| <b>Success response</b>                    | Code: 200 OK  |                  |                           |
| <b>Success response<br/>Error response</b> | [<alphanumeric>]  |                  |                           |
|  | Code: 401 UNAUTHORIZED<br>Code: 403 FORBIDDEN   |                  |                           |
| <b>Error response<br/>Code example</b>     | { "code" : <integer>, "error" : <integer>, "devmsg" : <alphanumeric> }  |                  |                           |
|  | <pre>\$.ajax({   type : "GET",   url : "/v2/tags",   headers : {authToken : "gfUH43trfdkjg34"},   dataType : "json",   success : function(data) {     console.log(data);   },   error : function(data) {     console.log(data);   } });</pre> |                  |                           |
| <b>Notes</b>                               | none  |                  |                           |
|  |   |                  |                           |

Table 37 Tag list request

### 2.5.3.1.27 Read a List of Tags Associated with a Contact

|                          |  |                  |                                  |
|--------------------------|--|------------------|----------------------------------|
| <b>Title</b>             | Retrieve a list of tags associated with a particular contact   |                  |                                  |
| <b>URL</b>               | /v2/contacts/:id/tags?callback=:callback   |                  |                                  |
| <b>Header attributes</b> | <b>Attribute</b>   | <b>Required?</b> | <b>Example</b>                   |
|                          | authToken  | yes              | authToken=gfUH43trfdkjg34        |
| <b>Method</b>            | GET  |                  |                                  |
| <b>URL parameters</b>    | <b>Parameter</b>   | <b>Required?</b> | <b>Example</b>                   |
|                          | id : <integer><br>callback : <string>  | Yes<br>No        | /231/<br>?callback=jsonpcallback |
| <b>Data</b>              | none   |                  |                                  |
| <b>Success response</b>  | Code: 200 OK   |                  |                                  |
|                          | [<alphanumeric>]   |                  |                                  |
| <b>Error response</b>    | Code: 400 BAD REQUEST<br>Code: 401 UNAUTHORIZED<br>Code: 403 FORBIDDEN   |                  |                                  |
|                          | { "code" : <integer>, "error" : <integer>, "devmsg" : <alphanumeric> }   |                  |                                  |
| <b>Code example</b>      | <pre>\$.ajax({   type : "GET",   url : "/v2/contacts/231/tags",   headers : {authToken : "gfUH43trfdkjg34"},   dataType : "json",   success : function(data) {     console.log(data);   },   error : function(data) {     console.log(data);   } });</pre> |                  |                                  |
| <b>Notes</b>             | none   |                  |                                  |

Table 38 Tag list request – associated with a contact

### 2.5.3.1.28 Read a List of Interactions

|  |  |                  |                           |
|--|--|------------------|---------------------------|
| <b>Title</b>                                     | Returns all interactions associated with the requesting user   |                  |                           |
| <b>URL</b>                                       | /v2/interactions?callback=:callback  |                  |                           |
| <b>Header attributes</b>                         | <b>Attribute</b>   | <b>Required?</b> | <b>Example</b>            |
|  | authToken  | yes              | authToken=gfUH43trfdkjg34 |
| <b>Method</b>                                    | GET  |                  |                           |
| <b>URL parameters</b>                            | <b>Parameter</b>   | <b>Required?</b> | <b>Example</b>            |
|  | callback : <string>  | no               | ?callback=jsonpcallback   |
| <b>Data</b>                                      | none   |                  |                           |
| <b>Success response</b>                          | Code: 200 OK   |                  |                           |
| <b>Success response</b><br><b>Error response</b> | <pre>[{   "id" : &lt;integer&gt;,   "organization" :     {       "id" : &lt;integer&gt;,       "displayName" : &lt;alphanumeric&gt;     },   "person" :     {       "id" : &lt;integer&gt;,       "displayName" : &lt;alphanumeric&gt;     }   "basicInfoId" : &lt;integer&gt;,   "type" : &lt;enum(call-incoming,call-outgoing,email-incoming,email-outgoing,im-incoming,im-outgoing,sms-incoming,sms-outgoing)&gt;,   "data" : &lt;alphanumeric&gt;,   "duration" : &lt;integer&gt;,   "externalSystems" :     [       {         "systemId" : &lt;alphanumeric&gt;,         "threadId" : &lt;alphanumeric&gt;,         "entityId" : &lt;alphanumeric&gt;       }     ]   "time" : &lt;integer&gt; }]</pre> |                  |                           |
|  | Code: 401 UNAUTHORIZED<br>Code: 403 FORBIDDEN  |                  |                           |
| <b>Error response</b><br><b>Code example</b>     | <pre>{ "code" : &lt;integer&gt;, "error" : &lt;integer&gt;, "devmsg" : &lt;alphanumeric&gt; }</pre>  |                  |                           |
|  | <pre>\$.ajax({   type : "GET",   url : "/v2/interactions",   headers : {authToken : "gfUH43trfdkjg34"},   dataType : "json",   success : function(data) {     console.log(data);   },   error : function(data) {     console.log(data);   } });</pre>  |                  |                           |

|              |  |
|--------------|--|
| <b>Notes</b> | <p>The <i>time</i> attribute holds the date when the interaction was created. This date is represented by the number of milliseconds since the standard base time known as "the epoch", namely January 1, 1970, 00:00:00 GMT.</p> <p>The interaction list is sorted by time, descending.</p> |
|              |  |

Table 39 Interaction list request

### 2.5.3.1.29 Read a List of Interactions Associated with a Contact

|                          |   |                  |                                 |
|--------------------------|---|------------------|---------------------------------|
| <b>Title</b>             | Retrieve a list of interactions associated with a particular contact  |                  |                                 |
| <b>URL</b>               | /v2/contacts/:id/interactions?callback=:callback  |                  |                                 |
| <b>Header attributes</b> | <b>Attribute</b>  | <b>Required?</b> | <b>Example</b>                  |
|                          | authToken   | yes              | authToken=gfUH43trfdkjg34       |
| <b>Method</b>            | GET   |                  |                                 |
| <b>URL parameters</b>    | <b>Parameter</b>  | <b>Required?</b> | <b>Example</b>                  |
|                          | id : <integer><br>callback : <string>   | Yes<br>no        | /23/<br>?callback=jsonpcallback |
| <b>Data</b>              | none  |                  |                                 |
| <b>Success response</b>  | Code: 200 OK  |                  |                                 |
|                          | <pre>[{   "id" : &lt;integer&gt;,   "organization":     {       "id" : &lt;integer&gt;,       "displayName" : &lt;alphanumeric&gt;     },   "person" :     {       "id" : &lt;integer&gt;,       "displayName" : &lt;alphanumeric&gt;     }   "basicInfoId" : &lt;integer&gt;,   "type" : &lt;enum(call-incoming,call-outgoing,email-incoming,email-outgoing,im-incoming,im-outgoing,sms-incoming,sms-outgoing)&gt;,   "data" : &lt;alphanumeric&gt;,   "duration" : &lt;integer&gt;,   "externalSystems" :     [{       "systemId" : &lt;alphanumeric&gt;,       "threadId" : &lt;alphanumeric&gt;,       "entityId" : &lt;alphanumeric&gt;     }]   "time" : &lt;integer&gt; }]</pre> |                  |                                 |
| <b>Error response</b>    | Code: 400 BAD REQUEST<br>Code: 401 UNAUTHORIZED<br>Code: 403 FORBIDDEN  |                  |                                 |
|                          | <pre>{"code" : &lt;integer&gt;, "error" : &lt;integer&gt;, "devmsg" : &lt;alphanumeric&gt;}</pre>   |                  |                                 |
| <b>Code example</b>      | <pre>\$.ajax({   type : "GET",   url : "/v2/contacts/23/interactions",   headers : {authToken : "gfUH43trfdkjg34"},   dataType : "json",   success : function(data) {     console.log(data);   },   error : function(data) {     console.log(data);   } });</pre>   |                  |                                 |



|              |  |
|--------------|--|
| <b>Notes</b> | <p>The <i>time</i> attribute holds the date when the interaction was created. This date is represented by the number of milliseconds since the standard base time known as "the epoch", namely January 1, 1970, 00:00:00 GMT.</p> <p>The interaction list is sorted by time, descending.</p> |
|--------------|--|

Table 40 Interaction list request - associated with a contact

### 2.5.3.1.30 Read an Interaction

|                          |   |                  |                                |
|--------------------------|---|------------------|--------------------------------|
| <b>Title</b>             | Retrieve data of a particular interaction   |                  |                                |
| <b>URL</b>               | /v2/interactions/:id?callback=:callback   |                  |                                |
| <b>Header attributes</b> | <b>Attribute</b>  | <b>Required?</b> | <b>Example</b>                 |
|                          | authToken   | yes              | authToken=gfUH43trfdkjg34      |
| <b>Method</b>            | GET   |                  |                                |
| <b>URL parameters</b>    | <b>Parameter</b>  | <b>Required?</b> | <b>Example</b>                 |
|                          | id : <integer><br>callback : <string>   | Yes<br>No        | /79<br>?callback=jsonpcallback |
| <b>Data</b>              | none  |                  |                                |
| <b>Success response</b>  | <p>Code: 200 OK</p> <p>Content:</p> <pre>{   "id" : &lt;integer&gt;,   "organization":     {       "id" : &lt;integer&gt;,       "displayName" : &lt;alphanumeric&gt;     },   "person" :     {       "id" : &lt;integer&gt;,       "displayName" : &lt;alphanumeric&gt;     }   "basicInfoId" : &lt;integer&gt;,   "type" : &lt;enum(call-incoming,call-outgoing,email-incoming,email-outgoing,im-incoming,im-outgoing,sms-incoming,sms-outgoing)&gt;,   "data" : &lt;alphanumeric&gt;,   "duration" : &lt;integer&gt;,   "externalSystems" :     [{       "systemId" : &lt;alphanumeric&gt;,       "threadId" : &lt;alphanumeric&gt;,       "entityId" : &lt;alphanumeric&gt;     }]   "time" : &lt;integer&gt; }</pre> |                  |                                |
| <b>Error response</b>    | <p>Code: 400 BAD REQUEST</p> <p>Code: 401 UNAUTHORIZED</p> <p>Code: 403 FORBIDDEN</p> <p>Code: 404 NOT FOUND</p> <p>Content:</p> <pre>{"code" : &lt;integer&gt;, "error" : &lt;integer&gt;, "devmsg" : &lt;alphanumeric&gt;}</pre>  |                  |                                |
| <b>Code example</b>      | <pre>\$.ajax({   type : "GET",   url : "/v2/interactions/79",   headers : {authToken : "gfUH43trfdkjg34"},   dataType : "json",   success : function(data) {     console.log(data);   } });</pre>   |                  |                                |

|              |  |
|--------------|--|
|              | <pre>    },<br/>    error : function(data) {<br/>        console.log(data);<br/>    }<br/>  });</pre>  |
| <b>Notes</b> | <p>The <i>time</i> attribute holds the date when the interaction was created. This date is represented by the number of milliseconds since the standard base time known as "the epoch", namely January 1, 1970, 00:00:00 GMT.</p> <p>The interaction list is sorted by time, descending.</p> |

Table 41 Interaction request

### 2.5.3.1.31 Update an Interaction

|                          |  |                  |                           |
|--------------------------|--|------------------|---------------------------|
| <b>Title</b>             | Update a particular interaction  |                  |                           |
| <b>URL</b>               | /v2/interactions/:id   |                  |                           |
| <b>Header attributes</b> | <b>Attribute</b>   | <b>Required?</b> | <b>Example</b>            |
|                          | authToken  | yes              | authToken=gfUH43trfdkjg34 |
| <b>Method</b>            | POST   |                  |                           |
| <b>URL parameters</b>    | <b>Parameter</b>   | <b>Required?</b> | <b>Example</b>            |
|                          | id : <integer>   | yes              | /1387                     |
| <b>Data</b>              | <pre>{   "basicInfoId" : &lt;integer&gt;,   "customTags" : &lt;alphanumeric&gt;,   "duration" : &lt;integer&gt;,   "externalSystems" :     [{       "name" : &lt;alphanumeric&gt;,       "threadId" : &lt;alphanumeric&gt;,       "entityId" : &lt;alphanumeric&gt;     }],   "organization":     {       "id" : &lt;integer&gt;     },   "person" :     {       "id" : &lt;integer&gt;     },   "status" : &lt;alphanumeric&gt; }</pre> |                  |                           |
| <b>Success response</b>  | Code: 200 OK   |                  |                           |
|                          | {"code" : 200, "entity" : <interaction>, "devmsg" : "success"}   |                  |                           |
| <b>Error response</b>    | Code: 400 BAD REQUEST  |                  |                           |
|                          | {"code" : <integer>, "error" : <integer>, "devmsg" : <alphanumeric>}   |                  |                           |
| <b>Code example</b>      | <pre>\$.ajax({   type : "POST",   url : "/v2/interactions/1387",   headers : {authToken : "gfUH43trfdkjg34"},   dataType : "json",   contentType : "application/json",   data : JSON.stringify({     "organizationId" : 12,     "personId" : 34   }),   success : function(data) {     console.log(data);   },   error : function(data) {     console.log(data);   } });</pre>   |                  |                           |
| <b>Notes</b>             | The purpose of this API call is linking a contact to a formerly unknown interaction list entry or setting a concrete contact person for an interaction with an organization. It is also possible to update an interaction (of type <i>call</i> ) with the duration when the call   |                  |                           |

|  |  |
|--|--|
|  | <p>ended, set custom tags and assign an ID for that interaction inside an external system.</p> <p>If the <i>externalSystem</i> entity is given at least one of <i>externalSystem.threadId</i> or <i>externalSystem.entityId</i> must be given. While the <i>threadId</i> is meant to reference the interaction parent (e.g. the im-conversation id) the <i>entityId</i> is meant to reference the concrete interaction message (e.g. im-message id) inside that parent.</p> <p>The <i>status</i> field is meant to represent the technical state of the interaction, e.g. "missed", "voicemail", "answered", ...</p> |
|--|--|

Table 42 Interaction update

### 2.5.3.1.32 Create Basicinfo

|                          |  |                  |                           |
|--------------------------|--|------------------|---------------------------|
| <b>Title</b>             | Create given basicinfo   |                  |                           |
| <b>URL</b>               | /v2/basicInfos   |                  |                           |
| <b>Header attributes</b> | <b>Attribute</b>   | <b>Required?</b> | <b>Example</b>            |
|                          | authToken  | yes              | authToken=gfUH43trfdkjg34 |
| <b>Method</b>            | PUT  |                  |                           |
| <b>URL parameters</b>    | none   |                  |                           |
| <b>Data</b>              | <pre>{   "excluded" : &lt;boolean&gt;,   "subtype" : &lt;enum(home,work,other)&gt;,   "type" : &lt;enum(email,fax,mobile,phone,website)&gt;,   "value" : &lt;alphanumeric&gt; }</pre>  |                  |                           |
| <b>Success response</b>  | Code: 201 CREATED<br>Content:<br><pre>{ "code" : 201, "entity" : &lt;basicinfo&gt;, "devmsg" : "success" }</pre>   |                  |                           |
| <b>Error response</b>    | Code: 400 BAD REQUEST<br>Code: 401 UNAUTHORIZED<br>Code: 403 FORBIDDEN<br>Content:<br><pre>{ "code" : &lt;integer&gt;, "error" : &lt;integer&gt;, "devmsg" : &lt;alphanumeric&gt; }</pre>  |                  |                           |
| <b>Code example</b>      | <pre>\$.ajax({   type : "PUT",   url : "/v2/basicInfos",   headers : {authToken : "gfUH43trfdkjg34"},   dataType : "json",   contentType : "application/json",   data : JSON.stringify({     "type" : "phone",     "value" : "+491774528462"     "excluded" : true   }),   success : function(data) {     console.log(data);   },   error : function(data) {     console.log (data);   } });</pre> |                  |                           |
| <b>Notes</b>             | The general purpose of this API call is excluding unknown phone numbers from Interact.   |                  |                           |

Table 43 Basicinfos creation

### 2.5.3.1.33 Update a Basicinfo

|                          |   |                  |                           |
|--------------------------|---|------------------|---------------------------|
| <b>Title</b>             | Update a particular basicinfo   |                  |                           |
| <b>URL</b>               | /v2/basicInfos/:id  |                  |                           |
| <b>Header attributes</b> | <b>Attribute</b>  | <b>Required?</b> | <b>Example</b>            |
|                          | authToken   | yes              | authToken=gfUH43trfdkjg34 |
| <b>Method</b>            | POST  |                  |                           |
| <b>URL parameters</b>    | <b>Parameter</b>  | <b>Required?</b> | <b>Example</b>            |
|                          | id : <integer>  | yes              | /246                      |
| <b>Data</b>              | <pre>{   "type" : &lt;enum(email,fax,mobile,phone,website)&gt;,   "subtype" : &lt;enum(home,work,other)&gt;,   "value" : &lt;alphanumeric&gt;,   "excluded" : &lt;boolean&gt; }</pre>   |                  |                           |
| <b>Success response</b>  | Code: 200 OK<br>Content:<br><pre>{ "code" : 200, "entity" : &lt;basicinfo&gt;, "devmsg" : "success" }</pre>   |                  |                           |
| <b>Error response</b>    | Code: 400 BAD REQUEST<br>Code: 401 UNAUTHORIZED<br>Code: 403 FORBIDDEN<br>Content:<br><pre>{ "code" : &lt;integer&gt;, "error" : &lt;integer&gt;, "devmsg" : &lt;alphanumeric&gt; }</pre>   |                  |                           |
| <b>Code example</b>      | <pre>\$.ajax({   type : "POST",   url : "/v2/basicInfos/246",   headers : {authToken : "gfUH43trfdkjg34"},   dataType : "json",   contentType : "application/json",   data : JSON.stringify({     "value" : "+493029352225",     "subtype" : "work",     "excluded" : true   }),   success : function(data) {     console.log(data);   },   error : function(data) {     console.log(data);   } });</pre> |                  |                           |
| <b>Notes</b>             | The general purpose of this API call is excluding known phone numbers from Interact.  |                  |                           |

Table 44 Basicinfo update

#### 2.5.3.1.34 Create Task

|                          |   |                  |                           |
|--------------------------|---|------------------|---------------------------|
| <b>Title</b>             | Create a task   |                  |                           |
| <b>URL</b>               | /v2/tasks   |                  |                           |
| <b>Header attributes</b> | <b>Attribute</b>  | <b>Required?</b> | <b>Example</b>            |
|                          | authToken   | yes              | authToken=gfUH43trfdkjg34 |
| <b>Method</b>            | PUT   |                  |                           |
| <b>URL parameters</b>    | none  |                  |                           |
| <b>Data</b>              | <pre>{   "assignedTo" :     {       "id" : &lt;integer&gt;     },   "concreteDueDate" : &lt;integer&gt;,   "content" : &lt;alphanumeric&gt;,   "created" : &lt;integer&gt;,   "duration" : &lt;integer&gt;,   "fuzzyDueDate" : &lt;enum(tomorrow,next_week,in_a_month,someday)&gt;,   "hot" : &lt;boolean&gt;,   "listId" : &lt;integer&gt;,   "phoneNumberIds" : [&lt;integer&gt;],   "relatedTo" :     {       "id" : &lt;integer&gt;,       "type" : &lt;enum(contact,deal)&gt;     },   "status" : &lt;enum(completed,open)&gt;,   "taskType" : &lt;enum(task,scheduled_call)&gt;,   "title" : &lt;alphanumeric&gt; }</pre> |                  |                           |
| <b>Success response</b>  | Code: 201 CREATED<br>Content:<br>{ "code" : 201, "entity" : <task>, "devmsg" : "success" }  |                  |                           |
| <b>Error response</b>    | Code: 400 BAD REQUEST<br>Code: 401 UNAUTHORIZED<br>Code: 403 FORBIDDEN<br>Content:<br>{ "code" : <integer>, "error" : <integer>, "devmsg" : <alphanumeric> }  |                  |                           |
| <b>Code example</b>      | <pre>\$.ajax({   type : "PUT",   url : "/v2/tasks",   headers : {authToken : "gfUH43trfdkjg34"},   dataType : "json",   contentType : "application/json",</pre>   |                  |                           |



|       |  |
|-------|--|
|       | <pre>data : JSON.stringify({   "content" : "Meeting with Remo at Joeys'",   "created" : 1360190185200,   "concreteDueDate" : 1360190188000,   "listId" : 95   "relatedTo" : {     "id" : 327,     "type" : "contact"   },   "status" : "open",   "taskType" : "task",   "title" : "Lunch with Remo" }), success : function(data) {   console.log(data); }, error : function(data) {   console.log(data); } });</pre>   |
| Notes | <p>The attributes <i>duration</i> and <i>phoneNumberIds</i> are only relevant when <i>taskType</i> is set to "scheduled_call".</p> <p><i>created</i> and <i>concreteDueDate</i> are represented by the number of milliseconds since the standard base time known as "the epoch", namely January 1, 1970, 00:00:00 GMT.</p> <p><i>fuzzyDueDate</i> rules are the following:</p> <p>"tomorrow" =&gt; <i>concreteDueDate</i> = current date + 1d</p> <p>"next_week" =&gt; <i>concreteDueDate</i> = current date + 7d</p> <p>"in_a_month" =&gt; <i>concreteDueDate</i> = current date + 30d</p> <p>"someday" =&gt; <i>concreteDueDate</i> = current date + 99d</p> |

Table 45 Tasks creation

### 2.5.3.1.35 Read a List of Tasks

|                          |  |                  |                           |
|--------------------------|--|------------------|---------------------------|
| <b>Title</b>             | Returns all the tasks associated to the requesting user.   |                  |                           |
| <b>URL</b>               | /v2/tasks?callback=:callback   |                  |                           |
| <b>Header attributes</b> | <b>Attribute</b>   | <b>Required?</b> | <b>Example</b>            |
|                          | authToken  | yes              | authToken=gfUH43trfdkjg34 |
| <b>Method</b>            | GET  |                  |                           |
| <b>URL parameters</b>    | <b>Parameter</b>   | <b>Required?</b> | <b>Example</b>            |
|                          | callback : <string>  | no               | ?callback=jsonpcallback   |
| <b>Data</b>              | none   |                  |                           |
| <b>Success response</b>  | <p>Code: 200 OK</p> <p>Content:</p> <pre>[{   "id" : &lt;integer&gt;,   "assignedTo" :     {       "id" : &lt;integer&gt;,       "displayName" : &lt;alphanumeric&gt;     },   "concreteDueDate" : &lt;integer&gt;,   "content" : &lt;alphanumeric&gt;,   "created" : &lt;integer&gt;,   "duration" : &lt;integer&gt;,   "fuzzyDueDate" : &lt;enum(tomorrow,next_week,in_a_month,someday)&gt;,   "hot" : &lt;boolean&gt;,   "listId" : &lt;integer&gt;,   "phoneNumbers" :     [{       "id" : &lt;integer&gt;,       "type" : &lt;enum(mobile,phone)&gt;,       "subtype" : &lt;enum(home,work,other)&gt;,       "value" : &lt;alphanumeric&gt;,       "excluded" : &lt;boolean&gt;     }],   "relatedTo" :     {       "id" : &lt;integer&gt;,       "type" : &lt;enum(contact,deal)&gt;,       "displayName" : &lt;alphanumeric&gt;     },   "status" : &lt;enum(completed,open)&gt;,   "taskType" : &lt;enum(task,scheduled_call)&gt;,   "title" : &lt;alphanumeric&gt; }]</pre> |                  |                           |
| <b>Error response</b>    | <p>Code: 401 UNAUTHORIZED</p> <p>Content:</p> <pre>{"code" : &lt;integer&gt;, "error" : &lt;integer&gt;, "devmsg" : &lt;alphanumeric&gt;}</pre>  |                  |                           |

|                     |  |
|---------------------|--|
| <b>Code example</b> | <pre>\$.ajax({   type : "GET",   url : "/v2/tasks",   headers : {authToken : "gfUH43trfdkjg34"},   dataType : "json",   success : function(data) {     console.log(data);   },   error : function(data) {     console.log(data);   } });</pre>   |
| <b>Notes</b>        | <p><i>created</i> and <i>concreteDueDate</i> are represented by the number of milliseconds since the standard base time known as "the epoch", namely January 1, 1970, 00:00:00 GMT.</p> <p>The list is sorted by <i>concreteDueDate</i>, descending.</p> <p>The attributes <i>duration</i> and <i>phoneNumbers</i> may only be set when <i>taskType</i> is "scheduled_call".</p> |
|                     |  |

Table 46 Task list request

### 2.5.3.1.36 Read a List of Tasks Associated with a Contact

|                          |  |                  |                                  |
|--------------------------|--|------------------|----------------------------------|
| <b>Title</b>             | Retrieve a list of tasks associated with a particular contact  |                  |                                  |
| <b>URL</b>               | /v2/contacts/:id/tasks?callback=:callback  |                  |                                  |
| <b>Header attributes</b> | <b>Attribute</b>   | <b>Required?</b> | <b>Example</b>                   |
|                          | authToken  | yes              | authToken=gfUH43trfdkjg34        |
| <b>Method</b>            | GET  |                  |                                  |
| <b>URL parameters</b>    | <b>Parameter</b>   | <b>Required?</b> | <b>Example</b>                   |
|                          | id : <integer><br>callback : <string>  | Yes<br>No        | /517/<br>?callback=jsonpcallback |
| <b>Data</b>              | none   |                  |                                  |
| <b>Success response</b>  | <p>Code: 200 OK</p> <p>Content:</p> <pre>[{   "id" : &lt;integer&gt;,   "assignedTo" :     {       "id" : &lt;integer&gt;,       "displayName" : &lt;alphanumeric&gt;     },   "concreteDueDate" : &lt;integer&gt;,   "content" : &lt;alphanumeric&gt;,   "created" : &lt;integer&gt;,   "duration" : &lt;integer&gt;,   "fuzzyDueDate" : &lt;enum(tomorrow,next_week,in_a_month,someday)&gt;,   "hot" : &lt;boolean&gt;,   "listId" : &lt;integer&gt;,   "phoneNumbers" :     [{       "id" : &lt;integer&gt;,       "type" : &lt;enum(mobile,phone)&gt;,       "subtype" : &lt;enum(home,work,other)&gt;,       "value" : &lt;alphanumeric&gt;,       "excluded" : &lt;boolean&gt;     }],   "relatedTo" :     {       "id" : &lt;integer&gt;,       "type" : &lt;enum(contact,deal)&gt;,       "displayName" : &lt;alphanumeric&gt;     },   "status" : &lt;enum(completed,open)&gt;,   "taskType" : &lt;enum(task,scheduled_call)&gt;,   "title" : &lt;alphanumeric&gt; }]</pre> |                  |                                  |
| <b>Error response</b>    | <p>Code: 401 UNAUTHORIZED</p> <p>Code: 403 FORBIDDEN</p>   |                  |                                  |

|                     |  |
|---------------------|--|
|                     | <p>Code: 404 NOT FOUND</p> <p>Content:</p> <pre>{"code" : &lt;integer&gt;, "error" : &lt;integer&gt;, "devmsg" : &lt;alphanumeric&gt;}</pre>   |
| <b>Code example</b> | <pre>\$.ajax({<br/>  type : "GET",<br/>  url : "/v2/contacts/517/tasks",<br/>  headers : {authToken : "gfUH43trfdkjg34"},<br/>  dataType : "json",<br/>  success : function(data) {<br/>    console.log(data);<br/>  },<br/>  error : function(data) {<br/>    console.log(data);<br/>  }<br/>});</pre>  |
| <b>Notes</b>        | <p>The <i>created</i> attribute holds the date when the task was created. This date is represented by the number of milliseconds since the standard base time known as "the epoch", namely January 1, 1970, 00:00:00 GMT. Same behavior is used for <i>concreteDueDate</i>.</p> <p>The list is sorted by <i>concreteDueDate</i>, descending.</p> <p>The attributes <i>duration</i> and <i>phoneNumbers</i> may only be set when <i>taskType</i> is "scheduled_call".</p> |

Table 47 Tasks list request - associated with a contact

### 2.5.3.1.37 Read a Task

|                          |  |                  |                                |
|--------------------------|--|------------------|--------------------------------|
| <b>Title</b>             | Retrieve data of a particular task   |                  |                                |
| <b>URL</b>               | /v2/tasks/:id?callback=:callback   |                  |                                |
| <b>Header attributes</b> | <b>Attribute</b>   | <b>Required?</b> | <b>Example</b>                 |
|                          | authToken  | yes              | authToken=gfUH43trfdkjg34      |
| <b>Method</b>            | GET  |                  |                                |
| <b>URL parameters</b>    | <b>Parameter</b>   | <b>Required?</b> | <b>Example</b>                 |
|                          | id : <integer><br>callback : <string>  | Yes<br>No        | /47<br>?callback=jsonpcallback |
| <b>Data</b>              | none   |                  |                                |
| <b>Success response</b>  | <p>Code: 200 OK</p> <p>Content:</p> <pre>{   "id" : &lt;integer&gt;,   "assignedTo" :     {       "id" : &lt;integer&gt;,       "displayName" : &lt;alphanumeric&gt;     },   "concreteDueDate" : &lt;integer&gt;,   "content" : &lt;alphanumeric&gt;,   "created" : &lt;integer&gt;,   "duration" : &lt;integer&gt;,   "fuzzyDueDate" : &lt;enum(tomorrow,next_week,in_a_month,someday)&gt;,   "hot" : &lt;boolean&gt;,   "listId" : &lt;integer&gt;,   "phoneNumbers" :     [{       "id" : &lt;integer&gt;,       "type" : &lt;enum(mobile,phone)&gt;,       "subtype" : &lt;enum(home,work,other)&gt;,       "value" : &lt;alphanumeric&gt;,       "excluded" : &lt;boolean&gt;     }],   "relatedTo" :     {       "id" : &lt;integer&gt;,       "type" : &lt;enum(contact,deal)&gt;,       "displayName" : &lt;alphanumeric&gt;     },   "status" : &lt;enum(completed,open)&gt;,   "taskType" : &lt;enum(task,scheduled_call)&gt;,   "title" : &lt;alphanumeric&gt; }</pre> |                  |                                |
| <b>Error response</b>    | <p>Code: 401 UNAUTHORIZED</p> <p>Code: 403 FORBIDDEN</p>   |                  |                                |

|                     |   |
|---------------------|---|
|                     | <p>Code: 404 NOT FOUND</p> <p>Content:</p> <pre>{"code" : &lt;integer&gt;, "error" : &lt;integer&gt;, "devmsg" : &lt;alphanumeric&gt;}</pre>  |
| <b>Code example</b> | <pre>\$.ajax({   type : "GET",   url : "/v2/tasks/47",   headers : {authToken : "gfUH43trfdkjg34"},   dataType : "json",   success : function(data) {     console.log(data);   },   error : function(data) {     console.log(data);   } });</pre>   |
| <b>Notes</b>        | <p><i>created</i> and <i>concreteDueDate</i> are represented by the number of milliseconds since the standard base time known as "the epoch", namely January 1, 1970, 00:00:00 GMT.</p> <p>The attributes <i>duration</i> and <i>phoneNumbers</i> may only be set when <i>taskType</i> is "scheduled_call".</p> |

Table 48 Task request

### 2.5.3.1.38 Update a Task

|                          |   |                  |                           |
|--------------------------|---|------------------|---------------------------|
| <b>Title</b>             | Update a particular task  |                  |                           |
| <b>URL</b>               | /v2/tasks/:id   |                  |                           |
| <b>Header attributes</b> | <b>Attribute</b>  | <b>Required?</b> | <b>Example</b>            |
|                          | authToken   | yes              | authToken=gfUH43trfdkjg34 |
| <b>Method</b>            | POST  |                  |                           |
| <b>URL parameters</b>    | <b>Parameter</b>  | <b>Required?</b> | <b>Example</b>            |
|                          | id : <integer>  | yes              | /734                      |
| <b>Data</b>              | <pre>{   "assignedTo" :     {       "id" : &lt;integer&gt;,     },   "concreteDueDate" : &lt;integer&gt;,   "content" : &lt;alphanumeric&gt;,   "created" : &lt;integer&gt;,   "duration" : &lt;integer&gt;,   "fuzzyDueDate" : &lt;enum(tomorrow,next_week,in_a_month,someday)&gt;,   "hot" : &lt;boolean&gt;,   "listId" : &lt;integer&gt;,   "phoneNumberIds" : [&lt;integer&gt;],   "relatedTo" :     {       "id" : &lt;integer&gt;,       "type" : &lt;enum(contact,deal)&gt;,     },   "status" : &lt;enum(completed,open)&gt;,   "title" : &lt;alphanumeric&gt; }</pre> |                  |                           |
| <b>Success response</b>  | Code: 200 OK<br>Content:<br><pre>{ "code" : 200, "entity" : &lt;task&gt;, "devmsg" : "success" }</pre>  |                  |                           |
| <b>Error response</b>    | Code: 400 BAD REQUEST<br>Code: 401 UNAUTHORIZED<br>Code: 403 FORBIDDEN<br>Content:<br><pre>{ "code" : &lt;integer&gt;, "error" : &lt;integer&gt;, "devmsg" : &lt;alphanumeric&gt; }</pre>   |                  |                           |
| <b>Code example</b>      | <pre>\$.ajax({   type : "POST",   url : "/v2/tasks/734",   headers : {authToken : "gfUH43trfdkjg34"},   dataType : "json",   contentType : "application/json",</pre>  |                  |                           |



|              |   |
|--------------|---|
|              | <pre>data : JSON.stringify({   "content" : "Call Nancy",   "dueDate" : 1360190157000,   "relatedTo" : {     "id" : 462,     "type" : "contact"   },   "status" : "completed",   "title" : "Birthday" }), success : function(data) {   console.log(data); }, error : function(data) {   console.log(data); } });</pre> |
| <b>Notes</b> | <p><i>dueDate</i> is represented by the number of milliseconds since the standard base time known as "the epoch", namely January 1, 1970, 00:00:00 GMT.</p> <p>The attributes <i>duration</i> and <i>phoneNumberIds</i> are only relevant when the task is a "scheduled call".</p>                                    |

Table 49 Task update

### 2.5.3.1.39 Delete Tasks

|                          |  |                  |                           |
|--------------------------|--|------------------|---------------------------|
| <b>Title</b>             | Delete tasks with the given ids  |                  |                           |
| <b>URL</b>               | /v2/tasks?ids=:ids   |                  |                           |
| <b>Header attributes</b> | <b>Attribute</b>   | <b>Required?</b> | <b>Example</b>            |
|                          | authToken  | yes              | authToken=gfUH43trfdkjg34 |
| <b>Method</b>            | DELETE   |                  |                           |
| <b>URL parameters</b>    | <b>Parameter</b>   | <b>Required?</b> | <b>Example</b>            |
|                          | ids : [<integer>]  | Yes              | ids=1056,973,1294         |
| <b>Data</b>              | none   |                  |                           |
| <b>Success response</b>  | Code: 200 OK<br>Content:<br>{"code" : 204, "devmsg" : "success"}   |                  |                           |
| <b>Error response</b>    | Code: 400 BAD REQUEST<br>Code: 401 UNAUTHORIZED<br>Code: 403 FORBIDDEN<br>Content:<br>{"code" : <integer>, "error" : <integer>, "devmsg" : <alphanumeric>} |                  |                           |

|                     |   |
|---------------------|---|
| <b>Code example</b> | <pre>\$.ajax({   type : "DELETE",   url : "/v2/tasks?ids=1056,973,1294",   headers : {authToken : "gfUH43trfdkjg34"},   dataType : "json",   success : function(data) {     console.log(data);   },   error : function(data) {     console.log(data);   } });</pre> |
| <b>Notes</b>        | none  |

Table 50 Tasks deletion

#### 2.5.3.1.40 Delete a Task

|                          |   |                  |                           |
|--------------------------|---|------------------|---------------------------|
| <b>Title</b>             | Delete a particular task  |                  |                           |
| <b>URL</b>               | /v2/tasks/:id   |                  |                           |
| <b>Header attributes</b> | <b>Attribute</b>  | <b>Required?</b> | <b>Example</b>            |
|                          | authToken   | yes              | authToken=gfUH43trfdkjg34 |
| <b>Method</b>            | DELETE  |                  |                           |
| <b>URL parameters</b>    | <b>Parameter</b>  | <b>Required?</b> | <b>Example</b>            |
|                          | id : <integer>  | yes              | /481                      |
| <b>Data</b>              | none  |                  |                           |
| <b>Success response</b>  | Code: 200 OK<br>Content:<br>{ "code" : 204, "devmsg" : "success" }  |                  |                           |
| <b>Error response</b>    | Code: 401 UNAUTHORIZED<br>Code: 403 FORBIDDEN<br>Content:<br>{ "code" : <integer>, "error" : <integer>, "devmsg" : <alphanumeric> }   |                  |                           |
| <b>Code example</b>      | <pre>\$.ajax({   type : "DELETE",   url : "/v2/tasks/481",   headers : {authToken : "gfUH43trfdkjg34"},   dataType : "json",   success : function(data) {     console.log(data);   },   error : function(data) {     console.log(data);   } });</pre> |                  |                           |
| <b>Notes</b>             | none  |                  |                           |

Table 51 Task deletion

#### 2.5.3.1.41 Create a Tasklist

|                          |   |                  |                           |
|--------------------------|---|------------------|---------------------------|
| <b>Title</b>             | Create a tasklist   |                  |                           |
| <b>URL</b>               | /v2/taskLists   |                  |                           |
| <b>Header attributes</b> | <b>Attribute</b>  | <b>Required?</b> | <b>Example</b>            |
|                          | authToken   | yes              | authToken=gfUH43trfdkjg34 |
| <b>Method</b>            | PUT   |                  |                           |
| <b>URL parameters</b>    | none  |                  |                           |
| <b>Data</b>              | {<br>"title" : <alphanumeric><br>}  |                  |                           |
| <b>Success response</b>  | Code: 201 CREATED   |                  |                           |
|                          | { "code" : 201, "entity" : <taskList>, "devmsg" : "success" }   |                  |                           |
| <b>Error response</b>    | Code: 400 BAD REQUEST<br>Code: 401 UNAUTHORIZED<br>Code: 403 FORBIDDEN  |                  |                           |
|                          | { "code" : <integer>, "error" : <integer>, "devmsg" : <alphanumeric> }  |                  |                           |
| <b>Code example</b>      | <pre>\$.ajax({<br/>  type : "PUT",<br/>  url : "/v2/taskLists",<br/>  headers : {authToken : "gfUH43trfdkjg34"},<br/>  dataType : "json",<br/>  contentType : "application/json",<br/>  data : JSON.stringify({<br/>    "title" : "EMEA"<br/>  })<br/>  },<br/>  success : function(data) {<br/>    console.log(data);<br/>  },<br/>  error : function(data) {<br/>    console.log(data);<br/>  }<br/>});</pre> |                  |                           |
| <b>Notes</b>             | none  |                  |                           |

Table 52 Tasklist creation

### 2.5.3.1.42 Read a List of Tasklists

|  |  |                  |                           |
|--|--|------------------|---------------------------|
| <b>Title</b>                                     | Returns all the tasks lists associated to the requesting user.   |                  |                           |
| <b>URL</b>                                       | /v2/taskLists?callback=:callback   |                  |                           |
| <b>Header attributes</b>                         | <b>Attribute</b>   | <b>Required?</b> | <b>Example</b>            |
|  | authToken  | yes              | authToken=gfUH43trfdkjg34 |
| <b>Method</b>                                    | GET  |                  |                           |
| <b>URL parameters</b>                            | <b>Parameter</b>   | <b>Required?</b> | <b>Example</b>            |
|  | callback : <string>  | no               | ?callback=jsonpcallback   |
| <b>Data</b>                                      | none   |                  |                           |
| <b>Success response</b>                          | Code: 200 OK   |                  |                           |
| <b>Success response</b><br><b>Error response</b> | <pre>[{   "id" : &lt;integer&gt;,   "title" : &lt;alphanumeric&gt;,   "tasks" :     [{       "id" : &lt;integer&gt;,       "assignedTo" :         {           "id" : &lt;integer&gt;,           "displayName" : &lt;alphanumeric&gt;         },       "concreteDueDate" : &lt;integer&gt;,       "content" : &lt;alphanumeric&gt;,       "created" : &lt;integer&gt;,       "duration" : &lt;integer&gt;,       "fuzzyDueDate" : &lt;enum(tomorrow,next_week,in_a_month,someday)&gt;,       "hot" : &lt;boolean&gt;,       "listId" : &lt;integer&gt;,       "phoneNumbers" :         [{           "id" : &lt;integer&gt;,           "type" : &lt;enum(mobile,phone)&gt;,           "subtype" : &lt;enum(home,work,other)&gt;,           "value" : &lt;alphanumeric&gt;,           "excluded" : &lt;boolean&gt;         }],       "relatedTo" :         {           "id" : &lt;integer&gt;,           "type" : &lt;enum(contact,deal)&gt;,           "displayName" : &lt;alphanumeric&gt;         },       "status" : &lt;enum(completed,open)&gt;,       "taskType" : &lt;enum(task,scheduled_call)&gt;,       "title" : &lt;alphanumeric&gt;     }] }]</pre> |                  |                           |
|  | Code: 401 UNAUTHORIZED   |                  |                           |
|  | Code: 403 FORBIDDEN  |                  |                           |
| <b>Error response</b>                            | { "code" : <integer>, "error" : <integer>, "devmsg" : <alphanumeric> }   |                  |                           |
| <b>Code example</b>                              | <pre>\$.ajax({   type : "GET",</pre>   |                  |                           |

|       |  |
|-------|--|
|       | <pre>url : "/v2/taskLists", headers : {authToken : "gfUH43trfdkjg34"}, dataType : "json", success : function(data) {   console.log(data); }, error : function(data) {   console.log(data); } });</pre> |
| Notes | none   |
|       |  |

Table 53 Tasklist list request

### 2.5.3.1.43 Read a Tasklist

|                          |  |                  |                                |
|--------------------------|--|------------------|--------------------------------|
| <b>Title</b>             | Returns the requested task list that is associated to the user.  |                  |                                |
| <b>URL</b>               | /v2/taskLists/:id?callback=:callback   |                  |                                |
| <b>Header attributes</b> | <b>Attribute</b>   | <b>Required?</b> | <b>Example</b>                 |
|                          | authToken  | yes              | authToken=gfUH43trfdkjg34      |
| <b>Method</b>            | GET  |                  |                                |
| <b>URL parameters</b>    | <b>Parameter</b>   | <b>Required?</b> | <b>Example</b>                 |
|                          | id : <integer><br>callback : <string>  | Yes<br>No        | /47<br>?callback=jsonpcallback |
| <b>Data</b>              | none   |                  |                                |
| <b>Success response</b>  | <p>Code: 200 OK</p> <p>Content:</p> <pre>{   "id" : &lt;integer&gt;,   "title" : &lt;alphanumeric&gt;,   "tasks" :     [{       "id" : &lt;integer&gt;,       "assignedTo" :         {           "id" : &lt;integer&gt;,           "displayName" : &lt;alphanumeric&gt;         },       "concreteDueDate" : &lt;integer&gt;,       "content" : &lt;alphanumeric&gt;,       "created" : &lt;integer&gt;,       "duration" : &lt;integer&gt;,       "fuzzyDueDate" : &lt;enum(tomorrow,next_week,in_a_month,someday)&gt;,       "hot" : &lt;boolean&gt;,       "listId" : &lt;integer&gt;,       "phoneNumbers" :         [{           "id" : &lt;integer&gt;,           "type" : &lt;enum(mobile,phone)&gt;,           "subtype" : &lt;enum(home,work,other)&gt;,           "value" : &lt;alphanumeric&gt;,           "excluded" : &lt;boolean&gt;         }],       "relatedTo" :         {           "id" : &lt;integer&gt;,           "type" : &lt;enum(contact,deal)&gt;,           "displayName" : &lt;alphanumeric&gt;         },       "status" : &lt;enum(completed,open)&gt;,       "taskType" : &lt;enum(task,scheduled_call)&gt;,       "title" : &lt;alphanumeric&gt;     }] }</pre> |                  |                                |

|                       |   |
|-----------------------|---|
|                       |   |
| <b>Error response</b> | Code: 401 UNAUTHORIZED<br>Code: 403 FORBIDDEN<br>Code: 404 NOT FOUND<br>Content:<br>{ "code" : <integer>, "error" : <integer>, "devmsg" : <alphanumeric> }  |
| <b>Code example</b>   | <pre>\$.ajax({   type : "GET",   url : "/v2/taskLists/47",   headers : { authToken : "gfUH43trfdkjg34" },   dataType : "json",   success : function(data) {     console.log(data);   },   error : function(data) {     console.log(data);   } });</pre> |
| <b>Notes</b>          | <i>none</i>   |

Table 54 Tasklist request



#### 2.5.3.1.44 Update a Tasklist

|                          |   |                  |                           |
|--------------------------|---|------------------|---------------------------|
| <b>Title</b>             | Update a particular tasklist  |                  |                           |
| <b>URL</b>               | /v2/tasksLists/:id  |                  |                           |
| <b>Header attributes</b> | <b>Attribute</b>  | <b>Required?</b> | <b>Example</b>            |
|                          | authToken   | yes              | authToken=gfUH43trfdkjg34 |
| <b>Method</b>            | POST  |                  |                           |
| <b>URL parameters</b>    | <b>Parameter</b>  | <b>Required?</b> | <b>Example</b>            |
|                          | id : <integer>  | yes              | /734                      |
| <b>Data</b>              | <pre>{   "title" : &lt;alphanumeric&gt; }</pre>   |                  |                           |
| <b>Success response</b>  | Code: 200 OK<br>Content:<br>{ "code" : 200, "entity" : <taskList>, "devmsg" : "success" }   |                  |                           |
| <b>Error response</b>    | Code: 400 BAD REQUEST<br>Code: 401 UNAUTHORIZED<br>Code: 403 FORBIDDEN<br>Content:<br>{ "code" : <integer>, "error" : <integer>, "devmsg" : <alphanumeric> }  |                  |                           |
| <b>Code example</b>      | <pre>\$.ajax({   type : "POST",   url : "/v2/tasksLists/734",   headers : {authToken : "gfUH43trfdkjg34"},   dataType : "json",   contentType : "application/json",   data : JSON.stringify({     "title" : "IBM EMEA"   }),   success : function(data) {     console.log(data);   },   error : function(data) {     console.log(data);   } });</pre> |                  |                           |
| <b>Notes</b>             | none  |                  |                           |

Table 55 Tasklist update

#### 2.5.3.1.45 Delete a Tasklist

|                          |   |                  |                           |
|--------------------------|---|------------------|---------------------------|
| <b>Title</b>             | Deletes the task list defined by the id path parameter.   |                  |                           |
| <b>URL</b>               | /v2/taskLists/:id   |                  |                           |
| <b>Header attributes</b> | <b>Attribute</b>  | <b>Required?</b> | <b>Example</b>            |
|                          | authToken   | yes              | authToken=gfUH43trfdkjg34 |
| <b>Method</b>            | DELETE  |                  |                           |
| <b>URL parameters</b>    | <b>Parameter</b>  | <b>Required?</b> | <b>Example</b>            |
|                          | id : <integer>  | yes              | /481                      |
| <b>Data</b>              | none  |                  |                           |
| <b>Success response</b>  | Code: 200 OK<br>Content:<br>{ "code" : 204, "devmsg" : "success" }  |                  |                           |
| <b>Error response</b>    | Code: 401 UNAUTHORIZED<br>Code: 403 FORBIDDEN<br>Content:<br>{ "code" : <integer>, "error" : <integer>, "devmsg" : <alphanumeric> }   |                  |                           |
| <b>Code example</b>      | <pre>\$.ajax({   type : "DELETE",   url : "/v2/taskLists/481",   headers : {authToken : "gfUH43trfdkjg34"},   dataType : "json",   success : function(data) {     console.log(data);   },   error : function(data) {     console.log(data);   } });</pre> |                  |                           |
| <b>Notes</b>             | none  |                  |                           |

Table 56 Tasklist deletion

#### 2.5.3.1.46 Create Deal

|                          |   |                  |                            |
|--------------------------|---|------------------|----------------------------|
| <b>Title</b>             | Create a deal   |                  |                            |
| <b>URL</b>               | /v2/deals   |                  |                            |
| <b>Header attributes</b> | <b>Attribute</b>  | <b>Required?</b> | <b>Example</b>             |
|                          | authToken   | yes              | authToken=gfUH43trfdkjpg34 |
| <b>Method</b>            | PUT   |                  |                            |
| <b>URL parameters</b>    | none  |                  |                            |
| <b>Data</b>              | <pre>{   "name" : &lt;alphanumeric&gt;,   "value" : &lt;integer&gt;,   "currency" : &lt;alphanumeric&gt;,   "hot" : &lt;boolean&gt;,   "relatedTo" :     {       "id" : &lt;integer&gt;     },   "source" : &lt;enum(website,referral,word_of_mouth,cold_call)&gt;,   "stage" :     &lt;enum(incoming,qualified,quote,closing,won,lost,unqualified)&gt; }</pre>                         |                  |                            |
| <b>Success response</b>  | Code: 201 CREATED<br>Content:<br>{ "code" : 201, "entity" : <deal>, "devmsg" : "success" }  |                  |                            |
| <b>Error response</b>    | Code: 400 BAD REQUEST<br>Code: 401 UNAUTHORIZED<br>Code: 403 FORBIDDEN<br>Content:<br>{ "code" : <integer>, "error" : <integer>, "devmsg" : <alphanumeric> }  |                  |                            |
| <b>Code example</b>      | <pre>\$.ajax({   type : "PUT",   url : "/v2/deals",   headers : {authToken : "gfUH43trfdkjpg34"},   dataType : "json",   contentType : "application/json",   data : JSON.stringify({     "name" : "Apple Deal",     "value" : 100000,     "currency" : "USD",     "hot" : yes,     "relatedTo" : { "id" : 317 },     "source" : "word_of_mouth",     "stage" : "incoming"   }) })</pre> |                  |                            |

|              |   |
|--------------|---|
|              | <pre>success : function(data) {<br/>  console.log(data);<br/>},<br/>error : function(data) {<br/>  console.log(data);<br/>}<br/>});</pre> |
| <b>Notes</b> | none  |

Table 57 Deals creation

### 2.5.3.1.47 Read a List of Deals

|                          |  |                  |                           |
|--------------------------|--|------------------|---------------------------|
| <b>Title</b>             | Returns all the deals associated to the requesting user  |                  |                           |
| <b>URL</b>               | /v2/deals?callback=:callback   |                  |                           |
| <b>Header attributes</b> | <b>Attribute</b>   | <b>Required?</b> | <b>Example</b>            |
|                          | authToken  | yes              | authToken=gfUH43trfdkjg34 |
| <b>Method</b>            | GET  |                  |                           |
| <b>URL parameters</b>    | <b>Parameter</b>   | <b>Required?</b> | <b>Example</b>            |
|                          | callback : <string>  | no               | ?callback=jsonpcallback   |
| <b>Data</b>              | none   |                  |                           |
| <b>Success response</b>  | <p>Code: 200 OK</p> <p>Content:</p> <pre>[{   "id" : &lt;integer&gt;,   "name" : &lt;alphanumeric&gt;,   "value" : &lt;integer&gt;,   "currency" : &lt;alphanumeric&gt;,   "hot" : &lt;boolean&gt;,   "relatedTo" :     {       "id" : &lt;integer&gt;,       "name" : &lt;alphanumeric&gt;     },   "source" : &lt;enum(website, referral, word_of_mouth, cold_call)&gt;,   "stage" :     &lt;enum(incoming, qualified, quote, closing, won, lost, unqualified)&gt;, )&gt; }]</pre> |                  |                           |
| <b>Error response</b>    | <p>Code: 401 UNAUTHORIZED</p> <p>Content:</p> <pre>{"code" : &lt;integer&gt;, "error" : &lt;integer&gt;, "devmsg" : &lt;alphanumeric&gt;}</pre>  |                  |                           |
| <b>Code example</b>      | <pre>\$.ajax({   type : "GET",   url : "/v2/deals",   headers : {authToken : "gfUH43trfdkjg34"},   dataType : "json",   success : function(data) {     console.log(data);   },   error : function(data) {     console.log(data);   } });</pre>   |                  |                           |
| <b>Notes</b>             | none   |                  |                           |

|  |  |
|--|--|
|  |  |
|--|--|

Table 58 Deal list request

### 2.5.3.1.48 Read a List of Deals Associated with a Contact

|                          |  |                  |                           |
|--------------------------|--|------------------|---------------------------|
| <b>Title</b>             | Retrieve a list of deals associated with a particular contact  |                  |                           |
| <b>URL</b>               | /v2/contacts/:id/deals?callback=:callback  |                  |                           |
| <b>Header attributes</b> | <b>Attribute</b>   | <b>Required?</b> | <b>Example</b>            |
|                          | authToken  | yes              | authToken=gfUH43trfdkjg34 |
| <b>Method</b>            | GET  |                  |                           |
| <b>URL parameters</b>    | <b>Parameter</b>   | <b>Required?</b> | <b>Example</b>            |
|                          | id : <integer>   | Yes              | /517/                     |
|                          | callback : <string>  | No               | ?callback=jsonpcallback   |
| <b>Data</b>              | none   |                  |                           |
| <b>Success response</b>  | Code: 200 OK<br>Content:<br><pre>[{   "id" : &lt;integer&gt;,   "name" : &lt;alphanumeric&gt;,   "value" : &lt;integer&gt;,   "currency" : &lt;alphanumeric&gt;,   "hot" : &lt;boolean&gt;,   "relatedTo" :     {       "id" : &lt;integer&gt;,       "name" : &lt;alphanumeric&gt;     },   "source" : &lt;enum(website,referral,word_of_mouth,cold_call)&gt;,   "stage" :     &lt;enum(incoming,qualified,quote,closing,won,lost,unqualified)&gt; }]</pre> |                  |                           |
| <b>Error response</b>    | Code: 401 UNAUTHORIZED<br>Code: 403 FORBIDDEN<br>Code: 404 NOT FOUND<br>Content:<br><pre>{"code" : &lt;integer&gt;, "error" : &lt;integer&gt;, "devmsg" : &lt;alphanumeric&gt;}</pre>  |                  |                           |
| <b>Code example</b>      | <pre>\$.ajax({   type : "GET",   url : "/v2/contacts/517/deals",   headers : {authToken : "gfUH43trfdkjg34"},   dataType : "json",   success : function(data) {</pre>  |                  |                           |

|              |  |
|--------------|--|
|              | <pre>console.log(data);<br/>},<br/>error : function(data) {<br/>  console.log(data);<br/>}<br/>});</pre> |
| <b>Notes</b> | none   |

Table 59 Deal list request - associated with a contact

### 2.5.3.1.49 Read a Deal

|                          |  |                  |                                 |
|--------------------------|--|------------------|---------------------------------|
| <b>Title</b>             | Retrieve data of a particular deal   |                  |                                 |
| <b>URL</b>               | /v2/deal/:id?callback=:callback  |                  |                                 |
| <b>Header attributes</b> | <b>Attribute</b>   | <b>Required?</b> | <b>Example</b>                  |
|                          | authToken  | yes              | authToken=gfUH43trfdkjg34       |
| <b>Method</b>            | GET  |                  |                                 |
| <b>URL parameters</b>    | <b>Parameter</b>   | <b>Required?</b> | <b>Example</b>                  |
|                          | id : <integer><br>callback : <string>  | Yes<br>No        | /587<br>?callback=jsonpcallback |
| <b>Data</b>              | none   |                  |                                 |
| <b>Success response</b>  | Code: 200 OK   |                  |                                 |
|                          | <pre>{   "id" : &lt;integer&gt;,   "name" : &lt;alphanumeric&gt;,   "value" : &lt;integer&gt;,   "currency" : &lt;alphanumeric&gt;,   "hot" : &lt;boolean&gt;,   "relatedTo" :     {       "id" : &lt;integer&gt;,       "name" : &lt;alphanumeric&gt;     },   "source" : &lt;enum(website,referral,word_of_mouth,cold_call)&gt;,   "stage" : &lt;enum(incoming,qualified,quote,closing,won,lost,unqualified)&gt; }</pre> |                  |                                 |
| <b>Error response</b>    | Code: 400 BAD REQUEST<br>Code: 401 UNAUTHORIZED<br>Code: 403 FORBIDDEN   |                  |                                 |
|                          | <pre>{"code" : &lt;integer&gt;, "error" : &lt;integer&gt;, "devmsg" : &lt;alphanumeric&gt;}</pre>  |                  |                                 |
| <b>Code example</b>      | <pre>\$.ajax({   type : "GET",   url : "/v2/deals/587",   headers : {authToken : "gfUH43trfdkjg34"},   dataType : "json",   success : function(data) {     console.log(data);   },   error : function(data) {     console.log(data);   } });</pre>   |                  |                                 |
| <b>Notes</b>             | none   |                  |                                 |

Table 60 Deal request



### 2.5.3.1.50 Update a Deal

|                          |  |                  |                           |
|--------------------------|--|------------------|---------------------------|
| <b>Title</b>             | Update a particular deal   |                  |                           |
| <b>URL</b>               | /v2/deals/:id  |                  |                           |
| <b>Header attributes</b> | <b>Attribute</b>   | <b>Required?</b> | <b>Example</b>            |
|                          | authToken  | yes              | authToken=gfUH43trfdkjg34 |
| <b>Method</b>            | POST   |                  |                           |
| <b>URL parameters</b>    | <b>Parameter</b>   | <b>Required?</b> | <b>Example</b>            |
|                          | id : <integer>   | yes              | /3812                     |
| <b>Data</b>              | <pre>{   "name" : &lt;alphanumeric&gt;,   "value" : &lt;integer&gt;,   "currency" : &lt;alphanumeric&gt;,   "hot" : &lt;boolean&gt;,   "relatedTo" :     {       "id" : &lt;integer&gt;     },   "source" : &lt;enum(website,referral,word_of_mouth,cold_call)&gt;,   "stage" :     &lt;enum(incoming,qualified,quote,closing,won,lost,unqualified)&gt;,)&gt; }</pre>                                  |                  |                           |
| <b>Success response</b>  | Code: 200 OK<br>Content:<br><pre>{"code" : 200, "entity" : &lt;deal&gt;, "devmsg" : "success"}</pre>   |                  |                           |
| <b>Error response</b>    | Code: 400 BAD REQUEST<br>Code: 401 UNAUTHORIZED<br>Code: 403 FORBIDDEN<br>Content:<br><pre>{"code" : &lt;integer&gt;, "error" : &lt;integer&gt;, "devmsg" : &lt;alphanumeric&gt;}</pre>  |                  |                           |
| <b>Code example</b>      | <pre>\$.ajax({   type : "POST",   url : "/v2/deals/3812",   headers : {authToken : "gfUH43trfdkjg34"},   dataType : "json",   contentType : "application/json",   data : JSON.stringify({     "name" : "xailabs interact.io",     "value" : 1555000,     "currency" : "EUR",     "hot" : yes,     "relatedTo" : { "id" : 38 },     "source" : "word_of_mouth",     "stage" : "qualified"   }) })</pre> |                  |                           |

|              |  |
|--------------|--|
|              | <pre>    })     success : function(data) {         console.log(data);     },     error : function(data) {         console.log(data);     }     });</pre> |
| <b>Notes</b> | none   |

Table 61 Deal update

### 2.5.3.1.51 Delete Deals

|                          |   |                  |                           |
|--------------------------|---|------------------|---------------------------|
| <b>Title</b>             | Delete deals with the given ids   |                  |                           |
| <b>URL</b>               | /v2/deals?ids=ids   |                  |                           |
| <b>Header attributes</b> | <b>Attribute</b>  | <b>Required?</b> | <b>Example</b>            |
|                          | authToken   | yes              | authToken=gfUH43trfdkjg34 |
| <b>Method</b>            | DELETE  |                  |                           |
| <b>URL parameters</b>    | <b>Parameter</b>  | <b>Required?</b> | <b>Example</b>            |
|                          | ids : [<integer>]   | Yes              | ids=56,2731,894           |
| <b>Data</b>              | none  |                  |                           |
| <b>Success response</b>  | Code: 200 OK<br>Content:<br>{ "code" : 204, "devmsg" : "success" }  |                  |                           |
| <b>Error response</b>    | Code: 400 BAD REQUEST<br>Code: 401 UNAUTHORIZED<br>Code: 403 FORBIDDEN<br>Content:<br>{ "code" : <integer>, "error" : <integer>, "devmsg" : <alphanumeric> }  |                  |                           |
| <b>Code example</b>      | <pre>\$.ajax({   type : "DELETE",   url : "/v2/deals?ids=56,2731,894",   headers : {authToken : "gfUH43trfdkjg34"},   dataType : "json",   success : function(data) {     console.log(data);   },   error : function(data) {     console.log(data);   } });</pre> |                  |                           |
| <b>Notes</b>             | none  |                  |                           |

Table 62 Deals deletion

### 2.5.3.1.52 Delete a Deal

|                          |   |                  |                           |
|--------------------------|---|------------------|---------------------------|
| <b>Title</b>             | Delete a particular deal  |                  |                           |
| <b>URL</b>               | /v2/deals/:id   |                  |                           |
| <b>Header attributes</b> | <b>Attribute</b>  | <b>Required?</b> | <b>Example</b>            |
|                          | authToken   | yes              | authToken=gfUH43trfdkjg34 |
| <b>Method</b>            | DELETE  |                  |                           |
| <b>URL parameters</b>    | <b>Parameter</b>  | <b>Required?</b> | <b>Example</b>            |
|                          | id : <integer>  | yes              | /122                      |
| <b>Data</b>              | none  |                  |                           |
| <b>Success response</b>  | Code: 200 OK<br>Content:<br>{ "code" : 204, "devmsg" : "success" }  |                  |                           |
| <b>Error response</b>    | Code: 400 BAD REQUEST<br>Code: 401 UNAUTHORIZED<br>Code: 403 FORBIDDEN<br>Content:<br>{ "code" : <integer>, "error" : <integer>, "devmsg" : <alphanumeric> }  |                  |                           |
| <b>Code example</b>      | <pre>\$.ajax({   type : "DELETE",   url : "/v2/deals/122",   headers : {authToken : "gfUH43trfdkjg34"},   dataType : "json",   success : function(data) {     console.log(data);   },   error : function(data) {     console.log(data);   } });</pre> |                  |                           |
| <b>Notes</b>             | none  |                  |                           |

Table 63 Deal deletion

### 2.5.3.1.53 Create User

|                          |  |                  |                           |
|--------------------------|--|------------------|---------------------------|
| <b>Title</b>             | Create given user  |                  |                           |
| <b>URL</b>               | /v2/admin/users  |                  |                           |
| <b>Header attributes</b> | <b>Attribute</b>   | <b>Required?</b> | <b>Example</b>            |
|                          | authToken  | yes              | authToken=gfUH43trfdkjg34 |
| <b>Method</b>            | PUT  |                  |                           |
| <b>URL parameters</b>    | none   |                  |                           |
| <b>Data</b>              | <pre>{   "email" : &lt;alphanumeric&gt;,   "password" : &lt;alphanumeric&gt;,   "companyId" : &lt;integer&gt; }</pre>  |                  |                           |
| <b>Success response</b>  | Code: 201 CREATED<br>Content:<br>{ "code" : 201, "entity" : <user>, "devmsg" : "success" }   |                  |                           |
| <b>Error response</b>    | Code: 400 BAD REQUEST<br>Code: 401 UNAUTHORIZED<br>Code: 409 CONFLICT<br>Content:<br>{ "code" : <integer>, "error" : <integer>, "devmsg" : <alphanumeric> }  |                  |                           |
| <b>Code example</b>      | <pre>\$.ajax({   type : "PUT",   url : "/v2/admin/users",   headers : {authToken : "gfUH43trfdkjg34"},   dataType : "json",   contentType : "application/json",   data : JSON.stringify({     "email" : "John@gmail.com",     "password" : "john04"   }),   success : function(data) {     console.log(data);   },   error : function(data) {     console.log(data);   } });</pre> |                  |                           |
| <b>Notes</b>             | The <i>companyId</i> can be given on creation. If not it can be given on update. However the <i>companyId</i> can NOT be changed after it was set in the first time.   |                  |                           |

Table 64 User creation

#### 2.5.3.1.54 Read a List of Users

|                          |  |                  |                            |
|--------------------------|--|------------------|----------------------------|
| <b>Title</b>             | Retrieve a list of users.  |                  |                            |
| <b>URL</b>               | /v2/admin/users?callback=:callback   |                  |                            |
| <b>Header attributes</b> | <b>Attribute</b>   | <b>Required?</b> | <b>Example</b>             |
|                          | authToken  | yes              | authToken=gfUH43trfdkjpg34 |
| <b>Method</b>            | GET  |                  |                            |
| <b>URL parameters</b>    | <b>Parameter</b>   | <b>Required?</b> | <b>Example</b>             |
|                          | callback : <string>  | no               | ?callback=jsonpcallback    |
| <b>Data</b>              | none   |                  |                            |
| <b>Success response</b>  | <p>Code: 200 OK</p> <p>Content:</p> <pre>[{   "active" : &lt;boolean&gt;,   "companyId" : &lt;integer&gt;,   "dateCreated" : &lt;integer&gt;,   "email" : &lt;alphanumeric&gt;,   "groups" :     [{       "id" : &lt;integer&gt;,       "name" : &lt;alphanumeric&gt;     }],   "id" : &lt;integer&gt;,   "interactionsCount" : &lt;integer&gt;,   "roles" : [&lt;alphanumeric&gt;] }]</pre> |                  |                            |
| <b>Error response</b>    | <p>Code: 401 UNAUTHORIZED</p> <p>Content:</p> <pre>{"code" : &lt;integer&gt;, "error" : &lt;integer&gt;, "devmsg" : &lt;alphanumeric&gt;}</pre>  |                  |                            |
| <b>Code example</b>      | <pre>\$.ajax({   type : "GET",   url : "/v2/admin/users",   headers : {authToken : "gfUH43trfdkjpg34"},   dataType : "json",   success : function(data) {     console.log(data);   },   error : function(data) {     console.log(data);   } });</pre>  |                  |                            |

|              |      |
|--------------|------|
| <b>Notes</b> | none |
|--------------|------|

Table 65 User list request

### 2.5.3.1.55 Read a User

|                          |  |                  |                                 |
|--------------------------|--|------------------|---------------------------------|
| <b>Title</b>             | Retrieve data about a particular user.   |                  |                                 |
| <b>URL</b>               | /v2/admin/users/:id?callback=:callback   |                  |                                 |
| <b>Header attributes</b> | <b>Attribute</b>   | <b>Required?</b> | <b>Example</b>                  |
|                          | authToken  | yes              | authToken=gfUH43trfdkjg34       |
| <b>Method</b>            | GET  |                  |                                 |
| <b>URL parameters</b>    | <b>Parameter</b>   | <b>Required?</b> | <b>Example</b>                  |
|                          | id : <integer><br>callback : <string>  | Yes<br>No        | /587<br>?callback=jsonpcallback |
| <b>Data</b>              | none   |                  |                                 |
| <b>Success response</b>  | Code: 200 OK<br>Content:<br><pre>{   "active" : &lt;boolean&gt;,   "companyId" : &lt;integer&gt;,   "dateCreated" : &lt;integer&gt;,   "email" : &lt;alphanumeric&gt;,   "groups" :     [{       "id" : &lt;integer&gt;,       "name" : &lt;alphanumeric&gt;     }],   "id" : &lt;integer&gt;,   "interactionsCount" : &lt;integer&gt;,   "roles" : [&lt;alphanumeric&gt;] }</pre> |                  |                                 |
| <b>Error response</b>    | Code: 401 UNAUTHORIZED<br>Code: 404 NOT FOUND<br>Content:<br><pre>{"code" : &lt;integer&gt;, "error" : &lt;integer&gt;, "devmsg" : &lt;alphanumeric&gt;}</pre>   |                  |                                 |
| <b>Code example</b>      | <pre>\$.ajax({   type : "GET",   url : "/v2/admin/users/587",   headers : {authToken : "gfUH43trfdkjg34"},   dataType : "json",   success : function(data) {     console.log(data);   }, </pre>  |                  |                                 |

|       |  |
|-------|--|
|       | <pre>error : function(data) {<br/>  console.log(data);<br/>}<br/>});</pre> |
| Notes | none   |

Table 66 Single user request

### 2.5.3.1.56 Delete Users

|                   |   |           |                           |
|-------------------|---|-----------|---------------------------|
| Title             | Delete users with the given ids   |           |                           |
| URL               | /v2/admin/users?ids=:ids  |           |                           |
| Header attributes | Attribute   | Required? | Example                   |
|                   | authToken   | Yes       | authToken=gfUH43trfdkjg34 |
| Method            | DELETE  |           |                           |
| URL parameters    | Parameter   | Required? | Example                   |
|                   | ids : [<integer>]   | Yes       | ids=56,2731,894           |
| Data              | none  |           |                           |
| Success response  | Code: 200 OK  |           |                           |
|                   | {"code" : 204, "devmsg" : "success"}  |           |                           |
| Error response    | Code: 401 UNAUTHORIZED<br>Code: 403 FORBIDDEN   |           |                           |
|                   | {"code" : <integer>, "error" : <integer>, "devmsg" : <alphanumeric>}  |           |                           |
| Code example      | <pre>\$.ajax({<br/>  type : "DELETE",<br/>  url : "/v2/admin/users?ids=56,2731,894",<br/>  headers : {authToken : "gfUH43trfdkjg34"},<br/>  dataType : "json",<br/>  success : function(data) {<br/>    console.log(data);<br/>  },<br/>  error : function(data) {<br/>    console.log(data);<br/>  }<br/>});</pre> |           |                           |
| Notes             | none  |           |                           |

Table 67 User deletion



### 2.5.3.1.57 Delete a User

|                          |   |                  |                           |
|--------------------------|---|------------------|---------------------------|
| <b>Title</b>             | Delete the user with the given id   |                  |                           |
| <b>URL</b>               | /v2/admin/users/:id   |                  |                           |
| <b>Header attributes</b> | <b>Attribute</b>  | <b>Required?</b> | <b>Example</b>            |
|                          | authToken   | yes              | authToken=gfUH43trfdkjg34 |
| <b>Method</b>            | DELETE  |                  |                           |
| <b>URL parameters</b>    | <b>Parameter</b>  | <b>Required?</b> | <b>Example</b>            |
|                          | id : <integer>  | Yes              | /734                      |
| <b>Data</b>              | none  |                  |                           |
| <b>Success response</b>  | Code: 200 OK<br>Content:<br>{ "code" : 204, "devmsg" : "success" }  |                  |                           |
| <b>Error response</b>    | Code: 401 UNAUTHORIZED<br>Code: 403 FORBIDDEN<br>Content:<br>{ "code" : <integer>, "error" : <integer>, "devmsg" : <alphanumeric> }   |                  |                           |
| <b>Code example</b>      | <pre>\$.ajax({   type : "DELETE",   url : "/v2/admin/users/734",   headers : {authToken : "gfUH43trfdkjg34"},   dataType : "json",   success : function(data) {     console.log(data);   },   error : function(data) {     console.log(data);   } });</pre> |                  |                           |
| <b>Notes</b>             | none  |                  |                           |

Table 68 User deletion

### 2.5.3.1.58 Create a Company

| <b>Title</b>             | Create a customer company.  |                  |                           |
|--------------------------|---|------------------|---------------------------|
| <b>URL</b>               | /v2/admin/companies   |                  |                           |
| <b>Header attributes</b> | <b>Attribute</b>  | <b>Required?</b> | <b>Example</b>            |
|                          | authToken   | yes              | authToken=gfUH43trfdkjg34 |
| <b>Method</b>            | PUT   |                  |                           |
| <b>URL parameters</b>    | none  |                  |                           |
| <b>Data</b>              | <pre>{   "name" : &lt;alphanumeric&gt; }</pre>  |                  |                           |
| <b>Success response</b>  | Code: 201 CREATED<br>Content:<br><pre>{ "code" : 201, "entity" : &lt;company&gt;, "devmsg" : "success" }</pre>  |                  |                           |
| <b>Error response</b>    | Code: 400 BAD REQUEST<br>Code: 401 UNAUTHORIZED<br>Code: 403 FORBIDDEN<br>Content:<br><pre>{ "code" : &lt;integer&gt;, "error" : &lt;integer&gt;, "devmsg" : &lt;alphanumeric&gt; }</pre>   |                  |                           |
| <b>Code example</b>      | <pre>\$.ajax({   type : "PUT",   url : "/v2/companies",   headers : { authToken : "gfUH43trfdkjg34" },   dataType : "json",   contentType : "application/json",   data : JSON.stringify({     "name" : "xailabs GmbH"   })   success : function(data) {     console.log(data);   },   error : function(data) {     console.log(data);   } });</pre> |                  |                           |
| <b>Notes</b>             | none  |                  |                           |

Table 69 Company creation

### 2.5.3.1.59 Read a List Companies

|                          |  |                  |                           |
|--------------------------|--|------------------|---------------------------|
| <b>Title</b>             | Retrieve a list of customer companies  |                  |                           |
| <b>URL</b>               | /v2/admin/companies?callback=:callback   |                  |                           |
| <b>Header attributes</b> | <b>Attribute</b>   | <b>Required?</b> | <b>Example</b>            |
|                          | authToken  | yes              | authToken=gfUH43trfdkjg34 |
| <b>Method</b>            | GET  |                  |                           |
| <b>URL parameters</b>    | <b>Parameter</b>   | <b>Required?</b> | <b>Example</b>            |
|                          | callback : <string>  | no               | ?callback=jsonpcallback   |
| <b>Data</b>              | none   |                  |                           |
| <b>Success response</b>  | <p>Code: 200 OK</p> <p>Content:</p> <pre>[{   "id" : &lt;integer&gt;,   "name" : &lt;alphanumeric&gt;,   "companyId" : &lt;integer&gt;,   "users" :     [{       "active" : &lt;boolean&gt;,       "companyId" : &lt;integer&gt;,       "dateCreated" : &lt;integer&gt;,       "email" : &lt;alphanumeric&gt;,       "groups" :         [{           "id" : &lt;integer&gt;,           "name" : &lt;alphanumeric&gt;         }],       "id" : &lt;integer&gt;,       "interactionsCount" : &lt;integer&gt;,       "roles" : [&lt;alphanumeric&gt;]     }] }]</pre> |                  |                           |
| <b>Error response</b>    | <p>Code: 401 UNAUTHORIZED</p> <p>Code: 403 FORBIDDEN</p> <p>Code: 404 NOT FOUND</p> <p>Content:</p> <pre>{"code" : &lt;integer&gt;, "error" : &lt;integer&gt;, "devmsg" : &lt;alphanumeric&gt;}</pre>  |                  |                           |
| <b>Code example</b>      | <pre>\$.ajax({   type : "GET",   url : "/v2/contacts/517/deals",   headers : {authToken : "gfUH43trfdkjg34"},   dataType : "json",   success : function(data) {     console.log(data);   }, </pre>   |                  |                           |

|              |  |
|--------------|--|
|              | <pre>error : function(data) {<br/>  console.log(data);<br/>}<br/>});</pre> |
| <b>Notes</b> | none   |

Table 70 Company list request

### 2.5.3.1.60 Read a Company

|                          |  |                  |                                 |
|--------------------------|--|------------------|---------------------------------|
| <b>Title</b>             | Retrieve data about a particular company.  |                  |                                 |
| <b>URL</b>               | /v2/admin/companies/:id?callback=:callback   |                  |                                 |
| <b>Header attributes</b> | <b>Attribute</b>   | <b>Required?</b> | <b>Example</b>                  |
|                          | authToken  | yes              | authToken=gfUH43trfdkjg34       |
| <b>Method</b>            | GET  |                  |                                 |
| <b>URL parameters</b>    | <b>Parameter</b>   | <b>Required?</b> | <b>Example</b>                  |
|                          | id : <integer><br>callback : <string>  | Yes<br>No        | /552<br>?callback=jsonpcallback |
| <b>Data</b>              | none   |                  |                                 |
| <b>Success response</b>  | <p>Code: 200 OK</p> <p>Content:</p> <pre>{   "id" : &lt;integer&gt;,   "name" : &lt;alphanumeric&gt;,   "companyId" : &lt;integer&gt;,   "users" :     [{       "active" : &lt;boolean&gt;,       "companyId" : &lt;integer&gt;,       "dateCreated" : &lt;integer&gt;,       "email" : &lt;alphanumeric&gt;,       "groups" :         [{           "id" : &lt;integer&gt;,           "name" : &lt;alphanumeric&gt;         }],       "id" : &lt;integer&gt;,       "interactionsCount" : &lt;integer&gt;,       "roles" : [&lt;alphanumeric&gt;]     }] }</pre> |                  |                                 |
| <b>Error response</b>    | <p>Code: 401 UNAUTHORIZED</p> <p>Code: 404 NOT FOUND</p> <p>Content:</p> <pre>{"code" : &lt;integer&gt;, "error" : &lt;integer&gt;, "devmsg" : &lt;alphanumeric&gt;}</pre>   |                  |                                 |
| <b>Code example</b>      | <pre>\$.ajax({   type : "GET",   url : "/v2/admin/companies/552",   headers : {authToken : "gfUH43trfdkjg34"},   dataType : "json",   success : function(data) {     console.log(data);   }, </pre>  |                  |                                 |

|              |  |
|--------------|--|
|              | <pre>error : function(data) {<br/>  console.log(data);<br/>}<br/>});</pre> |
| <b>Notes</b> | none   |

Table 71 Single company request

### 2.5.3.1.61 Delete Companies

|                          |  |                  |                           |
|--------------------------|--|------------------|---------------------------|
| <b>Title</b>             | Delete companies with the given ids  |                  |                           |
| <b>URL</b>               | /v2/admin/companies?ids=:ids   |                  |                           |
| <b>Header attributes</b> | <b>Attribute</b>   | <b>Required?</b> | <b>Example</b>            |
|                          | authToken  | yes              | authToken=gfUH43trfdkjg34 |
| <b>Method</b>            | DELETE   |                  |                           |
| <b>URL parameters</b>    | <b>Parameter</b>   | <b>Required?</b> | <b>Example</b>            |
|                          | ids : [<integer>]  | Yes              | ids=456,84,654            |
| <b>Data</b>              | none   |                  |                           |
| <b>Success response</b>  | Code: 200 OK<br>Content:<br>{ "code" : 204, "devmsg" : "success" }   |                  |                           |
| <b>Error response</b>    | Code: 400 BAD REQUEST<br>Code: 401 UNAUTHORIZED<br>Code: 403 FORBIDDEN<br>Content:<br>{ "code" : <integer>, "error" : <integer>, "devmsg" : <alphanumeric> }   |                  |                           |
| <b>Code example</b>      | <pre>\$.ajax({   type : "DELETE",   url : "/v2/admin/companies?ids=456,84,654",   headers : {authToken : "gfUH43trfdkjg34"},   dataType : "json",   success : function(data) {     console.log(data);   },   error : function(data) {     console.log(data);   } });</pre> |                  |                           |
| <b>Notes</b>             | none   |                  |                           |

Table 72 Companies deletion

### 2.5.3.1.62 Create a Group

|                          |   |                  |                            |
|--------------------------|---|------------------|----------------------------|
| <b>Title</b>             | Create a group for sharing contacts with users.   |                  |                            |
| <b>URL</b>               | /v2/admin/groups  |                  |                            |
| <b>Header attributes</b> | <b>Attribute</b>  | <b>Required?</b> | <b>Example</b>             |
|                          | authToken   | yes              | authToken=gfUH43trfdkjpg34 |
| <b>Method</b>            | PUT   |                  |                            |
| <b>URL parameters</b>    | none  |                  |                            |
| <b>Data</b>              | <pre>{   "name" : &lt;alphanumeric&gt;,   "companyId" : &lt;integer&gt; }</pre>   |                  |                            |
| <b>Success response</b>  | Code: 201 CREATED<br>Content:<br><pre>{"code" : 201, "entity" : &lt;group&gt;, "devmsg" : "success"}</pre>  |                  |                            |
| <b>Error response</b>    | Code: 400 BAD REQUEST<br>Code: 401 UNAUTHORIZED<br>Code: 403 FORBIDDEN<br>Content:<br><pre>{"code" : &lt;integer&gt;, "error" : &lt;integer&gt;, "devmsg" : &lt;alphanumeric&gt;}</pre>   |                  |                            |
| <b>Code example</b>      | <pre>\$.ajax({   type : "PUT",   url : "/v2/admin/groups",   headers : {authToken : "gfUH43trfdkjpg34"},   dataType : "json",   contentType : "application/json",   data : JSON.stringify({     "name" : "Sales dept.",     "companyId" : 12   }) }) success : function(data) {   console.log(data); }, error : function(data) {   console.log(data); } });</pre> |                  |                            |
| <b>Notes</b>             | none  |                  |                            |

Table 73 Group creation



### 2.5.3.1.63 Read a List of Groups Associated with a Company

|                          |  |                  |                                  |
|--------------------------|--|------------------|----------------------------------|
| <b>Title</b>             | Retrieve a list of groups associated with a particular company   |                  |                                  |
| <b>URL</b>               | /v2/admin/companies/:id/groups?callback=:callback  |                  |                                  |
| <b>Header attributes</b> | <b>Attribute</b>   | <b>Required?</b> | <b>Example</b>                   |
|                          | authToken  | yes              | authToken=gfUH43trfdkjg34        |
| <b>Method</b>            | GET  |                  |                                  |
| <b>URL parameters</b>    | <b>Parameter</b>   | <b>Required?</b> | <b>Example</b>                   |
|                          | id : <integer><br>callback : <string>  | Yes<br>No        | /758/<br>?callback=jsonpcallback |
| <b>Data</b>              | none   |                  |                                  |
| <b>Success response</b>  | <p>Code: 200 OK</p> <p>Content:</p> <pre>[{   "id" : &lt;integer&gt;,   "name" : &lt;alphanumeric&gt;,   "companyId" : &lt;integer&gt;,   "users" :     [{       "active" : &lt;boolean&gt;,       "companyId" : &lt;integer&gt;,       "dateCreated" : &lt;integer&gt;,       "email" : &lt;alphanumeric&gt;,       "groups" :         [{           "id" : &lt;integer&gt;,           "name" : &lt;alphanumeric&gt;         }],       "id" : &lt;integer&gt;,       "interactionsCount" : &lt;integer&gt;,       "roles" : [&lt;alphanumeric&gt;]     }] }]</pre> |                  |                                  |
| <b>Error response</b>    | <p>Code: 401 UNAUTHORIZED</p> <p>Code: 403 FORBIDDEN</p> <p>Code: 404 NOT FOUND</p> <p>Content:</p> <pre>{"code" : &lt;integer&gt;, "error" : &lt;integer&gt;, "devmsg" : &lt;alphanumeric&gt;}</pre>  |                  |                                  |
| <b>Code example</b>      | <pre>\$.ajax({   type : "GET",   url : "/v2/admin/companies/758/groups",   headers : {authToken : "gfUH43trfdkjg34"},   dataType : "json",   success : function(data) {</pre>  |                  |                                  |

|              |  |
|--------------|--|
|              | <pre>console.log(data); }, error : function(data) {   console.log(data); } });</pre> |
| <b>Notes</b> | none   |

Table 74 Group list request - associated with a company

### 2.5.3.1.64 Read a Group

|                          |  |                  |                                 |
|--------------------------|--|------------------|---------------------------------|
| <b>Title</b>             | Retrieve data about a particular group.  |                  |                                 |
| <b>URL</b>               | /v2/admin/groups/:id?callback=:callback  |                  |                                 |
| <b>Header attributes</b> | <b>Attribute</b>   | <b>Required?</b> | <b>Example</b>                  |
|                          | authToken  | yes              | authToken=gfUH43trfdkjg34       |
| <b>Method</b>            | GET  |                  |                                 |
| <b>URL parameters</b>    | <b>Parameter</b>   | <b>Required?</b> | <b>Example</b>                  |
|                          | id : <integer><br>callback : <string>  | Yes<br>No        | /875<br>?callback=jsonpcallback |
| <b>Data</b>              | none   |                  |                                 |
| <b>Success response</b>  | <p>Code: 200 OK</p> <p>Content:</p> <pre>{   "id" : &lt;integer&gt;,   "name" : &lt;alphanumeric&gt;,   "companyId" : &lt;integer&gt;,   "users" :     [{       "active" : &lt;boolean&gt;,       "companyId" : &lt;integer&gt;,       "dateCreated" : &lt;integer&gt;,       "email" : &lt;alphanumeric&gt;,       "groups" :         [{           "id" : &lt;integer&gt;,           "name" : &lt;alphanumeric&gt;         }],       "id" : &lt;integer&gt;,       "interactionsCount" : &lt;integer&gt;,       "roles" : [&lt;alphanumeric&gt;]     }] }</pre> |                  |                                 |
| <b>Error response</b>    | <p>Code: 401 UNAUTHORIZED</p> <p>Code: 404 NOT FOUND</p> <p>Content:</p> <pre>{"code" : &lt;integer&gt;, "error" : &lt;integer&gt;, "devmsg" : &lt;alphanumeric&gt;}</pre>   |                  |                                 |
| <b>Code example</b>      | <pre>\$.ajax({   type : "GET",   url : "/v2/admin/groups/875",   headers : {authToken : "gfUH43trfdkjg34"},   dataType : "json",   success : function(data) {     console.log(data);   }, </pre>   |                  |                                 |

|              |  |
|--------------|--|
|              | <pre>error : function(data) {<br/>  console.log(data);<br/>}<br/>});</pre> |
| <b>Notes</b> | none   |

Table 75 Single group request

### 2.5.3.1.65 Update a Group

|                          |   |                  |                           |
|--------------------------|---|------------------|---------------------------|
| <b>Title</b>             | Update a particular group   |                  |                           |
| <b>URL</b>               | /v2/admin/groups/:id  |                  |                           |
| <b>Header attributes</b> | <b>Attribute</b>  | <b>Required?</b> | <b>Example</b>            |
|                          | authToken   | yes              | authToken=gfUH43trfdkjg34 |
| <b>Method</b>            | POST  |                  |                           |
| <b>URL parameters</b>    | <b>Parameter</b>  | <b>Required?</b> | <b>Example</b>            |
|                          | id : <integer>  | yes              | /46                       |
| <b>Data</b>              | <pre>{   "name" : &lt;alphanumeric&gt; }</pre>  |                  |                           |
| <b>Success response</b>  | Code: 200 OK  |                  |                           |
|                          | <pre>{"code" : 200, "entity" : &lt;group&gt;, "devmsg" : "success"}</pre>   |                  |                           |
| <b>Error response</b>    | Code: 400 BAD REQUEST<br>Code: 401 UNAUTHORIZED<br>Code: 403 FORBIDDEN  |                  |                           |
|                          | <pre>{"code" : &lt;integer&gt;, "error" : &lt;integer&gt;, "devmsg" : &lt;alphanumeric&gt;}</pre>   |                  |                           |
| <b>Code example</b>      | <pre>\$.ajax({   type : "POST",   url : "/v2/admin/group/46",   headers : {authToken : "gfUH43trfdkjg34"},   dataType : "json",   contentType : "application/json",   data : JSON.stringify({     "name" : "sales department"   })   success : function(data) {     console.log(data);   },   error : function(data) {     console.log(data);   } });</pre> |                  |                           |
| <b>Notes</b>             | none  |                  |                           |

Table 76 Group update

### 2.5.3.1.66 Delete Groups

|                          |  |                  |                           |
|--------------------------|--|------------------|---------------------------|
| <b>Title</b>             | Delete groups with the given ids   |                  |                           |
| <b>URL</b>               | /v2/admin/groups?ids=:ids  |                  |                           |
| <b>Header attributes</b> | <b>Attribute</b>   | <b>Required?</b> | <b>Example</b>            |
|                          | authToken  | yes              | authToken=gfUH43trfdkjg34 |
| <b>Method</b>            | DELETE   |                  |                           |
| <b>URL parameters</b>    | <b>Parameter</b>   | <b>Required?</b> | <b>Example</b>            |
|                          | ids : [<integer>]  | Yes              | ids=56,2731,894           |
| <b>Data</b>              | none   |                  |                           |
| <b>Success response</b>  | Code: 200 OK<br>Content:<br>{ "code" : 204, "devmsg" : "success" }   |                  |                           |
| <b>Error response</b>    | Code: 400 BAD REQUEST<br>Code: 401 UNAUTHORIZED<br>Code: 403 FORBIDDEN<br>Content:<br>{ "code" : <integer>, "error" : <integer>, "devmsg" : <alphanumeric> }   |                  |                           |
| <b>Code example</b>      | <pre>\$.ajax({   type : "DELETE",   url : "/v2/admin/groups?ids=56,2731,894",   headers : {authToken : "gfUH43trfdkjg34"},   dataType : "json",   success : function(data) {     console.log(data);   },   error : function(data) {     console.log(data);   } });</pre> |                  |                           |
| <b>Notes</b>             | none   |                  |                           |

Table 77 Groups deletion

### 2.5.3.1.67 Delete a Group

|                          |  |                  |                           |
|--------------------------|--|------------------|---------------------------|
| <b>Title</b>             | Delete a particular group  |                  |                           |
| <b>URL</b>               | /v2/admin/groups/:id   |                  |                           |
| <b>Header attributes</b> | <b>Attribute</b>   | <b>Required?</b> | <b>Example</b>            |
|                          | authToken  | yes              | authToken=gfUH43trfdkjg34 |
| <b>Method</b>            | DELETE   |                  |                           |
| <b>URL parameters</b>    | <b>Parameter</b>   | <b>Required?</b> | <b>Example</b>            |
|                          | id : <integer>   | yes              | /289                      |
| <b>Data</b>              | none   |                  |                           |
| <b>Success response</b>  | Code: 200 OK<br>Content:<br>{ "code" : 204, "devmsg" : "success" }   |                  |                           |
| <b>Error response</b>    | Code: 400 BAD REQUEST<br>Code: 401 UNAUTHORIZED<br>Code: 403 FORBIDDEN<br>Content:<br>{ "code" : <integer>, "error" : <integer>, "devmsg" : <alphanumeric> }   |                  |                           |
| <b>Code example</b>      | <pre>\$.ajax({   type : "DELETE",   url : "/v2/admin/groups/289",   headers : {authToken : "gfUH43trfdkjg34"},   dataType : "json",   success : function(data) {     console.log(data);   },   error : function(data) {     console.log(data);   } });</pre> |                  |                           |
| <b>Notes</b>             | none   |                  |                           |

Table 78 Group deletion

### 2.5.3.1.68 Register a Device

|                          |  |                  |                           |
|--------------------------|--|------------------|---------------------------|
| <b>Title</b>             | Registers a new device for push notifications.   |                  |                           |
| <b>URL</b>               | /v2/devices  |                  |                           |
| <b>Header attributes</b> | <b>Attribute</b>   | <b>Required?</b> | <b>Example</b>            |
|                          | authToken  | Yes              | authToken=gfUH43trfdkjg34 |
| <b>Method</b>            | PUT  |                  |                           |
| <b>URL Parameters</b>    | none   |                  |                           |
| <b>Data</b>              | <pre>{   "active" : &lt;boolean&gt;,   "decoded" : &lt;boolean&gt;,   "deviceId" : &lt;alphanumeric&gt;,   "name" : &lt;alphanumeric&gt; }</pre>   |                  |                           |
| <b>Success response</b>  | Code: 201 CREATED  |                  |                           |
|                          | {"code" : 201, "entity" : <device>, "devmsg" : "success"}  |                  |                           |
| <b>Error response</b>    | Code: 400 BAD REQUEST<br>Code: 401 UNAUTHORIZED<br>Code: 403 FORBIDDEN   |                  |                           |
|                          | {"code" : <integer>, "error" : <integer>, "devmsg" : <alphanumeric>}   |                  |                           |
| <b>Code example</b>      | <pre>\$.ajax({   type : "PUT",   url : "/v2/devices",   headers : {authToken : "gfUH43trfdkjg34"},   dataType : "json",   contentType : "application/json",   data : JSON.stringify({     "deviceId" : "6g79bcd2b124bcd835a0769cas3f9b12bbd2b8a779f7fde29b7c11897dcff4q8",     "name" : "Ipad 2",     "decoded" : true,     "active" : true   }),   success : function(data) {     console.log(data);   },   error : function(data) {     console.log(data);   } });</pre> |                  |                           |
| <b>Notes</b>             | The <i>deviceId</i> can be passed as base64-encoded string of the raw-byte-data or as decoded hex-string (with 64 characters representing the 8 octets of the deviceId). If second option is used the <i>decoded</i> attribute must be set to <i>TRUE</i> .  |                  |                           |

Table 79 Register a device



### 2.5.3.1.69 Read a List of Devices

|                          |   |                  |                            |
|--------------------------|---|------------------|----------------------------|
| <b>Title</b>             | Read a list of devices.   |                  |                            |
| <b>URL</b>               | /v2/devices?callback=:callback  |                  |                            |
| <b>Header attributes</b> | <b>Attribute</b>  | <b>Required?</b> | <b>Example</b>             |
|                          | authToken   | Yes              | authToken=gfUH43trfdkjpg34 |
| <b>Method</b>            | GET   |                  |                            |
| <b>URL parameters</b>    | <b>Parameter</b>  | <b>Required?</b> | <b>Example</b>             |
|                          | callback : <string>   | no               | ?callback=jsonpcallback    |
| <b>Data</b>              | none  |                  |                            |
| <b>Success response</b>  | Code: 200 OK  |                  |                            |
|                          | <pre>[{   "id" : &lt;integer&gt;,   "active" : &lt;boolean&gt;,   "deviceId" : &lt;alphanumeric&gt;,   "name" : &lt;alphanumeric&gt; }]</pre>   |                  |                            |
| <b>Error response</b>    | Code: 401 UNAUTHORIZED  |                  |                            |
|                          | <pre>{"code" : &lt;integer&gt;, "error" : &lt;integer&gt;, "devmsg" : &lt;alphanumeric&gt;}</pre>   |                  |                            |
| <b>Code example</b>      | <pre>\$.ajax({   type : "GET",   url : "/v2/devices",   headers : {authToken : "gfUH43trfdkjpg34"},   dataType : "json",   success : function(data) {     console.log(data);   },   error : function(data) {     console.log(data);   } });</pre> |                  |                            |
| <b>Notes</b>             | none  |                  |                            |

Table 80 Read a list of Devices

### 2.5.3.1.70 Update a Device

|                          |  |                  |                           |
|--------------------------|--|------------------|---------------------------|
| <b>Title</b>             | Update a registered device   |                  |                           |
| <b>URL</b>               | /v2/devices/:id  |                  |                           |
| <b>Header attributes</b> | <b>Attribute</b>   | <b>Required?</b> | <b>Example</b>            |
|                          | authToken  | Yes              | authToken=gfUH43trfdkjg34 |
| <b>Method</b>            | POST   |                  |                           |
| <b>URL parameters</b>    | <b>Parameter</b>   | <b>Required?</b> | <b>Example</b>            |
|                          | id : <integer>   | yes              | /31                       |
| <b>Data</b>              | <pre>{   "name" : &lt;alphanumeric&gt;,   "active" : &lt;boolean&gt; }</pre>   |                  |                           |
| <b>Success response</b>  | Code: 200 OK<br>Content:<br><pre>{ "code" : 200, "entity" : &lt;device&gt;, "devmsg" : "success" }</pre>   |                  |                           |
| <b>Error response</b>    | Code: 400 BAD REQUEST<br>Code: 401 UNAUTHORIZED<br>Code: 403 FORBIDDEN<br>Content:<br><pre>{ "code" : &lt;integer&gt;, "error" : &lt;integer&gt;, "devmsg" : &lt;alphanumeric&gt; }</pre>  |                  |                           |
| <b>Code example</b>      | <pre>\$.ajax({   type : "POST",   url : "/v2/devices/31",   headers : { authToken : "gfUH43trfdkjg34" },   dataType : "json",   contentType : "application/json",   data : JSON.stringify({     "name" : "Ipad 2",     "active" : false   }),   success : function(data) {     console.log(data);   },   error : function(data) {     console.log(data);   } });</pre> |                  |                           |
| <b>Notes</b>             | none   |                  |                           |

Table 81 Update a device

### 2.5.3.1.71 Delete a Device

|                          |   |                  |                           |
|--------------------------|---|------------------|---------------------------|
| <b>Title</b>             | Delete a device   |                  |                           |
| <b>URL</b>               | /v2/devices/:id   |                  |                           |
| <b>Header attributes</b> | <b>Attribute</b>  | <b>Required?</b> | <b>Example</b>            |
|                          | authToken   | Yes              | authToken=gfUH43trfdkjg34 |
| <b>Method</b>            | DELETE  |                  |                           |
| <b>URL parameters</b>    | <b>Parameter</b>  | <b>Required</b>  | <b>Example</b>            |
|                          | id : <integer>  | Yes              | /3                        |
| <b>Data</b>              | none  |                  |                           |
| <b>Success response</b>  | Code: 200 OK  |                  |                           |
|                          | {"code" : 204, "devmsg" : "success"}  |                  |                           |
| <b>Error response</b>    | Code: 400 BAD REQUEST<br>Code: 401 UNAUTHORIZED<br>Code: 403 FORBIDDEN  |                  |                           |
|                          | {"code" : <integer>, "error" : <integer>, "devmsg" : <alphanumeric>}  |                  |                           |
| <b>Code example</b>      | <pre>\$.ajax({   type : "DELETE",   url : "/v2/devices/3",   headers : {authToken : "gfUH43trfdkjg34"},   dataType : "json",   success : function(data) {     console.log(data);   },   error : function(data) {     console.log(data);   } });</pre> |                  |                           |
| <b>Notes</b>             | none  |                  |                           |

Table 82 Delete a device

### 2.5.3.1.72 Create a Custom Field

|                          |   |                  |                           |
|--------------------------|---|------------------|---------------------------|
| <b>Title</b>             | Create a custom field for an entity type.   |                  |                           |
| <b>URL</b>               | /v2/admin/customFields  |                  |                           |
| <b>Header attributes</b> | <b>Attribute</b>  | <b>Required?</b> | <b>Example</b>            |
|                          | authToken   | yes              | authToken=gfUH43trfdkjg34 |
| <b>Method</b>            | PUT   |                  |                           |
| <b>URL parameters</b>    | none  |                  |                           |
| <b>Data</b>              | <pre>{   "companyId" : &lt;integer&gt;,   "dataType" : &lt;enum(varchar)&gt;,   "entityType" : &lt;enum(contact)&gt;,   "name" : &lt;alphanumeric&gt; }</pre>   |                  |                           |
| <b>Success response</b>  | Code: 201 CREATED   |                  |                           |
|                          | {"code" : 201, "entity" : <customField>, "devmsg" : "success"}  |                  |                           |
| <b>Error response</b>    | Code: 400 BAD REQUEST<br>Code: 401 UNAUTHORIZED<br>Code: 403 FORBIDDEN  |                  |                           |
|                          | {"code" : <integer>, "error" : <integer>, "devmsg" : <alphanumeric>}  |                  |                           |
| <b>Code example</b>      | <pre>\$.ajax({   type : "PUT",   url : "/v2/customFields",   headers : {authToken : "gfUH43trfdkjg34"},   dataType : "json",   contentType : "application/json",   data : JSON.stringify({     "name" : "family status",     "dataType" : "varchar",     "entityType" : "contact"   })   success : function(data) {     console.log(data);   },   error : function(data) {     console.log(data);   } });</pre> |                  |                           |
| <b>Notes</b>             | <p>For now only text fields with <i>datatype</i> varchar can be created for entities of type contact.</p> <p>If no <i>companyId</i> is given, the creating user must be a member of a company himself and his <i>companyId</i> will be used.</p>  |                  |                           |

Table 83 Custom field creation

### 2.5.3.1.73 Read a List of Custom Fields Associated with a Company

|                          |  |                  |                           |
|--------------------------|--|------------------|---------------------------|
| <b>Title</b>             | Retrieve a list of custom fields associated with a company.  |                  |                           |
| <b>URL</b>               | /v2/admin/company/:id/customFields?entityType=:type&callback=:callback   |                  |                           |
| <b>Header attributes</b> | <b>Attribute</b>   | <b>Required?</b> | <b>Example</b>            |
|                          | authToken  | yes              | authToken=gfUH43trfdkjg34 |
| <b>Method</b>            | GET  |                  |                           |
| <b>URL parameters</b>    | <b>Parameter</b>   | <b>Required?</b> | <b>Example</b>            |
|                          | id : <integer>   | yes              | /23                       |
|                          | type : <alphanumeric>  | no               | ?entityType=contact       |
|                          | callback : <string>  | no               | &callback=jsonpcallback   |
| <b>Data</b>              | none   |                  |                           |
| <b>Success response</b>  | Code: 200 OK   |                  |                           |
|                          | <pre>[{   "id" : &lt;integer&gt;,   "dataType" : &lt;enuam(vchar)&gt;,   "entityType" : &lt;enuam(contact)&gt;,   "name" : &lt;alphanumeric&gt; }]</pre>   |                  |                           |
| <b>Error response</b>    | Code: 400 BAD REQUEST<br>Code: 401 UNAUTHORIZED<br>Code: 403 FORBIDDEN   |                  |                           |
|                          | <pre>{"code" : &lt;integer&gt;, "error" : &lt;integer&gt;, "devmsg" : &lt;alphanumeric&gt;}</pre>  |                  |                           |
| <b>Code example</b>      | <pre>\$.ajax({   type : "GET",   url : "/v2/admin/customFields?offset=0&amp;limit=25",   headers : { authToken : "gfUH43trfdkjg34" },   dataType : "json",   success : function(data) {     console.log(data);   },   error : function(data) {     console.log(data);   } });</pre>  |                  |                           |
| <b>Notes</b>             | <p><i>offset</i> and <i>limit</i> parameters are used for pagination. If both are specified, the response will contain according <i>length</i> and <i>startIndex</i> attributes as well as an additional <i>totalLength</i> attribute to indicate whether there are more custom fields available.</p> <p>The <i>entityType</i> parameter can be used to filter custom fields for a particular type of entity. For now, the only supported entity type is "contact" – so setting a different type would lead to an empty result list.</p> |                  |                           |

Table 84 Custom field list request – associated with a company

### 2.5.3.1.74 Read a Custom Field

|                          |   |                  |                                 |
|--------------------------|---|------------------|---------------------------------|
| <b>Title</b>             | Retrieve data of a particular custom field  |                  |                                 |
| <b>URL</b>               | /v2/admin/customFields/:id?callback=:callback   |                  |                                 |
| <b>Header attributes</b> | <b>Attribute</b>  | <b>Required?</b> | <b>Example</b>                  |
|                          | authToken   | yes              | authToken=gfUH43trfdkjg34       |
| <b>Method</b>            | GET   |                  |                                 |
| <b>URL parameters</b>    | <b>Parameter</b>  | <b>Required?</b> | <b>Example</b>                  |
|                          | id : <integer><br>callback : <string>   | Yes<br>No        | /261<br>?callback=jsonpcallback |
| <b>Data</b>              | none  |                  |                                 |
| <b>Success response</b>  | Code: 200 OK  |                  |                                 |
|                          | <pre>{   "id" : &lt;integer&gt;,   "dataType" : &lt;enuam(vchar)&gt;,   "entityType" : &lt;enuam(contact)&gt;,   "name" : &lt;alphanumeric&gt; }</pre>  |                  |                                 |
| <b>Error response</b>    | Code: 400 BAD REQUEST<br>Code: 401 UNAUTHORIZED<br>Code: 403 FORBIDDEN  |                  |                                 |
|                          | <pre>{"code" : &lt;integer&gt;, "error" : &lt;integer&gt;, "devmsg" : &lt;alphanumeric&gt;}</pre>   |                  |                                 |
| <b>Code example</b>      | <pre>\$.ajax({   type : "GET",   url : "/v2/admin/customFields/261",   headers : {authToken : "gfUH43trfdkjg34"},   dataType : "json",   success : function(data) {     console.log(data);   },   error : function(data) {     console.log(data);   } });</pre> |                  |                                 |
| <b>Notes</b>             | none  |                  |                                 |

Table 85 Custom field request

### 2.5.3.1.75 Update a Custom Field

|                          |   |                  |                           |
|--------------------------|---|------------------|---------------------------|
| <b>Title</b>             | Update a particular custom field.   |                  |                           |
| <b>URL</b>               | /v2/admin/customFields/:id  |                  |                           |
| <b>Header attributes</b> | <b>Attribute</b>  | <b>Required?</b> | <b>Example</b>            |
|                          | authToken   | yes              | authToken=gfUH43trfdkjg34 |
| <b>Method</b>            | POST  |                  |                           |
| <b>URL parameters</b>    | <b>Parameter</b>  | <b>Required?</b> | <b>Example</b>            |
|                          | id : <integer>  | yes              | /463                      |
| <b>Data</b>              | <pre>{   "name" : &lt;alphanumeric&gt; }</pre>  |                  |                           |
| <b>Success response</b>  | Code: 200 OK  |                  |                           |
|                          | <pre>{"code" : 200, "entity" : &lt;customField&gt;, "devmsg" : "success"}</pre>   |                  |                           |
| <b>Error response</b>    | Code: 400 BAD REQUEST<br>Code: 401 UNAUTHORIZED<br>Code: 403 FORBIDDEN  |                  |                           |
|                          | <pre>{"code" : &lt;integer&gt;, "error" : &lt;integer&gt;, "devmsg" : &lt;alphanumeric&gt;}</pre>   |                  |                           |
| <b>Code example</b>      | <pre>\$.ajax({   type : "POST",   url : "/v2/admin/customFields/463",   headers : {authToken : "gfUH43trfdkjg34"},   dataType : "json",   contentType : "application/json",   data : JSON.stringify({     "name" : "hair color"   })   success : function(data) {     console.log(data);   },   error : function(data) {     console.log(data);   } });</pre> |                  |                           |
| <b>Notes</b>             | none  |                  |                           |

Table 86 Custom field update

### 2.5.3.1.76 Delete Custom Fields

|                          |  |                  |                           |
|--------------------------|--|------------------|---------------------------|
| <b>Title</b>             | Delete custom fields with the given ids  |                  |                           |
| <b>URL</b>               | /v2/admin/customFields?ids=:ids  |                  |                           |
| <b>Header attributes</b> | <b>Attribute</b>   | <b>Required?</b> | <b>Example</b>            |
|                          | authToken  | Yes              | authToken=gfUH43trfdkjg34 |
| <b>Method</b>            | DELETE   |                  |                           |
| <b>URL parameters</b>    | <b>Parameter</b>   | <b>Required?</b> | <b>Example</b>            |
|                          | ids : [<integer>]  | Yes              | ids=371,455               |
| <b>Data</b>              | none   |                  |                           |
| <b>Success response</b>  | Code: 200 OK   |                  |                           |
|                          | {"code" : 204, "devmsg" : "success"}   |                  |                           |
| <b>Error response</b>    | Code: 401 UNAUTHORIZED<br>Code: 403 FORBIDDEN  |                  |                           |
|                          | {"code" : <integer>, "error" : <integer>, "devmsg" : <alphanumeric>}   |                  |                           |
| <b>Code example</b>      | <pre>\$.ajax({   type : "DELETE",   url : "/v2/admin/customFields?ids=371,455",   headers : {authToken : "gfUH43trfdkjg34"},   dataType : "json",   success : function(data) {     console.log(data);   },   error : function(data) {     console.log(data);   } });</pre> |                  |                           |
| <b>Notes</b>             | none   |                  |                           |

Table 87 Custom fields deletion



### 2.5.3.2 Extended functions

Extended functions are represented by a *cmd* query parameter.

#### 2.5.3.2.1 Synchronize Offline Data

|                          |   |                  |                                     |
|--------------------------|---|------------------|-------------------------------------|
| <b>Title</b>             | Synchronize local DB with data from cloud DB.   |                  |                                     |
| <b>URL</b>               | /v2/sync?deviceId=:token&since=:time  |                  |                                     |
| <b>Header attributes</b> | <b>Attribute</b>  | <b>Required?</b> | <b>Example</b>                      |
|                          | authToken   | Yes              | authToken=gfUH43trfdkjg34           |
| <b>Method</b>            | GET   |                  |                                     |
| <b>URL parameters</b>    | <b>Parameter</b>  | <b>Required?</b> | <b>Example</b>                      |
|                          | token : <alphanumeric><br>time : <integer>  | yes<br>no        | ?token=12345<br>&time=1366819829170 |
| <b>Data</b>              | none  |                  |                                     |
| <b>Success response</b>  | Code: 200 OK<br>Content:<br><pre>{   "contacts" : [&lt;contact&gt;],   "deals" : [&lt;deal&gt;],   "interactions" : [&lt;interaction&gt;],   "notes" : [&lt;note&gt;],   "taskLists" : [&lt;tasklist&gt;],   "tasks" : [&lt;task&gt;],   "deleted" :     [{       "id" : &lt;integer&gt;,       "type" : &lt;enum(contact,deal,interaction,note,taskList,task)&gt;     }] }</pre> |                  |                                     |
| <b>Error response</b>    | Code: 400 BAD REQUEST<br>Code: 401 UNAUTHORIZED<br>Code: 403 FORBIDDEN<br>Content:<br><pre>{"code" : &lt;integer&gt;, "error" : &lt;integer&gt;, "devmsg" : &lt;alphanumeric&gt;}</pre>   |                  |                                     |
| <b>Code example</b>      | <pre>\$.ajax({   type : "GET",   url : "/v2/sync?deviceId=12345",   headers : {authToken : "gfUH43trfdkjg34"},   dataType : "json",   success : function(data) {     console.log(data);   }, }</pre>  |                  |                                     |

|              |  |
|--------------|--|
|              | <pre>error : function(data) {<br/>  console.log(data);<br/>}<br/>});</pre>   |
| <b>Notes</b> | <p>The given <i>deviceId</i> must be a token formerly given to “Register a Device”.</p> <p>The <i>time</i> parameter defines the start point from which to get changed data. It is represented by the number of milliseconds since the standard base time known as "the epoch", namely January 1, 1970, 00:00:00 GMT. If the time parameter is omitted or it is set to a time after the last sync-time of the specified device, that last sync-time is used instead.</p> |

Table 88 Synchronize offline data

### 2.5.3.2.2 Wipe-out a User Account

|                          |   |                  |                           |
|--------------------------|---|------------------|---------------------------|
| <b>Title</b>             | Wipe-out data of a particular user account  |                  |                           |
| <b>URL</b>               | /v2/admin/users/:id?cmd=wipeAccount   |                  |                           |
| <b>Header attributes</b> | <b>Attribute</b>  | <b>Required?</b> | <b>Example</b>            |
|                          | authToken   | Yes              | authToken=gfUH43trfdkjg34 |
| <b>Method</b>            | POST  |                  |                           |
| <b>URL parameters</b>    | <b>Parameter</b>  | <b>Required?</b> | <b>Example</b>            |
|                          | id : <integer>  | yes              | /23                       |
| <b>Data</b>              | { } or null   |                  |                           |
| <b>Success response</b>  | Code: 200 OK  |                  |                           |
|                          | { "code" : 200, "devmsg" : "success" }  |                  |                           |
| <b>Error response</b>    | Code: 400 BAD REQUEST<br>Code: 401 UNAUTHORIZED<br>Code: 403 FORBIDDEN  |                  |                           |
|                          | { "code" : <integer>, "error" : <integer>, "devmsg" : <alphanumeric> }  |                  |                           |
| <b>Code example</b>      | <pre>\$.ajax({   type : "POST",   url : "/v2/admin/users/23?cmd=wipeAccount",   headers : {authToken : "gfUH43trfdkjg34"},   dataType : "json",   contentType : "application/json",   data : JSON.stringify({}),   success : function(data) {     console.log(data);   },   error : function(data) {     console.log(data);   } });</pre> |                  |                           |
| <b>Notes</b>             | none  |                  |                           |

Table 89 User account wipe-out

### 2.5.3.2.3 Read a List of Contact Groups From an External System

|                          |  |                  |                           |
|--------------------------|--|------------------|---------------------------|
| <b>Title</b>             | Read contact groups defined in an external system  |                  |                           |
| <b>URL</b>               | /v2/import?cmd=getContactGroups  |                  |                           |
| <b>Header attributes</b> | <b>Attribute</b>   | <b>Required?</b> | <b>Example</b>            |
|                          | authToken  | Yes              | authToken=gfUH43trfdkjg34 |
| <b>Method</b>            | POST   |                  |                           |
| <b>URL parameters</b>    | none   |                  |                           |
| <b>Data</b>              | <pre>{   "externalSystem" : "google",   "username" : &lt;alphanumeric&gt;,   "password" : &lt;alphanumeric&gt; }</pre>   |                  |                           |
| <b>Success response</b>  | Code: 200 OK   |                  |                           |
|                          | <pre>[{   "externalId" : &lt;alphanumeric&gt;,   "name" : &lt;alphanumeric&gt; }]</pre>  |                  |                           |
| <b>Error response</b>    | Code: 401 UNAUTHORIZED<br>Code: 403 FORBIDDEN<br>Code: 503 SERVICE UNAVAILABLE   |                  |                           |
|                          | <pre>{"code" : &lt;integer&gt;, "error" : &lt;integer&gt;, "devmsg" : &lt;alphanumeric&gt;}</pre>  |                  |                           |
| <b>Code example</b>      | <pre>\$.ajax({   type : "POST",   url : "/v2/import?cmd=getContactGroups",   headers : {authToken : "gfUH43trfdkjg34"},   dataType : "json",   contentType : "application/json",   data : JSON.stringify({     "externalSystem" : "google",     "username" : "john.doe@googlemail.com",     "password" : "pa55w0rd"   }),   success : function(data) {     console.log(data);   },   error : function(data) {     console.log(data);   } });</pre> |                  |                           |
| <b>Notes</b>             | Ids of returned data can be passed as query parameters for "Import Person Contacts".<br>For now the only supported external system is google (gmail).  |                  |                           |

Table 90 External contact groups request

#### 2.5.3.2.4 Import Person Contacts

|                          |   |                  |                                  |
|--------------------------|---|------------------|----------------------------------|
| <b>Title</b>             | Import contacts from an external system   |                  |                                  |
| <b>URL</b>               | /v2/import?cmd=importContacts&nameRequired=:reqN&phoneRequired=:reqP&emailRequired=:reqE&updated-min=:time&groupIds=:ids  |                  |                                  |
| <b>Header attributes</b> | <b>Attribute</b>  | <b>Required?</b> | <b>Example</b>                   |
|                          | authToken   | Yes              | authToken=gfUH43trfdkjg34        |
| <b>Method</b>            | POST  |                  |                                  |
| <b>URL parameters</b>    | <b>Parameter</b>  | <b>Required?</b> | <b>Example</b>                   |
|                          | reqN : <boolean>  | no               | &nameRequired=1                  |
|                          | reqP : <boolean>  | no               | &phoneRequired=0                 |
|                          | reqE : <boolean>  | no               | &emailRequired=0                 |
|                          | time : <datetime>   | no               | &updated-min=2012-12-31T00:00:00 |
|                          | ids : [<alphanumeric>]  | no               | &groupIds=dfdg4f,6get54,none     |
| <b>Data</b>              | <pre>{   "externalSystem" : "google",   "username" : &lt;alphanumeric&gt;,   "password" : &lt;alphanumeric&gt; }</pre>  |                  |                                  |
| <b>Success response</b>  | Code: 200 OK  |                  |                                  |
|                          | <pre>{   "externalSystem" : "google",   "externalSystemAccount" : &lt;alphanumeric&gt;,   "importTime" : &lt;integer&gt;,   "failed" : [&lt;integer&gt;],   "created" : [&lt;integer&gt;],   "updated" : [&lt;integer&gt;],   "deleted" : [&lt;integer&gt;] }</pre>   |                  |                                  |
| <b>Error response</b>    | Code: 401 UNAUTHORIZED<br>Code: 403 FORBIDDEN<br>Code: 503 SERVICE UNAVAILABLE  |                  |                                  |
|                          | <pre>{"code" : &lt;integer&gt;, "error" : &lt;integer&gt;, "devmsg" : &lt;alphanumeric&gt;}</pre>   |                  |                                  |
| <b>Code example</b>      | <pre>\$.ajax({   type : "POST",   url : "/v2/import?cmd=importContacts&amp;nameRequired=1&amp;groupIds=none",   headers : {authToken : "gfUH43trfdkjg34"},   dataType : "json",   contentType : "application/json",   data : JSON.stringify({     "externalSystem" : "google",     "username" : "john.doe@googlemail.com",     "password" : "pa55w0rd"   }),   success : function(data) {     console.log(data);   },   error : function(data) {     console.log(data);   } });</pre> |                  |                                  |

|              |   |
|--------------|---|
|              | <pre>}<br/>});</pre>  |
| <b>Notes</b> | <p>Data returned by the failed array is not stored as contact data in the database. User is supposed to resolve these data and call create/update/merge later.</p> <p>As group ids you can pass values earlier retrieved by Synchronize Offline Data. In addition you can pass none as groupid to import contacts without any group membership in the external system.</p> <p>If the updated-min parameter is set, only contacts created or updated after the specified time (in UTC datetime format yyyy-MM-dd'T'HH:mm:ss.SSS'Z') will be downloaded. Note that if updated-min is not set, the default value is the last download time. In this case only contacts created or changed after the last download will be downloaded.</p> <p>For now the only supported external system is google (gmail).</p> |

Table 91 Person contacts import

### 2.5.3.2.5 Find Duplicates of Basicinfos

|                          |  |                  |                           |
|--------------------------|--|------------------|---------------------------|
| <b>Title</b>             | Find basicinfos, phone numbers especially, which are assigned to multiple contacts.  |                  |                           |
| <b>URL</b>               | /v2/cleanup?cmd=getDuplicates  |                  |                           |
| <b>Header attributes</b> | <b>Attribute</b>   | <b>Required?</b> | <b>Example</b>            |
|                          | authToken  | Yes              | authToken=gfUH43trfdkjg34 |
| <b>Method</b>            | GET  |                  |                           |
| <b>URL parameters</b>    | none   |                  |                           |
| <b>Data</b>              | none   |                  |                           |
| <b>Success response</b>  | Code: 200 OK   |                  |                           |
|                          | [<alphanumeric>]   |                  |                           |
| <b>Error response</b>    | Code: 401 UNAUTHORIZED<br>Code: 403 FORBIDDEN  |                  |                           |
|                          | { "code" : <integer>, "error" : <integer>, "devmsg" : <alphanumeric> }   |                  |                           |
| <b>Code example</b>      | <pre>\$.ajax({   type : "GET",   url : "/v2/cleanup?cmd=getDuplicates",   headers : {authToken : "gfUH43trfdkjg34"},   dataType : "json",   success : function(data) {     console.log(data);   },   error : function(data) {     console.log(data);   } });</pre> |                  |                           |
| <b>Notes</b>             | <p>Data returned contains all values which are assigned multiple times. The values may be assigned to actual contacts but also to failed imports. The values retrieved can be passed to "Get Conflicted Contacts".</p>   |                  |                           |

Table 92 Find basicinfo duplicates

### 2.5.3.2.6 Get Conflicted Contacts

|                          |  |                  |                           |
|--------------------------|--|------------------|---------------------------|
| <b>Title</b>             | Return contacts having the same basicinfo value assigned.  |                  |                           |
| <b>URL</b>               | /v2/cleanup?cmd=getConflicts&value=:value  |                  |                           |
| <b>Header attributes</b> | <b>Attribute</b>   | <b>Required?</b> | <b>Example</b>            |
|                          | authToken  | Yes              | authToken=gfUH43trfdkjg34 |
| <b>Method</b>            | GET  |                  |                           |
| <b>URL parameters</b>    | <b>Parameter</b>   | <b>Required?</b> | <b>Example</b>            |
|                          | value : <alphanumeric>   | yes              | &value=+12025552846       |
| <b>Data</b>              | none   |                  |                           |
| <b>Success response</b>  | Code: 200 OK   |                  |                           |
|                          | <pre>{   "data" : [&lt;object&gt;] }</pre>   |                  |                           |
| <b>Error response</b>    | Code: 401 UNAUTHORIZED   |                  |                           |
|                          | Code: 403 FORBIDDEN  |                  |                           |
|                          | <pre>{"code" : &lt;integer&gt;, "error" : &lt;integer&gt;, "devmsg" : &lt;alphanumeric&gt;}</pre>  |                  |                           |
| <b>Code example</b>      | <pre>\$.ajax({   type : "GET",   url : "/v2/cleanup?cmd=getConflicts&amp;value=12025552846",   headers : {authToken : "gfUH43trfdkjg34"},   dataType : "json",   success : function(data) {     console.log(data);   },   error : function(data) {     console.log(data);   } });</pre>                        |                  |                           |
| <b>Notes</b>             | <p>Data returned is an array of contact objects using <i>projection=base</i> (as described in "Read a Person <b>Contact</b>", "Read an Organization Contact" resp.)</p> <p>The user is supposed to merge the contact data manually. Then the client should pass the result to "Merge Contact <b>Data</b>".</p> |                  |                           |

Table 93 Find conflicted contacts



### 2.5.3.2.7 Merge Contact Data

|                          |  |                  |                           |
|--------------------------|--|------------------|---------------------------|
| <b>Title</b>             | Merge contact data from different contacts into one contact.   |                  |                           |
| <b>URL</b>               | /v2/contacts?cmd=merge   |                  |                           |
| <b>Header attributes</b> | <b>Attribute</b>   | <b>Required?</b> | <b>Example</b>            |
|                          | authToken  | Yes              | authToken=gfUH43trfdkjg34 |
| <b>Method</b>            | POST   |                  |                           |
| <b>URL parameters</b>    | none   |                  |                           |
| <b>Data</b>              | <pre>{   "contactIds" : [&lt;integer&gt;],   "importContactIds" : [&lt;integer&gt;],   "contact" : &lt;contact&gt; }</pre>   |                  |                           |
| <b>Success response</b>  | Code: 200 OK   |                  |                           |
|                          | {"code" : 200, "entity" : <contact>, "devmsg" : "success"}   |                  |                           |
| <b>Error response</b>    | Code: 400 BAD REQUEST<br>Code: 401 UNAUTHORIZED<br>Code: 403 FORBIDDEN   |                  |                           |
|                          | {"code" : <integer>, "error" : <integer>, "devmsg" : <alphanumeric>}   |                  |                           |
| <b>Code example</b>      | <pre>\$.ajax({   type : "POST",   url : "/v2/contacts?cmd=merge",   headers : {authToken : "gfUH43trfdkjg34"},   dataType : "json",   contentType : "application/json",   data : JSON.stringify({     "contactIds" : [12],     "importContactIds" : [11,23,32],     "contact" : {       "id" : 52,       "version" : 4,       "firstName" : "Remo",       "basicInfos" : [         { "id" : 46 }, { "id" : "23" }, { "id" : "142" }       ]     }   }) },   success : function(data) {     console.log(data);   },   error : function(data) {     console.log(data);   } });</pre> |                  |                           |
| <b>Notes</b>             | <p>All related entities (deals, interactions, notes, tasks) of the former separated contacts will be attached to the new merged contact.</p> <p>Contacts represented by the <i>contactIds</i> attribute will be deleted, imported contacts (which are non-active contacts) represented by the <i>importContactIds</i> will be deleted as well. Those two attributes are supposed to reflect the contact data which has been merged into the new/updated contact represented by the <i>contact</i> attribute.</p>   |                  |                           |

Table 94 Merge contacts



### 2.5.3.2.8 Share Contact With Group(s)

|                          |   |                  |                           |
|--------------------------|---|------------------|---------------------------|
| <b>Title</b>             | Share contact data with one or multiple groups  |                  |                           |
| <b>URL</b>               | /v2/contacts/:id?cmd=share&groups=:groups   |                  |                           |
| <b>Header attributes</b> | <b>Attribute</b>  | <b>Required?</b> | <b>Example</b>            |
|                          | authToken   | Yes              | authToken=gfUH43trfdkjg34 |
| <b>Method</b>            | POST  |                  |                           |
| <b>URL parameters</b>    | <b>Parameter</b>  | <b>Required?</b> | <b>Example</b>            |
|                          | id : <integer><br>groups : [<integer>]  | yes<br>yes       | /31<br>&groups=12,32      |
| <b>Data</b>              | { } Or null   |                  |                           |
| <b>Success response</b>  | Code: 200 OK  |                  |                           |
|                          | { "code" : 200, "entity" : <contact>, "devmsg" : "success" }  |                  |                           |
| <b>Error response</b>    | Code: 400 BAD REQUEST<br>Code: 401 UNAUTHORIZED<br>Code: 403 FORBIDDEN  |                  |                           |
|                          | { "code" : <integer>, "error" : <integer>, "devmsg" : <alphanumeric> }  |                  |                           |
| <b>Code example</b>      | <pre>\$.ajax({   type : "POST",   url : "/v2/contacts/31?cmd=share&amp;groups=12,32",   headers : {authToken : "gfUH43trfdkjg34"},   dataType : "json",   data : JSON.stringify({}),   success : function(data) {     console.log(data);   },   error : function(data) {     console.log(data);   } });</pre> |                  |                           |
| <b>Notes</b>             | <p>Sharing means that each user – even the sharing user himself – receives a shallow-copy of the shared contact. That's why the <b>returned contact will have a different id</b>.</p> <p>To share with all members of the company they have to be put into a group to share the contact with.</p>             |                  |                           |

Table 95 Share a contact

### 2.5.3.2.9 Assign User Roles

|                          |   |                  |                           |
|--------------------------|---|------------------|---------------------------|
| <b>Title</b>             | Assign roles to a user.   |                  |                           |
| <b>URL</b>               | /v2/admin/users/:id/roles?cmd=:cmd  |                  |                           |
| <b>Header attributes</b> | <b>Attribute</b>  | <b>Required?</b> | <b>Example</b>            |
|                          | authToken   | Yes              | authToken=gfUH43trfdkjg34 |
| <b>Method</b>            | POST  |                  |                           |
| <b>URL parameters</b>    | <b>Parameter</b>  | <b>Required?</b> | <b>Example</b>            |
|                          | id : <integer><br>cmd : <enum(add,remove,set)>  | yes<br>yes       | /31<br>?cmd=set           |
| <b>Data</b>              | [<alphanumeric>]  |                  |                           |
| <b>Success response</b>  | <b>Code: 200 OK</b>   |                  |                           |
|                          | <pre>{   "active" : &lt;boolean&gt;,   "companyId" : &lt;integer&gt;,   "dateCreated" : &lt;integer&gt;,   "email" : &lt;alphanumeric&gt;,   "groups" :     [       {         "id" : &lt;integer&gt;,         "name" : &lt;alphanumeric&gt;       }     ],   "id" : &lt;integer&gt;,   "interactionsCount" : &lt;integer&gt;,   "roles" : [&lt;alphanumeric&gt;] }</pre>                  |                  |                           |
| <b>Error response</b>    | Code: 400 BAD REQUEST<br>Code: 401 UNAUTHORIZED<br>Code: 403 FORBIDDEN  |                  |                           |
|                          | <pre>{"code" : &lt;integer&gt;, "error" : &lt;integer&gt;, "devmsg" : &lt;alphanumeric&gt;}</pre>   |                  |                           |
| <b>Code example</b>      | <pre>\$.ajax({   type : "POST",   url : "/v2/admin/users/31/roles?cmd=set",   headers : {authToken : "gfUH43trfdkjg34"},   dataType : "json",   contentType : "application/json",   data : JSON.stringify([     "interact_admin", "customer_admin", "user"   ]),   success : function(data) {     console.log(data);   },   error : function(data) {     console.log(data);   } });</pre> |                  |                           |
| <b>Notes</b>             | The payload data of the request is an array of role names.  |                  |                           |

Table 96 Assign roles to user



### 2.5.3.2.10 Assign User Groups

|                          |  |                  |                           |
|--------------------------|--|------------------|---------------------------|
| <b>Title</b>             | Assign groups to a user.   |                  |                           |
| <b>URL</b>               | /v2/admin/users/:id/groups?cmd=:cmd  |                  |                           |
| <b>Header attributes</b> | <b>Attribute</b>   | <b>Required?</b> | <b>Example</b>            |
|                          | authToken  | Yes              | authToken=gfUH43trfdkjg34 |
| <b>Method</b>            | POST   |                  |                           |
| <b>URL parameters</b>    | <b>Parameter</b>   | <b>Required?</b> | <b>Example</b>            |
|                          | id : <integer><br>cmd : <enum(add,remove,set)>   | yes<br>yes       | /31<br>?cmd=set           |
| <b>Data</b>              | [<integer>]  |                  |                           |
| <b>Success response</b>  | <b>Code: 200 OK</b>  |                  |                           |
|                          | <pre>{   "active" : &lt;boolean&gt;,   "companyId" : &lt;integer&gt;,   "dateCreated" : &lt;integer&gt;,   "email" : &lt;alphanumeric&gt;,   "groups" :     [       {         "id" : &lt;integer&gt;,         "name" : &lt;alphanumeric&gt;       }     ],   "id" : &lt;integer&gt;,   "interactionsCount" : &lt;integer&gt;,   "roles" : [&lt;alphanumeric&gt;] }</pre> |                  |                           |
| <b>Error response</b>    | Code: 400 BAD REQUEST<br>Code: 401 UNAUTHORIZED<br>Code: 403 FORBIDDEN   |                  |                           |
|                          | <pre>{"code" : &lt;integer&gt;, "error" : &lt;integer&gt;, "devmsg" : &lt;alphanumeric&gt;}</pre>  |                  |                           |
| <b>Code example</b>      | <pre>\$.ajax({   type : "POST",   url : "/v2/admin/users/31/groups?cmd=add",   headers : {authToken : "gfUH43trfdkjg34"},   dataType : "json",   contentType : "application/json",   data : JSON.stringify([     12,453,28,199   ]),   success : function(data) {     console.log(data);   },   error : function(data) {     console.log(data);   } });</pre>            |                  |                           |
| <b>Notes</b>             | The payload data of the request is an array of group ids.  |                  |                           |

Table 97 Assign groups to user



#### 2.5.3.2.11 Reset User Password

|                          |  |
|--------------------------|--|
| <b>Title</b>             | Reset the password of a user.  |
| <b>URL</b>               | /v2/myAccount?cmd=resetPwd   |
| <b>Header Attributes</b> | none   |
| <b>Method</b>            | POST   |
| <b>URL parameters</b>    | none   |
| <b>Data</b>              | <pre>{   "email" : &lt;alphanumeric&gt; }</pre>  |
| <b>Success response</b>  | Code: 200 OK   |
|                          | <pre>{ "code" : 200, "devmsg" : "success" }</pre>  |
| <b>Error response</b>    | Code: 400 BAD REQUEST  |
|                          | <pre>{ "code" : &lt;integer&gt;, "error" : &lt;integer&gt;, "devmsg" : &lt;alphanumeric&gt; }</pre>  |
| <b>Code example</b>      | <pre>\$.ajax({   type : "POST",   url : "/v2/myAccount?cmd=resetPwd",   dataType : "json",   contentType : "application/json",   data : JSON.stringify({     "email" : "test@interact.io"   }),   success : function(data) {     console.log(data);   },   error : function(data) {     console.log(data);   } });</pre> |
| <b>Notes</b>             | none   |

Table 98 Reset the password of a user



### 2.5.3.2.12 Change a User password

|                          |   |                  |                           |
|--------------------------|---|------------------|---------------------------|
| <b>Title</b>             | Change the password of a suser.   |                  |                           |
| <b>URL</b>               | /v2/myAccount?cmd=changePwd   |                  |                           |
| <b>Header attributes</b> | <b>Attribute</b>  | <b>Required?</b> | <b>Example</b>            |
|                          | authToken   | Yes              | authToken=gfUH43trfdkjg34 |
| <b>Method</b>            | POST  |                  |                           |
| <b>URL parameters</b>    | none  |                  |                           |
| <b>Data</b>              | <pre>{   "oldPassword" : &lt;alphanumeric&gt;,   "newPassword" : &lt;alphanumeric&gt; }</pre>   |                  |                           |
| <b>Success response</b>  | Code: 200 OK  |                  |                           |
|                          | {"code" : 200, "devmsg" : "success"}  |                  |                           |
| <b>Error response</b>    | Code: 400 BAD REQUEST   |                  |                           |
|                          | {"code" : <integer>, "error" : <integer>, "devmsg" : <alphanumeric>}  |                  |                           |
| <b>Code example</b>      | <pre>\$.ajax({   type : "POST",   url : "/v2/myAccount?cmd=changePwd",   dataType : "json",   contentType : "application/json",   data : JSON.stringify({     "oldPassword" : "bad",     "newPassword" : "\$aFeP4Ssw0rD!",   }),   success : function(data) {     console.log(data);   },   error : function(data) {     console.log(data);   } });</pre> |                  |                           |
| <b>Notes</b>             | none  |                  |                           |

Table 99 Change the password of a user

## 2.6 Error codes

Besides the http failure code, error results of an API call always return a dedicated 14-digit error code for better error handling. The first quad (4 digits) represents the exception type. The second quad (3 digits) represents the action which caused the exception. The third quad represents the realm in which the action was (or was supposed to be) executed. The forth quad (4 digits) is used for further differentiation required by the Server. The following lists show possible error codes and their according meaning:

| Error Code (Exception) |     |     |      | Description   |
|------------------------|-----|-----|------|---|
| 9000                   | xxx | xxx | xxxx | General failure   |
| 9001                   | xxx | xxx | xxxx | Internal Server failure   |
| 9002                   | xxx | xxx | xxxx | External failure or Java core failure   |
| 9100                   | xxx | xxx | xxxx | Indicates a requested entity was not found                                      |
| 9101                   | xxx | xxx | xxxx | Indicates a requested address was not found                                     |
| 9102                   | xxx | xxx | xxxx | Indicates a requested basicinfo was not found                                   |
| 9103                   | xxx | xxx | xxxx | Indicates a requested company was not found                                     |
| 9104                   | xxx | xxx | xxxx | Indicates a requested contact was not found                                     |
| 9105                   | xxx | xxx | xxxx | Indicates a requested organization contact was not found                        |
| 9106                   | xxx | xxx | xxxx | Indicates a requested person contact was not found                              |
| 9107                   | xxx | xxx | xxxx | Indicates a requested deal was not found  |
| 9108                   | xxx | xxx | xxxx | Indicates a requested device was not found                                      |
| 9109                   | xxx | xxx | xxxx | Indicates a requested group was not found                                       |
| 9110                   | xxx | xxx | xxxx | Indicates a requested interaction was not found                                 |
| 9111                   | xxx | xxx | xxxx | Indicates a requested note was not found  |
| 9112                   | xxx | xxx | xxxx | Indicates a requested social profile or instant messenger profile was not found |
| 9113                   | xxx | xxx | xxxx | Indicates a requested role was not found  |
| 9114                   | xxx | xxx | xxxx | Indicates a requested tag was not found   |
| 9115                   | xxx | xxx | xxxx | Indicates a requested task was not found  |
| 9116                   | xxx | xxx | xxxx | Indicates a requested tasklist was not found                                    |
| 9117                   | xxx | xxx | xxxx | Indicates a requested user was not found  |
| 9118                   | xxx | xxx | xxxx | Indicates a requested basicinfo variation was not found                         |
| 9119                   | xxx | xxx | xxxx | Indicates a requested contact picture was not found                             |
| 9200                   | xxx | xxx | xxxx | Data validation failure   |
| 9201                   | xxx | xxx | xxxx | Indicates invalid request data  |
| 9202                   | xxx | xxx | xxxx | Indicates missing mandatory request data  |
| 9300                   | xxx | xxx | xxxx | Bad request data  |
| 9301                   | xxx | xxx | xxxx | Indicates an attempt to assign one basicinfo to multiple contacts               |

|      |     |     |      |   |
|------|-----|-----|------|---|
| 9302 | xxx | xxx | xxxx | Indicates an attempt to register a device which is already registered   |
| 9303 | xxx | xxx | xxxx | Indicates an attempt to assign an email address to multiple users       |
| 9304 | xxx | xxx | xxxx | Indicates an attempt to update outdated data                            |
| 9305 | xxx | xxx | xxxx | Indicates an attempt to touch a contact picture from an external system |
| 9306 | xxx | xxx | xxxx | Indicates a requested report does not exist                             |
| 9401 | xxx | xxx | xxxx | Authentication failure  |
| 9402 | xxx | xxx | xxxx | Indicates requesting user has no permission to execute request          |
| 9999 | xxx | xxx | xxxx | Unhandled external failure or Java core failure                         |

Table 100 Error codes (first quad)

| Error Code (Action) |     |     |      | Description                    |
|---------------------|-----|-----|------|--------------------------------|
| xxxx                | 010 | xxx | xxxx | View                           |
| xxxx                | 011 | xxx | xxxx | Edit, Update                   |
| xxxx                | 012 | xxx | xxxx | Create                         |
| xxxx                | 013 | xxx | xxxx | Merge                          |
| xxxx                | 014 | xxx | xxxx | Delete, Remove                 |
| xxxx                | 015 | xxx | xxxx | Import                         |
| xxxx                | 016 | xxx | xxxx | Share                          |
| xxxx                | 017 | xxx | xxxx | Pull Synchronization Data      |
| xxxx                | 018 | xxx | xxxx | Bulk Push Synchronization Data |
| xxxx                | 019 | xxx | xxxx | Open Websocket                 |
| xxxx                | 020 | xxx | xxxx | Login                          |
| xxxx                | 021 | xxx | xxxx | Logout                         |
| xxxx                | 022 | xxx | xxxx | Erase, Reset, Wipe-Out, Zero   |

Table 101 Error codes (second quad)

| Error Code (Realm) |     |     |      | Description          |
|--------------------|-----|-----|------|----------------------|
| xxxx               | xxx | 000 | xxxx | Activities           |
| xxxx               | xxx | 040 | xxxx | Authentication       |
| xxxx               | xxx | 050 | xxxx | Data Synchronization |
| xxxx               | xxx | 060 | xxxx | Websocket            |
| xxxx               | xxx | 090 | xxxx | Data Cleanup         |
| xxxx               | xxx | 100 | xxxx | Contacts             |
| xxxx               | xxx | 103 | xxxx | Contact Relations    |
| xxxx               | xxx | 104 | xxxx | Contact Deals        |
| xxxx               | xxx | 105 | xxxx | Contact Interactions |
| xxxx               | xxx | 106 | xxxx | Contact Notes        |

|      |     |     |      |                             |
|------|-----|-----|------|-----------------------------|
| xxxx | xxx | 107 | xxxx | Contact Profiles            |
| xxxx | xxx | 108 | xxxx | Contact Searchterms         |
| xxxx | xxx | 109 | xxxx | Contact Tags                |
| xxxx | xxx | 110 | xxxx | Contact Tasks               |
| xxxx | xxx | 111 | xxxx | Contact Import              |
| xxxx | xxx | 200 | xxxx | Deals                       |
| xxxx | xxx | 201 | xxxx | Deal Notes                  |
| xxxx | xxx | 202 | xxxx | Deal Tasks                  |
| xxxx | xxx | 300 | xxxx | Tasks                       |
| xxxx | xxx | 301 | xxxx | Task Notes                  |
| xxxx | xxx | 302 | xxxx | Tasklists                   |
| xxxx | xxx | 400 | xxxx | Notes                       |
| xxxx | xxx | 500 | xxxx | Tags                        |
| xxxx | xxx | 600 | xxxx | Devices                     |
| xxxx | xxx | 601 | xxxx | Trigger Devices             |
| xxxx | xxx | 700 | xxxx | Administration              |
| xxxx | xxx | 701 | xxxx | Company Administration      |
| xxxx | xxx | 702 | xxxx | Role Administration         |
| xxxx | xxx | 703 | xxxx | User Administration         |
| xxxx | xxx | 704 | xxxx | Group Administration        |
| xxxx | xxx | 705 | xxxx | Custom field administration |
| xxxx | xxx | 750 | xxxx | My Account                  |
| xxxx | xxx | 800 | xxxx | Basicinfos                  |
| xxxx | xxx | 900 | xxxx | Interactions                |

Table 102 Error codes (third quad)

For your information here is the complete list of possible values for the forth quad:

|                          |
|--------------------------|
| 1001                     |
| 2001 2002 2003 2004 2005 |
| 3003                     |
| 4003 4004                |
| 5001 5002 5003           |
| 6001 6002                |
| 7001 7002                |

Table 103 Error codes (forth quad)

## 3 Index of tables

|   |    |
|---|----|
| Table 1 API call documentation template.....                          | 6  |
| Table 2 General API pattern.....                                      | 7  |
| Table 3 API call overview .....                                       | 9  |
| Table 4 Push interaction notification .....                           | 10 |
| Table 5 Push interaction notification (via APN) .....                 | 11 |
| Table 6 Push synchronization hint.....                                | 12 |
| Table 7 Login .....   | 14 |
| Table 8 Logout .....  | 15 |
| Table 9 Trigger event.....  | 17 |
| Table 10 Register a trigger device .....                              | 18 |
| Table 11 Read the Trigger Token of a Trigger Device .....             | 19 |
| Table 12 Activities list request .....                                | 21 |
| Table 13 Person creation .....  | 24 |
| Table 14 Organization creation.....                                   | 26 |
| Table 15 Contact list request.....                                    | 28 |
| Table 16 Contacts list request - associated with another contact..... | 30 |
| Table 17 Person contact request .....                                 | 33 |
| Table 18 Organization request .....                                   | 36 |
| Table 19 Person update .....  | 39 |
| Table 20 Organization update .....                                    | 42 |
| Table 21 Contact(s) deletion.....                                     | 43 |
| Table 22 Contact deletion.....  | 44 |
| Table 23 Picture upload .....   | 45 |
| Table 24 Picture request.....   | 46 |
| Table 25 Picture list request – associated with a contact .....       | 47 |
| Table 26 Picture update .....   | 48 |
| Table 27 Pictures deletion.....                                       | 49 |

|   |    |
|---|----|
| Table 28 Picture deletion .....                                     | 50 |
| Table 29 Notes creation .....                                       | 51 |
| Table 30 Note list request .....                                    | 52 |
| Table 31 Note list request – associated with a contact.....         | 53 |
| Table 32 Note update .....  | 54 |
| Table 33 Notes deletion .....                                       | 55 |
| Table 34 Note deletion.....   | 56 |
| Table 35 Profiles list request – associated with a contact .....    | 58 |
| Table 36 Search term list request – associated with a contact ..... | 59 |
| Table 37 Tag list request .....                                     | 60 |
| Table 38 Tag list request – associated with a contact .....         | 61 |
| Table 39 Interaction list request .....                             | 63 |
| Table 40 Interaction list request - associated with a contact ..... | 65 |
| Table 41 Interaction request.....                                   | 67 |
| Table 42 Interaction update.....                                    | 69 |
| Table 43 Basicinfos creation .....                                  | 70 |
| Table 44 Basicinfo update .....                                     | 71 |
| Table 45 Tasks creation .....                                       | 73 |
| Table 46 Task list request .....                                    | 75 |
| Table 47 Tasks list request - associated with a contact .....       | 77 |
| Table 48 Task request .....   | 79 |
| Table 49 Task update .....  | 81 |
| Table 50 Tasks deletion.....  | 82 |
| Table 51 Task deletion .....  | 83 |
| Table 52 Tasklist creation .....                                    | 84 |
| Table 53 Tasklist list request .....                                | 86 |
| Table 54 Tasklist request .....                                     | 88 |
| Table 55 Tasklist update .....                                      | 89 |
| Table 56 Tasklist deletion.....                                     | 90 |

|   |     |
|---|-----|
| Table 57 Deals creation .....                                 | 92  |
| Table 58 Deal list request .....                              | 94  |
| Table 59 Deal list request - associated with a contact.....   | 95  |
| Table 60 Deal request .....                                   | 96  |
| Table 61 Deal update .....                                    | 98  |
| Table 62 Deals deletion.....                                  | 99  |
| Table 63 Deal deletion .....                                  | 100 |
| Table 64 User creation.....                                   | 101 |
| Table 65 User list request .....                              | 103 |
| Table 66 Single user request .....                            | 104 |
| Table 67 User deletion .....                                  | 104 |
| Table 68 User deletion .....                                  | 105 |
| Table 69 Company creation .....                               | 106 |
| Table 70 Company list request .....                           | 108 |
| Table 71 Single company request.....                          | 110 |
| Table 72 Companies deletion .....                             | 111 |
| Table 73 Group creation.....                                  | 112 |
| Table 74 Group list request - associated with a company ..... | 114 |
| Table 75 Single group request.....                            | 116 |
| Table 76 Group update .....                                   | 117 |
| Table 77 Groups deletion.....                                 | 118 |
| Table 78 Group deletion .....                                 | 119 |
| Table 79 Register a device .....                              | 120 |
| Table 80 Read a list of Devices .....                         | 121 |
| Table 81 Update a device .....                                | 122 |
| Table 82 Delete a device .....                                | 123 |
| Table 83 Synchronize offline data .....                       | 130 |
| Table 84 User account wipe-out .....                          | 131 |
| Table 85 External contact groups request .....                | 132 |

---

|  |     |
|--|-----|
| Table 86 Person contacts import.....         | 134 |
| Table 87 Find basicinfo duplicates .....     | 135 |
| Table 88 Find conflicted contacts .....      | 136 |
| Table 89 Merge contacts.....                 | 137 |
| Table 90 Share a contact .....               | 139 |
| Table 91 Assign roles to user .....          | 140 |
| Table 92 Assign groups to user .....         | 142 |
| Table 93 Reset the password of a user .....  | 144 |
| Table 94 Change the password of a user ..... | 145 |
| Table 95 Error codes (first quad) .....      | 147 |
| Table 96 Error codes (second quad) .....     | 147 |
| Table 97 Error codes (third quad) .....      | 148 |
| Table 98 Error codes (forth quad) .....      | 148 |



## 4 Attachments

- Javadoc