

## Functional and logic programming

- written exam -

### Important:

1. Subjects are graded as follows: of - 1p; A – 1.5p; B - 2.5p; C - 2.5p; D - 2.5p.
2. Prolog problems will be resolved using SWI Prolog. The following are required: (1) explanation of the code and of the reasoning behind it; (2) recursive model that solves the problem, for all the predicates used; (3) specification of every predicate (parameters and their meaning, flow model, type of the predicate - deterministic/non-deterministic).
3. Lisp problems will be resolved using Common Lisp. The following are required: (1) explanation of the code and of the reasoning behind it; (2) recursive model that solves the problem, for each function used; (3) specification of every function (parameters and their meaning).

**A.** Given the following PROLOG predicate definition **f(integer, integer)**, with the flow model (i, o):

f(0, 0):-!.  
f(I,Y):-J is I-1, **f(J,V)**, V>1, !, K is I-2, Y is K.

f(I,Y):-J is I-1, **f(J,V)**, Y is V+1.

Rewrite the definition in order to avoid the recursive call **f(J,V)** in both clauses. Do NOT redefine the predicate. Justify your answer.

**B.** Given a nonlinear list that contains numerical and non-numerical atoms, write a LISP program that replaces each even numerical atom on odd levels with the sum of its digits. The superficial level is odd. For example, for the list (A 2 (B 31 F (D 102 5 T (66) E) (D 10 (E R 51)) 99)) the result will be (A 2 (B 31 F (D 3 5 T (66) E) (D 1 (E R 51)) 99)).

**C.** Given a list made of integer numbers, generate using PROLOG the list of arrangements with even number of elements, having the sum an odd number. Write mathematical models and flow models for the predicates used. For example, for the list  $L=[2,3,4] \Rightarrow [[2,3],[3,2],[3,4],[4,3]]$  (not necessarily in this order).

**D.** An n-ary tree is represented in Lisp as ( node subtree1 subtree2 ...). Write a Lisp function to return the list of nodes on the given level **k**. The root level is assumed zero. **A MAP function shall be used.** ***Example*** for the tree (a (b (g)) (c (d (e)) (f)))

**a)** k=2 => (g d)      **b)** k=5 => ()