

## Functional and logic programming

- written exam -

### **Important:**

1. Subjects are graded as follows: of - 1p; A – 1.5p; B - 2.5p; C - 2.5p; D - 2.5p.
2. Prolog problems will be resolved using SWI Prolog. The following are required: (1) explanation of the code and of the reasoning behind it; (2) recursive model that solves the problem, for all the predicates used; (3) specification of every predicate (parameters and their meaning, flow model, type of the predicate - deterministic/non-deterministic).
3. Lisp problems will be resolved using Common Lisp. The following are required: (1) explanation of the code and of the reasoning behind it; (2) recursive model that solves the problem, for each function used; (3) specification of every function (parameters and their meaning).

**A.** The following function definition in LISP is given

```
(DEFUN F(L)
  (COND
    ((NULL L) 0)
    (> (F (CDR L)) 2) (+ (F (CDR L)) (CAR L)))
    (T (+ (F (CDR L)) 1))
  )
)
```

Rewrite the definition in order to avoid the repeated recursive call **(F (CDR L))**. Do NOT redefine the function. Do NOT use SET, SETQ, SETF. Justify your answer.

**B.** Given a heterogeneous list made of numbers and nonempty numeric lists, write a SWI-PROLOG program that verifies if all numbers (including those in sublists) form an increasing sequence of numbers. For example, for the list [2,4,6, [10, 12, 19], 30, 201, [1000, 1003, 1006, 2003], 2020] the result will be true, but for the list [2,4,6, [10, 12, 11], 30, 201, [1000, 1003, 1006, 2003], 2020] the result will be false.

**C.** Write a PROLOG program that generates the list of all subsets of  $k$  elements (all elements being odd numbers) in arithmetic progression. Write the mathematical models and flow models for the predicates used. For example, for  $L=[1,5,2,9,3]$  and  $k=3 \Rightarrow [[1,5,9],[1,3,5]]$  (not necessarily in this order).

**D.** Given a nonlinear list, write a Lisp function to return the list with all atoms on level **k** replaced by **0**. The superficial level is assumed 1. **A MAP function shall be used.**

**Example** for the list (a (1 (2 b)) (c (d)))

**(a)** k=2 => (a (0 (2 b)) (0 (d)))

**(b)** k=1 => (0 (1 (2 b)) (c (d)))

**(c)** k=4 => the list does not change