

S1



CLI

IOS Command Line Interface

```
Switch>en
Switch#show running-config
Building configuration...

Current configuration : 1080 bytes
!
version 12.2
no service timestamps log datetime msec
no service timestamps debug datetime msec
no service password-encryption
!
hostname Switch
!
!
!
!
!
spanning-tree mode pvst
spanning-tree extend system-id
!
interface FastEthernet0/1
!
interface FastEthernet0/2
!
interface FastEthernet0/3
!
interface FastEthernet0/4
!
interface FastEthernet0/5
!
interface FastEthernet0/6
!
interface FastEthernet0/7
!
```


Ctrl+F6 to exit CLI focus


Copy


Paste

☐ Top









IOS Command Line Interface

```
User Access Verification

Password:

S1>enable
Password:
S1#show running-config
Building configuration...

Current configuration : 1125 bytes
!
version 12.2
no service timestamps log datetime msec
no service timestamps debug datetime msec
no service password-encryption
!
hostname S1
!
enable password c1$c0
!
!
!
!
!
!
spanning-tree mode pvst
spanning-tree extend system-id
!
interface FastEthernet0/1
!

S1#config t
Enter configuration commands, one per line. End with CNTL/Z.
S1(config)#service password-encryption
S1(config)#exit
```

Ctrl+F6 to exit CLI focus

Copy

Paste



IOS Command Line Interface

```
!  
!  
!  
spanning-tree mode pvst  
spanning-tree extend system-id  
!  
interface FastEthernet0/1  
!  
  
S1#config t  
Enter configuration commands, one per line. End with CNTL/Z.  
S1(config)#service password-encryption  
S1(config)#exit  
S1#  
%SYS-5-CONFIG_I: Configured from console by console  
  
S1#config t  
Enter configuration commands, one per line. End with CNTL/Z.  
S1(config)#banner motd "Somente pessoal autorizado"  
S1(config)#exit  
S1#  
%SYS-5-CONFIG_I: Configured from console by console  
  
S1#copy running-config startup-config  
Destination filename [startup-config]?  
Building configuration...  
[OK]  
S1#config t  
Enter configuration commands, one per line. End with CNTL/Z.  
S1(config)#enable secret itsasecret  
S1(config)#exit  
S1#  
%SYS-5-CONFIG_I: Configured from console by console
```

Ctrl+F6 to exit CLI focus

Copy

Paste



Cisco Packet Tracer - C:\Users\Adairton\Downloads\2.5.5 Packet Tracer - Configure Initial Switch Settings (1).pka

File Edit Options View Tools Extensions Window Help

Activity Results

Time Elapsed: 01:58:08

Congratulations Guest! You completed the activity.

Overall Feedback Assessment Items Connectivity Tests

Expand/Collapse All Show Incorrect Items

Assessment Items	Status	Points	Component(s)	Feedback
Network				
S1				
Banner MOTD	Correct	6	Basic Security ...	
Console Line				
Login	Correct	4	Basic Security ...	
Password	Correct	4	Basic Security ...	
Enable Password	Correct	4	Basic Security ...	
Enable Secret	Correct	4	Basic Security ...	
Host Name	Correct	5	Hostname Conf...	
Service Password Encryption	Correct	4	Basic Security ...	
Startup Config	Correct	5	Configuration M...	
S2				
Banner MOTD	Correct	6	Basic Security ...	
Console Line				
Login	Correct	4	Basic Security ...	
Password	Correct	4	Basic Security ...	
Enable Password	Correct	4	Basic Security ...	
Enable Secret	Correct	4	Basic Security ...	
Host Name	Correct	5	Hostname Conf...	
Service Password Encryption	Correct	4	Basic Security ...	
Startup Config	Correct	5	Configuration M...	

Score: 72/72

Item Count: 16/16

Component	Items/Total	Score
Basic Security Configuration	12/12	52/52
Configuration Management	2/2	10/10
Hostname Configuration	2/2	10/10

Close

Windows Search: Digite aqui para pesquisar

Taskbar icons: File Explorer, Edge, Word, Excel, PowerPoint, Teams, Chrome, etc.

System tray: 27°C, 18:06, 12/10/2021