Modelo físico PostgreSQL instalado

Base red_house, esquema red_house. Metadatos exportados de la instancia Docker aislada. No contiene filas de negocio ni credenciales.

71 tablas físicas y 145 índices. Las vistas access_* adaptan los contratos sin duplicar estas tablas. Algunas tablas conservadas de main no son escritas por los servicios actuales; consultar la correspondencia en Esquema_compartido.md.

Metadatos verificables · SQL de instalación · Diagrama físico completo, ampliable

account_role

Columna	Tipo físico	NULL	Predeterminado
account_id	uuid	NO	—
role_code	character varying(30)	NO	—
institution_id	uuid	YES	—
region_name	character varying(80)	YES	—

Restricciones:

- account_role_check: CHECK (((institution_id IS NOT NULL) <> (region_name IS NOT NULL))).
- account_role_check1: CHECK ((((role_code)::text <> 'OPERATOR'::text) OR (institution_id IS NOT NULL))).
- account_role_check2: CHECK ((((role_code)::text <> ALL (ARRAY[('MEDICAL'::character varying)::text, ('TRANSPORT'::character varying)::text])) OR (institution_id IS NOT NULL))).
- account_role_pkey: PRIMARY KEY (account_id).
- account_role_account_id_fkey: FOREIGN KEY (account_id) REFERENCES red_house.user_account(account_id) DEFERRABLE.
- account_role_institution_id_fkey: FOREIGN KEY (institution_id) REFERENCES red_house.institution(institution_id) DEFERRABLE.
- account_role_role_code_fkey: FOREIGN KEY (role_code) REFERENCES red_house.role(role_code) DEFERRABLE.

Índices:

- account_role_pkey: CREATE UNIQUE INDEX account_role_pkey ON red_house.account_role USING btree (account_id).
- account_role_scope_idx: CREATE INDEX account_role_scope_idx ON red_house.account_role USING btree (institution_id).

algorithm_run

Columna	Tipo físico	NULL	Predeterminado
run_id	uuid	NO	gen_random_uuid()
institution_id	uuid	NO	—
actor_id	uuid	YES	—
operation	text	NO	—
algorithm_version	text	NO	—
blood_evaluation_id	uuid	YES	—
organ_evaluation_id	uuid	YES	—
inputs	jsonb	NO	—
factors	jsonb	NO	—
result	jsonb	NO	—
elapsed_ms	double precision	NO	—

Columna	Tipo físico	NULL	Predeterminado
created_at	timestamp with time zone	NO	now()

Restricciones:

- algorithm_run_check: CHECK ((num_nonnulls(blood_evaluation_id, organ_evaluation_id) <= 1)).
- algorithm_run_elapsed_ms_check: CHECK ((elapsed_ms >= (0)::double precision)).
- algorithm_run_operation_check: CHECK ((operation = ANY (ARRAY['RANKING'::text, 'BALANCING'::text]))).
- algorithm_run_pkey: PRIMARY KEY (run_id).
- algorithm_run_actor_id_fkey: FOREIGN KEY (actor_id) REFERENCES red_house.user_account(account_id) DEFERRABLE.
- algorithm_run_blood_evaluation_id_fkey: FOREIGN KEY (blood_evaluation_id) REFERENCES red_house.candidate_evaluation(evaluation_id) DEFERRABLE.
- algorithm_run_institution_id_fkey: FOREIGN KEY (institution_id) REFERENCES red_house.institution(institution_id) DEFERRABLE.
- algorithm_run_organ_evaluation_id_fkey: FOREIGN KEY (organ_evaluation_id) REFERENCES red_house.organ_evaluation(evaluation_id) DEFERRABLE.

Índices:

- algorithm_run_pkey: CREATE UNIQUE INDEX algorithm_run_pkey ON red_house.algorithm_run USING btree (run_id).

allocation_operation

Columna	Tipo físico	NULL	Predeterminado
id	uuid	NO	—
user_id	uuid	NO	—
tenant_id	uuid	NO	—
key	text	NO	—
fingerprint	text	NO	—
input	jsonb	NO	—
status	text	NO	'PENDING'::text
hold_id	uuid	YES	—
error	text	YES	—
last_recovery_at	timestamp with time zone	YES	—
created_at	timestamp with time zone	NO	now()

Restricciones:

- api_operations_pkey: PRIMARY KEY (id).
- api_operations_user_id_key_key: UNIQUE (user_id, key).
- shared_operations_tenant_id: FOREIGN KEY (tenant_id) REFERENCES red_house.institution(institution_id) DEFERRABLE.
- shared_operations_user_id: FOREIGN KEY (user_id) REFERENCES red_house.user_account(account_id) DEFERRABLE.

Índices:

- api_operations_pkey: CREATE UNIQUE INDEX api_operations_pkey ON red_house.allocation_operation USING btree (id).
- api_operations_user_id_key_key: CREATE UNIQUE INDEX api_operations_user_id_key_key ON red_house.allocation_operation USING btree (user_id, key).

appointment

Columna	Tipo físico	NULL	Predeterminado
appointment_id	uuid	NO	—
donor_id	uuid	NO	—
campaign_id	uuid	NO	—
current_status	text	NO	'BOOKED'::text
created_at	timestamp with time zone	NO	now()
tenant_id	uuid	NO	—

Restricciones:

- appointment_pkey: PRIMARY KEY (appointment_id).
- api_appointments_campaign_id_fkey: FOREIGN KEY (campaign_id) REFERENCES red_house.campaign(campaign_id) DEFERRABLE.
- api_appointments_donor_id_fkey: FOREIGN KEY (donor_id) REFERENCES red_house.donor(donor_id) DEFERRABLE.
- shared_appointments_tenant_id: FOREIGN KEY (tenant_id) REFERENCES red_house.institution(institution_id) DEFERRABLE.

Índices:

- appointment_pkey: CREATE UNIQUE INDEX appointment_pkey ON red_house.appointment USING btree (appointment_id).
- api_active_appointment: CREATE UNIQUE INDEX api_active_appointment ON red_house.appointment USING btree (donor_id, campaign_id) WHERE (current_status = 'BOOKED'::text).
- appointment_active: CREATE UNIQUE INDEX appointment_active ON red_house.appointment USING btree (donor_id, campaign_id) WHERE (current_status = 'BOOKED'::text).

audit_change

Columna	Tipo físico	NULL	Predeterminado
event_id	uuid	NO	—
field_name	character varying(60)	NO	—
previous_value	character varying(240)	YES	—
new_value	character varying(240)	YES	—

Restricciones:

- audit_change_pkey: PRIMARY KEY (event_id, field_name).
- audit_change_event_id_fkey: FOREIGN KEY (event_id) REFERENCES red_house.audit_event(event_id) DEFERRABLE.

Índices:

- audit_change_pkey: CREATE UNIQUE INDEX audit_change_pkey ON red_house.audit_change USING btree (event_id, field_name).

audit_event

Columna	Tipo físico	NULL	Predeterminado
event_id	uuid	NO	—
actor_id	uuid	YES	—
institution_id	uuid	NO	—

Columna	Tipo físico	NULL	Predeterminado
region_name	character varying(80)	YES	—
occurred_at	timestamp with time zone	NO	now()
action	text	NO	—
entity_type	character varying(40)	YES	—
entity_reference	character varying(80)	YES	—
outcome	character varying(12)	YES	—
correlation_id	uuid	YES	—
reason	character varying(240)	YES	—
source_service	text	NO	—
metadata	jsonb	YES	'{}'::jsonb
region_id	uuid	NO	—
event	jsonb	NO	—

Restricciones:

- audit_event_outcome_check: CHECK (((outcome)::text = ANY (ARRAY[('SUCCESS'::character varying)::text, ('DENIED'::character varying)::text, ('FAILED'::character varying)::text]))).
- audit_event_pkey: PRIMARY KEY (event_id).
- shared_audit_events_actor_id: FOREIGN KEY (actor_id) REFERENCES red_house.user_account(account_id) DEFERRABLE.
- shared_audit_events_tenant_id: FOREIGN KEY (institution_id) REFERENCES red_house.institution(institution_id) DEFERRABLE.

Índices:

- audit_event_pkey: CREATE UNIQUE INDEX audit_event_pkey ON red_house.audit_event USING btree (event_id).
- api_audit_search: CREATE INDEX api_audit_search ON red_house.audit_event USING btree (region_id, institution_id, occurred_at).
- audit_region_time_idx: CREATE INDEX audit_region_time_idx ON red_house.audit_event USING btree (region_name, occurred_at DESC).
- audit_scope_time_idx: CREATE INDEX audit_scope_time_idx ON red_house.audit_event USING btree (institution_id, occurred_at DESC).

balance_proposal

Columna	Tipo físico	NULL	Predeterminado
id	uuid	NO	—
tenant_id	uuid	NO	—
algorithm_version	text	NO	—
snapshots	jsonb	NO	—
result	jsonb	NO	—
elapsed_ms	double precision	NO	—
slot_count	integer	NO	—
matched_count	integer	NO	—
created_at	timestamp with time zone	NO	now()

Restricciones:

- api_proposals_pkey: PRIMARY KEY (id).
- shared_proposals_tenant_id: FOREIGN KEY (tenant_id) REFERENCES red_house.institution(institution_id) DEFERRABLE.

Índices:

- api_proposals_pkey: CREATE UNIQUE INDEX api_proposals_pkey ON red_house.balance_proposal USING btree (id).

blood_allocation

Columna	Tipo físico	NULL	Predeterminado
allocation_id	uuid	NO	—
request_id	uuid	NO	—
candidate_id	uuid	YES	—
resource_id	uuid	NO	—
origin_id	uuid	NO	—
destination_id	uuid	NO	—
authorized_by	uuid	YES	—
authorization_reason	character varying(240)	YES	—
current_status	text	NO	'PENDING'::text
reserved_at	timestamp with time zone	NO	now()
received_at	timestamp with time zone	YES	—
version_no	integer	YES	1
review_id	uuid	YES	—
operation_id	uuid	NO	—
recipient_id	uuid	NO	—
region_id	uuid	NO	—
hold_id	uuid	NO	—
evaluation_id	uuid	NO	—
route_id	uuid	NO	—
route_version	integer	NO	—
shipment_id	uuid	YES	—
shipment_sequence	integer	NO	0

Restricciones:

- api_reservations_hold_id_key: UNIQUE (hold_id).
- api_reservations_operation_id_key: UNIQUE (operation_id).
- blood_allocation_candidate_id_key: UNIQUE (candidate_id).
- blood_allocation_pkey: PRIMARY KEY (allocation_id).
- api_reservations_operation_id_fkey: FOREIGN KEY (operation_id) REFERENCES red_house.allocation_operation(id) DEFERRABLE.
- api_reservations_resource_id_fkey: FOREIGN KEY (resource_id) REFERENCES red_house.resource(resource_id) DEFERRABLE.
- blood_allocation_authorized_by_fkey: FOREIGN KEY (authorized_by) REFERENCES red_house.user_account(account_id) DEFERRABLE.

- blood_allocation_candidate_id_fkey: FOREIGN KEY (candidate_id) REFERENCES red_house.blood_candidate(candidate_id) DEFERRABLE.
- blood_allocation_review_id_fkey: FOREIGN KEY (review_id) REFERENCES red_house.blood_review(review_id) DEFERRABLE.
- shared_reservations_destination_id: FOREIGN KEY (destination_id) REFERENCES red_house.institution(institution_id) DEFERRABLE.
- shared_reservations_evaluation_id: FOREIGN KEY (evaluation_id) REFERENCES red_house.candidate_evaluation(evaluation_id) DEFERRABLE.
- shared_reservations_hold_id: FOREIGN KEY (hold_id) REFERENCES red_house.request_hold(id) DEFERRABLE.
- shared_reservations_origin_id: FOREIGN KEY (origin_id) REFERENCES red_house.institution(institution_id) DEFERRABLE.
- shared_reservations_recipient_id: FOREIGN KEY (recipient_id) REFERENCES red_house.recipient(recipient_id) DEFERRABLE.
- shared_reservations_request_id: FOREIGN KEY (request_id) REFERENCES red_house.blood_request(request_id) DEFERRABLE.
- shared_reservations_route_id: FOREIGN KEY (route_id) REFERENCES red_house.regional_route(route_id) DEFERRABLE.

Índices:

- api_reservations_hold_id_key: CREATE UNIQUE INDEX api_reservations_hold_id_key ON red_house.blood_allocation USING btree (hold_id).
- api_reservations_operation_id_key: CREATE UNIQUE INDEX api_reservations_operation_id_key ON red_house.blood_allocation USING btree (operation_id).
- blood_allocation_candidate_id_key: CREATE UNIQUE INDEX blood_allocation_candidate_id_key ON red_house.blood_allocation USING btree (candidate_id).
- blood_allocation_pkey: CREATE UNIQUE INDEX blood_allocation_pkey ON red_house.blood_allocation USING btree (allocation_id).
- allocation_request_idx: CREATE INDEX allocation_request_idx ON red_house.blood_allocation USING btree (request_id).
- allocation_resource_exclusive: CREATE UNIQUE INDEX allocation_resource_exclusive ON red_house.blood_allocation USING btree (resource_id) WHERE (current_status <> 'CANCELLED'::text).
- api_resource_reserved: CREATE UNIQUE INDEX api_resource_reserved ON red_house.blood_allocation USING btree (resource_id) WHERE (current_status <> 'CANCELLED'::text).

blood_candidate

Columna	Tipo físico	NULL	Predeterminado
candidate_id	uuid	NO	gen_random_uuid()
evaluation_id	uuid	NO	—
resource_id	uuid	NO	—
rank_no	integer	NO	—
unit_version	integer	NO	—
donor_group	character varying(3)	NO	—
recipient_group	character varying(3)	NO	—
urgency	character varying(20)	NO	—
wait_minutes	integer	NO	—
distance_km	integer	NO	—
travel_minutes	integer	NO	—
route_version	integer	NO	—
expires_at	timestamp with time zone	NO	—

Columna	Tipo físico	NULL	Predeterminado
explanation	character varying(1000)	NO	—

Restricciones:

- blood_candidate_rank_no_check: CHECK ((rank_no > 0)).
- blood_candidate_wait_minutes_check: CHECK ((wait_minutes >= 0)).
- blood_candidate_evaluation_id_rank_no_key: UNIQUE (evaluation_id, rank_no).
- blood_candidate_evaluation_id_resource_id_key: UNIQUE (evaluation_id, resource_id).
- blood_candidate_pkey: PRIMARY KEY (candidate_id).
- blood_candidate_evaluation_id_fkey: FOREIGN KEY (evaluation_id) REFERENCES red_house.candidate_evaluation(evaluation_id) DEFERRABLE.
- blood_candidate_resource_id_fkey: FOREIGN KEY (resource_id) REFERENCES red_house.blood_unit(resource_id) DEFERRABLE.

Índices:

- blood_candidate_evaluation_id_rank_no_key: CREATE UNIQUE INDEX blood_candidate_evaluation_id_rank_no_key ON red_house.blood_candidate USING btree (evaluation_id, rank_no).
- blood_candidate_evaluation_id_resource_id_key: CREATE UNIQUE INDEX blood_candidate_evaluation_id_resource_id_key ON red_house.blood_candidate USING btree (evaluation_id, resource_id).
- blood_candidate_pkey: CREATE UNIQUE INDEX blood_candidate_pkey ON red_house.blood_candidate USING btree (candidate_id).

blood_classification

Columna	Tipo físico	NULL	Predeterminado
resource_id	uuid	NO	—
recorded_group_code	character varying(3)	NO	—
source_reference	character varying(120)	NO	—
recorded_at	timestamp with time zone	NO	now()

Restricciones:

- blood_classification_recorded_group_code_check: CHECK (((recorded_group_code)::text = ANY (ARRAY[('O-'::character varying)::text, ('O+'::character varying)::text, ('A-'::character varying)::text, ('A+'::character varying)::text, ('B-'::character varying)::text, ('B+'::character varying)::text, ('AB-'::character varying)::text, ('AB+'::character varying)::text]))).
- blood_classification_pkey: PRIMARY KEY (resource_id).
- blood_classification_resource_id_fkey: FOREIGN KEY (resource_id) REFERENCES red_house.blood_unit(resource_id) DEFERRABLE.

Índices:

- blood_classification_pkey: CREATE UNIQUE INDEX blood_classification_pkey ON red_house.blood_classification USING btree (resource_id).

blood_component

Columna	Tipo físico	NULL	Predeterminado
component_id	uuid	NO	gen_random_uuid()
component_code	character varying(30)	NO	—

Columna	Tipo físico	NULL	Predeterminado
component_name	character varying(100)	NO	—
region_name	character varying(80)	NO	—
is_active	boolean	NO	true
version_no	integer	NO	1

Restricciones:

- blood_component_component_code_key: UNIQUE (component_code).
- blood_component_pkey: PRIMARY KEY (component_id).

Índices:

- blood_component_component_code_key: CREATE UNIQUE INDEX blood_component_component_code_key ON red_house.blood_component USING btree (component_code).
- blood_component_pkey: CREATE UNIQUE INDEX blood_component_pkey ON red_house.blood_component USING btree (component_id).

blood_movement

Columna	Tipo físico	NULL	Predeterminado
movement_id	uuid	NO	—
resource_id	uuid	NO	—
sequence	integer	YES	—
previous_status	character varying(16)	YES	—
new_status	character varying(16)	YES	—
origin_location_id	uuid	YES	—
destination_location_id	uuid	YES	—
occurred_at	timestamp with time zone	NO	now()
actor_id	uuid	NO	—
reason	character varying(240)	YES	—
action	text	NO	—

Restricciones:

- blood_movement_pkey: PRIMARY KEY (movement_id).
- api_movements_resource_id_fkey: FOREIGN KEY (resource_id) REFERENCES red_house.resource(resource_id) DEFERRABLE.
- blood_movement_destination_location_id_fkey: FOREIGN KEY (destination_location_id) REFERENCES red_house.storage_location(location_id) DEFERRABLE.
- blood_movement_origin_location_id_fkey: FOREIGN KEY (origin_location_id) REFERENCES red_house.storage_location(location_id) DEFERRABLE.
- shared_movements_actor_id: FOREIGN KEY (actor_id) REFERENCES red_house.user_account(account_id) DEFERRABLE.

Índices:

- blood_movement_pkey: CREATE UNIQUE INDEX blood_movement_pkey ON red_house.blood_movement USING btree (movement_id).

blood_request

Columna	Tipo físico	NULL	Predeterminado
request_id	uuid	NO	—
request_code	character varying(30)	YES	—
recipient_id	uuid	NO	—
component_id	uuid	YES	—
quantity	integer	NO	—
urgency	character varying(20)	YES	—
justification	character varying(1000)	YES	—
current_status	text	NO	'OPEN'::text
responsible_id	uuid	YES	—
requested_at	timestamp with time zone	NO	now()
closed_at	timestamp with time zone	YES	—
version_no	integer	NO	1
tenant_id	uuid	NO	—
kind	text	NO	—
component	text	NO	—
priority_level	integer	NO	—

Restricciones:

- api_requests_check: CHECK (((kind <> 'ORGAN'::text) OR (quantity = 1))).
- api_requests_quantity_check: CHECK ((quantity > 0)).
- api_requests_urgency_check: CHECK (((priority_level >= 1) AND (priority_level <= 3))).
- blood_request_urgency_check: CHECK (((urgency)::text = ANY (ARRAY[('URGENT'::character varying)::text, ('PRIORITY'::character varying)::text, ('ROUTINE'::character varying)::text]))).
- blood_request_pkey: PRIMARY KEY (request_id).
- blood_request_request_code_key: UNIQUE (request_code).
- api_requests_recipient_id_fkey: FOREIGN KEY (recipient_id) REFERENCES red_house.recipient(recipient_id) DEFERRABLE.
- blood_request_component_id_fkey: FOREIGN KEY (component_id) REFERENCES red_house.blood_component(component_id) DEFERRABLE.
- blood_request_responsible_id_fkey: FOREIGN KEY (responsible_id) REFERENCES red_house.user_account(account_id) DEFERRABLE.
- shared_requests_tenant_id: FOREIGN KEY (tenant_id) REFERENCES red_house.institution(institution_id) DEFERRABLE.

Índices:

- blood_request_pkey: CREATE UNIQUE INDEX blood_request_pkey ON red_house.blood_request USING btree (request_id).
- blood_request_request_code_key: CREATE UNIQUE INDEX blood_request_request_code_key ON red_house.blood_request USING btree (request_code).
- api_active_organ_request: CREATE UNIQUE INDEX api_active_organ_request ON red_house.blood_request USING btree (recipient_id) WHERE ((kind = 'ORGAN'::text) AND (current_status = ANY (ARRAY['OPEN'::text, 'IN_PROGRESS'::text]))).
- request_queue_idx: CREATE INDEX request_queue_idx ON red_house.blood_request USING btree (current_status, urgency, requested_at).
- request_recipient_idx: CREATE INDEX request_recipient_idx ON red_house.blood_request USING btree (recipient_id).

blood_review

Columna	Tipo físico	NULL	Predeterminado
review_id	uuid	NO	—
candidate_id	uuid	YES	—
actor_id	uuid	NO	—
decision	text	NO	—
reason	text	NO	—
occurred_at	timestamp with time zone	NO	now()
evaluation_id	uuid	NO	—
resource_id	uuid	NO	—
tenant_id	uuid	NO	—

Restricciones:

- api_reviews_evaluation_id_resource_id_key: UNIQUE (evaluation_id, resource_id).
- blood_review_pkey: PRIMARY KEY (review_id).
- api_reviews_evaluation_id_fkey: FOREIGN KEY (evaluation_id) REFERENCES red_house.candidate_evaluation(evaluation_id) DEFERRABLE.
- blood_review_candidate_id_fkey: FOREIGN KEY (candidate_id) REFERENCES red_house.blood_candidate(candidate_id) DEFERRABLE.
- shared_reviews_actor_id: FOREIGN KEY (actor_id) REFERENCES red_house.user_account(account_id) DEFERRABLE.
- shared_reviews_resource_id: FOREIGN KEY (resource_id) REFERENCES red_house.resource(resource_id) DEFERRABLE.
- shared_reviews_tenant_id: FOREIGN KEY (tenant_id) REFERENCES red_house.institution(institution_id) DEFERRABLE.

Índices:

- api_reviews_evaluation_id_resource_id_key: CREATE UNIQUE INDEX api_reviews_evaluation_id_resource_id_key ON red_house.blood_review USING btree (evaluation_id, resource_id).
- blood_review_pkey: CREATE UNIQUE INDEX blood_review_pkey ON red_house.blood_review USING btree (review_id).

blood_status_transition

Columna	Tipo físico	NULL	Predeterminado
previous_status	character varying(16)	NO	—
new_status	character varying(16)	NO	—
is_illustrative	boolean	NO	true

Restricciones:

- blood_status_transition_check: CHECK (((previous_status)::text <> (new_status)::text)).
- blood_status_transition_is_illustrative_check: CHECK (is_illustrative).
- blood_status_transition_new_status_check: CHECK (((new_status)::text = ANY (ARRAY[('AVAILABLE'::character varying)::text, ('QUARANTINED'::character varying)::text, ('WITHDRAWN'::character varying)::text]))).
- blood_status_transition_previous_status_check: CHECK (((previous_status)::text = ANY (ARRAY[('AVAILABLE'::character varying)::text, ('QUARANTINED'::character varying)::text]))).
- blood_status_transition_pkey: PRIMARY KEY (previous_status, new_status).

Índices:

- blood_status_transition_pkey: CREATE UNIQUE INDEX blood_status_transition_pkey ON red_house.blood_status_transition USING btree (previous_status, new_status).

blood_unit

Columna	Tipo físico	NULL	Predeterminado
resource_id	uuid	NO	—
component_id	uuid	NO	—
location_id	uuid	NO	—
collected_at	timestamp with time zone	NO	—
expires_at	timestamp with time zone	NO	—
current_status	character varying(16)	NO	—
version_no	integer	NO	1
registered_at	timestamp with time zone	NO	now()

Restricciones:

- blood_unit_current_status_check: CHECK (((current_status)::text = ANY (ARRAY[('AVAILABLE'::character varying)::text, ('QUARANTINED'::character varying)::text, ('WITHDRAWN'::character varying)::text, ('RESERVED'::character varying)::text, ('IN_TRANSIT'::character varying)::text, ('DELIVERED'::character varying)::text]))).
- blood_unit_check: CHECK ((expires_at > collected_at)).
- blood_unit_pkey: PRIMARY KEY (resource_id).
- blood_unit_component_id_fkey: FOREIGN KEY (component_id) REFERENCES red_house.blood_component(component_id) DEFERRABLE.
- blood_unit_location_id_fkey: FOREIGN KEY (location_id) REFERENCES red_house.storage_location(location_id) DEFERRABLE.
- blood_unit_resource_id_fkey: FOREIGN KEY (resource_id) REFERENCES red_house.resource(resource_id) DEFERRABLE.

Índices:

- blood_unit_pkey: CREATE UNIQUE INDEX blood_unit_pkey ON red_house.blood_unit USING btree (resource_id).
- blood_unit_component_idx: CREATE INDEX blood_unit_component_idx ON red_house.blood_unit USING btree (component_id).
- blood_unit_expiry_idx: CREATE INDEX blood_unit_expiry_idx ON red_house.blood_unit USING btree (expires_at) WHERE ((current_status)::text = 'AVAILABLE'::text).
- blood_unit_location_idx: CREATE INDEX blood_unit_location_idx ON red_house.blood_unit USING btree (location_id).

cache_revision

Columna	Tipo físico	NULL	Predeterminado
name	text	NO	—
revision	bigint	NO	0

Restricciones:

- cache_revision_pkey: PRIMARY KEY (name).

Índices:

- cache_revision_pkey: CREATE UNIQUE INDEX cache_revision_pkey ON red_house.cache_revision USING btree (name).

campaign

Columna	Tipo físico	NULL	Predeterminado
campaign_id	uuid	NO	—
institution_id	uuid	NO	—

Columna	Tipo físico	NULL	Predeterminado
title	text	NO	—
starts_at	timestamp with time zone	NO	—
ends_at	timestamp with time zone	NO	—
capacity	integer	NO	—
current_status	text	NO	'OPEN'::text
version_no	integer	NO	1

Restricciones:

- api_campaigns_capacity_check: CHECK ((capacity > 0)).
- api_campaigns_check: CHECK ((ends_at > starts_at)).
- campaign_pkey: PRIMARY KEY (campaign_id).
- shared_campaigns_tenant_id: FOREIGN KEY (institution_id) REFERENCES red_house.institution(institution_id) DEFERRABLE.

Índices:

- campaign_pkey: CREATE UNIQUE INDEX campaign_pkey ON red_house.campaign USING btree (campaign_id).

candidate_evaluation

Columna	Tipo físico	NULL	Predeterminado
evaluation_id	uuid	NO	—
request_id	uuid	NO	—
algorithm_version	text	NO	—
request_version	integer	NO	—
recipient_version	integer	NO	—
actor_id	uuid	YES	—
occurred_at	timestamp with time zone	NO	now()
elapsed_ms	double precision	NO	—
tenant_id	uuid	NO	—
kind	text	NO	—
snapshot	jsonb	NO	—
candidates	jsonb	NO	—

Restricciones:

- candidate_evaluation_pkey: PRIMARY KEY (evaluation_id).
- candidate_evaluation_actor_id_fkey: FOREIGN KEY (actor_id) REFERENCES red_house.user_account(account_id) DEFERRABLE.
- shared_evaluations_request_id: FOREIGN KEY (request_id) REFERENCES red_house.blood_request(request_id) DEFERRABLE.
- shared_evaluations_tenant_id: FOREIGN KEY (tenant_id) REFERENCES red_house.institution(institution_id) DEFERRABLE.

Índices:

- candidate_evaluation_pkey: CREATE UNIQUE INDEX candidate_evaluation_pkey ON red_house.candidate_evaluation USING btree (evaluation_id).

capability

Columna	Tipo físico	NULL	Predeterminado
capability_code	character varying(40)	NO	—
capability_name	character varying(100)	NO	—

Restricciones:

- capability_pkey: PRIMARY KEY (capability_code).

Índices:

- capability_pkey: CREATE UNIQUE INDEX capability_pkey ON red_house.capability USING btree (capability_code).

catalogue_entry

Columna	Tipo físico	NULL	Predeterminado
id	uuid	NO	—
tenant_id	uuid	NO	—
kind	text	NO	—
name	text	NO	—
parent_id	uuid	YES	—
details	jsonb	NO	—
active	boolean	NO	true
version	integer	NO	1
created_at	timestamp with time zone	NO	now()

Restricciones:

- api_catalogue_kind_check: CHECK ((kind = ANY (ARRAY['sites'::text, 'contacts'::text, 'schedules'::text, 'capacities'::text, 'locations'::text]))).
- api_catalogue_pkey: PRIMARY KEY (id).
- api_catalogue_tenant_id_kind_name_key: UNIQUE (tenant_id, kind, name).
- api_catalogue_parent_id_fkey: FOREIGN KEY (parent_id) REFERENCES red_house.catalogue_entry(id) DEFERRABLE.
- api_catalogue_tenant_id_fkey: FOREIGN KEY (tenant_id) REFERENCES red_house.institution(institution_id) DEFERRABLE.

Índices:

- api_catalogue_pkey: CREATE UNIQUE INDEX api_catalogue_pkey ON red_house.catalogue_entry USING btree (id).
- api_catalogue_tenant_id_kind_name_key: CREATE UNIQUE INDEX api_catalogue_tenant_id_kind_name_key ON red_house.catalogue_entry USING btree (tenant_id, kind, name).
- api_catalogue_tenant: CREATE INDEX api_catalogue_tenant ON red_house.catalogue_entry USING btree (tenant_id, kind, name, id).

contact

Columna	Tipo físico	NULL	Predeterminado
contact_id	uuid	NO	gen_random_uuid()
contact_name	character varying(120)	NO	—

Columna	Tipo físico	NULL	Predeterminado
contact_function	character varying(80)	NO	—

Restricciones:

- contact_pkey: PRIMARY KEY (contact_id).

Índices:

- contact_pkey: CREATE UNIQUE INDEX contact_pkey ON red_house.contact USING btree (contact_id).

contact_method

Columna	Tipo físico	NULL	Predeterminado
contact_id	uuid	NO	—
method_kind	character varying(10)	NO	—
method_value	character varying(180)	NO	—

Restricciones:

- contact_method_method_kind_check: CHECK (((method_kind)::text = ANY (ARRAY[('EMAIL'::character varying)::text, ('PHONE'::character varying)::text]))).
- contact_method_pkey: PRIMARY KEY (contact_id, method_kind).
- contact_method_contact_id_fkey: FOREIGN KEY (contact_id) REFERENCES red_house.contact(contact_id) DEFERRABLE.

Índices:

- contact_method_pkey: CREATE UNIQUE INDEX contact_method_pkey ON red_house.contact_method USING btree (contact_id, method_kind).

custody_chain

Columna	Tipo físico	NULL	Predeterminado
id	uuid	NO	—
region_id	uuid	NO	—
origin_id	uuid	NO	—
destination_id	uuid	NO	—
last_sequence	integer	NO	0
last_hash	text	NO	''::text

Restricciones:

- api_chains_pkey: PRIMARY KEY (id).
- shared_chains_destination_id: FOREIGN KEY (destination_id) REFERENCES red_house.institution(institution_id) DEFERRABLE.
- shared_chains_id: FOREIGN KEY (id) REFERENCES red_house.shipment(shipment_id) DEFERRABLE.
- shared_chains_origin_id: FOREIGN KEY (origin_id) REFERENCES red_house.institution(institution_id) DEFERRABLE.

Índices:

- api_chains_pkey: CREATE UNIQUE INDEX api_chains_pkey ON red_house.custody_chain USING btree (id).

custody_event

Columna	Tipo físico	NULL	Predeterminado
event_id	uuid	NO	—
shipment_id	uuid	NO	—
sequence	integer	NO	—
status	character varying(20)	YES	—
actor_id	uuid	YES	—
occurred_at	timestamp with time zone	NO	now()
location_description	character varying(240)	YES	—
observation	character varying(1000)	YES	—
evidence_reference	character varying(240)	YES	—
previous_hash	text	NO	—
event_hash	text	NO	—
event	jsonb	NO	—

Restricciones:

- api_custody_events_shipment_id_sequence_key: UNIQUE (shipment_id, sequence).
- custody_event_pkey: PRIMARY KEY (event_id).
- api_custody_events_shipment_id_fkey: FOREIGN KEY (shipment_id) REFERENCES red_house.custody_chain(id) DEFERRABLE.
- custody_event_actor_id_fkey: FOREIGN KEY (actor_id) REFERENCES red_house.user_account(account_id) DEFERRABLE.

Índices:

- api_custody_events_shipment_id_sequence_key: CREATE UNIQUE INDEX api_custody_events_shipment_id_sequence_key ON red_house.custody_event USING btree (shipment_id, sequence).
- custody_event_pkey: CREATE UNIQUE INDEX custody_event_pkey ON red_house.custody_event USING btree (event_id).

donation

Columna	Tipo físico	NULL	Predeterminado
donation_id	uuid	NO	—
donor_id	uuid	NO	—
review_id	uuid	YES	—
donation_code	character varying(30)	YES	—
current_status	text	NO	'COLLECTED'::text
collected_at	timestamp with time zone	NO	—
processed_at	timestamp with time zone	YES	—
created_by	uuid	YES	—
registered_at	timestamp with time zone	NO	now()
version_no	integer	NO	1
tenant_id	uuid	NO	—
kind	text	NO	—
component	text	NO	—

Columna	Tipo físico	NULL	Predeterminado
blood_group	text	NO	—

Restricciones:

- api_donations_kind_check: CHECK ((kind = ANY (ARRAY['BLOOD'::text, 'ORGAN'::text]))).
- donation_donation_code_key: UNIQUE (donation_code).
- donation_pkey: PRIMARY KEY (donation_id).
- api_donations_donor_id_fkey: FOREIGN KEY (donor_id) REFERENCES red_house.donor(donor_id) DEFERRABLE.
- donation_created_by_fkey: FOREIGN KEY (created_by) REFERENCES red_house.user_account(account_id) DEFERRABLE.
- donation_review_id_fkey: FOREIGN KEY (review_id) REFERENCES red_house.donor_review(review_id) DEFERRABLE.
- shared_donations_tenant_id: FOREIGN KEY (tenant_id) REFERENCES red_house.institution(institution_id) DEFERRABLE.

Índices:

- donation_donation_code_key: CREATE UNIQUE INDEX donation_donation_code_key ON red_house.donation USING btree (donation_code).
- donation_pkey: CREATE UNIQUE INDEX donation_pkey ON red_house.donation USING btree (donation_id).

donation_event

Columna	Tipo físico	NULL	Predeterminado
event_id	uuid	NO	—
donation_id	uuid	NO	—
status	text	NO	—
actor_id	uuid	NO	—
occurred_at	timestamp with time zone	NO	now()
observation	text	NO	—

Restricciones:

- donation_event_pkey: PRIMARY KEY (event_id).
- api_donation_steps_donation_id_fkey: FOREIGN KEY (donation_id) REFERENCES red_house.donation(donation_id) DEFERRABLE.
- shared_donation_steps_actor_id: FOREIGN KEY (actor_id) REFERENCES red_house.user_account(account_id) DEFERRABLE.

Índices:

- donation_event_pkey: CREATE UNIQUE INDEX donation_event_pkey ON red_house.donation_event USING btree (event_id).

donation_unit

Columna	Tipo físico	NULL	Predeterminado
resource_id	uuid	NO	—
donation_id	uuid	NO	—
released_by	uuid	NO	—
release_reference	character varying(240)	NO	—
created_at	timestamp with time zone	NO	now()

Restricciones:

- donation_unit_pkey: PRIMARY KEY (resource_id).
- donation_unit_donation_id_fkey: FOREIGN KEY (donation_id) REFERENCES red_house.donation(donation_id) DEFERRABLE.
- donation_unit_released_by_fkey: FOREIGN KEY (released_by) REFERENCES red_house.user_account(account_id) DEFERRABLE.
- donation_unit_resource_id_fkey: FOREIGN KEY (resource_id) REFERENCES red_house.blood_unit(resource_id) DEFERRABLE.

Índices:

- donation_unit_pkey: CREATE UNIQUE INDEX donation_unit_pkey ON red_house.donation_unit USING btree (resource_id).

donor

Columna	Tipo físico	NULL	Predeterminado
donor_id	uuid	NO	—
institution_id	uuid	NO	—
record_code	text	NO	—
display_name	text	NO	—
blood_group	text	NO	—
donation_kind	text	YES	—
background	text	YES	—
restrictions	text	YES	—
consent_reference	text	YES	—
consent_at	text	YES	—
current_status	text	NO	'PRELIMINARY'::text
created_by	uuid	YES	—
registered_at	timestamp with time zone	NO	now()
version_no	integer	NO	1
account_id	uuid	YES	—
consent	boolean	NO	—

Restricciones:

- api_donors_consent_check: CHECK (consent).
- api_donors_donation_kind_check: CHECK ((donation_kind = ANY (ARRAY['VOLUNTARY'::text, 'REPLACEMENT'::text]))).
- api_donors_tenant_id_folio_key: UNIQUE (institution_id, record_code).
- donor_pkey: PRIMARY KEY (donor_id).
- donor_created_by_fkey: FOREIGN KEY (created_by) REFERENCES red_house.user_account(account_id) DEFERRABLE.
- shared_donors_tenant_id: FOREIGN KEY (institution_id) REFERENCES red_house.institution(institution_id) DEFERRABLE.
- shared_donors_user_id: FOREIGN KEY (account_id) REFERENCES red_house.user_account(account_id) DEFERRABLE.

Índices:

- api_donors_tenant_id_folio_key: CREATE UNIQUE INDEX api_donors_tenant_id_folio_key ON red_house.donor USING btree (institution_id, record_code).
- donor_pkey: CREATE UNIQUE INDEX donor_pkey ON red_house.donor USING btree (donor_id).

- api_donor_account: CREATE UNIQUE INDEX api_donor_account ON red_house.donor USING btree (account_id) WHERE (account_id IS NOT NULL).
- donor_institution_idx: CREATE INDEX donor_institution_idx ON red_house.donor USING btree (institution_id).

donor_review

Columna	Tipo físico	NULL	Predeterminado
review_id	uuid	NO	—
donor_id	uuid	NO	—
decision	text	NO	—
reason	text	NO	—
actor_id	uuid	NO	—
occurred_at	timestamp with time zone	NO	now()

Restricciones:

- donor_review_pkey: PRIMARY KEY (review_id).
- api_donor_reviews_donor_id_fkey: FOREIGN KEY (donor_id) REFERENCES red_house.donor(donor_id) DEFERRABLE.
- shared_donor_reviews_actor_id: FOREIGN KEY (actor_id) REFERENCES red_house.user_account(account_id) DEFERRABLE.

Índices:

- donor_review_pkey: CREATE UNIQUE INDEX donor_review_pkey ON red_house.donor_review USING btree (review_id).

institution

Columna	Tipo físico	NULL	Predeterminado
institution_id	uuid	NO	—
institution_code	character varying(30)	YES	—
institution_name	text	NO	—
institution_type	character varying(40)	YES	—
region_name	character varying(80)	YES	—
city	character varying(100)	YES	—
street	character varying(200)	YES	—
participation_status	character varying(10)	YES	'ACTIVE'::character varying
version_no	integer	NO	1
registered_at	timestamp with time zone	YES	now()
operating_hours	character varying(240)	YES	''::character varying
region_id	uuid	NO	—
active	boolean	NO	true
created_by	uuid	YES	—

Restricciones:

- institution_institution_type_check: CHECK (((institution_type)::text = ANY (ARRAY[('BLOOD_BANK'::character varying)::text, ('HOSPITAL'::character varying)::text, ('COORDINATION'::character varying)::text, ('TRANSPLANT_CENTER'::character varying)::text]))).

- institution_participation_status_check: CHECK (((participation_status)::text = ANY (ARRAY[('ACTIVE'::character varying)::text, ('INACTIVE'::character varying)::text]))).
- institution_institution_code_key: UNIQUE (institution_code).
- institution_pkey: PRIMARY KEY (institution_id).
- api_institutions_created_by_fkey: FOREIGN KEY (created_by) REFERENCES red_house.user_account(account_id) DEFERRABLE.

Índices:

- institution_institution_code_key: CREATE UNIQUE INDEX institution_institution_code_key ON red_house.institution USING btree (institution_code).
- institution_pkey: CREATE UNIQUE INDEX institution_pkey ON red_house.institution USING btree (institution_id).

institution_capability

Columna	Tipo físico	NULL	Predeterminado
institution_id	uuid	NO	—
capability_code	character varying(40)	NO	—

Restricciones:

- institution_capability_pkey: PRIMARY KEY (institution_id, capability_code).
- institution_capability_capability_code_fkey: FOREIGN KEY (capability_code) REFERENCES red_house.capability(capability_code) DEFERRABLE.
- institution_capability_institution_id_fkey: FOREIGN KEY (institution_id) REFERENCES red_house.institution(institution_id) DEFERRABLE.

Índices:

- institution_capability_pkey: CREATE UNIQUE INDEX institution_capability_pkey ON red_house.institution_capability USING btree (institution_id, capability_code).

institution_contact

Columna	Tipo físico	NULL	Predeterminado
institution_id	uuid	NO	—
contact_id	uuid	NO	—

Restricciones:

- institution_contact_contact_id_key: UNIQUE (contact_id).
- institution_contact_pkey: PRIMARY KEY (institution_id, contact_id).
- institution_contact_contact_id_fkey: FOREIGN KEY (contact_id) REFERENCES red_house.contact(contact_id) DEFERRABLE.
- institution_contact_institution_id_fkey: FOREIGN KEY (institution_id) REFERENCES red_house.institution(institution_id) DEFERRABLE.

Índices:

- institution_contact_contact_id_key: CREATE UNIQUE INDEX institution_contact_contact_id_key ON red_house.institution_contact USING btree (contact_id).
- institution_contact_pkey: CREATE UNIQUE INDEX institution_contact_pkey ON red_house.institution_contact USING btree (institution_id, contact_id).

login_attempt

Columna	Tipo físico	NULL	Predeterminado
attempt_id	bigint	NO	—
identity_hash	character(64)	NO	—
address_hash	character(64)	NO	—
occurred_at	timestamp with time zone	NO	now()
was_successful	boolean	NO	—

Restricciones:

- login_attempt_pkey: PRIMARY KEY (attempt_id).

Índices:

- login_attempt_pkey: CREATE UNIQUE INDEX login_attempt_pkey ON red_house.login_attempt USING btree (attempt_id).
- login_address_time_idx: CREATE INDEX login_address_time_idx ON red_house.login_attempt USING btree (address_hash, occurred_at DESC).
- login_identity_time_idx: CREATE INDEX login_identity_time_idx ON red_house.login_attempt USING btree (identity_hash, occurred_at DESC).

notification

Columna	Tipo físico	NULL	Predeterminado
notification_id	uuid	NO	—
event_id	uuid	NO	—
institution_id	uuid	NO	—
target_role	text	NO	—
target_account_id	uuid	YES	—
message_code	text	NO	—
entity_reference	text	NO	—
current_status	text	NO	'OPEN'::text
acknowledged_by	uuid	YES	—
created_at	timestamp with time zone	NO	now()
region_id	uuid	NO	—

Restricciones:

- api_alerts_event_id_tenant_id_target_role_key: UNIQUE (event_id, institution_id, target_role).
- notification_pkey: PRIMARY KEY (notification_id).
- shared_alerts_acknowledged_by: FOREIGN KEY (acknowledged_by) REFERENCES red_house.user_account(account_id) DEFERRABLE.
- shared_alerts_target_user_id: FOREIGN KEY (target_account_id) REFERENCES red_house.user_account(account_id) DEFERRABLE.
- shared_alerts_tenant_id: FOREIGN KEY (institution_id) REFERENCES red_house.institution(institution_id) DEFERRABLE.

Índices:

- api_alerts_event_id_tenant_id_target_role_key: CREATE UNIQUE INDEX api_alerts_event_id_tenant_id_target_role_key ON red_house.notification USING btree (event_id, institution_id, target_role).
- notification_pkey: CREATE UNIQUE INDEX notification_pkey ON red_house.notification USING btree (notification_id).

organ_allocation

Columna	Tipo físico	NULL	Predeterminado
allocation_id	uuid	NO	gen_random_uuid()
candidate_id	uuid	NO	—
review_id	uuid	NO	—
offer_id	uuid	NO	—
recipient_id	uuid	NO	—
authorized_by	uuid	NO	—
authorization_reference	character varying(240)	NO	—
current_status	character varying(12)	NO	'RESERVED'::character varying
transport_id	uuid	YES	—
vehicle	character varying(120)	YES	—
departure_at	timestamp with time zone	YES	—
eta	timestamp with time zone	YES	—
reserved_at	timestamp with time zone	NO	now()
received_at	timestamp with time zone	YES	—
version_no	integer	NO	1

Restricciones:

- organ_allocation_check: CHECK (((eta IS NULL) OR (eta > departure_at))).
- organ_allocation_current_status_check: CHECK (((current_status)::text = ANY (ARRAY[('RESERVED'::character varying)::text, ('SCHEDULED'::character varying)::text, ('PREPARED'::character varying)::text, ('COLLECTED'::character varying)::text, ('IN_TRANSIT'::character varying)::text, ('DELIVERED'::character varying)::text, ('ACCEPTED'::character varying)::text, ('CANCELLED'::character varying)::text]))).
- organ_allocation_pkey: PRIMARY KEY (allocation_id).
- organ_allocation_authorized_by_fkey: FOREIGN KEY (authorized_by) REFERENCES red_house.user_account(account_id) DEFERRABLE.
- organ_allocation_candidate_id_fkey: FOREIGN KEY (candidate_id) REFERENCES red_house.organ_candidate(candidate_id) DEFERRABLE.
- organ_allocation_offer_id_fkey: FOREIGN KEY (offer_id) REFERENCES red_house.organ_offer(offer_id) DEFERRABLE.
- organ_allocation_recipient_id_fkey: FOREIGN KEY (recipient_id) REFERENCES red_house.organ_recipient(recipient_id) DEFERRABLE.
- organ_allocation_review_id_fkey: FOREIGN KEY (review_id) REFERENCES red_house.organ_review(review_id) DEFERRABLE.
- organ_allocation_transport_id_fkey: FOREIGN KEY (transport_id) REFERENCES red_house.user_account(account_id) DEFERRABLE.

Índices:

- organ_allocation_pkey: CREATE UNIQUE INDEX organ_allocation_pkey ON red_house.organ_allocation USING btree (allocation_id).
- organ_exclusive_offer: CREATE UNIQUE INDEX organ_exclusive_offer ON red_house.organ_allocation USING btree (offer_id) WHERE ((current_status)::text <> 'CANCELLED'::text).

- organ_exclusive_recipient: CREATE UNIQUE INDEX organ_exclusive_recipient ON red_house.organ_allocation USING btree (recipient_id) WHERE ((current_status)::text <> 'CANCELLED'::text).

organ_candidate

Columna	Tipo físico	NULL	Predeterminado
candidate_id	uuid	NO	gen_random_uuid()
evaluation_id	uuid	NO	—
offer_id	uuid	NO	—
recipient_id	uuid	NO	—
offer_version	integer	NO	—
recipient_version	integer	NO	—
route_version	integer	NO	—
rank_no	integer	NO	—
algorithm_version	character varying(40)	NO	—
explanation	text	NO	—
distance_km	integer	NO	—
travel_minutes	integer	NO	—
evaluated_by	uuid	NO	—
evaluated_at	timestamp with time zone	NO	now()

Restricciones:

- organ_candidate_rank_no_check: CHECK ((rank_no > 0)).
- organ_candidate_evaluation_id_recipient_id_key: UNIQUE (evaluation_id, recipient_id).
- organ_candidate_pkey: PRIMARY KEY (candidate_id).
- organ_candidate_evaluated_by_fkey: FOREIGN KEY (evaluated_by) REFERENCES red_house.user_account(account_id) DEFERRABLE.
- organ_candidate_evaluation_id_fkey: FOREIGN KEY (evaluation_id) REFERENCES red_house.organ_evaluation(evaluation_id) DEFERRABLE.
- organ_candidate_offer_id_fkey: FOREIGN KEY (offer_id) REFERENCES red_house.organ_offer(offer_id) DEFERRABLE.
- organ_candidate_recipient_id_fkey: FOREIGN KEY (recipient_id) REFERENCES red_house.organ_recipient(recipient_id) DEFERRABLE.

Índices:

- organ_candidate_evaluation_id_recipient_id_key: CREATE UNIQUE INDEX organ_candidate_evaluation_id_recipient_id_key ON red_house.organ_candidate USING btree (evaluation_id, recipient_id).
- organ_candidate_pkey: CREATE UNIQUE INDEX organ_candidate_pkey ON red_house.organ_candidate USING btree (candidate_id).
- organ_candidates_offer: CREATE INDEX organ_candidates_offer ON red_house.organ_candidate USING btree (offer_id, evaluated_at).

organ_custody_event

Columna	Tipo físico	NULL	Predeterminado
event_id	uuid	NO	gen_random_uuid()
allocation_id	uuid	NO	—
status	character varying(20)	NO	—

Columna	Tipo físico	NULL	Predeterminado
actor_id	uuid	NO	—
occurred_at	timestamp with time zone	NO	now()
location_description	character varying(240)	NO	—
observation	text	NO	—
evidence_reference	character varying(240)	NO	—
previous_hash	text	YES	—
event_hash	text	YES	—

Restricciones:

- organ_custody_event_pkey: PRIMARY KEY (event_id).
- organ_custody_event_actor_id_fkey: FOREIGN KEY (actor_id) REFERENCES red_house.user_account(account_id) DEFERRABLE.
- organ_custody_event_allocation_id_fkey: FOREIGN KEY (allocation_id) REFERENCES red_house.organ_allocation(allocation_id) DEFERRABLE.

Índices:

- organ_custody_event_pkey: CREATE UNIQUE INDEX organ_custody_event_pkey ON red_house.organ_custody_event USING btree (event_id).
- organ_custody_allocation: CREATE INDEX organ_custody_allocation ON red_house.organ_custody_event USING btree (allocation_id, occurred_at).

organ_donor

Columna	Tipo físico	NULL	Predeterminado
donor_id	uuid	NO	gen_random_uuid()
institution_id	uuid	NO	—
record_code	character varying(30)	NO	—
display_name	character varying(120)	NO	—
abo	character varying(2)	NO	—
donation_kind	character varying(12)	NO	—
consent_reference	character varying(240)	NO	—
studies	text	NO	—
hla	text	NO	—
clinical_reference	character varying(240)	NO	—
reviewed_by	uuid	NO	—
registered_at	timestamp with time zone	NO	now()

Restricciones:

- organ_donor_abo_check: CHECK (((abo)::text = ANY (ARRAY[('O'::character varying)::text, ('A'::character varying)::text, ('B'::character varying)::text, ('AB'::character varying)::text]))).
- organ_donor_donation_kind_check: CHECK (((donation_kind)::text = ANY (ARRAY[('LIVING'::character varying)::text, ('DECEASED'::character varying)::text]))).
- organ_donor_pkey: PRIMARY KEY (donor_id).
- organ_donor_record_code_key: UNIQUE (record_code).

- organ_donor_institution_id_fkey: FOREIGN KEY (institution_id) REFERENCES red_house.institution(institution_id) DEFERRABLE.
- organ_donor_reviewed_by_fkey: FOREIGN KEY (reviewed_by) REFERENCES red_house.user_account(account_id) DEFERRABLE.

Índices:

- organ_donor_pkey: CREATE UNIQUE INDEX organ_donor_pkey ON red_house.organ_donor USING btree (donor_id).
- organ_donor_record_code_key: CREATE UNIQUE INDEX organ_donor_record_code_key ON red_house.organ_donor USING btree (record_code).

organ_evaluation

Columna	Tipo físico	NULL	Predeterminado
evaluation_id	uuid	NO	gen_random_uuid()
offer_id	uuid	NO	—
evaluated_by	uuid	NO	—
algorithm_version	character varying(40)	NO	—
evaluated_at	timestamp with time zone	NO	now()

Restricciones:

- organ_evaluation_pkey: PRIMARY KEY (evaluation_id).
- organ_evaluation_evaluated_by_fkey: FOREIGN KEY (evaluated_by) REFERENCES red_house.user_account(account_id) DEFERRABLE.
- organ_evaluation_offer_id_fkey: FOREIGN KEY (offer_id) REFERENCES red_house.organ_offer(offer_id) DEFERRABLE.

Índices:

- organ_evaluation_pkey: CREATE UNIQUE INDEX organ_evaluation_pkey ON red_house.organ_evaluation USING btree (evaluation_id).

organ_offer

Columna	Tipo físico	NULL	Predeterminado
offer_id	uuid	NO	gen_random_uuid()
donor_id	uuid	NO	—
record_code	character varying(30)	NO	—
organ_type	character varying(12)	NO	—
anatomical_description	character varying(240)	NO	—
recovered_at	timestamp with time zone	NO	—
preservation_until	timestamp with time zone	NO	—
preservation_reference	character varying(240)	NO	—
released_by	uuid	NO	—
current_status	character varying(12)	NO	'AVAILABLE'::character varying
version_no	integer	NO	1
registered_at	timestamp with time zone	NO	now()

Restricciones:

- organ_offer_check: CHECK ((preservation_until > recovered_at)).

- organ_offer_current_status_check: CHECK (((current_status)::text = ANY (ARRAY[('AVAILABLE'::character varying)::text, ('RESERVED'::character varying)::text, ('IN_TRANSIT'::character varying)::text, ('RECEIVED'::character varying)::text, ('WITHDRAWN'::character varying)::text]))).
- organ_offer_organ_type_check: CHECK (((organ_type)::text = ANY (ARRAY[('KIDNEY'::character varying)::text, ('LIVER'::character varying)::text, ('HEART'::character varying)::text]))).
- organ_offer_pkey: PRIMARY KEY (offer_id).
- organ_offer_record_code_key: UNIQUE (record_code).
- organ_offer_donor_id_fkey: FOREIGN KEY (donor_id) REFERENCES red_house.organ_donor(donor_id) DEFERRABLE.
- organ_offer_released_by_fkey: FOREIGN KEY (released_by) REFERENCES red_house.user_account(account_id) DEFERRABLE.

Índices:

- organ_offer_pkey: CREATE UNIQUE INDEX organ_offer_pkey ON red_house.organ_offer USING btree (offer_id).
- organ_offer_record_code_key: CREATE UNIQUE INDEX organ_offer_record_code_key ON red_house.organ_offer USING btree (record_code).

organ_recipient

Columna	Tipo físico	NULL	Predeterminado
recipient_id	uuid	NO	gen_random_uuid()
institution_id	uuid	NO	—
record_code	character varying(30)	NO	—
display_name	character varying(120)	NO	—
organ_type	character varying(12)	NO	—
abo	character varying(2)	NO	—
studies	text	NO	—
hla	text	NO	—
urgency	character varying(12)	NO	—
waiting_since	timestamp with time zone	NO	—
clinical_reference	character varying(240)	NO	—
responsible_id	uuid	NO	—
current_status	character varying(12)	NO	'ACTIVE'::character varying
version_no	integer	NO	1
registered_at	timestamp with time zone	NO	now()

Restricciones:

- organ_recipient_organ_type_check: CHECK (((organ_type)::text = ANY (ARRAY[('KIDNEY'::character varying)::text, ('LIVER'::character varying)::text, ('HEART'::character varying)::text]))).
- organ_recipient_abo_check: CHECK (((abo)::text = ANY (ARRAY[('O'::character varying)::text, ('A'::character varying)::text, ('B'::character varying)::text, ('AB'::character varying)::text]))).
- organ_recipient_current_status_check: CHECK (((current_status)::text = ANY (ARRAY[('ACTIVE'::character varying)::text, ('INACTIVE'::character varying)::text, ('RESERVED'::character varying)::text, ('CLOSED'::character varying)::text]))).
- organ_recipient_urgency_check: CHECK (((urgency)::text = ANY (ARRAY[('URGENT'::character varying)::text, ('PRIORITY'::character varying)::text, ('ROUTINE'::character varying)::text]))).
- organ_recipient_pkey: PRIMARY KEY (recipient_id).
- organ_recipient_record_code_key: UNIQUE (record_code).

- organ_recipient_institution_id_fkey: FOREIGN KEY (institution_id) REFERENCES red_house.institution(institution_id) DEFERRABLE.
- organ_recipient_responsible_id_fkey: FOREIGN KEY (responsible_id) REFERENCES red_house.user_account(account_id) DEFERRABLE.

Índices:

- organ_recipient_pkey: CREATE UNIQUE INDEX organ_recipient_pkey ON red_house.organ_recipient USING btree (recipient_id).
- organ_recipient_record_code_key: CREATE UNIQUE INDEX organ_recipient_record_code_key ON red_house.organ_recipient USING btree (record_code).

organ_review

Columna	Tipo físico	NULL	Predeterminado
review_id	uuid	NO	gen_random_uuid()
candidate_id	uuid	NO	—
decision	character varying(12)	NO	—
hla_assessment	text	NO	—
size_assessment	text	NO	—
crossmatch_reference	character varying(240)	NO	—
clinical_reference	character varying(240)	NO	—
reviewed_by	uuid	NO	—
occurred_at	timestamp with time zone	NO	now()

Restricciones:

- organ_review_decision_check: CHECK (((decision)::text = ANY (ARRAY[('FAVORABLE'::character varying)::text, ('REJECTED'::character varying)::text]))).
- organ_review_pkey: PRIMARY KEY (review_id).
- organ_review_candidate_id_fkey: FOREIGN KEY (candidate_id) REFERENCES red_house.organ_candidate(candidate_id) DEFERRABLE.
- organ_review_reviewed_by_fkey: FOREIGN KEY (reviewed_by) REFERENCES red_house.user_account(account_id) DEFERRABLE.

Índices:

- organ_review_pkey: CREATE UNIQUE INDEX organ_review_pkey ON red_house.organ_review USING btree (review_id).

parameter_version

Columna	Tipo físico	NULL	Predeterminado
parameter_version_id	uuid	NO	gen_random_uuid()
parameter_code	character varying(40)	NO	—
region_name	character varying(80)	NO	—
version_no	integer	NO	—
scalar_value	integer	NO	—
measurement_unit	character varying(10)	NO	'HOURS'::character varying
is_illustrative	boolean	NO	true
approved_by	uuid	YES	—
valid_from	timestamp with time zone	NO	now()

Columna	Tipo físico	NULL	Predeterminado

Restricciones:

- parameter_version_is_illustrative_check: CHECK (is_illustrative).
- parameter_version_measurement_unit_check: CHECK (((measurement_unit)::text = 'HOURS'::text)).
- parameter_version_parameter_code_check: CHECK (((parameter_code)::text = 'EXPIRY_WARNING_HOURS'::text)).
- parameter_version_scalar_value_check: CHECK (((scalar_value >= 1) AND (scalar_value <= 720))).
- parameter_version_pkey: PRIMARY KEY (parameter_version_id).
- parameter_version_region_name_parameter_code_version_no_key: UNIQUE (region_name, parameter_code, version_no).
- parameter_version_approved_by_fkey: FOREIGN KEY (approved_by) REFERENCES red_house.user_account(account_id) DEFERRABLE.

Índices:

- parameter_version_pkey: CREATE UNIQUE INDEX parameter_version_pkey ON red_house.parameter_version USING btree (parameter_version_id).
- parameter_version_region_name_parameter_code_version_no_key: CREATE UNIQUE INDEX parameter_version_region_name_parameter_code_version_no_key ON red_house.parameter_version USING btree (region_name, parameter_code, version_no).

party

Columna	Tipo físico	NULL	Predeterminado
party_id	uuid	NO	gen_random_uuid()
party_name	character varying(120)	NO	—

Restricciones:

- party_pkey: PRIMARY KEY (party_id).

Índices:

- party_pkey: CREATE UNIQUE INDEX party_pkey ON red_house.party USING btree (party_id).

ranking_run

Columna	Tipo físico	NULL	Predeterminado
id	uuid	NO	—
tenant_id	uuid	NO	—
evaluation_id	uuid	NO	—
algorithm_version	text	NO	—
factors	jsonb	NO	—
result	jsonb	NO	—
elapsed_ms	double precision	NO	—
created_at	timestamp with time zone	NO	now()

Restricciones:

- api_rankings_pkey: PRIMARY KEY (id).

- shared_rankings_evaluation_id: FOREIGN KEY (evaluation_id) REFERENCES red_house.candidate_evaluation(evaluation_id) DEFERRABLE.
- shared_rankings_tenant_id: FOREIGN KEY (tenant_id) REFERENCES red_house.institution(institution_id) DEFERRABLE.

Índices:

- api_rankings_pkey: CREATE UNIQUE INDEX api_rankings_pkey ON red_house.ranking_run USING btree (id).

recipient

Columna	Tipo físico	NULL	Predeterminado
recipient_id	uuid	NO	—
institution_id	uuid	NO	—
record_code	text	NO	—
display_name	text	NO	—
blood_group	text	NO	—
requirement	text	YES	—
legacy_urgency	character varying(20)	YES	—
studies	text	NO	—
restrictions	text	YES	—
current_status	text	NO	'ACTIVE'::text
responsible_id	uuid	YES	—
registered_at	timestamp with time zone	YES	now()
version_no	integer	NO	1
kind	text	NO	—
organ_type	text	YES	—

Restricciones:

- api_recipients_check: CHECK ((((kind = 'BLOOD'::text) AND (organ_type IS NULL)) OR ((kind = 'ORGAN'::text) AND (organ_type = ANY (ARRAY['KIDNEY'::text, 'LIVER'::text, 'HEART'::text])))))).
- api_recipients_kind_check: CHECK ((kind = ANY (ARRAY['BLOOD'::text, 'ORGAN'::text]))).
- recipient_urgency_check: CHECK (((legacy_urgency)::text = ANY (ARRAY[('URGENT'::character varying)::text, ('PRIORITY'::character varying)::text, ('ROUTINE'::character varying)::text]))).
- api_recipients_tenant_id_folio_key: UNIQUE (institution_id, record_code).
- recipient_pkey: PRIMARY KEY (recipient_id).
- recipient_responsible_id_fkey: FOREIGN KEY (responsible_id) REFERENCES red_house.user_account(account_id) DEFERRABLE.
- shared_recipients_tenant_id: FOREIGN KEY (institution_id) REFERENCES red_house.institution(institution_id) DEFERRABLE.

Índices:

- api_recipients_tenant_id_folio_key: CREATE UNIQUE INDEX api_recipients_tenant_id_folio_key ON red_house.recipient USING btree (institution_id, record_code).
- recipient_pkey: CREATE UNIQUE INDEX recipient_pkey ON red_house.recipient USING btree (recipient_id).
- recipient_institution_idx: CREATE INDEX recipient_institution_idx ON red_house.recipient USING btree (institution_id).

regional_route

Columna	Tipo físico	NULL	Predeterminado
route_id	uuid	NO	—
origin_id	uuid	NO	—
destination_id	uuid	NO	—
distance_km	double precision	NO	—
travel_minutes	integer	NO	—
source_reference	text	NO	—
recorded_by	uuid	YES	—
recorded_at	timestamp with time zone	NO	now()
version_no	integer	NO	1
region_id	uuid	NO	—

Restricciones:

- api_routes_distance_km_check: CHECK ((distance_km >= (0)::double precision)).
- api_routes_travel_minutes_check: CHECK ((travel_minutes >= 0)).
- api_routes_origin_id_destination_id_key: UNIQUE (origin_id, destination_id).
- regional_route_pkey: PRIMARY KEY (route_id).
- regional_route_recorded_by_fkey: FOREIGN KEY (recorded_by) REFERENCES red_house.user_account(account_id) DEFERRABLE.
- shared_routes_destination_id: FOREIGN KEY (destination_id) REFERENCES red_house.institution(institution_id) DEFERRABLE.
- shared_routes_origin_id: FOREIGN KEY (origin_id) REFERENCES red_house.institution(institution_id) DEFERRABLE.

Índices:

- api_routes_origin_id_destination_id_key: CREATE UNIQUE INDEX api_routes_origin_id_destination_id_key ON red_house.regional_route USING btree (origin_id, destination_id).
- regional_route_pkey: CREATE UNIQUE INDEX regional_route_pkey ON red_house.regional_route USING btree (route_id).

request_event

Columna	Tipo físico	NULL	Predeterminado
event_id	uuid	NO	gen_random_uuid()
request_id	uuid	NO	—
action	character varying(30)	NO	—
actor_id	uuid	NO	—
occurred_at	timestamp with time zone	NO	now()
observation	character varying(240)	NO	—

Restricciones:

- request_event_pkey: PRIMARY KEY (event_id).
- request_event_actor_id_fkey: FOREIGN KEY (actor_id) REFERENCES red_house.user_account(account_id) DEFERRABLE.
- request_event_request_id_fkey: FOREIGN KEY (request_id) REFERENCES red_house.blood_request(request_id) DEFERRABLE.

Índices:

- request_event_pkey: CREATE UNIQUE INDEX request_event_pkey ON red_house.request_event USING btree (event_id).

request_hold

Columna	Tipo físico	NULL	Predeterminado
id	uuid	NO	—
request_id	uuid	NO	—
recipient_id	uuid	NO	—
operation_id	uuid	NO	—
resource_id	uuid	NO	—
kind	text	NO	—
request_version	integer	NO	—
region_id	uuid	NO	—
status	text	NO	'HELD'::text
created_at	timestamp with time zone	NO	now()

Restricciones:

- api_holds_operation_id_key: UNIQUE (operation_id).
- api_holds_pkey: PRIMARY KEY (id).
- api_holds_recipient_id_fkey: FOREIGN KEY (recipient_id) REFERENCES red_house.recipient(recipient_id) DEFERRABLE.
- api_holds_request_id_fkey: FOREIGN KEY (request_id) REFERENCES red_house.blood_request(request_id) DEFERRABLE.
- shared_holds_resource_id: FOREIGN KEY (resource_id) REFERENCES red_house.resource(resource_id) DEFERRABLE.

Índices:

- api_holds_operation_id_key: CREATE UNIQUE INDEX api_holds_operation_id_key ON red_house.request_hold USING btree (operation_id).
- api_holds_pkey: CREATE UNIQUE INDEX api_holds_pkey ON red_house.request_hold USING btree (id).
- api_organ_patient_reserved: CREATE UNIQUE INDEX api_organ_patient_reserved ON red_house.request_hold USING btree (recipient_id) WHERE ((kind = 'ORGAN'::text) AND (status = ANY (ARRAY['HELD'::text, 'CONFIRMED'::text, 'RECEIVED'::text]))).

resource

Columna	Tipo físico	NULL	Predeterminado
resource_id	uuid	NO	—
traceability_code	character varying(40)	YES	—
resource_kind	text	NO	—
tenant_id	uuid	NO	—
region_id	uuid	NO	—
folio	text	NO	—
current_institution_id	uuid	NO	—
donation_id	uuid	YES	—
component	text	NO	—
blood_group	text	NO	—

Columna	Tipo físico	NULL	Predeterminado
expires_at	timestamp with time zone	NO	—
status	text	NO	'QUARANTINE'::text
version	integer	NO	1
created_at	timestamp with time zone	NO	now()
location_id	uuid	YES	—
collected_at	timestamp with time zone	YES	—

Restricciones:

- api_resources_kind_check: CHECK ((resource_kind = ANY (ARRAY['BLOOD'::text, 'ORGAN'::text]))).
- api_resources_tenant_id_folio_key: UNIQUE (tenant_id, folio).
- resource_pkey: PRIMARY KEY (resource_id).
- resource_traceability_code_key: UNIQUE (traceability_code).
- shared_resources_current_institution_id: FOREIGN KEY (current_institution_id) REFERENCES red_house.institution(institution_id) DEFERRABLE.
- shared_resources_donation_id: FOREIGN KEY (donation_id) REFERENCES red_house.donation(donation_id) DEFERRABLE.
- shared_resources_tenant_id: FOREIGN KEY (tenant_id) REFERENCES red_house.institution(institution_id) DEFERRABLE.

Índices:

- api_resources_tenant_id_folio_key: CREATE UNIQUE INDEX api_resources_tenant_id_folio_key ON red_house.resource USING btree (tenant_id, folio).
- resource_pkey: CREATE UNIQUE INDEX resource_pkey ON red_house.resource USING btree (resource_id).
- resource_traceability_code_key: CREATE UNIQUE INDEX resource_traceability_code_key ON red_house.resource USING btree (traceability_code).
- api_availability_page: CREATE INDEX api_availability_page ON red_house.resource USING btree (region_id, expires_at, resource_id) WHERE (status = 'AVAILABLE'::text).
- api_available_resources: CREATE INDEX api_available_resources ON red_house.resource USING btree (region_id, resource_kind, component, expires_at) WHERE (status = 'AVAILABLE'::text).

resource_review

Columna	Tipo físico	NULL	Predeterminado
id	uuid	NO	—
resource_id	uuid	NO	—
actor_id	uuid	NO	—
decision	text	NO	—
reason	text	NO	—
created_at	timestamp with time zone	NO	now()

Restricciones:

- api_resource_reviews_pkey: PRIMARY KEY (id).
- api_resource_reviews_resource_id_fkey: FOREIGN KEY (resource_id) REFERENCES red_house.resource(resource_id) DEFERRABLE.
- shared_resource_reviews_actor_id: FOREIGN KEY (actor_id) REFERENCES red_house.user_account(account_id) DEFERRABLE.

Índices:

- api_resource_reviews_pkey: CREATE UNIQUE INDEX api_resource_reviews_pkey ON red_house.resource_review USING btree (id).

role

Columna	Tipo físico	NULL	Predeterminado
role_code	character varying(30)	NO	—
role_name	character varying(80)	NO	—
is_enabled	boolean	NO	—

Restricciones:

- role_pkey: PRIMARY KEY (role_code).

Índices:

- role_pkey: CREATE UNIQUE INDEX role_pkey ON red_house.role USING btree (role_code).

schema_migration

Columna	Tipo físico	NULL	Predeterminado
version	integer	NO	—
description	text	NO	—
installed_at	timestamp with time zone	NO	now()

Restricciones:

- schema_migration_pkey: PRIMARY KEY (version).

Índices:

- schema_migration_pkey: CREATE UNIQUE INDEX schema_migration_pkey ON red_house.schema_migration USING btree (version).

service_activity_events

Columna	Tipo físico	NULL	Predeterminado
service	text	NO	—
id	uuid	NO	—
tenant_id	uuid	NO	—
event	jsonb	NO	—
created_at	timestamp with time zone	NO	now()

Restricciones:

- service_activity_events_pkey: PRIMARY KEY (service, id).

Índices:

- service_activity_events_pkey: CREATE UNIQUE INDEX service_activity_events_pkey ON red_house.service_activity_events USING btree (service, id).

service_decisions

Columna	Tipo físico	NULL	Predeterminado
service	text	NO	—
id	uuid	NO	—
resource_id	uuid	NO	—
tenant_id	uuid	NO	—
actor_id	uuid	NO	—
action	text	NO	—
reason	text	NO	—
changes	jsonb	NO	'{}'::jsonb
created_at	timestamp with time zone	NO	now()

Restricciones:

- service_decisions_pkey: PRIMARY KEY (service, id).

Índices:

- service_decisions_pkey: CREATE UNIQUE INDEX service_decisions_pkey ON red_house.service_decisions USING btree (service, id).

service_health_check

Columna	Tipo físico	NULL	Predeterminado
check_id	uuid	NO	—
service	text	NO	—
state	text	NO	—
elapsed_ms	double precision	NO	—
dependency	text	YES	—
last_error	text	YES	—
deployed_version	text	YES	—
checked_at	timestamp with time zone	NO	now()

Restricciones:

- service_health_check_pkey: PRIMARY KEY (check_id).

Índices:

- service_health_check_pkey: CREATE UNIQUE INDEX service_health_check_pkey ON red_house.service_health_check USING btree (check_id).
- api_checks_latest: CREATE INDEX api_checks_latest ON red_house.service_health_check USING btree (service, checked_at DESC).
- health_service_time: CREATE INDEX health_service_time ON red_house.service_health_check USING btree (service, checked_at DESC).

service_idempotency

Columna	Tipo físico	NULL	Predeterminado
service	text	NO	—

Columna	Tipo físico	NULL	Predeterminado
id	uuid	NO	—
user_id	uuid	NO	—
key	text	NO	—
operation	text	NO	—
fingerprint	text	NO	—
result	jsonb	NO	—
created_at	timestamp with time zone	NO	now()

Restricciones:

- service_idempotency_pkey: PRIMARY KEY (service, id).
- service_idempotency_service_user_id_key_key: UNIQUE (service, user_id, key).

Índices:

- service_idempotency_pkey: CREATE UNIQUE INDEX service_idempotency_pkey ON red_house.service_idempotency USING btree (service, id).
- service_idempotency_service_user_id_key_key: CREATE UNIQUE INDEX service_idempotency_service_user_id_key_key ON red_house.service_idempotency USING btree (service, user_id, key).

service_inbox

Columna	Tipo físico	NULL	Predeterminado
service	text	NO	—
event_id	uuid	NO	—
fingerprint	text	NO	—
created_at	timestamp with time zone	NO	now()

Restricciones:

- service_inbox_pkey: PRIMARY KEY (service, event_id).

Índices:

- service_inbox_pkey: CREATE UNIQUE INDEX service_inbox_pkey ON red_house.service_inbox USING btree (service, event_id).

service_outbox

Columna	Tipo físico	NULL	Predeterminado
service	text	NO	—
id	uuid	NO	—
event_id	uuid	NO	—
target	text	NO	—
event	jsonb	NO	—
created_at	timestamp with time zone	NO	now()
delivered_at	timestamp with time zone	YES	—
attempts	integer	NO	0

Columna	Tipo físico	NULL	Predeterminado
next_attempt	timestamp with time zone	NO	now()
last_error	text	YES	—

Restricciones:

- service_outbox_pkey: PRIMARY KEY (service, id).
- service_outbox_service_event_id_target_key: UNIQUE (service, event_id, target).

Índices:

- service_outbox_pkey: CREATE UNIQUE INDEX service_outbox_pkey ON red_house.service_outbox USING btree (service, id).
- service_outbox_service_event_id_target_key: CREATE UNIQUE INDEX service_outbox_service_event_id_target_key ON red_house.service_outbox USING btree (service, event_id, target).
- shared_outbox_pending: CREATE INDEX shared_outbox_pending ON red_house.service_outbox USING btree (service, next_attempt, created_at) WHERE (delivered_at IS NULL).

service_schema_version

Columna	Tipo físico	NULL	Predeterminado
service	text	NO	—
version	integer	NO	—
installed_at	timestamp with time zone	NO	now()

Restricciones:

- service_schema_version_pkey: PRIMARY KEY (service, version).

Índices:

- service_schema_version_pkey: CREATE UNIQUE INDEX service_schema_version_pkey ON red_house.service_schema_version USING btree (service, version).

service_worker_health

Columna	Tipo físico	NULL	Predeterminado
service	text	NO	—
id	integer	NO	—
checked_at	timestamp with time zone	NO	—
last_success	timestamp with time zone	YES	—
last_error	text	YES	—

Restricciones:

- service_worker_health_id_check: CHECK ((id = 1)).
- service_worker_health_pkey: PRIMARY KEY (service, id).

Índices:

- service_worker_health_pkey: CREATE UNIQUE INDEX service_worker_health_pkey ON red_house.service_worker_health USING btree (service, id).

shipment

Columna	Tipo físico	NULL	Predeterminado
shipment_id	uuid	NO	—
allocation_id	uuid	NO	—
transport_id	uuid	NO	—
vehicle	character varying(120)	YES	—
departure_at	timestamp with time zone	NO	—
eta	timestamp with time zone	NO	—
current_status	text	NO	'PLANNED'::text
version_no	integer	NO	1
organ_allocation_id	uuid	YES	—
origin_id	uuid	NO	—
destination_id	uuid	NO	—
region_id	uuid	NO	—
sequence	integer	NO	0
inventory_pending	boolean	NO	true
expires_at	timestamp with time zone	NO	—

Restricciones:

- api_shipments_check: CHECK ((eta > departure_at)).
- api_shipments_check1: CHECK ((eta < expires_at)).
- api_shipments_reservation_id_key: UNIQUE (allocation_id).
- shipment_organ_allocation_id_key: UNIQUE (organ_allocation_id).
- shipment_pkey: PRIMARY KEY (shipment_id).
- shared_shipments_destination_id: FOREIGN KEY (destination_id) REFERENCES red_house.institution(institution_id) DEFERRABLE.
- shared_shipments_origin_id: FOREIGN KEY (origin_id) REFERENCES red_house.institution(institution_id) DEFERRABLE.
- shared_shipments_reservation_id: FOREIGN KEY (allocation_id) REFERENCES red_house.blood_allocation(allocation_id) DEFERRABLE.
- shared_shipments_transport_user_id: FOREIGN KEY (transport_id) REFERENCES red_house.user_account(account_id) DEFERRABLE.
- shipment_organ_allocation_id_fkey: FOREIGN KEY (organ_allocation_id) REFERENCES red_house.organ_allocation(allocation_id) DEFERRABLE.

Índices:

- api_shipments_reservation_id_key: CREATE UNIQUE INDEX api_shipments_reservation_id_key ON red_house.shipment USING btree (allocation_id).
- shipment_organ_allocation_id_key: CREATE UNIQUE INDEX shipment_organ_allocation_id_key ON red_house.shipment USING btree (organ_allocation_id).
- shipment_pkey: CREATE UNIQUE INDEX shipment_pkey ON red_house.shipment USING btree (shipment_id).
- shipment_transport_idx: CREATE INDEX shipment_transport_idx ON red_house.shipment USING btree (transport_id).

shipment_transition

Columna	Tipo físico	NULL	Predeterminado
id	uuid	NO	—
shipment_id	uuid	NO	—

Columna	Tipo físico	NULL	Predeterminado
sequence	integer	NO	—
state	text	NO	—
actor_id	uuid	NO	—
reason	text	NO	—
evidence	jsonb	YES	—
created_at	timestamp with time zone	NO	now()

Restricciones:

- api_transitions_pkey: PRIMARY KEY (id).
- api_transitions_shipment_id_sequence_key: UNIQUE (shipment_id, sequence).
- api_transitions_shipment_id_fkey: FOREIGN KEY (shipment_id) REFERENCES red_house.shipment(shipment_id) DEFERRABLE.
- shared_transitions_actor_id: FOREIGN KEY (actor_id) REFERENCES red_house.user_account(account_id) DEFERRABLE.

Índices:

- api_transitions_pkey: CREATE UNIQUE INDEX api_transitions_pkey ON red_house.shipment_transition USING btree (id).
- api_transitions_shipment_id_sequence_key: CREATE UNIQUE INDEX api_transitions_shipment_id_sequence_key ON red_house.shipment_transition USING btree (shipment_id, sequence).

site

Columna	Tipo físico	NULL	Predeterminado
site_id	uuid	NO	gen_random_uuid()
institution_id	uuid	NO	—
site_code	character varying(30)	NO	—
site_name	character varying(120)	NO	—
street	character varying(200)	NO	—
city	character varying(100)	NO	—
site_status	character varying(10)	NO	'ACTIVE'::character varying
version_no	integer	NO	1

Restricciones:

- site_site_status_check: CHECK (((site_status)::text = ANY (ARRAY[('ACTIVE'::character varying)::text, ('INACTIVE'::character varying)::text]))).
- site_institution_id_site_code_key: UNIQUE (institution_id, site_code).
- site_pkey: PRIMARY KEY (site_id).
- site_institution_id_fkey: FOREIGN KEY (institution_id) REFERENCES red_house.institution(institution_id) DEFERRABLE.

Índices:

- site_institution_id_site_code_key: CREATE UNIQUE INDEX site_institution_id_site_code_key ON red_house.site USING btree (institution_id, site_code).
- site_pkey: CREATE UNIQUE INDEX site_pkey ON red_house.site USING btree (site_id).
- site_institution_idx: CREATE INDEX site_institution_idx ON red_house.site USING btree (institution_id).

site_schedule

Columna	Tipo físico	NULL	Predeterminado
schedule_id	uuid	NO	gen_random_uuid()
site_id	uuid	NO	—
weekday	smallint	NO	—
opens_at	time without time zone	NO	—
closes_at	time without time zone	NO	—

Restricciones:

- site_schedule_check: CHECK ((closes_at > opens_at)).
- site_schedule_weekday_check: CHECK (((weekday >= 1) AND (weekday <= 7))).
- site_schedule_pkey: PRIMARY KEY (schedule_id).
- site_schedule_site_id_weekday_opens_at_key: UNIQUE (site_id, weekday, opens_at).
- site_schedule_site_id_fkey: FOREIGN KEY (site_id) REFERENCES red_house.site(site_id) DEFERRABLE.

Índices:

- site_schedule_pkey: CREATE UNIQUE INDEX site_schedule_pkey ON red_house.site_schedule USING btree (schedule_id).
- site_schedule_site_id_weekday_opens_at_key: CREATE UNIQUE INDEX site_schedule_site_id_weekday_opens_at_key ON red_house.site_schedule USING btree (site_id, weekday, opens_at).

storage_location

Columna	Tipo físico	NULL	Predeterminado
location_id	uuid	NO	gen_random_uuid()
site_id	uuid	NO	—
location_code	character varying(30)	NO	—
location_description	character varying(150)	NO	—
is_active	boolean	NO	true
version_no	integer	NO	1

Restricciones:

- storage_location_pkey: PRIMARY KEY (location_id).
- storage_location_site_id_location_code_key: UNIQUE (site_id, location_code).
- storage_location_site_id_fkey: FOREIGN KEY (site_id) REFERENCES red_house.site(site_id) DEFERRABLE.

Índices:

- storage_location_pkey: CREATE UNIQUE INDEX storage_location_pkey ON red_house.storage_location USING btree (location_id).
- storage_location_site_id_location_code_key: CREATE UNIQUE INDEX storage_location_site_id_location_code_key ON red_house.storage_location USING btree (site_id, location_code).
- storage_site_idx: CREATE INDEX storage_site_idx ON red_house.storage_location USING btree (site_id).

stored_file

Columna	Tipo físico	NULL	Predeterminado
file_id	uuid	NO	—
shipment_id	uuid	NO	—

Columna	Tipo físico	NULL	Predeterminado
owner_id	uuid	NO	—
object_path	text	NO	—
mime_type	text	NO	—
size_bytes	integer	NO	—
sha256	text	NO	—
current_status	text	NO	'PENDING'::text
generation	text	YES	—
created_at	timestamp with time zone	NO	now()

Restricciones:

- api_files_object_path_key: UNIQUE (object_path).
- api_files_size_check: CHECK (((size_bytes >= 1) AND (size_bytes <= 10485760))).
- stored_file_pkey: PRIMARY KEY (file_id).
- api_files_shipment_id_fkey: FOREIGN KEY (shipment_id) REFERENCES red_house.shipment(shipment_id) DEFERRABLE.
- shared_files_owner_id: FOREIGN KEY (owner_id) REFERENCES red_house.user_account(account_id) DEFERRABLE.

Índices:

- api_files_object_path_key: CREATE UNIQUE INDEX api_files_object_path_key ON red_house.stored_file USING btree (object_path).
- stored_file_pkey: CREATE UNIQUE INDEX stored_file_pkey ON red_house.stored_file USING btree (file_id).

transport_telemetry

Columna	Tipo físico	NULL	Predeterminado
telemetry_id	uuid	NO	—
shipment_id	uuid	NO	—
actor_id	uuid	NO	—
latitude	double precision	NO	—
longitude	double precision	NO	—
captured_at	timestamp with time zone	NO	—
created_at	timestamp with time zone	NO	now()

Restricciones:

- transport_telemetry_pkey: PRIMARY KEY (telemetry_id).
- api_telemetry_shipment_id_fkey: FOREIGN KEY (shipment_id) REFERENCES red_house.shipment(shipment_id) DEFERRABLE.
- shared_telemetry_actor_id: FOREIGN KEY (actor_id) REFERENCES red_house.user_account(account_id) DEFERRABLE.

Índices:

- transport_telemetry_pkey: CREATE UNIQUE INDEX transport_telemetry_pkey ON red_house.transport_telemetry USING btree (telemetry_id).
- telemetry_shipment_time: CREATE INDEX telemetry_shipment_time ON red_house.transport_telemetry USING btree (shipment_id, captured_at).

user_account

Columna	Tipo físico	NULL	Predeterminado
account_id	uuid	NO	—
party_id	uuid	YES	—
login_email	character varying(180)	YES	—
password_hash	text	NO	—
account_status	character varying(10)	YES	'ACTIVE'::character varying
version_no	integer	NO	1
registered_at	timestamp with time zone	YES	now()
username	text	NO	—
tenant_id	uuid	NO	—
role	text	NO	—
active	boolean	NO	true

Restricciones:

- api_users_role_check: CHECK ((role = ANY (ARRAY['ADMIN'::text, 'OPERATOR'::text, 'MEDICAL'::text, 'COORDINATOR'::text, 'TRANSPORT'::text, 'AUDITOR'::text, 'DONOR'::text]))).
- user_account_account_status_check: CHECK (((account_status)::text = ANY (ARRAY[('ACTIVE'::character varying)::text, ('INACTIVE'::character varying)::text]))).
- user_account_login_email_check: CHECK (((login_email)::text = lower((login_email)::text))).
- api_users_username_key: UNIQUE (username).
- user_account_login_email_key: UNIQUE (login_email).
- user_account_party_id_key: UNIQUE (party_id).
- user_account_pkey: PRIMARY KEY (account_id).
- api_users_tenant_id_fkey: FOREIGN KEY (tenant_id) REFERENCES red_house.institution(institution_id) DEFERRABLE.
- shared_users_tenant_id: FOREIGN KEY (tenant_id) REFERENCES red_house.institution(institution_id) DEFERRABLE.
- user_account_party_id_fkey: FOREIGN KEY (party_id) REFERENCES red_house.party(party_id) DEFERRABLE.

Índices:

- api_users_username_key: CREATE UNIQUE INDEX api_users_username_key ON red_house.user_account USING btree (username).
- user_account_login_email_key: CREATE UNIQUE INDEX user_account_login_email_key ON red_house.user_account USING btree (login_email).
- user_account_party_id_key: CREATE UNIQUE INDEX user_account_party_id_key ON red_house.user_account USING btree (party_id).
- user_account_pkey: CREATE UNIQUE INDEX user_account_pkey ON red_house.user_account USING btree (account_id).

web_session

Columna	Tipo físico	NULL	Predeterminado
session_id	uuid	NO	—
account_id	uuid	NO	—
expires_at	timestamp with time zone	NO	—
revoked_at	timestamp with time zone	YES	—
created_at	timestamp with time zone	YES	now()

Restricciones:

- web_session_pkey: PRIMARY KEY (session_id).
- api_sessions_user_id_fkey: FOREIGN KEY (account_id) REFERENCES red_house.user_account(account_id) DEFERRABLE.

Índices:

- web_session_pkey: CREATE UNIQUE INDEX web_session_pkey ON red_house.web_session USING btree (session_id).
- web_session_account_idx: CREATE INDEX web_session_account_idx ON red_house.web_session USING btree (account_id).

Almacenamiento técnico del portal: web_runtime.session_revocations

Además de las 71 tablas anteriores, el portal utiliza una tabla técnica en el esquema web_runtime de la misma base PostgreSQL. El instalador aplica web_sessions.sql con permisos exclusivos para rh_web_sessions; los servicios de dominio no tienen acceso. Total instalado tras esta actualización: 72 tablas entre ambos esquemas.

Columna	Tipo	Regla
id	text	PK; SHA-256 de la cookie opaca, 64 caracteres hexadecimales
payload	bytea, admite NULL	Credenciales cifradas pendientes de revocar; se elimina al confirmar
expires	timestamptz	NOT NULL; marca de cierre conservada hasta 24 horas
confirmed	boolean	NOT NULL, false inicial; true después de confirmar revocación

Índices: clave primaria sobre id; session_revocations_pending sobre expires para filas sin confirmar; session_revocations_expiry para limpiar vencidas. Sin claves foráneas al dominio: identifica la sesión técnica del navegador, no un expediente clínico. El worker reintenta cierres pendientes; una marca confirmada impide reactivar la cookie desde una copia antigua de Redis. El respaldo PostgreSQL incluye este esquema.

Las sesiones activas y concesiones de renovación residen en Redis con TTL. La credencial Redis del portal solo accede al prefijo web:*; la credencial SQL solo accede a esta tabla.

Referencias y archivos de esta sección

Diagrama físico completo, ampliable: documentation/segundo-parcial/diagramas/postgresql-completo.svg

Metadatos verificables: documentation/evidencias/segundo-parcial/postgresql-physical.json

SQL de instalación: data/database/schema.sql

web_sessions.sql: data/database/web_sessions.sql