


BS-2306 Infusion Pump



> Features:

- **Bright & Large LED Display**——Super visibility of Infused Volume; Current Infusion Rate; Volume Limit Displayed in LED.
- **Audible & Visual Alarms**——Color Indicator Alarms for "COMPLETE", "OCCLUSION", "AIR-IN-LINE", "DOOR OPEN" and "LOW BATT".
- **Convenient DC 12V Input**——DC 12V input and built-in rechargeable Ni-MH Battery provides reliable AC power in a mobile environment.



> Specification:

Flow Rate Range	1~1000ml/h at 1 ml/h increments.
Volume to be Infused	1~9999ml
KVO Flow Rate	1 ml/hr (will be activated while "Complete" or "Air-In-Line" alarms)
Compatible I.V Set	Compatible with major brand I.V sets.
Alarms	Audible and Visual Alarms of "COMPLETE", "OCCLUSION", "AIR-IN-LINE", "DOOR OPEN" and "LOW BATT".
Pumping Mechanism	Linear Peristaltic
Power Supply	AC 220/240V 50Hz or DC 12V (AC 105/135V 60 Hz available if required)
Power Consumption	Less than 40VA
Battery Capacity	Approximate 4 hours continuous operation at 100 ml/hr with built-in rechargeable Ni-MH battery
Ambient Temperature	5°C ~ 40°C
Coating	Durable rust proof.
Hosting	Aluminium Alloy
Dimensions	D*W*H: 190*125*250 mm D*W*H: 7.48"*4.92"*9.84"
Net Weight	4.95Kg / 9.35 lbs