

BS-7408 Microplate Reader










Features:

- 1. Bichromatic optic system with 4 wavelengths.
- 2. 8-channel optic fiber system, get reading result in just 5 seconds.
- 3. Large LCD display, Win CE compatible operating system.
- 4. Touch-screen or external mouse.
- 5. Large memory to store 10000 results.
- 6. Shaking plate feature.
- Performing 12 different tests just in one plate. 7.
- Multi-forms in result output including patient comprehensive report. 8.
- Easy software upgrade by SD card. 9.

Name: <u>Susan</u> Date: <u>20/10/2</u> 003		Sex: <u>female</u> Sample:05	Report	Age: <u>25</u> Bed No:006	Dept: <u>xxx</u> Sender <u>:</u> xxx
Program	Full name	Result	Unit	Diagnosis	Reference range
HIV HbsAG HbsAb T3		0.163 0.283 0.634 3.374	s/co- s/co- s/co-	Neg- Neg- Neg-	(0.000-1.000) (0.000-1.000) (0.000-1.000)
Operator:				Checker:	




Patient data setting



>Technical Specifications:

Wavelengths	405,450,492,630nm,4 more filters optional	Resolution	0.001Abs(displayed) 0.0001Abs(calculated)
Light Source	Halogen lamp	Photometric Range	0.000-4.000Abs
Wavelength Accu- racy	±1nm	Band width	<8nm
Accuracy	±1% or ± 0.005A	Display	6" LCD
Memory	100 test, up to 10000 test results	Shaking Plate	Shaking time and speed adjustable
Calculation Mode	ABS, % ABS, cut-off, linear, point to point, log, exponent, power regres- sion	Interface	RS-232, UBS,SD card interface
Power Supply	AC 110V-220V±10%, 50 -60Hz	Reading Speed	5 sacs for 96 well plate (single wave- length)
Input	Touch screen, mouse or external keyboard	Output	External printer (optional)
Net Weight	8 KG	Dimensions L×W×H (mm)	460×330×200

Plate setting



Programming



© Copyright 2007 Biosun Technology Co., Ltd. All Rights Reserved.

BioSun™

Biosun Technology Co., Ltd. Distributor: Address: #C2-1812, Futong-Haowangjiao, Baoandadao Rd. Bao-an Dist.,
Shenzhen, Guangdong, 518101, P.R. China.

Tel: +86-755-83086501
Fax: +86-755-83066155

Website: www.biosun.com.hk
E-mail: market@biosun.com.hk