

## BS-2405 Feeding Pump



### > Application:

BIOSUN supplies the intellectual feeding Pump BS-2405 for your patients who depend on tube feeding. The pump has various functions of alarming and flow rate auto-correction. The flow rate controlled BS-2405 Feeding Pump guarantees highest precision with simple handing and a wide range of flow rate setting.

### > Features:

1. Presetting of dose volume
2. Total volume indicator
3. Regulating the flow rate conveniently
4. Lock the flow rate for preventing accident
5. Fast-infusion control
6. Audio and visual alarms
7. Correcting the flow rate automatically
8. Internal Battery
9. Mains and battery indicators
10. Bionic designing

### Feeding Tubes



CY-A



CY-B

### > Specification:

|                        |   |   |
|------------------------|---|---|
| Flow rate:             | 1ml/h-300ml/h (1ml/h increments)  |   |
| Preset dose volume:    | 0-999ml (5ml increments)  |   |
| Indicate total volume: | 0-999ml   |   |
| Flow error:            | ±10%  |   |
| Alarms:                | 1. Flow error (Empty, OCCLUSION)<br>2. Low battery<br>3. AC power error<br>5. Preset dose delivered finished<br>5. Reminder alarm |   |
| Operation Conditions:  | Power Supply  | AC 220V ± 22V 50Hz                                  |
|                        | Battery:  | DC 12V  |
|                        | Automobile Battery:   | 4 hours continuously work after 15 hours recharged. |
|                        | Operational Temperature:  | -5-40℃  |
|                        | Relative Humidity:  | 80%   |
| Dimension & Weight:    | Dimension   | 130(L)* 105(H)* 193(D) (mm)                         |
|                        | Net Weight  | 1.6kg   |