

BS-7106

Electrolytic Analyzer







>Technical Features:

- Reliable long-life electrode
- Automatic intelligent working
- Advanced and particular flow path design
- Independent and convenient sampling system
- Three measures for guaranteeing precision



>Technical Specification:

| Measuring item | K, Na, Cl, | Data storage | 10000 |
|-----------------------------------------|-----------------------------------------------|-----------------------------------------|------------------------------------------------|
| Sampler method | Automatic | Communication interface | 232 interface |
| Calculating item | | Display | 240×64 LCD |
| Measuring time | 40s | Printer | 58mm |
| Sample size | 100ul | Power supply | AC 220V±22V 50Hz 50W |
| Air bubble test | YES | Alarm for waste liquid over- flow | YES |
| Alarm for standard liquid level | Option | Standard liquid level indicator lamp | YES |
| Sample liquid level indi- cator lamp | YES | Automatic sampling | 25-bit sampling system for option |
| Products size | 408mm×390mm×376mm | Product weight | 7 KG |
| Measuring method | ISE TCO2 adopts pressure- measuring method | Working condition | Temperature:10°C~32°C Relative humidity≤85% |

>Measurement parameters specifications:

| Measuring item | Measuring scope | Resolving power | Precision |
|----------------|-----------------|-----------------|-----------|
| (K+) | 0.515.00 | 0.01 | CV≤1.0% |
| (Na+) | 30.0200.0 | 0.1 | CV≤1.0% |
| (CI-) | 30.0200.0 | 0.1 | CV≤1.0% |

© Copyright 2007 Biosun Technology Co., Ltd. All Rights Reserved.

BioSun™

Biosun Technology Co., Ltd.

Address: #C2-1812, Futong-Haowangjiao, Baoandadao Rd. Bao-an Dist., Shenzhen, Guangdong, 518101, P.R. China.

Tel: +86-755-83088501
+86-755-83068155

Tel: +86-755-83088501
Fax: +86-755-83066155
Website: www.biosun.com.hk
E-mail: market@biosun.com.hk

Distributor: