



Flow transition over surface gaps in 2D incompressible laminar boundary layers

Víctor Ballester Ribó¹, Jeffrey Crouch²,
Yongyun Hwang¹, Spencer Sherwin¹

¹Department of Aeronautics, Imperial College London, UK

²The Boeing Company, USA

2 July 2025

IMPERIAL



Motivation



Figure: Wing of a Boeing 737-800

Setup




Figure: Domain setup for the steady-state finder

- **Aim:** Study the stability of the system as a function of the depth d and width w of the gap.
- 2D incompressible NS
- $\text{Re}_{\delta^*} = 1000 \implies \text{Re}_x = 3.38 \times 10^5$

Stability results





Figure: Classification of the stability of points downstream of the gap.

Stability results



$$d/\delta^* = 4, \quad w/\delta^* = 15$$




Figure: Classification of the stability of points downstream of the gap.

Stability results




Figure: Classification of the stability of points downstream of the gap.

Stability results




Figure: Classification of the stability of points downstream of the gap.

Stability results




Figure: Classification of the stability of points downstream of the gap.

Stability results





Figure: Classification of the stability of points downstream of the gap.

Stability results



$$d/\delta^* = 2.25, \quad w/\delta^* = 35$$




Figure: Classification of the stability of points downstream of the gap.

Framework for the LST (TS-wave transition)

- We linearize the flow around a steady baseflow:

$$\mathbf{u}(x, y, t) = \mathbf{U}(x, y) + \tilde{\mathbf{u}}(x, y, t)$$

Framework for the LST (TS-wave transition)

- We linearize the flow around a steady baseflow:

$$\mathbf{u}(x, y, t) = \mathbf{U}(x, y) + \tilde{\mathbf{u}}(x, y, t)$$

- From LST we can obtain disturbances of the form:

$$\tilde{\mathbf{u}} = \phi(y)e^{-\alpha_i x}e^{i(\alpha_r x - \omega t)}$$

Framework for the LST (TS-wave transition)

- We linearize the flow around a steady baseflow:

$$\mathbf{u}(x, y, t) = \mathbf{U}(x, y) + \tilde{\mathbf{u}}(x, y, t)$$

- From LST we can obtain disturbances of the form:

$$\tilde{\mathbf{u}} = \phi(y)e^{-\alpha_i x}e^{i(\alpha_r x - \omega t)}$$

- But this is a local representation! To account for streamwise growth in the BL we use the e^N -method. Fixing $\omega \in \mathbb{R}$:

$$n(x, \omega) = - \int_{x_0}^x \alpha_i(s, \omega) \, ds = \log \left(\frac{|\tilde{\mathbf{u}}(x, \omega)|}{|\tilde{\mathbf{u}}_0|} \right)$$
$$N(x) = \sup_{\omega} n(x, \omega)$$

Framework for the LST (TS-wave transition)

- We linearize the flow around a steady baseflow:

$$\mathbf{u}(x, y, t) = \mathbf{U}(x, y) + \tilde{\mathbf{u}}(x, y, t)$$

- From LST we can obtain disturbances of the form:

$$\tilde{\mathbf{u}} = \phi(y) e^{-\alpha_i x} e^{i(\alpha_r x - \omega t)}$$

- But this is a local representation! To account for streamwise growth in the BL we use the e^N -method. Fixing $\omega \in \mathbb{R}$:

$$n(x, \omega) = - \int_{x_0}^x \alpha_i(s, \omega) \, ds = \log \left(\frac{|\tilde{\mathbf{u}}(x, \omega)|}{|\tilde{\mathbf{u}}_0|} \right)$$
$$N(x) = \sup_{\omega} n(x, \omega)$$

\implies Disturbances of amplitude A_0 satisfy $A(x) \leq A_0 e^{N(x)}$.

Previous Work

Flow (2022), 2 E8
doi:10.1017/fo.2022.1

Flow CAMBRIDGE
UNIVERSITY PRESS

Characterizing surface-gap effects on boundary-layer transition dominated by Tollmien–Schlichting instability

J. D. Crouch^{1,*}, V. S. Kosorygin², M. I. Sutanto¹ and G. D. Miller¹

¹The Boeing Company, P.O. Box 3707, Seattle, WA 98124-2207, USA

²Institute of Theoretical and Applied Mechanics, Novosibirsk 630090, Russia

*Corresponding author. E-mail: jeffrey.d.crouch@boeing.com

Received: 7 July 2021; Revised: 24 January 2022; Accepted: 24 January 2022




Figure: $\Delta N = N - N_{\text{ref}}$ for different gap dimensions

Crouch JD, Kosorygin VS, Sutanto MI, Miller GD. Characterizing surface-gap effects on boundary-layer transition dominated by Tollmien–Schlichting instability. *Flow*. 2022;2:E8.

Perturbed system setup




Figure: Domain setup for the perturbed system

e^N -method results




Figure: Interpolated $\Delta N = N - N_{\text{ref}}$ in the globally-stable region.

e^N -method results




Figure: Interpolated $\Delta N = N - N_{\text{ref}}$ in the equilibra region. Magenta lines indicate the contour levels of the experimental data.

Future Work

- Go to higher Ma (compressible regime).

Future Work

- Go to higher Ma (compressible regime).
- Account for spanwise effects (quasi-3d simulations).