

MASTER THESIS

2D Turbulence spreading

Author:

Víctor Ballester

Supervisors:

Alexandros Alexakis^{*}

Emmanuel Dormy[†]

Abstract

This will be an abstract.

M2 Applied and Theoretical Mathematics
Université Paris Dauphine - PSL
Laboratoire de Physique de l'École Normale Supérieure

June 30, 2024

^{*}Professor in the Department of Physics at École Normale Supérieure. Webpage: <https://www.phys.ens.fr/~alexakis/>

[†]Professor in the Department of Mathematics at École Normale Supérieure. Webpage: <https://www.math.ens.fr/~dormy/>

Contents

1	Introduction	1
2	Theoretical background	1
2.1	Stream function formulation	1
2.2	Fourier space	2
2.3	Reynolds number	3
2.4	Point-vortex model	3
2.5	Monitored quantities	4
3	Simulation	4
3.1	Numerical setup	4
3.2	Results	4
4	Conclusions	4
	References	4

1 Introduction

prova¹ Alexakis 2023.

2 Theoretical background

As mentioned in the introduction, the primary focus of this work is the integration of the incompressible Navier-Stokes equations with a random forcing term:

$$\partial_t \mathbf{u} + (\mathbf{u} \cdot \nabla) \mathbf{u} = -\nabla p + \nu \Delta \mathbf{u} + \mathbf{f} \quad (1)$$

$$\nabla \cdot \mathbf{u} = 0 \quad (2)$$

where \mathbf{u} is the velocity field, p is the pressure, ν is the kinematic viscosity, and \mathbf{f} is a random forcing term. The second equation is called *incompressibility condition* and it translates the fact that the fluid cannot be compressed. The forcing term is chosen to be Gaussian for the stream function formulation, which is detailed below.

2.1 Stream function formulation

In Batchelor 2000, a new variable is introduced in order to simplify the integration of the 2D incompressible Navier-Stokes equations. This quantity, called *stream function* and denoted by ψ , is defined as the flow rate across a given line. More accurately, if \mathcal{C} is a curve joining two points O (fixed) and $P = (x, y)$, the stream function stream function a function f the coordinates of the point P is then

$$\psi(x, y) - \psi_0 = \int_{\mathcal{C}} \mathbf{u}^\perp \cdot d\mathbf{s} = \int_O^P -v dx + u dy \quad (3)$$

where $\mathbf{u} = (u, v)$ is the velocity field, $d\mathbf{s} = (dx, dy)$ is the tangent vector to the curve, and ψ_0 is a reference value. In differential form, it can be written as

$$d\psi = -v dx + u dy = \frac{\partial \psi}{\partial x} dx + \frac{\partial \psi}{\partial y} dy \quad (4)$$

where the last equality follows from the exact differential property. Thus, one obtain the following useful relations:

$$u = \frac{\partial \psi}{\partial y} \quad \text{and} \quad v = -\frac{\partial \psi}{\partial x} \quad (5)$$

Note the arbitrary choice of \mathbf{u}^\perp in the definition of the stream function. In the present work, the choice is made to be $\mathbf{u}^\perp = (-v, u)$, in order to keep the same sign convention as in similar works (Boffetta and

¹This is a footnote.

Ecke 2012; Alexakis and Biferale 2018). The formulation with the alternative stream function $\psi' := -\psi$ is sometimes used in other fields of fluid dynamics, mostly in meteorology and oceanography.

Note that using this definition, the incompressible condition $\nabla \cdot \mathbf{u} = 0$ is automatically satisfied. Finally, introducing the scalar vorticity $\omega := \nabla \times \mathbf{u} = \frac{\partial v}{\partial x} - \frac{\partial u}{\partial y} = -\Delta \psi$, one can rewrite the Navier-stokes equations in terms of the vorticity:

$$\partial_t \omega + (\mathbf{u} \cdot \nabla) \omega = \nu \Delta \omega + f_\omega \quad (6)$$

$$\nabla \cdot \boldsymbol{\omega} = 0 \quad (7)$$

where the rotational has been taken to both sides of Eqs. (1) and (2) and some basic vector have been used. The main objects of interest in the vorticity formulation are the *vortices*, which according to Saffman 1993 are the local regions on the plane with non vanishing vorticity and surrounded with an irrotational flow.

Now, using the relation between the stream function and the vorticity one obtains:

$$\partial_t \psi + \Delta^{-1} (\mathbf{u} \cdot \nabla) \Delta \psi = \nu \Delta \psi + f_\psi \quad (8)$$

The reader may quickly notice that this equation seems more complicated than the first one. However, when transforming the equation to Fourier space, it becomes much more simply (see Eq. (13)), with the advantage of having a scalar function as the main unknown variable and removing the incompressible condition.

The forcing term is assumed to be Gaussian, in particular it is taken of the form:

$$f_\psi(x, y) = \sum_{i=1}^{10} A_i \exp \left(-\frac{k_\ell^2}{2} [(x - x_{i,1})^2 + (y - y_{i,1})^2] \right) - A_i \exp \left(-\frac{k_\ell^2}{2} [(x - x_{i,2})^2 + (y - y_{i,2})^2] \right) \quad (9)$$

With this forcing we are introducing 10 pairs of vortices with opposite vorticity in order not to introduce a nonzero momentum to the dynamics. The quantities A_i follow a uniform distribution between 0 and a prescribed maximum amplitude for the forcing term f_0 ; k_ℓ quantifies the size of the vortices (thought in Fourier space), and the coordinates $x_{i,k}$, $y_{i,k}$, for $k = 1, 2$ are random variables that position the vortices inside a small disk of radius k_r centered at the origin such that the density of vortices is (almost) constant. To be more clear, if we express the coordinates of the vortices in polar coordinates, the angular variable is uniformly distributed between 0 and 2π and the radial variable follows a distribution $\sqrt{\mathcal{U}(0, \pi/k_r)}$ where $\mathcal{U}(a, b)$ is the uniform distribution between a and b . Indeed, one can easily check that the probability of finding a vortex inside a disk of ring $(r - dr, r)$ does not depend on r :

$$\mathbb{P}(r - dr < \sqrt{\mathcal{U}(0, \pi/k_r)} \leq r) = \int_{(r-dr)^2}^{r^2} \frac{1}{\pi/k_r} ds \simeq Cr dr + \mathcal{O}(dr^2) \quad (10)$$

Thus, since the area of the ring $\{(x, y) \in \mathbb{R}^2 : r - dr < \sqrt{x^2 + y^2} \leq r\}$ is proportional to $r dr$ at first order, the density of vortices is constant up to a small error of order dr .

2.2 Fourier space

The *Fourier transform* (FT) of a function $f : \mathbb{R}^2 \rightarrow \mathbb{R}$ is defined as

$$\hat{f}(\boldsymbol{\xi}) = \int_{\mathbb{R}^2} f(\mathbf{x}) e^{-i\boldsymbol{\xi} \cdot \mathbf{x}} d\mathbf{x} \quad (11)$$

for all $\boldsymbol{\xi} \in \mathbb{R}^2$ and its discrete version (DFT) for a square domain with N points in each direction is

$$\hat{f}(\mathbf{k}) = \sum_{\mathbf{n} \in \mathbf{N}} \mathbf{f}_{\mathbf{n}} e^{-i\mathbf{k} \cdot \mathbf{f}_{\mathbf{n}}/N} \quad (12)$$

where $\mathbf{N} = \{0, 1, \dots, N-1\}^2$ is the set of points in the Fourier grid, $\mathbf{f}_{\mathbf{n}}$ is the value of the function in the physical space at the point \mathbf{n} , and $\mathbf{k} = (k_x, k_y)$ is the wave vector.

Taking the Fourier transform on both sides of Eq. (8) and using the well-known properties of the Fourier transform, one obtains:

$$\partial_t \widehat{\psi} - k^{-2} \widehat{(\mathbf{u} \cdot \nabla) \Delta \psi} = -\nu k^2 \widehat{\psi} + \widehat{f_\psi} \quad (13)$$

where $k := |\mathbf{k}|$. Note that the non-linear term in the above equation has not been simplified. This is because in the simulation that term is backward-transformed to the physical space, computed, and then transformed back to the Fourier space, as it is less expensive than computing the non-linear term in Fourier space.

2.3 Reynolds number

The Reynolds number is a dimensionless quantity that characterizes the ratio of inertial forces to viscous forces in a fluid. It is usually defined as $\text{Re} := UL/\nu$, where U is a characteristic velocity of the flow, L is a characteristic length-scale and ν is the kinematic viscosity. In the present work,

2.4 Point-vortex model

The study has accomplished another simulation, far from the Navier-Stokes equations, but aiming to obtain qualitatively and quantitatively similar results. This simulation is based on the point-vortex model, which is a simplified version of the dynamics of a set of vortices.

More precisely, in the point-vortex model that follows, the viscous term is neglected. Thus this problems aims to mimic in some way the dynamics of the Navier-Stokes equations as $\nu \rightarrow 0$ (or equivalently $\text{Re} \rightarrow \infty$, see POSAR REF REYNOLDS). Moreover, the vortices are considered as point-like objects, that is to say, being the vorticity singular at the position of the vortices. Because of that, the vortices are characterized by their circulation

$$\Gamma = \lim_{\text{diam}(\mathcal{C}) \rightarrow 0} \int_{\mathcal{C}} \mathbf{u} \cdot d\mathbf{s} \quad (14)$$

where \mathcal{C} is a curve surrounding the vortex. In those conditions and in absence of external forces, the vorticity field ω is only advected and its evolution in time is described by the following transport equation:

$$\partial_t \omega + (\mathbf{u} \cdot \nabla) \omega = 0 \quad (15)$$

together with the incompressible condition $\nabla \cdot \mathbf{u} = 0$ (Ceci and Seis 2022). Here \mathbf{u} is the velocity field generated by the vortices. An interesting interpretation of the vortices involves the Dirac's delta distribution. Specifically, the vorticity field generated by a point vortex located at \mathbf{y} can be represented as a distribution of the form:

$$\omega(\mathbf{x}, t) = \Gamma \delta(\mathbf{x} - \mathbf{y}) \quad (16)$$

where Γ is the circulation of the vortex (Saffman 1993). The dynamics of N point vortices in the \mathbb{R}^2 plane are described in the following theorem:

Theorem 1. Consider N vortices at positions $\mathbf{z}_1, \dots, \mathbf{z}_N \in \mathbb{R}^2$ and with circulations $\Gamma_1, \dots, \Gamma_N$. Then, their evolution in time is described by the following system of ordinary differential equations:

$$\dot{x}_i = - \sum_{j \neq i} \frac{\Gamma_j}{2\pi} \frac{y_i - y_j}{(x_i - x_j)^2 + (y_i - y_j)^2} \quad (17)$$

$$\dot{y}_i = \sum_{j \neq i} \frac{\Gamma_j}{2\pi} \frac{x_i - x_j}{(x_i - x_j)^2 + (y_i - y_j)^2} \quad (18)$$

for $i = 1, \dots, N$, where $\mathbf{z}_i = (x_i, y_i)$ (Aref 2007).

Proof. Since there is no viscosity in the equations, each vortex is advected with the velocity field generated by all the other vortices. Now, given $\mathbf{f} \in \mathcal{C}^1(\mathbb{R}^2, \mathbb{R}^2)$ and $\mathbf{g} := \nabla \times \mathbf{f}$, by Biot-Savart law one can invert the curl operator using the Biot-Savart kernel (see Griffiths 2023):

$$\mathbf{f}(\mathbf{x}) = (\mathbf{K} * \mathbf{g})(\mathbf{x}) = \int_{\mathbb{R}^2} \mathbf{K}(\mathbf{x} - \mathbf{y}) \mathbf{g}(\mathbf{y}) d\mathbf{y} \quad (19)$$

where $\mathbf{K}(x) = \frac{1}{2\pi} \frac{(-x_2, x_1)}{|x|^2}$ is the Biot-Savart kernel. In our case, the \mathbf{g} is the vorticity field which is a sum of δ 's. Thus, taking into consideration Eq. (16), the velocity field generated by a vortex at \mathbf{z}_j with circulation Γ_j is:

$$\mathbf{u}_j(\mathbf{x}) = \mathbf{K}(\mathbf{x} - \mathbf{z}_j)\Gamma_j \quad (20)$$

We conclude using the superposition principle. \square

2.5 Monitored quantities

3 Simulation

3.1 Numerical setup

3.2 Results

4 Conclusions

Acknowledgements

I would not like to finish this project without thanking the people who have helped me along the way. First and foremost, I would like to thank my two supervisors, Prof. Alexandros Alexakis and Prof. Emmanuel Dormy, for their guidance and constant support throughout the project. This project was, in the theoretical perspective, a bit far from my previous works, but their continuous help and advice made it possible. I would also like to thank the whole group led by Professor Stéphan Fauve in the Laboratoire de Physique de l'École Normale Supérieure, for giving me a desk and a place to work during my internship. Finally, I appreciate the huge amount of time and resources that both supercomputer centers, IDRIS and MESOPSL, have provided me during the development of this project. Without their technological resources, this project would have been impossible to carry out.

References

- Alexakis, A. and L. Biferale (2018). “Cascades and transitions in turbulent flows.” In: *Physics Reports* 767-769. Cascades and transitions in turbulent flows, pp. 1–101. ISSN: 0370-1573. DOI: [10.1016/j.physrep.2018.08.001](https://doi.org/10.1016/j.physrep.2018.08.001). URL: [↗](#).
- Alexakis, A. (2023). “How far does turbulence spread?” In: *Journal of Fluid Mechanics* 977, R1. DOI: [10.1017/jfm.2023.951](https://doi.org/10.1017/jfm.2023.951).
- Aref, H. (June 2007). “Point vortex dynamics: A classical mathematics playground.” In: *Journal of Mathematical Physics* 48.6, p. 065401. ISSN: 0022-2488. DOI: [10.1063/1.2425103](https://doi.org/10.1063/1.2425103). URL: [↗](#).
- Batchelor, G. K. (2000). *An Introduction to Fluid Dynamics*. Cambridge Mathematical Library. Cambridge University Press.
- Boffetta, G. and R. E. Ecke (2012). “Two-Dimensional Turbulence.” In: *Annual Review of Fluid Mechanics* 44. Volume 44, 2012, pp. 427–451. ISSN: 1545-4479. DOI: [10.1146/annurev-fluid-120710-101240](https://doi.org/10.1146/annurev-fluid-120710-101240). URL: [↗](#).
- Ceci, S. and C. Seis (2022). “On the dynamics of point vortices for the two-dimensional Euler equation with L^p vorticity.” In: *Philosophical Transactions of the Royal Society A: Mathematical, Physical and Engineering Sciences* 380.2226, p. 20210046. DOI: [10.1098/rsta.2021.0046](https://doi.org/10.1098/rsta.2021.0046). URL: [↗](#).
- Griffiths, D. J. (2023). *Introduction to Electrodynamics*. 5th ed. Cambridge University Press.
- Saffman, P. G. (1993). *Vortex Dynamics*. Cambridge Monographs on Mechanics. Cambridge University Press.