

Helicopter vs Car Travel Time Analysis: A Comprehensive Comparison of Traffic Scenarios for New York and Los Angeles Airports

REVO Helicopter Services
Strategic Analysis Division

December 2025

Abstract

This study presents a comprehensive analysis comparing helicopter and car travel times to major airports in New York (JFK) and Los Angeles (LAX) under multiple traffic scenarios. Using real Google Traffic historical data, we evaluate four distinct scenarios: Fast (free flow), Normal (1.25x multiplier), Rush Hour (1.68x multiplier), and Worst Case (4.68x multiplier based on pessimistic historical data). Our analysis covers 114 ZIP codes (70 in NY, 44 in LA) and demonstrates that helicopter travel provides significant time savings, particularly under severe traffic conditions. In worst-case scenarios, helicopter travel saves an average of **147 minutes in New York** and **143 minutes in Los Angeles**, representing time reductions of 66% and 64% respectively. The study also reveals that during worst traffic conditions, average car speeds drop to approximately 12 km/h—barely faster than walking pace.

Contents

1	Introduction	3
1.1	Research Objectives	3
1.2	Scope	3
2	Methodology	3
2.1	Traffic Multipliers	3
2.2	Journey Models	3
2.2.1	Car Journey	3
2.2.2	Helicopter Journey	4
2.3	Manhattan Helipad Restrictions	4
3	Traffic Multiplier Analysis	5
3.1	Impact on Travel Time	5
4	Results	6
4.1	Scenario Comparison Overview	6
4.2	Comprehensive Statistics	6
4.3	Time Savings Distribution	7
4.4	Speed Analysis	7
4.5	Time per 100 Meters	8
4.6	Normal vs Worst Case Comparison	9
4.7	Multiplier Effect on Car Travel	10
4.8	Savings Distribution Histogram	11
4.9	Time Breakdown Analysis	12
5	Discussion	12
5.1	Key Findings	12
5.2	Practical Implications	12
5.3	Limitations	13
6	Conclusions	13
7	Summary Statistics	13
A	Data Sources	14
B	Technical Parameters	14

1 Introduction

Urban traffic congestion represents one of the most significant challenges facing business travelers attempting to reach airports from city centers. This study examines the potential of helicopter transport as an alternative to ground transportation, with particular focus on extreme traffic scenarios.

1.1 Research Objectives

1. Compare helicopter vs. car travel times across multiple traffic scenarios
2. Quantify the impact of traffic congestion on travel times
3. Evaluate the time savings potential of helicopter transport
4. Provide data-driven insights for strategic planning

1.2 Scope

The analysis covers:

- **New York:** 70 wealthy ZIP codes → JFK International Airport
- **Los Angeles:** 44 wealthy ZIP codes → LAX International Airport
- **Traffic Scenarios:** Fast, Normal, Rush Hour, and Worst Case

2 Methodology

2.1 Traffic Multipliers

Traffic multipliers were derived from Google Traffic historical data, specifically using the **pessimistic** duration estimates which represent worst-case historical conditions.

Table 1: Traffic Multiplier Definitions

Scenario	Multiplier	Time Increase	Description
Fast	1.00x	Baseline	Free-flowing traffic
Normal	1.25x	+25%	Typical daytime conditions
Rush Hour	1.68x	+68%	Peak hour traffic (7-9 AM, 5-7 PM)
Worst Case	4.68x	+368%	Severe congestion (pessimistic)

2.2 Journey Models

2.2.1 Car Journey

The car journey to the airport consists of:

1. Drive from origin through city streets and highways

2. Airport access roads
3. Parking and terminal walk

Total car time = Base OSRM time $\times$ Traffic Multiplier

2.2.2 Helicopter Journey

The helicopter journey includes:

1. **Car to Helipad:** Drive to nearest helipad (affected by traffic)
2. **Check-in:** 10 minutes at helipad
3. **Flight:** Direct helicopter flight at 200 km/h average speed
4. **Airport Transfer:** 10 minutes from helipad to terminal




Figure 1: Journey Flow Comparison: Car vs Helicopter

2.3 Manhattan Helipad Restrictions

For Manhattan ZIP codes, only Manhattan-based helipads are used:

- **JRB** - Downtown Manhattan/Wall St Heliport
- **JRA** - West 30th St Heliport
- **6N5** - East 34th Street Heliport
- **3NY2** - Astoria Heliport (Queens, nearby)

Exclusion: Police helipads (e.g., One Police Plaza) are excluded from analysis.

3 Traffic Multiplier Analysis

Understanding traffic multipliers is crucial for interpreting the results.




Figure 2: Traffic Multiplier Visualization

3.1 Impact on Travel Time

A 30-minute base journey becomes:

- **Fast:** 30 minutes (baseline)
- **Normal:** 38 minutes (+25%)
- **Rush Hour:** 50 minutes (+68%)
- **Worst Case:** 140 minutes (+368%)

The 4.68x multiplier for worst-case scenarios reflects severe congestion events such as:

- Major accidents
- Severe weather conditions
- Special events (concerts, sports games)
- Holiday travel periods

4 Results

4.1 Scenario Comparison Overview




Figure 3: Travel Time Comparison: Car vs Helicopter by Traffic Scenario

4.2 Comprehensive Statistics

Table 2: Complete Scenario Comparison Statistics

Metric	New York				Los Angeles			
	Fast	Normal	Rush	Worst	Fast	Normal	Rush	Worst
Car Time (min)	47	59	79	221	47	59	80	222
Heli Time (min)	44	46	49	74	46	48	52	79
Savings (min)	3	13	30	147	1	11	28	143
Savings (%)	6%	22%	38%	66%	2%	19%	35%	64%
Speed (km/h)	55	44	33	12	58	47	34	14

4.3 Time Savings Distribution




Figure 4: Time Savings Distribution by Scenario (Boxplot)

The boxplot reveals:

- In **Fast** conditions, savings are minimal (median 3 min)
- In **Worst Case**, median savings exceed 140 minutes
- LA shows slightly less variance due to more consistent traffic patterns

4.4 Speed Analysis




Figure 5: Average Speed by Traffic Scenario

Key findings:

- **Worst Case Speed:** NY averages 12 km/h, LA averages 14 km/h

- Walking speed (5 km/h) is shown as reference
- During worst traffic, cars move only 2-3x faster than walking

4.5 Time per 100 Meters




Figure 6: Time Required to Travel 100 Meters

In worst-case scenarios:

- NY: 30 seconds per 100m
- LA: 26 seconds per 100m
- Walking pace (72 seconds per 100m) shown as reference

4.6 Normal vs Worst Case Comparison




Figure 7: Direct Comparison: Normal Conditions vs Worst Case

This comparison highlights the dramatic difference between typical and worst-case scenarios:

- Car travel time increases by **3.7x** from normal to worst
- Helicopter time increases by only **1.6x**
- Savings increase by **11x** (from 12 min to 145 min average)

4.7 Multiplier Effect on Car Travel




Figure 8: How Traffic Congestion Multiplies Travel Time

The horizontal dashed lines show helicopter times, which remain relatively stable across all scenarios because most of the helicopter journey (flight + fixed transfers) is unaffected by ground traffic.

4.8 Savings Distribution Histogram




Figure 9: Distribution of Time Savings: Normal vs Worst Case

Key observations:

- **Normal scenario:** Savings centered around 10-15 minutes
- **Worst case:** Savings range from 100-200+ minutes
- Nearly all ZIP codes (99%) show positive savings in worst case

4.9 Time Breakdown Analysis




Figure 10: Time Component Breakdown: Car vs Helicopter (Worst Case)

5 Discussion

5.1 Key Findings

1. **Worst-case scenarios show dramatic helicopter advantage:** With 4.68x traffic multipliers, helicopter travel saves 2-3 hours compared to driving.
2. **Speed degradation is severe:** In worst traffic, average speeds drop to 12-14 km/h—approaching bicycle speed.
3. **Helicopter time stability:** Because the majority of helicopter journey time is fixed (check-in, flight, transfer), total time increases only modestly with traffic.
4. **Manhattan shows strong advantage:** With helipads in Manhattan, residents avoid crossing congested bridges and tunnels.

5.2 Practical Implications

For Business Travelers:

- Helicopter service provides scheduling reliability
- Time savings of 2+ hours can mean the difference between making or missing flights
- Reduced stress and fatigue from avoiding traffic

For Service Providers:

- Target marketing during known high-traffic periods
- Price premium justified during worst-case conditions
- Strategic helipad placement maximizes coverage

5.3 Limitations

- Weather conditions may ground helicopter operations
- Helipad availability may be limited during peak demand
- Analysis assumes optimal helipad selection
- Cost differential not included in analysis

6 Conclusions

This comprehensive analysis demonstrates that helicopter transport provides significant time advantages over car travel, particularly during severe traffic conditions. Key conclusions:

1. In **worst-case scenarios** (4.68x traffic), helicopter saves:
 - New York: **147 minutes** (66% reduction)
 - Los Angeles: **143 minutes** (64% reduction)
2. The advantage increases exponentially with traffic severity
3. **99% of ZIP codes** show helicopter advantage during worst traffic
4. Ground speeds during worst traffic (12 km/h) make helicopter the only viable option for time-sensitive travel

7 Summary Statistics

Comprehensive Scenario Comparison Summary

Metric	NY Fast	NY Normal	NY Rush	NY Worst	LA Fast	LA Normal	LA Rush	LA Worst
Car Time (min)	47	59	79	221	47	59	80	222
Heli Time (min)	40	42	46	74	43	45	50	79
Savings (min)	7	17	33	147	4	14	30	143
Savings (%)	15%	28%	42%	66%	9%	23%	38%	64%
Speed (km/h)	55.7	55.7	33.1	11.9	63.9	64.0	38.1	13.7
Time/100m (sec)	6.5	8.1	10.9	30.4	5.9	7.3	9.9	27.5
% Heli Advantage	56%	87%	97%	99%	59%	68%	82%	98%

Figure 11: Complete Summary Statistics Table

A Data Sources

- **Traffic Data:** Google Traffic API (Pessimistic Duration)
- **Routing:** OSRM (Open Source Routing Machine)
- **Helipad Data:** FAA Airport/Heliport Database
- **ZIP Code Data:** Top 10% wealthiest ZIP codes by income

B Technical Parameters

Table 3: Analysis Parameters

Parameter	Value
Helicopter cruise speed	200 km/h
Helipad check-in time	10 minutes
Airport transfer time	10 minutes
Number of NY ZIP codes	70
Number of LA ZIP codes	44
Manhattan ZIP codes	27
Total heliports considered	65 (34 NY, 31 LA)