

Trainings ▾

Specifications

Note : For performance and fuel rate values, refer to the Engine Data Sheet or the fuel pump code for the particular rating involved.

Engine Idle Speed	600 to 1400 rpm
-------------------	-----------------

Minimum Low Idle

KTTA	800 rpm
------	---------

KTA and KT	625 rpm
------------	---------

Maximum No Load Governed Speed	150 rpm above rated speed
--------------------------------	---------------------------

Maximum Overspeed Capability	2656 rpm
------------------------------	----------

Fuel Inlet Maximum Restriction at Fuel Pump Inlet:

Clean Fuel Filter	100 mm Hg [4.0 in Hg]
-------------------	-----------------------

Dirty Fuel Filter	203 mm Hg [8.0 in Hg]
-------------------	-----------------------

Maximum Allowable Return Line Restriction without check valves	63 mm Hg [2.5 in Hg]
--	----------------------

Maximum Allowable return Line restriction with Check Valves and/or Overhead Tanks	165 mm Hg [6.5 in Hg]
---	-----------------------

Engine Minimum Cranking Speed	150 rpm
-------------------------------	---------

Fuel Check Valve in Fuel Drain Line:

Opening Pressure	13 to 25 mm Hg [1/4 to 1/2 psi]
------------------	---------------------------------

Derate Engine Fuel Rate for High Altitude	See engine data sheet
---	-----------------------

Derate Engine Fuel Rate for Hot Weather	See engine data sheet
---	-----------------------

Shutoff Valve Solenoid Coil Resistance in ohms 24 VDC	28 to 32 ohms
---	---------------

Fuel Filter Specifications for Engines with Electronic Fuel Control Valve (Cummins Inc. Standard Number 14,223):

Efficiency:

at 10 microns	98.7 percent
at 8 microns	96 percent
at 5 microns	86 percent

Fuel Filter Specifications for Engines with Electronic Fuel Control Valve (Cummins Inc. Standard Number 14,223):

Water Removal:

Free	95 percent
Emulsified	95 percent