

Trainings ▾

Specifications

Holset® ST676 A/C Model

The following specifications are for a upright two-cylinder air compressor (Holset® ST676 Air Compressor Model)

Cylinders	2
Compressor Capacity (at 1250 rpm)	14.2 liter [30.00 cfm] per second
Piston Displacement	676 cc [41.3 C.I.D.]
Bore	92.08 mm [3.625 in]
Stroke	50.8 mm [2 in]
Speed	Engine speed
Cooling	Engine coolant
Lubrication	Engine lubricating oil

Plumbing Line Sizes:

Coolant Inlet and Outlet (pipe fitting)	12.7 mm NPTF [0.50 in NPTF]
Air Inlet (inside diameter)	22.22 mm [0.875 in]
Air Outlet (minimum inside diameter)	15.88 mm [0.625 in]
Height, Overall (approximate)	34.3 cm [13.5 in]
Width, Overall (approximate)	17.8 cm [7 in]
Length, Overall (approximate)	28.7 cm [11.30 in]
Weight (approximate)	33.5 kg [74.5 lb]

Note : In applications where duty cycles average 10 percent or more or air pressures are above 862 kPa [125 psi], use a discharge line with a minimum inside diameter of 15.9 mm [0.625 in] for single-cylinder compressors and 25.4 mm [1 in] for twin-cylinder compressors to prevent carbon buildup. Examples of these applications are as follows:

- Refuse trucks
- Pickup and delivery trucks
- Transit buses
- Equipment with high accessory air usage.

Holset® SS296, SS296E, and SS338E A/C Model

The following specifications are for a upright single-cylinder air compressor (Holset® SS338/QE338 Air Compressor Models)

Cylinders	1
Compressor Capacity (at 1250 rpm)	7.1 liter [15.00 cfm] per second
Piston Displacement	338 cc [20.63 C.I.D.]
Bore	98.4 mm [3.875 in]
Stroke	44.5 mm [1.75 in]
Speed	Engine speed
Cooling	Engine coolant
Lubrication	Engine lubricating oil

Plumbing Line Sizes:

Coolant Inlet and Outlet (pipe fitting)	9.53 mm NPTF [0.375 in NPTF]
Air Inlet (inside diameter)	22.22 mm [0.875 in]
Air Outlet (minimum inside diameter)	12.7 mm [0.5 in]
Height, Overall (approximate)	31.1 cm [12.25 in]
Width, Overall (approximate)	14.6 cm [5.75 in]
Length, Overall (approximate)	22.9 cm [9 in]
Weight (approximate)	18 kg [40 lb]

Holset® SS296/SS296E/QE296 A/C Models

The following specifications are for a upright single-cylinder air compressor (Holset® SS296/SS296E/QE296 Air Compressor Models)

Cylinders	1
Compressor Capacity (at 1250 rpm)	6.2 liter [13.20 cfm] per second
Piston Displacement	296 cc [18.06 C.I.D.]
Bore	92.08 mm [3.625 in]
Stroke	44.5 mm [1.75 in]
Speed	Engine speed
Cooling	Engine coolant
Lubrication	Engine lubricating oil

Plumbing Line Sizes:

Coolant Inlet and Outlet (pipe fitting)	9.53 mm NPTF [0.375 in NPTF]
Air Inlet (inside diameter)	22.22 mm [0.875 in]
Air Outlet (minimum inside diameter)	12.7 mm [0.5 in]
Height, Overall (approximate)	31.1 cm [12.25 in]
Width, Overall (approximate)	14.6 cm [5.75 in]
Length, Overall (approximate)	22.9 cm [9 in]
Weight (approximate)	18 kg [40 lb]

Compressor Spring Force Specifications

Spring Use	Approximate Free Length	Number of Coils	Wire Diameter	Measurement Length	Minimum	Maximum
Exhaust Valve	17.02 mm [0.670 in]	3.0	2.03 mm [0.080 in]	7.11 mm [0.280 in]	3.63 N [8.00 lb]	4.72 N [10.40 lb]
Intake Valve	12.70 mm [0.500 in]	2.8	1.58 mm [0.062 in]	7.11 mm [0.280 in]	0.25 N [0.50 lb]	0.50 N [1.10 lb]

Compressor Spring Force Specifications						
Spring Use	Approximate Free Length	Number of Coils	Wire Diameter	Measurement Length	Minimum	Maximum
Unloading Valve (Naturally Aspirated)	41.91 mm [1.650 in]	11.5	2.03 mm [0.080 in]	24.89 mm [0.980 in]	13.6 N [30.00 lb]	17.23 N [38.00 lb]
Unloading Valve (Turbocharged up to 1270 mm Hg [50 in Hg])	41.91 mm [1.650 in]	12.0	1.83 mm [0.072 in]	24.89 mm [0.980 in]	7.72 N [17.00 lb]	9.98 N [22.00 lb]
Unloading Valve (all Turbocharged Engines)	41.91 mm [1.650 in]	10.8	2.89 mm [0.065 in]	24.89 mm [0.980 in]	5.4 N [12.00 lb]	7.72 N [17.00 lb]

Last Modified: 12-Aug-2019
