

Trainings ▾

Specifications

Oil Pressure (with 15W-40 oil at 107°C [225°F]):

At Idle (minimum allowable)	138 kPa [20 psi]
-----------------------------	--------------------

Oil Pressure (with 15W-40 oil at 93°C to 121°C [200°F to 250°F]):

At No-Load Governed Speed	345 to 551 kPa [50 to 80 psi]
---------------------------	---------------------------------

Oil Temperature Maximum:	120°C [250°F]
--------------------------	-----------------

Oil Filter Capacity:

Bypass Filter	2.3 liters [0.6 U.S. gal]
---------------	-----------------------------

Full-Flow Filter	2.7 liters [0.7 U.S. gal]
------------------	-----------------------------

Combination Filter	2.3 liters [0.6 U.S. gal]
--------------------	-----------------------------

Venturi Combination Filter	2.5 liters [0.66 U.S. gal]
----------------------------	------------------------------

Centrifuge Filter	1.0 liters [0.26 U.S. gal]
-------------------	------------------------------

Total lubricating oil system capacity (in liters/gal) can be determined by adding the high level of the oil in the oil pan, to the capacity of the two combination full-flow bypass oil filters. See chart below.

Sump Configuration with Listed Capacity	Sump Capacity at Low Level On Dipstick	Sump Capacity at High Mark On Dipstick	Total System Capacity Sump and Two Combo Oil Filters
37.8 liters [10 U.S. gal] shallow rear sump 37.8 liters [10 U.S. gal] shallow full length sump	32.1 liters [8.5 U.S. gal]	37.8 liters [10 U.S. gal]	42.4 liters [11.2 U.S. gal]

Sump Configuration with Listed Capacity	Sump Capacity at Low Level On Dipstick	Sump Capacity at High Mark On Dipstick	Total System Capacity Sump and Two Combo Oil Filters
60.6 liters [16 U.S. gal] front-center sump 60.6 liters [16 U.S. gal] center-rear sump 60.6 liters [16 U.S. gal] deep front sump 60.6 liters [16 U.S. gal] deep center sump	49.2 liters [13 U.S. gal]	60.6 liters [16 U.S. gal]	65.2 liters [17.2 U.S. gal]
71.9 liters [19 U.S. gal] deep rear sump	64.3 liters [17 U.S. gal]	72 liters [19 U.S. gal]	76.6 liters [20.2 U.S. gal]
113.6 liters [30 U.S. gal] deep full length sump	102.2 liters [27 U.S. gal]	113.5 liters [30 U.S. gal]	118.1 liters [31.1 U.S. gal]

Last Modified: 03-Jan-2023
