

Trainings ▾

Specifications

Maximum Starting Circuit Resistance:

24 - VDC starter	0.00200 ohm
------------------	-------------

Battery Cable Sizes - American Wire Gauge (maximum length in cranking motor circuit) 24 to 32 - VDC

Number 00	6.1 m [20 ft]
-----------	---------------

Battery Cable Sizes - American Wire Gauge (maximum length in cranking motor circuit) 24 to 32 - VDC

Number 000	8.2 m [27 ft]
------------	---------------

Battery Cable Sizes - American Wire Gauge (maximum length in cranking motor circuit) 24 to 32 - VDC

Number 0000 or two Number 0*	10.7 m [35 ft]
------------------------------	----------------

Battery Cable Sizes - American Wire Gauge (maximum length in cranking motor circuit) 24 to 32 - VDC

Two Number 00	13.7 m [45 ft]
---------------	----------------

Minimum Cranking Speed without Starting Aid	150 rpm
---	---------

* Two strands of Number 0 cable can be used instead of one Number 0000 cable, provided that all connections are carefully made to provide equal current flow in each parallel cable.

Starting aids, such as block heaters, lubricating oil pan heaters, and so forth, are available to aid in cold weather starting.

System Voltage	Ambient Temperatures			
	-18°C [0°F]		0°C [32°F]	
	Cold Cranking Amperes	Reserve Capacity* Amperes	Cold Cranking Amperes	Reserve Capacity* Amperes
24 VDC**	900	320	640	240

* The number of plates within a given battery size determines reserve capacity. Reserve capacity is the length of time sustained cranking can occur.

** CCA ratings are based on two 12-VDC batteries in series.

Battery State of Charge	Specific Gravity @ 27°C [80°F]
100%	1.260 to 1.280
75%	1.230 to 1.250
50%	1.200 to 1.220
25%	1.170 to 1.190
Discharged	1.110 to 1.130

Last Modified: 05-Nov-2013
