

Trainings ▾

Specifications

Holset® ST676 A/C Model

The following specifications are for a upright two-cylinder air compressor (Holset® ST676 Air Compressor Model)

Cylinders	2
Compressor Capacity (at 1250 rpm)	14.2 liter [30.00 cfm] per second
Piston Displacement	676 cc [41.3 C.I.D.]
Bore	92.08 mm [3.625 in]
Stroke	50.8 mm [2 in]
Speed	Engine speed
Cooling	Engine coolant
Lubrication	Engine lubricating oil

Plumbing Line Sizes:

Coolant Inlet and Outlet (pipe fitting) 12.7 mm NPTF [0.50 in NPTF]

Plumbing Line Sizes:

Air Inlet (inside diameter) 22.22 mm [0.875 in]

Plumbing Line Sizes:

Air Outlet (minimum inside diameter) 15.88 mm [0.625 in]

Height, Overall (approximate)	34.3 cm [13.5 in]
Width, Overall (approximate)	17.8 cm [7 in]
Length, Overall (approximate)	28.7 cm [11.30 in]
Weight (approximate)	33.5 kg [74.5 lb]

Note : In applications where duty cycles average 10 percent or more or air pressures are above 862 kPa [125 psi], use a discharge line with a minimum inside diameter of 15.9 mm [0.625 in] for single-cylinder compressors and 25.4 mm [1 in] for twin-cylinder compressors to prevent carbon buildup. Examples of these applications are as follows:

- Refuse trucks
- Pickup and delivery trucks
- Transit buses
- Equipment with high accessory air usage.

Holset® SS296, SS296E, and SS338E A/C Model

The following specifications are for a upright single-cylinder air compressor (Holset® SS338/QE338 Air Compressor Models)

Cylinders	1
Compressor Capacity (at 1250 rpm)	7.1 liter [15.00 cfm] per second
Piston Displacement	338 cc [20.63 C.I.D.]
Bore	98.4 mm [3.875 in]
Stroke	44.5 mm [1.75 in]
Speed	Engine speed
Cooling	Engine coolant
Lubrication	Engine lubricating oil

Plumbing Line Sizes:

Coolant Inlet and Outlet (pipe fitting) 9.53 mm NPTF [0.375 in NPTF]

Plumbing Line Sizes:

Air Inlet (inside diameter) 22.22 mm [0.875 in]

Plumbing Line Sizes:

Air Outlet (minimum inside diameter) 12.7 mm [0.5 in]

Height, Overall (approximate)	31.1 cm [12.25 in]
Width, Overall (approximate)	14.6 cm [5.75 in]
Length, Overall (approximate)	22.9 cm [9 in]
Weight (approximate)	18 kg [40 lb]

Holset® SS296/SS296E/QE296 A/C Models

The following specifications are for a upright single-cylinder air compressor (Holset® SS296/SS296E/QE296 Air Compressor Models)

Cylinders	1
Compressor Capacity (at 1250 rpm)	6.2 liter [13.20 cfm] per second
Piston Displacement	296 cc [18.06 C.I.D.]
Bore	92.08 mm [3.625 in]
Stroke	44.5 mm [1.75 in]
Speed	Engine speed
Cooling	Engine coolant
Lubrication	Engine lubricating oil

Plumbing Line Sizes:

Coolant Inlet and Outlet (pipe fitting) 9.53 mm NPTF [0.375 in NPTF]

Plumbing Line Sizes:

Air Inlet (inside diameter) 22.22 mm [0.875 in]

Plumbing Line Sizes:

Air Outlet (minimum inside diameter) 12.7 mm [0.5 in]

Height, Overall (approximate)	31.1 cm [12.25 in]
Width, Overall (approximate)	14.6 cm [5.75 in]
Length, Overall (approximate)	22.9 cm [9 in]
Weight (approximate)	18 kg [40 lb]