

Trainings ▾

Specifications

Fleetguard is a subsidiary of Cummins Inc. Fleetguard® filters are developed through joint testing at Cummins Inc. and Fleetguard. Fleetguard® filters are standard on new Cummins® engines. Cummins Inc. recommends their use.

Fleetguard® products meet all Cummins Inc. Source Approval Test standards to provide the quality filtration necessary to achieve the engine's design life. If other brands are substituted, the purchaser **must** insist on products the supplier has tested to meet Cummins Inc. high-quality standards.

Cummins Inc. can **not** be responsible for problems caused by non-genuine filters that do **not** meet Cummins Inc. performance or durability requirements.

When a lubricating oil filter (full flow) is used, a lubricating oil filter (bypass) **must** also be used.

Filters for Engines with Mechanical Fuel Injectors

Cummins® Part Number	Fleetguard® Part Number	Filter Style
3889310	LF670	Lubricating Oil Filter (full flow)
3889311	LF777	Lubricating Oil Filter (bypass)
3318853	LF3000	Lubricating Oil Filter (combination)
3161407	FS1000	Fuel Filter (Industrial applications) (10 micron, water separation)
3100308	WF2075	Coolant Filter
331673	FS1009	Fuel Filter (Marine applications) (10 micron, water separation with metal drain valve)
-	CS41011	Eliminator Filter

Filters for Engines with Electronic Fuel Injectors

Cummins® Part Number	Fleetguard® Part Number	Filter Style
3101869	LF9001	Lubricating Oil Filter (Venturi Combo)
3100308	WF2075	Coolant Filter

Filters for Engines with Electronic Fuel Injectors		
Cummins® Part Number	Fleetguard® Part Number	Filter Style
5417137 ⁽¹⁾	FF5782NN ⁽¹⁾	Fuel Filter, Stage 2 (NanoNet™ media)
-	FS19763	Fuel and Water Separator, Stage 1 (FH234 Series Industrial Pro, StratoPore™ media)
4328040	FS53015	Fuel and Water Separator, Stage 1 (FH239 Series Industrial Pro™, NanoNet™ media)
4328043	FS53014	Fuel and Water Separator, Stage 1 (FH239 Series Industrial Pro™, NanoNet™ media)
4380004	FS53021	Fuel and Water Separator, Stage 1 (FH240 Series Sea Pro, NanoNet™ media)
-	FS1984100	Fuel Filter, Spin-on (Marine Application) (7 micron)
-	CS41011	Eliminator Filter
(1) - An equivalent Stage 2 fuel filter can be used, but it must meet or exceed the following characteristics: Beta Ratio (filtration efficiency) rating of $\beta_{4@} = 1000$.		

Fleetguard® DCA4 Service Filters and Liquid Precharge